## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ 27 47

Dated: 27/12/18

## FIRE SAFETY CERTIFICATE

Certified that the Konien Dx. Guest House located at 7975, Arakashan Road, Pahar Ganj, New Delhi comprised of Basement + Ground + 04 Upper floors, Basement (01 office cum store room), Ground floor (Reception + 02 guest rooms), 1st floor to 2nd floor (05 guest rooms + 01 store room at each floor), 3rd floor (05 guest rooms) and 4th floor (02 guest room + 01 store room + pantry for staff), total 19 guest rooms owned/occupied by Konica Dx. Guest House was granted FSC by this department vide letter No.F6/DFS/NIS/G11/2015/NDZ/2260 dated 31/12/15. The premises was re-inspected by the officer concerned of this department on 09/12/18 in the presence of Sh. Sahil (Manger) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 19 guest rooms only with effect from -27/(2-11-2---- for period of three years in accordance with rule 36 unless repewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the canditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issurd 27 (14) - at New Delhi by.

120/2

(Vipin Kental) Chief Fire Officer Delhi Fire Service Of m

## Copy to:-

- 1. The Addl. Commissioner of Police (Lic). First Floor, P.S. Defence Colony New Delhi. 2. The Nanager,

Konica Dx. Guest House at 7975, Arakashan Road, Pahar Ganj, New Delhi.

## Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- of life or property due to non functional fire safety measures shall be at the respondibility of the management.
- ed fire fighting staff should be available round the clock.
- 4. Any d lation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- This fire safety certificate may not be treated in any case for regularization of unauthorized construction, it any.
- or accupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The mass of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an em ency.
- 8. The ox per/occupier shall apply for renewal of this Fire Safety Certificate to the Director in [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry"

TAI	CD	EC	LIO	TI	DE	DO	DΊ	7
IIN	OL	CC.	$\cup$	INI	VE.		$L_1$	

1. Name & address of the building Konica Dx. Guest House located at 7975,

Arakashan Road, Pahar Ganj, New Delhi. 2. Type of occupancy:-Residential, Sub Division-A-1

B+Gr. + 04 Upper floors (total 19 Guest rooms) Basement (01 office cum store room), Ground floor (Reception + 02 guest rooms), 1<sup>st</sup> floor to 2<sup>nd</sup> floor (05 guest rooms + 01 store room at each floor), 3<sup>rd</sup>

floor (05 guest rooms) and 4th floor (02 guest room +

01 store room + pantry for staff)

3. Type of case:-Renewal

4. Details of previous FSC:-No. F6/DFS/MS/GH/2015/NDZ/2260 dated

N/A

31/12/15.

5. Fire safety directives No.-

6. Date of inspection:-

7. Name of the inspecting officer:-

8. Name & designation of officer From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

09/12/18 Sh. Manoj Kumar Sharma (ADO/CC)

Sh. Sahil (Manager)

1990

Nil dated 27/11/18

10	. Applicant's letter No:-	Mil dated 2	//11/10	Old Case
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing fire safety arrangements	Provided at site	Remarks MR/NMR
1.	Access to Building		3	
	1) Road width	N/A	35 feet apporex	MR
	2) Gate width	N/A	N/A	N/A
	3)Width of internal road	N/A	N/A	N/A
2.	Number, Width Type & Arra	angement of E	exits	
	A. Number of staircases		5 o	
	1. Upper floors	01 Nos.	01 Nos.	MR
	2. Basements	01 Nos.	01 Nos.	MR
	B. Width of staircase			×
	1. Upper floors	0.80 mtr.	1.15 to 1.20 mtr.	MR
	2. Basements	0.80 mtr.	1.15 to 1.20 mtr.	MR
	C. Protection of exits			
	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A	N/A	N/A
	D. No. of continuous staircase to terrace	01 Nos.	01 Nos.	MR
	E. Width of corridor	N/A	N/A	N/A
	F. Door size	1 mtr.	1 mtr.	MR
3.	Compartmentation			
×	1) Fire check door	N/A	N/A	N/A
	2) Sealing of electrical shafts	N/A	N/A	N/A
	3) Fire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	N/A	N/A
4.	Smoke Management System			
	1) Basements	30 ACPH	Exhaust fan	MR
	2) Upper floors	12 a/c per hour	Natural Ventilation	MR

5.	Fire Extinguishers		1			
	1) Total numbers	12 Nos.	12 Nos.	MR		
	2) Types	ABC & CO2	ABC & CO2	MR		
	3) ISI marking	Required	Provided	MR		
6.	First-Aid Hose Reel	*				
	1) Total number of eachfloor	01	01	MR		
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR		
	3) Nozzle diameter	05 mm	05 mm	MR		
7.	Automatic Fire Detection & Alarming System					
	1) Type of detectors	N/A	N/A	N/A		
	2) Location of main panel	N/A	N/A	N/A		
	3) Location of repeater panel	N/A	N/A	N/A		
	4) Alternate source of power	N/A	N/A	N/A		
	5) Hooter's Location	N/A	N/A	N/A		
8.	MOEFA	N/A	N/A	N/A		
9.	Public Address System	Required	Provided	MR		
10.	Automatic Sprinkler System	ı				
	1) Basement	Required	Provided	MR		
	2) Upper floors	N/A	N/A	N/A		
	3) Sprinkler above false	N/A	N/A	N/A		
	ceiling		8			
11.	Internal Hydrants					
	1) Size of riser/down-comer	N/A	N/A	N/A		
	2) Number of hydrants per	N/A	N/A	N/A		
	floor		1 1			
	3) Hose box	N/A	N/A	N/A		
12.	Yard Hydrants					
	1) Total number of hydrants	N/A	N/A	N/A		
	2) Hose box	N/A	N/A	N/A		
13.	Pumping Arrangement					
	1) Ground level	N/A	N/A	N/A		
	a) Discharge of main pump	N/A	N/A	N/A		
	b) Head of main pump	N/A	N/A	N/A		
	c) Number of main pur	np N/A	N/A	N/A		
	d) Jockey pump out pu		N/A	N/A		
	e) Jockey pump head	N/A	N/A	N/A		
	f) Stand by pump outp	ut N/A	N/A	N/A		
	g) Stand by pump head	N/A	N/A	N/A		
	h) Auto starting/Manua stopping	al N/A	N/A	N/A		
	2) Terrace level					
	a) Discharge of pump	450 LPM	450 LPM	MR		
	b) Head of pump	30 mtr.	30 mtr.	MR		
	c) Power supply	Required	Provided	MR		
	d) Auto starting of pun	np Required	Provided	MR		

11

14.		Captive Water Storage for Fire Fighting					
	Under ground tank     capacity	N/A	N/A	N/A			
	a) Draw-off connection	N/A	N/A	N/A			
	b) Fire service inlet	N/A	N/A	N/A			
	c) Access to tank	N/A	N/A	N/A			
	d) Over head tank capacity	2500 ltr.	2500 ltr.	MR			
15.	Exit Signage.	Required	Provided	MR			
16.	Provision of Lifts.						
	a) Pressurization of lift shaft	N/A	N/A	N/A			
	b) Pressurization of lift lobby	N/A	N/A	N/A			
	c) Communication in lift car	N/A	N/A	N/A			
	d) Fireman's switch	N/A	N/A	N/A			
	e) Lift signage	N/A	N/A	N/A			
17.	Stand by Power Supply	Required	Provided	MR			
18.	Refuge Area	N/A	N/A	N/A			
	Total area location	N/A	N/A	N/A			
19.	Fire Control Room	N/A	N/A	N/A			
	a) Detector system panel	N/A	N/A	N/A			
	b) Flow switch panel	N/A	N/A	N/A			
	c) PA system panel	N/A	N/A	N/A			
	d) Battery backup	N/A	N/A	N/A			
	e) Building floor plan	N/A	N/A	N/A			
20.	Special Fire Protection Syst Risk, if any:	em for Protec	ction of special	NA			

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2015/NDZ/2260 dated 31/12/2015 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

2010 C/20 NDZ

2010 Dy. CFO/NDZ

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

F710.

1. M. Scel

17/10

trap for 6 gr. p