## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ 2762

Dated :----

## FIRE SAFETY CERTIFICATE

Certified that the Rahul Palace Dx. located at 5577, Gali Shora Kothi, Basant Road, Pahar Ganj, New Delhi comprised of Ground + 02 Upper floors, Ground floor (shops), 1<sup>st</sup> floor (04 guest rooms + reception), 2<sup>nd</sup> floor (05 guest room), total 09 guest rooms owned/occupied by Rahul Palace Dx. was granted FSC by this department vide letter No.F6/DFS/MS/GH/2015/NDZ/1886 dated 20/10/15. The premises was re-inspected by the officer concerned of this department on 10/12/18 in the presence of Sh. Rakesh (Prop.) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 09 guest rooms only with effect from ---28/142/13-for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued ---- at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.

2. The Manager,

Rahul Palace Dx. at 5577, Gali Shora Kothi, Basant Road, Pahar Ganj, New Delhi. Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPOR	

Name & address of the building:- Rahul Palace Dx. at 5577, Gali Shora Kothi,

Basant Road, Pahar Ganj, New Delhi

2. Type of occupancy:- Residential, Sub Division-A-1

Gr. + 02 Upper floors (total 09 Guest rooms) Ground floor (shops), 1<sup>st</sup> floor (04 guest rooms +

reception), 2<sup>nd</sup> floor (05 guest room)

3. Type of case:- Renew

4. Details of previous FSC:- No. F6/DFS/MS/GH/2015/NDZ/1886 dated

20/10/15.

5. Fire safety directives No.- N/A

6. Date of inspection:- 10/12/18

7. Name of the inspecting officer:- Sh. Manoj Kumar Sharma (ADO/CC)

8. Name & designation of officer

From the building side:- Sh. Rakesh Vear of construction:- 2001

9. Year of construction:10. Applicant's letter No:2001
Nil dated 27/11/2018

				Old Case
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing fire safety arrangements	Provided at site	Remarks MR/NMR
1.	Access to Building			/
	1) Road width	N/A	N/A	N/A
	2) Gate width	N/A	N/A	N/A
	3)Width of internal road	N/A	N/A	N/A
2.	Number, Width Type & Arra		xits	
4.	A. Number of staircases			
	1. Upper floors	01 Nos.	01 Nos.	MR
	2. Basements	N/A	N/A	N/A
	B. Width of staircase			
	1. Upper floors	0.80 mtr.	0.83 mtr.	MR
	2. Basements	N/A	N/A	N/A
	C. Protection of exits			
	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A	N/A	N/A
	D. No. of continuous	N/A	N/A	N/A
	staircase to terrace	N/A	N/A	N/A
	E. Width of corridor  F. Door size	1 mtr.	1 mtr.	MR
2		1 mu.	1 11101.	
3.	Compartmentation	N/A	N/A	N/A
	<ol> <li>Fire check door</li> <li>Sealing of electrical shafts</li> </ol>	N/A	N/A	N/A
	3) Fire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	N/A	N/A
4.	Smoke Management System			
4.	1) Basements	30 ACPH	N/A	N/A
	2) Upper floors	12 a/c per hour	Natural Ventilation	MR

E	Five Vertinaviahora							
5.	Fire Extinguishers  1) Total numbers  06 Nos.		04	Nos.	M	P		
	2) Types		C & CO2		BC & CO2	M		
	3) ISI marking			-	rovided	M		
6.	First-Aid Hose Reel	Required		11	Ovided	IVI	11	
0.	1) Total number of eachfloor	V V V V V V V V V V V V V V V V V V V				M	D	
	2) Length of hose reel hose	30 m		01	) m	M		
	3) Nozzle diameter	05 r		-	mm	M		
7.	Automatic Fire Detection &				7 111111	IVI		
1.	1) Type of detectors	N/A		T	/ ^	N	A	
	2) Location of main panel	N/A N/A		N/A N/A			A	
	3) Location of repeater panel	N/A		-	/A	_	A	
	4) Alternate source of power	N/A		-			A	
	5) Hooter's Location	N/A N/A		N/A N/A		_	-	
8.	MOEFA	N/A		-	/A	_	N/A N/A	
9.	Public Address System	N/A		-	/A	-	A	
10.	Automatic Sprinkler System			14	4.8	11		
AU.	1) Basement	N/A		N	/A	N	/A	
	2) Upper floors	N/A		-	/A		A	
	3) Sprinkler above false	N/A		-	/A	_	A	
	ceiling	11/1/				1		
11.	Internal Hydrants	1			-			
	1) Size of riser/down-comer	N/A		N/A		N	/A	
	2) Number of hydrants per	-	N/A		/A ·		/A	
	floor							
	3) Hose box	N/A		N	/A	N	/A	
12.	Yard Hydrants							
	1) Total number of hydrants	N/A	1	N	/A	N	/ <u>A</u>	
	2) Hose box	N/A		N	/A	N	/A	
13.	Pumping Arrangement				The second			
	1) Ground level		N/A		N/A		N/A	
			N/A N/A		N/A N/A		N/A N/A	
	a) Ground level a) Discharge of main pump			_				
	a) Discharge of main							
	a) Discharge of main pump		N/A		N/A	1	N/A	
	<ul><li>a) Discharge of main pump</li><li>b) Head of main pump</li></ul>	np 1	N/A N/A		N/A N/A		N/A N/A N/A N/A	
	<ul> <li>a) Discharge of main pump</li> <li>b) Head of main pump</li> <li>c) Number of main pur</li> </ul>	mp 1	N/A N/A N/A		N/A N/A N/A		N/A N/A N/A	
	<ul> <li>a) Discharge of main pump</li> <li>b) Head of main pump</li> <li>c) Number of main pur</li> <li>d) Jockey pump out pur</li> </ul>	mp 1	N/A N/A N/A N/A	-	N/A N/A N/A		N/A N/A N/A N/A N/A N/A	
	a) Discharge of main pump b) Head of main pump c) Number of main pum d) Jockey pump out pume e) Jockey pump head	np 1	N/A N/A N/A N/A N/A		N/A N/A N/A N/A		N/A N/A N/A N/A N/A N/A N/A	
	a) Discharge of main pump b) Head of main pump c) Number of main pur d) Jockey pump out pu e) Jockey pump head f) Stand by pump outp	mp 1 t 1 t 1 t 1 t 1 t 1 t 1 t 1 t 1 t 1	N/A N/A N/A N/A N/A N/A N/A	-	N/A N/A N/A N/A N/A N/A		N/A N/A N/A N/A N/A N/A	
	a) Discharge of main pump b) Head of main pump c) Number of main pur d) Jockey pump out pu e) Jockey pump head f) Stand by pump outp g) Stand by pump head h) Auto starting/Manua stopping	mp 1 t 1 t 1 t 1 t 1 t 1 t 1 t 1 t 1 t 1	N/A N/A N/A N/A N/A N/A N/A N/A N/A		N/A N/A N/A N/A N/A N/A N/A		N/A N/A N/A N/A N/A N/A N/A	
	a) Discharge of main pump b) Head of main pump c) Number of main pum d) Jockey pump out pu e) Jockey pump head f) Stand by pump outp g) Stand by pump head h) Auto starting/Manua	mp 1 t 1 t 1 t 1 t 1 t 1 t 1 t 1 t 1 t 1	N/A		N/A		N/A	
	a) Discharge of main pump b) Head of main pump c) Number of main pur d) Jockey pump out pu e) Jockey pump head f) Stand by pump outp g) Stand by pump head h) Auto starting/Manua stopping 2) Terrace level a) Discharge of pump	mp 1 t 1 t 1 t 1 t 1 t 1 t 1 t 1 t 1 t 1	N/A N/A N/A N/A N/A N/A N/A N/A N/A		N/A N/A N/A N/A N/A N/A N/A		N/A	
	a) Discharge of main pump b) Head of main pump c) Number of main pur d) Jockey pump out pu e) Jockey pump head f) Stand by pump outp g) Stand by pump head h) Auto starting/Manua stopping 2) Terrace level	mp 1 t 1 t 1 t 1 t 1 t 1 t 1 t 1 t 1 t 1	N/A		N/A		N/A	
	a) Discharge of main pump b) Head of main pump c) Number of main pur d) Jockey pump out pu e) Jockey pump head f) Stand by pump outp g) Stand by pump head h) Auto starting/Manua stopping 2) Terrace level a) Discharge of pump	mp 1 t 1 t 1 t 1 t 1 t 1 t 1 t 1 t 1 t 1	N/A N/A N/A N/A N/A N/A N/A N/A		N/A		N/A	

h

14.	Captive Water Storage for 1	Fire Fighting	7	
	1) Under ground tank capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2500 ltr.	2500 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syste Risk, if any:	m for Protect	tion of special	NA

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2015/NDZ/1886 dated 20/10/2015 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

M.s cell FT/0.