## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2018/ 07

Dated :- 02/0///9

## FIRE SAFETY CERTIFICATE

Certified that the M/s Shree Delhi Gujrati Samaj located at 2, Raj Niwas Marg, Civil Line, Delhi comprised of Ground floor (18 guest room + reception + 01 dormitory), 1st floor (27 guest rooms + 01 dormitory), 2nd floor (32 guest rooms + 02 dormitory) and floor (21 guest room + 05 dormitory), total 98 guest rooms & 09 dormitory owned/occupied by M/s Shree Delhi Gujrati Samaj was granted FSC by this department vide letter No.F6/DFS/MS/GH/2015/NDZ/1837 dated 13/10/15. The premises was re-inspected by the officer concerned of this department on 08/12/18 in the presence of Sh. Nilesh Shah and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 98 guest the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued --- at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service OLM

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.
- M/s Shree Delhi Gujrati Samaj at 2, Raj Niwas Marg, Civil Line, Delhi. Condition for the validity of fire safety certificate
  - 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.

2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.

8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

		1745				
	INSI	PECTION REPO	RT			
Name d	& address of the building:-		elhi Gujrati Samaj a	t 2, Raj		
		Niwas Marg, Civil Line, Delhi				
2.	Type of occupancy:-	Residential, Sub Division-A-1				
		floors (total 98 Guest				
		Ground floor (18 guest room + reception + 01 dormitory), 1 <sup>st</sup> floor (27 guest rooms + 01 dormitory),				
		2 <sup>nd</sup> floor (32 guest rooms + 02 dormitory), and 3 <sup>rd</sup> floo				
			+ 05 dormitory)			
3.	Type of case:-	Renewal				
4.	Details of previous FSC:-	No. F6/DFS/MS/GH/2015/NDZ/1837 dated				
		13/10/15.				
	Fire safety directives No	N/A				
	6. Date of inspection: 08/12/18					
	Name of the inspecting officer		Kumar Sharma (AD	OO/CC)		
8.	Name & designation of officer		~			
	From the building side:-	Sh. Nilesh	Shah			
- 5	Year of construction:-	1988	N /T ! /TT 1 / 100	/10/2010		
10	. Applicant's letter No:-	4553/Joint. C.I	P. /Lic.(H) dated 09/	10/2018		
				Old Case		
S.No.	Minimum Standards on fire	Requirement	Provided at site	Remarks		
	Prevention and fire safety	Existing fire		MR/NMR		
	U/R 33	safety				
4	A D THE	arrangements				
1.	Access to Building	37/4	10	) (D)		
	1) Road width	N/A	12 mtr.	MR		
	2) Gate width	N/A	3.65 mtr.	MR		
	3)Width of internal road	N/A	3.65 mtr.	MR		
2.	Number, Width Type & Ar	rangement of E	xits			
	A. Number of staircases	02.11	02.21	MD		
	1. Upper floors	02 Nos.	02 Nos.	MR		
	2. Basements	N/A	N/A	N/A		
	B. Width of staircase	0.00	1.26 to 1.36 mtr.	MD		
	1. Upper floors	0.80 mtr.	1.20 to 1.30 mtr.	MR		
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits		4, 1			
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	N/A	N/A	N/A		
	1		1	1		

N/A

N/A

N/A

N/A

N/A

N/A

30 ACPH

1 mtr.

N/A

1 mtr.

N/A

N/A

N/A

N/A

N/A

N/A

N/A

MR

N/A

N/A

N/A

N/A

N/A

N/A

staircase to terrace

2) Sealing of electrical shafts

Smoke Management System

3) Fire rating of shaft door

E. Width of corridor

Compartmentation 1) Fire check door

4) Water curtain

5) Fire Dampers

1) Basements

F. Door size

3.

4.

	2) Upper floors	12 a/c per hour	Natural Ventilation	MR		
5.	Fire Extinguishers	(5)				
	1) Total numbers	48 Nos.	48 Nos.	MR		
	2) Types	ABC & CO2		MR		
	3) ISI marking	Required	Provided	MR		
6.	First-Aid Hose Reel	1				
	1) Total number of eachfloor	02	02	MR		
	2) Length of hose reel hose	30 m	30 m	MR		
	3) Nozzle diameter	05 mm	05 mm	MR		
7.	Automatic Fire Detection & Alarming System					
	1) Type of detectors	N/A	N/A	N/A		
	2) Location of main panel	N/A	N/A	N/A		
	3) Location of repeater panel	N/A	N/A	N/A		
	4) Alternate source of power	N/A	N/A	N/A		
	5) Hooter's Location	N/A	N/A	N/A		
8.	MOEFA	N/A	N/A	N/A		
9.	Public Address System	Required	Provided	MR		
10.	Automatic Sprinkler System	I .				
	1) Basement	N/A	N/A	N/A		
	2) Upper floors	N/A	N/A	N/A		
	3) Sprinkler above false	N/A	N/A	N/A		
	ceiling					
11.	Internal Hydrants	_				
	1) Size of riser/down-comer	N/A	100 mm	N/A		
	2) Number of hydrants per	N/A	02	N/A		
	floor		v . * *			
	3) Hose box	N/A	02	N/A		
12.	Yard Hydrants					
	1) Total number of hydrants	N/A	N/A	N/A		
	2) Hose box	N/A	N/A	N/A		
13.	Pumping Arrangement					
	1) Ground level	N/A	N/A	N/A		
	a) Discharge of main pump	N/A	N/A	N/A		
	b) Head of main pump	N/A	N/A	N/A		
	c) Number of main pun	1	N/A	N/A		
	d) Jockey pump out put	: N/A	N/A	N/A		
	e) Jockey pump head	N/A	N/A	N/A		
	f) Stand by pump outpu		N/A	N/A		
	g) Stand by pump head		N/A	N/A		
	h) Auto starting/Manua stopping	l N/A	N/A	N/A		
	2) Terrace level		а п	The state of the s		
	a) Discharge of pump	450 LPM	450 LPM	MR		
1	b) Head of pump	30 mtr	30 mtr	MR		
	o) Head of pullip					
	c) Power supply	Required	Provided	MR		

hu

	CA TVI 4 CA CON I	ive Fighting		
14.	Captive Water Storage for F	N/A	N/A	N/A
	Under ground tank     capacity	IN/A	14/14	2.00
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	25,000 ltr.	25,000 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
10.	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	Required	Provided	MR
	d) Fireman's switch	Required	Provided	MR
	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Sys Risk, if any:	stem for Prote	ction of special	NA

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2015/NDZ/1837 dated 13/10/2015 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

TOZ. D. FIM.

(F.O. M. SCELL WITHER

OF D. HW is put up of