## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI-110001

No. F.6/DFS/MS/2018/SZ/ 37

## FIRE SAFETY CERTIFICATE

Issued on at New Delhi by

(Vipin Kental) Chief Fire Officer Ph: 011-23412225

Copy to: -

1. Officer-in-Charge, "Shaurya" CRPF Officer's Institute, Plot No-8, Institutional Area, C-9, Vasant Kunj, New Delhi-110070

## Conditions for the validity of Fire Safety Certificate: -

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire fighting system.
- 4. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of DFS Rules, 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.

	INSPECTIO	N REPURI	PF Officers Institute, Plot	Vo-08.			
1	Name & Address of the Building	"SHAURYA" CR	C O Vacant Kuni New D	elhi-70			
		Institutional Area, C-9, Vasant Kunj, New Delhi-70					
2	Type of Occupancy	Assembly Building	anly) Block-2 not constru	icted			
3	Building Comprised of	B+G+01 (Block-1 only), Block-2 not constructed					
4	Type of Case	Renewal	/SZ/558 dated 08-04-2016				
5	Details of Previous NOC	F6/DFS/MS/2010/	003/1524 dated 09-07-200	3			
6	Fire Safety Directives Letter No		003/1324 dated 07 07 200				
7	Date of Inspection	10-12-2018 Mehmood, ADO (SJ)					
8	Name of the Inspecting Officers	Sh. Raj Kumar, (S	(SI/CRDE)				
9	Name & Designation of Officers	Sh. Raj Kumai, (S	5.1./CRT 1 )				
	from the building side	2008					
10	Year of construction	Outdoor Diary No	15566 dated 26-10-2018				
11	Applicant letter No.	Outdoor Diary No. 15566 dated 26-10-2018  Old NOC Provided at Site Remark					
No.	Minimum standards on Fire Prevention	Requirement		MR/NMR			
	and Fire Safety U/R 33	Requirement					
1	Access to Building.	06 mtr	12 mtr	MR			
9440	<ul> <li>Road width</li> </ul>	5 mtr	Provided	MR			
	Gate width	-NA-	-NA-	-NA-			
	Width of internal road						
2	Number, width, type & arrangement of exits.						
	a) Number of Staircase	03 + 01 ramp	Provided	MR			
	Upper floors.		Provided	MR			
	Basement floor.	04 + 01 ramp	Tiovided				
	b) Width of Staircase		1.5m each & 1.2m ramp	MR			
	Upper floors	1.5m	200 March 1900 - 2-0 Carolina (1900 - 1900 -				
	Basement floor	1.5m / 1.25m	1.5m (03), 1.25m (01) &	MR			
		1.51117 1.25111	5.9m ramp				
	c) Protection of exits			) (D)			
	Fire check door	Required	Provided	MR			
	> Pressurization	-NA-	-NA-	-NA-			
	1 1 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	One	Provided	MR			
		-NA-	-NA-	-NA-			
		1.5m	1.5m (04no. in auditorium	) MR			
2							
3	Compartmentation.  • Fire check door.	Required	Provided	MR			
	<ul><li>Fire check door.</li><li>Sealing of electrical shafts.</li></ul>	Required	Provided	MR			
	T' C-l-A door	-NA-	-NA-	-NA			
	<ul><li>Fire rating of shall door.</li><li>Water curtain</li></ul>	-NA-	-NA-	-NA			
	water curtain     Fire dampers.	-NA-	-NA-	-NA			
A	Smoke Management system.						
4.	Basement	30 ACPH	Exhaust fan provided	MR			
		12 ACPH	Exhaust fan provided				
	Upper floors	12110111	1				
5.	Fire Extinguishers.	30 Nos	34 Nos	MF			
	Total numbers	ABC / CO2	W.CO2 & CO2	MF			
	• Types		Provided	MF			
	ISI Marking	ISI marked	Tiovided				
6.	First Aid Hose Reels.	02 Noc	Provided	MI			
	Total numbers on each floor.	02 Nos	Provided	MI			
	<ul> <li>Length of hose-reel hose.</li> </ul>	30 mtr	,				
	Nozzle Diameter	5 mm	Provided	MI			

7	Automotic fine detection for clauming quatern			
/	Automatic fire detection & alarming system.	Required	Heat, Smoke & Beam	MR
	Type of detectors  Leasting of Main Panel	Required	Ground floor	MR
	Location of Main Panel	Required	Fire Control Room	-NA-
	Location of Repeater Panel	Required	Provided On each floor	MR MR
	<ul><li>Alternate source of power</li><li>Hooter's location</li></ul>	Required		
0		Required	Provided	MR
<b>8. 9.</b>	MOEFA  Dublic Address System	Required	Provided	MR
10.	Public Address System Automatic Sprinkler System	Required	Flovided	IVIIX
10.	Basement	Required	Provided	MR
		Required	Provided	MR
	Upper floors     Sprinkler shows false spiling.	Required	Provided	MR
11	Sprinkler above false ceiling	Required	Provided	IVIIX
11.	Internal Hydrants.	150 mm	Provided	MR
	Size of Riser/Down-comer	02 Nos	Provided	MR
	Number of Hydrant per floor			
10	Hose box.	02 Nos	Provided	MR
12.	Yard Hydrants.	D 1	Duox: 1 - 1	MD
	Total number of hydrants.	Required	Provided	MR
	Hose box.	Required	Provided	MR
13.	Pumping arrangements.			
	Ground Level			
	Discharge of main pump.	2850 LPM	2280 & 2250 LPM	MR
	Head of main pump.	70m	70m	MR
	Number of main pumps.	01 No	02 Nos	MR
	Jockey Pump output.	180 LPM	180 LPM	MR
	Jockey Pump head.	70m	70m	MR
	<ul><li>Standby Pump output.</li><li>Standby Pump head.</li></ul>	2850 LPM	2850 LPM	-NA
	<ul><li>Auto Starting / Manual Stopping.</li></ul>	70m	70m	-NA
	> Pump house access.	Required	Provided	MR
	*	Required	Provided	MR
	Terrace Level			
	Discharge of pump.	-NA-	-NA-	-NA
	> Head of pump.	-NA-	-NA-	-NA
	<ul><li>Power supply.</li><li>Auto starting of pump.</li></ul>	-NA-	-NA-	-NA
1.4		-NA-	-NA-	-NA
14.	Captive water storage for fire fighting.	0.00.000 1		) (D
	Underground tank capacity.	2,00,000 Ltr	Provided	MR
	> Draw-off connection.	Required	Provided	MR
	Fire Service Inlet.	Required	Provided	MR
	Access to tank.	Required	Provided	MR
15	Overhead tank capacity.  Exit Signage.	10,000 Ltr	20,000 Ltr	MR
15. 16.	Exit Signage. Provision of Lifts.	Required	Provided	MR
10.		NTA	NT A	»T.A
	Pressurization of lift labby	-NA-	-NA-	-NA
	<ul><li>Pressurization of lift lobby.</li><li>Communication in lift car.</li></ul>	-NA-		-NA
	TO SECOND AND A MANY ASSESSMENT AND A SECOND ASSESSMENT AND A SECOND ASSESSMENT ASSESSME	Required	Provided	MR
1.09	• Fireman's switch.	Required	Provided	MR
	• Lift signage.	Required	Provided	MR
17.	Standby Power Supply	Required	Provided	MR
18.	Refuge Area	771	·	
	Total area	-NA-	-NA-	-NA
	<ul> <li>Location</li> </ul>	-NA-	-NA-	-NA

"SHAURYA" CRPF Officers Institute at Plot No-08, Institutional Area, C-9, Vasant Kunj, New Delhi

19.	Fire Control Room.			
	Detector system panel.	Required	Provided	MR
	Flow switch panel.	-NA-	-NA-	-NA-
	PA system panel.	Required	Provided	MR
	Battery backup.	Required	Provided	MR
	Building floor plan.	-NA-	-NA-	-NA-
20.	Special Fire Protection System for the Protection of special Risk, if any.			-NA-

The fire protection system provided in the building/ premises were tested, checked at random and found functional at the time of inspection. Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No. F. 6/DFS/MS/2016/SZ/558 dated 08/04/2016, renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: Mehmood Design: ADO (SJ)

"SHAURYA" CRPF Officers Institute at Plot No-08, Institutional Area, C-9, Vasant Kunj, New Delhi

DO (SD

9.67 letter lurry for Signapur Sean