GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/NDZ/2019/ 33/0

FIRE SAFETY CERTIFICATE

Issued -- at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Ofe,

Copy to:-

The Project Manager (Electrical),
Office of Project Manager (E),
North Delhi Municipal Corporation,
Floor No. 22, E-1 Block, Dr. SPM Civic Center, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION	NC	REP	ORT

1. Name & address of the building: Civic Center, E – 1, J.L.N. Marg, New Delhi.

2. Type of occupancy : Business Building

3B + Gr.+ 27 upper floor

3. Type of case:-: Renewal

4. Details of previous FSC : F6/DFS/MS/2015/877 dated 29/05/2015

5. Fire safety directives No. : N/A 6. Date of inspection:-21/01/19

7. Name of the inspecting officer :Sh. M.K. Sharma ADO/CC

8. Name & designation of officer From the building side

0	From the building side		h Kumar JE (E)				
9.	Year of construction	: 2010					
10	. Applicant's letter No	: D/PM (Ele	ct.)CC/18-19/231d	ated 29/08/1			
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/Exi sting fire safety arrangements	Provided at site	Remarks MR/NMR			
•	Access to Building		2				
	1) Road width	12 mtr.	25 mtr.	MR			
	2) Gate width	4.5 mtr.	06 mtr.	MR			
	3) Width of internal road	06 mtr.	06 mtr.	MR			
2.	Number, Width Type & Arra		Too mit.	IVIIX			
	A. Number of staircases						
	1. Upper floors	02 Nos.	02 Nos.	MR			
	2. Basements	02 Nos.	02 Nos.	MR			
	B. Width of staircase						
	1. Upper floors	1.25 mtr.	1.25 mtr. & 1.50 mtr.	MR			
2.	2. Basements	1.25 mtr.	1.25 mtr. & 1.50 mtr.	MR			
	C. Protection of exits						
	1. Fire check door	Required	Provided	MR			
	2. Pressurization	Required	Provided	MR			
D. No. of continuous staircase to terrace		02	02				
	E. Width of corridor	1.50 mtr.	1.5 mtr.	MR			
	F. Door size	1.25 mtr.	1.25 & 1.50 mtr.	MR			
	Compartmentation			*			
	1) Fire check door	Required	Provided	MR			
	2) Sealing of electrical shafts	Required	Provided	MR			
	3) Fire rating of shaft door	2 hrs.	Provided	MR			
	4) Water curtain	Required	Provided	MR			
	5) Fire Dampers	Required	Provided MR				
	Smoke Management System 1) Basements 30 ACPH Provided MP						
-	2) Upper floors	30 ACPH	Provided	MR			
i,	Fire Extinguishers			MR			
	1) Total numbers						
-	2) Types	120 Nos.	300 Nos.	MR			
		ABC, CO2, W.CO2 & DCP	ABC, CO2, W.CO2 & DCP	MR			
	3) ISI marking	Required	Provided	MR			
	First-Aid Hose Reel	00					
+	1)Total number	02	02	MR			
-	2) Length of hose reel hose3) Nozzle diameter	30 m	30 m 5 mm	MR			
				MR			

7.	Automatic Fire Detection & A	Alarmir	ng System		***	200
	1) Type of detectors	Requ	iired	Prov	rided	MR
	2) Location of main panel	Gr. F	Floor	Prov	rided	MR
	3) Location of repeater panel	Requ	iired	Prov	rided	MR
	4) Alternate source of power	Requ	iired	Prov	rided	MR
	5) Hooter's Location	Requ	iired	Prov	rided	MR
8.	MOEFA	Requ	iired	Prov		
9.	Public Address System	Requ	iired	Pro	vided	MR MR
10.	Automatic Sprinkler System					
	1) Basement	Requ	iired	Prov	rided	MR
	2) Upper floors	Requ	ired	Prov	rided	MR
	3) Sprinkler above false	Pegu	Required		rided	MR
	ceiling	Requ	ineu			
11.	Internal Hydrants					
	1) Size of riser/down-comer	150 N	MM	150	MM	MR
	2) Number of hydrants per	02	02			MR
	Basement		*		¥	
	3) Hose box each floor	02		02		MR
12.	Yard Hydrants					
	1) Total number of hydrants	02	8	02		MR
1.0	2) Hose box	02		02		MR
13.	Pumping Arrangement			×		
	1) Ground level					
	a) Discharge of ma	in	2850 LPM	ſ	2850 LPM	MR
	pump		_		V	
	b) Head of main pu		150 mtr.	•	150 mtr.	MR
	c) Number of main		02		02	MR
	d) Jockey pump ou		180 LPM		180 LPM	MR
	e) Jockey pump he	ad	70, 50, 110	0 mtr.	70, 50, 110 mtr.	MR
	f) Stand by pump of	output	2850 LPM	[2850 LPM	MR
	g) Stand by pump h	nead	150mtr.		150mtr.	MR
	h) Auto starting/Ma		Required		Provided	MR
	stopping		1			1,11
	2) Terrace level					
	a) Discharge of pur	np	N/A		N/A	N/A
	b) Head of pump	•	N/A	,	N/A	N/A
	c) Power supply		N/A		N/A	N/A
	d) Auto starting of	pump	N/A		N/A	N/A
14.	Captive Water Storage f				1,	14/11
	Under ground tan capacity	nk	3,00,000 ltr	•	3,00,000 ltr.	MR
	a) Draw-off connec	tion	Required		Provided	MR
	b) Fire service inlet		Required		Provided	MR
	c) Access to tank		Required		Provided	MR
	d) Over head tank capacity		50,000 ltr.		50,000 ltr.	MR
15.	Exit Signage.		Required	×.	Provided	MR
16.	Provision of Lifts.					IVIIC
	a) Pressurization of shaft		Required		Provided	MR
	b) Pressurization of lobby	lift	Required		Provided	MR
	c) Communication	in	Required		Provided	MR



	1 1	57	1
1		-	

	d) Fireman's switch	Required	Provided	MR
	e) Lift signage	Required	Provided	MR
7.	Stand by Power Supply	Required	Provided	MR
8.	Refuge Area			
	Total area location	7,11,16,21 & 26 floor	Provided	MR
19.	Fire Control Room	Required	Provided	MR
	a) Detector system panel	Required	Provided	MR
	b) Flow switch panel	Required	Provided	MR
	c) PA system panel	Required	Provided	MR
	d) Battery backup	Required	Provided	MR
	e) Building floor plan	Required	Provided	MR
20.	Special Fire Protection Syste any:	m for Protection of s	pecial Risk, if	MR

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/2015/NDZ/877 dated 20/05/2015 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma

Designation: - ADO (CC)

Mrscell F7 M.
W30/1
F.T. letter is put up for sign

CRO(NDZ) MISCH 46/2