GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

Fax No. 011-23412593, Ph. 011-23412225

No. F.6 DFS/MS/School/2019/SZ/ 359

Dated: 8/2/19

FIRE SAFETY CERTIFICATE

Certified that the Glory Public School located at Pocket - B, Sarita Vihar, New Delhi-110076 comprised of ground plus one upper floor only was issued FSC by this department vide letter No. F.6/DFS/MS/School/2015/SZ/1767 dated 01/10/2015. The said premises was re-inspected by officer concerned of this department on 16/01/2019 in presence of Mrs. Bharti Gaur (Admin) and found that school building have deemed complied with the fire prevention and fire safety requirements in accordance with Directorate of Education circular no. F.16//Estate/CC/Fire Safety/2011/3298 to 3398 dated 01.03.2011 issued by Director of Education, Govt. of NCT of Delhi and that the school building is fit for occupancy class "Educational Building" Group-B, effect from the date of issue of this certificate for a period of Three years subject to compliance the conditions below.

Issued on 8/2/19 at New Delhi by

(Vipin Kental)
Chief Fire Officer

Copy to: -

- 1. The Manager, Glory Public School, Pocket B, Sarita Vihar, New Delhi-110076
- 2. Directorate of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi.

Conditions for the validity of Fire Safety Certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of firefighting system.
- 4. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

			ON REPORT Glory Public School	Pocket - R Sarita	Vihar.			
1	Name	e & Address of the Building	Glory Public School	, I UCKCI - D, Dalita	,,			
			New Delhi-110076					
2	Type	of Occupancy	Educational, Group-B	(School)				
3	Buile	ling Comprised of	Ground plus One Upper floors					
		of Case	Renewal 1/2015/07/17/7 4-4-4 01/10/2015					
5	Deta	ils of Previous NOC	F.6/DFS/MS/School/2015/SZ/1767 dated 01/10/2015					
6	Fire Safety Directives Letter No		F.16//Estate/CC/Fire Safety/2011/3298 to 3398 dated					
			01.03.2011					
7	Date	of Inspection						
8	Nam	e of the Inspecting Officers	Mehmood, ADO (SJ) Mrs. Bharti Gaur (Admin)					
9	Name & Designation of Officers		Mrs. Bharti Gaui (Au					
	fron	the building side	1000					
10		r of construction	1998 Nil dated 31/12/2018					
11	Applicant letter No.		As Per Old NOC	Provided at Site	Remarks			
No.	Minimum standards on Fire Prevention		As Per Old NOC	1 TOVICE CONTRACT	MR/NMR			
		Fire Safety U/R 33						
1	Acc	ess to Building.	6 mtr	6 m	MR			
		 Road width 	4.5m	4.5m	MR			
		Gate width	-NA-	-NA-	-NA-			
		Width of internal road						
2	Number, width, type & arrangement of exits.							
	a)	Number of Staircase		Provided 02	MR			
		> Upper floors.	01 No's	-NA-	-NA-			
		Basement floor.	-NA-	-IVA-	1112			
	b)	Width of Staircase		1.07 0.1	MR			
	10)	> Upper floors	1.50m/0.75m	1.27 m &1 m	-NA-			
		Basement floor	-NA-	-NA-	-NA-			
	c)	Protection of exits		T.A.	-NA-			
	-	Fire check door	-NA-	-NA-				
		Pressurization	-NA-	-NA-	-NA-			
	1)	No. of continuous staircase to terrace	01 No	Provided	MR			
	<u>a)</u>	Width of corridor	1.5m	1.90m	MR			
			1m	Provided	MR			
		Door size	8					
3	C	• Fire check door.	-NA-	-NA-	-NA-			
			-NA-	-NA-	-NA-			
		Sealing of electrical shafts. Fire retire of shaft door. The shaft door.	-NA-	-NA-	-NA-			
		Fire rating of shaft door. Water curtain.	-NA-	-NA-	-NA-			
		Water curtain Fire demonstrates	-NA-	-NA-	-NA-			
		• Fire dampers.						
4.	Sı	moke Management system.	30 ACPH	-NA-	-NA-			
		Basement	12 ACPH	-NA-	-NA			
		Upper floors	12110111					
5.	F	i <mark>re Extinguishers.</mark>	15 Nos	15 Nos	MR			
		Total numbers	ABC / CO2	ABC & Co2	MR			
		• Types	ISI marked	Provided	MR			
		ISI Marking	151 marked	Tiovided				
6.	F	irst Aid Hose Reels.	NIA	-NA-	-NA			
		 Total numbers on each floor. 	-NA-		-NA			
		 Length of hose-reel hose. 	-NA-	-NA-	-NA			
			-NA-	-NA-	-NA			

7. A	utomatic fire detection & alarming system.		NIA	-NA-
	Type of detectors	-NA-	-NA-	-NA-
	Location of Main Panel	-NA-	-NA-	-NA-
	Location of Repeater Panel	-NA-	-NA-	-NA-
	Alternate source of power	-NA-		-NA-
	Hooter's location	-NA-	-NA-	-NA-
8. N	MOEFA	-NA-	-NA-	-NA-
	Public Address System	-NA-	-NA-	-NA-
	Automatic Sprinkler System		NIA	-NA-
	Basement	NA-	-NA-	-NA-
	• Upper floors	-NA-	-NA-	-NA-
	Sprinkler above false ceiling	-NA-	-NA-	-11//-
11. I	Internal Hydrants.		NIA	-NA-
	Size of Riser/Down-comer	-NA-	-NA-	
	 Number of Hydrant per floor 	-NA-	-NA-	-NA-
\	Hose box.	-NA-	-NA-	-NA-
12.	Yard Hydrants.			NT A
A. ded 0	Total number of hydrants.	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-NA-
13.	Pumping arrangements.			
15.	Ground Level			7.7.4
	Discharge of main pump.	-NA-	-NA-	-NA-
	Head of main pump.	-NA-	-NA-	-NA-
	Number of main pumps.	-NA-	-NA-	-NA-
	➤ Jockey Pump output.	-NA-	-NA-	-NA-
	➤ Jockey Pump head.	-NA-	-NA-	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump head.	-NA-	-NA-	-NA-
	Auto Starting / Manual Stopping.	-NA-	-NA-	-NA-
	Pump house access.	-NA-	-NA-	-NA-
	Terrace Level			NIA
	Discharge of pump.	-NA-	-NA-	-NA-
	Head of pump.	-NA-	NA-	-NA-
	Power supply.	-NA-	-NA-	-NA-
	Auto starting of pump.	-NA-	-NA-	-NA-
1.4	Captive water storage for fire fighting.			
14.	Underground tank capacity.	-NA-	-NA-	-NA-
	Onderground tank capacity.Draw-off connection.	-NA-	-NA-	-NA-
	Fire Service Inlet.	-NA-	-NA-	-NA-
	Access to tank.	-NA-	-NA-	-NA-
	Overhead tank capacity.	-NA-	-NA-	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
10.	Pressurization of lift shaft.	-NA-	-NA-	-NA-
	Pressurization of lift lobby.	-NA-	-NA-	-NA
	Communication in lift car.	-NA-	-NA-	-NA
	• Fireman's switch.	-NA-	-NA-	-NA
	• Lift signage.	-NA-	-NA-	-NA
17.	Standby Power Supply	-NA-	-NA-	-NA

18.	Refuge Area					
	Total area	-NA-	-NA-	-NA-		
	• Location	-NA-	-NA-	-NA-		
19.	Fire Control Room.					
	 Detector system panel. 	-NA-	-NA-	-NA-		
	• Flow switch panel.	-NA-	-NA-	-NA-		
	PA system panel.	-NA-	-NA-	-NA-		
	Battery backup.	-NA-	-NA-	-NA-		
	Building floor plan.	-NA-	-NA-	-NA-		
20.	Special Fire Protection System for the	-NA-	-NA-	-NA-		
	Protection of special Risk, if any.	****	1111	-INA-		

The Fire protection systems provided in the premises were checked / operated at random and found functional at the time of inspection.

Keeping in view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the DOE circular, FSC issued vide letter No. F.6/DFS/MS/School/2015/SZ/1767 dated 01/10/2015renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: Mehmood Design: ADO (SJ)

DO (8D)
31/1/13

Dy. 020(52)

Date 37-1-19 #

Cho of

m. scell

F7/07

4/2

Searc

A. B. T Lelm smug

212 19