GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No.F6/DFS/MS/School/2019/NDZ/ 526

Dated: 14/3/18

FIRE SAFETY CERTIFICATE

Issued on....at New Delhi by

(Sunil Chawdhary)
Dy. Chief Fire Officer

6 LC

To,

The Manager, M/s National Victor Public School C-Block, DDA Colony, West Gorakh Park, Shahdara, Delhi-110032

Copy:-

 The Dy. Director of Education, B-Block Yamuna Vihar, Delhi-110053

CONDITIONS

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form 'J' [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry.
- 8. Basement shall be used as per BBL.

Doent

1. Name & address of the building

: National Victor Public School,

C-Block, DDA Colony, West Gorakh Park,

Shahdara, Delhi-110032

2. Building is comprised of

: Basement plus Ground plus one upper floor

3. Type of Occupancy

: Educational

4. Type of Case

: Renewal

5. Details of Previous NOC letter

: F6/DFS/MS/School/2016/NDZ/263 dt 18/02/16

6. Fire Safety direction letter No

: Circular 2005 issued by DoE

7. Date of Inspection

: 22/02/2019

8. Name of the Inspecting officers

: ADO Vijay Bahadur

9. Name and designation of Officer

from the building side

: Mr. Aashish (Teacher)

10. Year of Construction

: 2003-2004

11. Applicant's letter No

: NVPS/18-19/Jan/017, Dated- 01/02/19

| Sr. No. | Minimum Standards on Fire Prevention and Fire Safety U/R33 | Circular Requirement | Provided at Site | Remarks MR/NMF | | | |
|------------|--|-------------------------|----------------------|-------------------|--|--|--|
| 01 | Access to Building. | rtoquiiomont | | 1011 (71 (1011 | | | |
| | Road width | 06 mtr. | 06 mtr. | MR | | | |
| | Gate width | N/A | N/A | N/A | | | |
| | Width of internal road | N/A | N/A | N/A | | | |
| 02 | Number, Width, Type and Arrangement of Exits. | | | | | | |
| | a. Number of Staircases | | | | | | |
| | Upper floor | 01 Nos. | 01 Nos. | MR | | | |
| | Basement | 01+ 01 EE | 01+ 01 EE | MR | | | |
| | b. Width of Staircases | | | | | | |
| | Upper floor | 1.50 mtr. | 1.55 mtr | MR | | | |
| | Basement | 1.25 mtr | 1.55 mtr & 0.80 mtr | MR | | | |
| | c. Protection of exits | - N | | | | | |
| | Fire check door | N/A | N/A | N/A | | | |
| | Pressurization | N/A | N/A | N/A | | | |
| | d. No. of Continuous Staircases to Terrace | 01Nos. | 01 Nos. | MR | | | |
| | e. Width of Corridor | 1.50 mtr. | 1.50 mtr. | MR | | | |
| | f. Door Size | 01 mtr. | 01 mtr. | MR | | | |
| 03 | Compartmentation. | | | | | | |
| | Fire check door | N/A | N/A | N/A | | | |
| | Sealing of electrical shafts | N/A | N/A | N/A | | | |
| | Fire rating of shaft door | N/A | N/A | N/A | | | |
| | Water curtain | N/A | N/A | N/A | | | |
| | Fire dampers | N/A | N/A | N/A | | | |
| 04 | Smoke Management System. | | | | | | |
| | Basement | N/A | N/A | N/A | | | |
| | Upper floor | N/A | N/A | N/A | | | |
| 05. | Fire Extinguishers. | | | | | | |
| | Total numbers | 06 nos. | 06 nos. | MR | | | |
| | Types | ABC /CO ₂ | ABC /CO ₂ | MR | | | |
| | IS marking | ISI marked | ISI marked | MR | | | |

| 06 | First-Aid-Hose Reels. | | | | | | |
|----|--|------------|-------------|-----|--|--|--|
| | Total numbers on each floor | 01 No. | 01 No. | MR | | | |
| | Length of hose reel hose | 30 mtr. | 30 mtr. | MR | | | |
| | Nozzle diameter | 05 mm | 05 mm | MR | | | |
| 07 | Automatic Fire Detection and Alarming System. | | | | | | |
| | Type of detectors | N/A | N/A | N/A | | | |
| | Location of main panel | N/A | N/A | N/A | | | |
| | Location of repeater panel | N/A | N/A | N/A | | | |
| | Alternate source of power | N/A | N/A | N/A | | | |
| | Hooter's location | N/A | N/A | N/A | | | |
| 08 | MOEFA | N/A | Provided | MR | | | |
| 09 | Public Address System. | N/A | Provided | MR | | | |
| 10 | Automatic Sprinkler System. | | | | | | |
| | Basement | Required | Provided | MR | | | |
| | upper floor | N/A | N/A | N/A | | | |
| | sprinkler above false ceiling | N/A | N/A | N/A | | | |
| 11 | Internal Hydrants | | | | | | |
| | size of riser/down-comer | 100 mm | 100 mm | MR | | | |
| | Number of hydrants per floor | 01 no. | 01 no. | MR | | | |
| | Hose box | 01 no. | 01 no. | MR | | | |
| 12 | Yard Hydrants. | | | | | | |
| | Total number of hydrants | N/A | N/A | N/A | | | |
| | Hose box | N/A | N/A | N/A | | | |
| 13 | Pumping Arrangements. | | | | | | |
| | > Ground Level | | | | | | |
| | Discharge of main pump | N/A | N/A | N/A | | | |
| | Head of main pump | N/A | N/A | N/A | | | |
| | Number of main pumps | N/A | N/A | N/A | | | |
| | Jockey pump out put | N/A | N/A | N/A | | | |
| | Jockey pump head | N/A | N/A | N/A | | | |
| | Standby pump out put | N/A | N/A | N/A | | | |
| | Standby pump head | N/A | N/A | N/A | | | |
| | Auto starting /manual stopping | N/A _ | N/A | N/A | | | |
| | Pump house access | N/A | N/A | N/A | | | |
| | > Terrace Level | | | | | | |
| | Discharge of pump | 450 Lpm. | 450 Lpm. | MR | | | |
| | Head of the pump | 40 M | 40 M | MR | | | |
| | Power supply | Required | Provided | MR | | | |
| | Auto Starting of pump | Required | Provided | MR | | | |
| 14 | Captive Water Storage for Fire Fighting. | | | | | | |
| | Underground tank capacity | N/A | N/A | N/A | | | |
| | Draw-off connection | N/A | N/A | N/A | | | |
| | Fire service inlet | N/A | N/A | N/A | | | |
| | Access to tank | N/A | N/A | N/A | | | |
| | Overhead tank capacity | 5,000 Ltr. | 10,000 Ltr. | MR | | | |
| 15 | Exit Signage. | Required | Provided | MR | | | |

| 16 | Provision of Lifts. | | | *** |
|----|--|-----|-----|-----|
| | Pressurization of lift shaft | N/A | N/A | N/A |
| | Pressurization of lift lobby | N/A | N/A | N/A |
| | Communication in lift car | N/A | N/A | N/A |
| | Firemen's grounding switch | N/A | N/A | N/A |
| | Lift signage | N/A | N/A | N/A |
| 17 | Standby Power Supply | N/A | N/A | N/A |
| 18 | Refuge Area. | | | |
| | Total area | N/A | N/A | N/A |
| | Location | N/A | N/A | N/A |
| 19 | Fire Control Room | | | |
| | Detector system panel | N/A | N/A | N/A |
| | Flow switch panel | N/A | N/A | N/A |
| | PA system panel | N/A | N/A | N/A |
| | Battery backup | N/A | N/A | N/A |
| | Building floor plans | N/A | N/A | N/A |
| 20 | Special Fire Protection Systems for Protection of Special Risks, if any: | N/A | N/A | N/A |

The fire protection systems provided in the building were tested/checked and found functional at the time of inspection.

Keeping in view the deemed compliance of the minimum standards on fire prevention and fire safety required under circular No. 262-232 dated 17/01/2005 issued by Director of Education, it is recommended to renew Fire Safety Certificate.

Signature of the Inspecting Officer

Name

- Vijay Bahadur

Designation

- A.D.O

DY CHOINDY

Stor. F.T. Letter is put up far your trived singulature Blease.

Dy CF.O (NDZ)

Dynh.L.