## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/GH/2019/ 72/

Dated :- 5-1-1-9-

## **FIRE SAFETY CERTIFICATE**

Certified that the Priya Palace Guest Houe located at 8484-8485, Arya Nagar, Pahar Ganj, New Delhi comprised of Ground + 04 Upper floors, Ground floor (Reception + 01 guest rooms + 01 Office), 1st floor to 4th floor (05 guest rooms at each floor), total 21 guest rooms was granted **FSC** by this department No.F6/DFS/MS/GH/2016/NDZ/361 dated 04/03/16. The premises was re-inspected by the officer concerned of this department on 30/03/19 in the presence of Sh. Ashok and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 21 guest rooms only with effect from ---- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -----at New Delhi by.

(Sunil Chowdhary)
Dy. Chief Fire Officer
Delhi Fire Service

## Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.
- 2. The Manager,
  Priya Palace Guest Houe at 8484-8485, Arya Nagar, Pahar Ganj, New Delhi.
- 3. The Commissioner North MCD.....with a request to get the height of the building measured and intimate to this department for taking further action at our end, if any.

## Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 9. Any flammable material for interior decoration is prohibited.

|       | DI  | CDECENO  |   |                   |  |  |  |  |
|-------|---|--|---|-------------------|--|--|--|--|
| 1.    | Name & address of the build   | SPECTION REI   | PORT                                    |                   |  |  |  |  |
|       | 1. Name & address of the building Priya Palace Guest Houe at 8484-8485, |  |   |                   |  |  |  |  |
| 2.    | Type of occupancy:-   | Arya Nagar, Pahar Ganj, New Delhi  |   |                   |  |  |  |  |
|       | -yr or occupancy.   | Residential, Sub Division-A-1 Gr. + 04 Upper floors (total 24 Guest rooms) |   |                   |  |  |  |  |
|       |   | Ground floo  | or (Reception + 02 gues                 | t rooms + 01      |  |  |  |  |
|       |   | Office), 1st   | floor to 4 <sup>th</sup> floor (05 gue  | est rooms at each |  |  |  |  |
| 2     | T   | floor),  | (** 8**                                 | ost rooms at each |  |  |  |  |
|       | Type of case:-  | Renewal  |   |                   |  |  |  |  |
| 4.    | No. F6/DFS/MS/GH/2016/NDZ/361 dated                                     |  |   |                   |  |  |  |  |
| 5     | Eine gefete 1:  | 04/03/16.  |   |                   |  |  |  |  |
| 6     | Fire safety directives No   | N/A  |   |                   |  |  |  |  |
| 7     | Date of inspection:   | 30/03/19   |   |                   |  |  |  |  |
| 8     | Name of the inspecting office   | er:- Sh. Mano  | j Kumar Sharma (A                       | ADO/CC)           |  |  |  |  |
| 0.    | Name & designation of office From the building side:-                   |  |   |                   |  |  |  |  |
| 9     | Year of construction:-  | Sh. Ashol  | <b>K</b>                                |                   |  |  |  |  |
|       | Applicant's letter No:-   | 2002   |   |                   |  |  |  |  |
| 10.   | - Approved 5 letter 140:-   | 590/Jt. C.P  | ./Lic. (H) dated 13.02                  |                   |  |  |  |  |
| S.No. | Minimum Standards on fire   | Dogwinson  | D 111                                   | Old Case          |  |  |  |  |
|       | Prevention and fire safety  | Requirement Existing   | Provided at site                        | The second second |  |  |  |  |
|       | U/R 33  | Existing   | PSS                                     | MR/NMR            |  |  |  |  |
| 1.    | Access to Building  |  |   |                   |  |  |  |  |
|       | 1) Road width   | N/A  | 04 mtr.                                 | 1.00              |  |  |  |  |
|       | 2) Gate width   | N/A  | N/A                                     | MR                |  |  |  |  |
|       | 3)Width of internal road  | N/A  | 100000000000000000000000000000000000000 | MR                |  |  |  |  |
| 2.    | Number Width Type & A   |  | N/A                                     | N/A               |  |  |  |  |
| -     | Number, Width Type & Arrangement of Exits  A. Number of staircases      |  |   |                   |  |  |  |  |
|       | 1. Upper floors   | 01 Nos.  | 01.31                                   |                   |  |  |  |  |
|       | 2. Basements  | N/A  | 01 Nos.                                 | MR                |  |  |  |  |
|       | B. Width of staircase   | IN/A   | N/A                                     | N/A               |  |  |  |  |
|       | 1. Upper floors   | 0.80 mtr.  | 1.25.16                                 | 1                 |  |  |  |  |
|       |   | 0.80 mtr.  | 1.25 Mtr.                               | MR                |  |  |  |  |
|       | 2. Basements  | N/A  | N/A                                     | N/A               |  |  |  |  |
|       | C. Protection of exits  |  |   | 11111             |  |  |  |  |
|       | 1. Fire check door  | N/A  | N/A                                     | N/A               |  |  |  |  |
|       | 2. Pressurization   | N/A  | N/A                                     | N/A               |  |  |  |  |
|       | D. No. of continuous  | 01   | 01                                      | MR                |  |  |  |  |
| -     | staircase to terrace  |  | 01                                      | IVIIX             |  |  |  |  |
|       | E. Width of corridor  | N/A  | N/A                                     | N/A               |  |  |  |  |
|       | F. Door size  | 1 mtr.   | 1 mtr.                                  | MR                |  |  |  |  |
| 3.    | Compartmentation  |  | 1 11111.                                | IVIIX             |  |  |  |  |
|       | 1) Fire check door  | N/A  | N/A                                     | N/A               |  |  |  |  |
|       | 2) Sealing of electrical shafts   | N/A  | N/A                                     | N/A               |  |  |  |  |
|       | 3) Fire rating of shaft door  | N/A  | N/A                                     | N/A               |  |  |  |  |
|       | 4) Water curtain  | N/A  | N/A                                     | N/A<br>N/A        |  |  |  |  |
|       | 5) Fire Dampers   | N/A  | N/A                                     | N/A<br>N/A        |  |  |  |  |
|       | Smoke Management System   | 1  | 11//1                                   | IN/A              |  |  |  |  |
|       | 1) Basements  | 30 ACPH  | N/A                                     | N/A               |  |  |  |  |
|       | 2) Upper floors   | 12 a/c per   |   | MR                |  |  |  |  |
|       |   | hour   | ratural                                 | IAIL              |  |  |  |  |
|       |   | -10 012  |   |                   |  |  |  |  |

| 5.  | Fire Extinguishers                        |     |          | 1   |                |     |      |  |
|-----|---|-----|----------|-----|----------------|-----|------|--|
|     | 1) Total numbers 10                       |     | Nos.     |     | Nos.           | M   | IR   |  |
|     | 2) Types                                  | AE  | 3C & CO2 | A   | BC & CO2       | M   | IR   |  |
|     | 3) ISI marking                            | Re  | quired   | Pı  | rovided        | M   | IR . |  |
| 6.  | First-Aid Hose Reel                       | ,   |          |     |                |     |      |  |
|     | 1) Total number of eachfloor 0            |     |          | 0   | /              |     | IR.  |  |
|     | 2) Length of hose reel hose               |     | mtr.     | 30  | 0 mtr.         | N   | IR.  |  |
|     | 3) Nozzle diameter                        | 05  | mm       | 0:  | 5 mm 🥒         | N   | IR.  |  |
| 7.  | Automatic Fire Detection & Alarming Syste |     |          |     |                |     |      |  |
|     | 1) Type of detectors                      | N/  | A        | N/A |                | N/A |      |  |
|     | 2) Location of main panel                 | N/  | A        | N/A |                | -   | [/A  |  |
|     | 3) Location of repeater panel             |     |          |     | /A             | 1   | [/A  |  |
|     | 4) Alternate source of power              |     |          | -   | /A             |     | [/A  |  |
|     | 5) Hooter's Location                      | N/  | A        | N   | /A             | N   | I/A  |  |
| 8.  | MOEFA                                     | N/  | N/A      |     | N/A            |     | I/A  |  |
| 9.  | Public Address System                     |     | A        | N/A |                | N   | Ī/A  |  |
| 10. | Automatic Sprinkler System                | m   |          |     |                |     |      |  |
|     |   |     | 'A       | N/A |                |     | I/A  |  |
|     | 2) Upper floors                           | N/  | 'A       | N   | N/A            |     | N/A  |  |
|     | 3) Sprinkler above false                  | N/  | 'A       | N   | I/A            | N   | I/A  |  |
|     | ceiling                                   |     |          |     |                |     |      |  |
| 11. | Internal Hydrants                         |     |          |     |                |     |      |  |
|     | 1) Size of riser/down-comer               | N/  | 'A       | N   | I/A            | _   | J/A  |  |
|     | 2) Number of hydrants per                 | N/  | 'A       | N   | I/A            | I   | J/A  |  |
|     | floor                                     |     |          |     | N Constitution |     |      |  |
|     | 3) Hose box                               |     | 'A       | N   | I/A            | I   | J/A  |  |
| 12. | Yard Hydrants                             |     |          |     |                | 1   |      |  |
|     | 1) Total number of hydrants               | N/  |          | _   | I/A            | _   | J/A  |  |
|     | 2) Hose box                               | N/  | /A       | N   | I/A            |     | I/A  |  |
| 13. | <b>Pumping Arrangement</b>                |     |          |     |                |     |      |  |
|     | 1) Ground level                           |     | N/A      |     | N/A            |     | N/A  |  |
|     | a) Discharge of main pump                 | L   | N/A      |     | N/A            |     | N/A  |  |
|     | b) Head of main pum                       | np  | N/A      | ,   | N/A            | 1   | N/A  |  |
|     | c) Number of main p                       |     | N/A      |     | N/A            |     | N/A  |  |
|     | d) Jockey pump out                        |     | N/A      |     | N/A            |     | N/A  |  |
|     | e) Jockey pump head                       |     | N/A      |     | N/A            | -   | N/A  |  |
|     | f) Stand by pump ou                       |     | N/A      |     | N/A            |     | N/A  |  |
|     | g) Stand by pump he                       |     | N/A      |     | N/A            |     | N/A  |  |
|     | h) Auto starting/Man<br>stopping          |     | N/A      |     | N/A            |     | N/A  |  |
| -   | 2) Terrace level                          |     |          |     |                | ,   |      |  |
|     | a) Discharge of pump                      |     | 450 LPM  |     | 450 LPM /      |     | MR   |  |
|     | b) Head of pump                           |     | 30 mtr.  | ·   | 30 mtr.        | /   | MR   |  |
|     | c) Power supply                           |     | Required |     | Provided       |     | MR   |  |
|     | d) Auto starting of p                     | ump | Required |     | Provided       |     | MR   |  |
| a   |   | r   | 1        |     |                |     |      |  |
|     |   |     |          |     |                |     |      |  |

| 14. | Captive Water Storage for                      | Fire Fighting |                |       |
|-----|--|---------------|----------------|-------|
|     | 1) Under ground tank capacity                  | N/A           | N/A            | N/A   |
|     | a) Draw-off connection                         | N/A           | N/A            | N/A   |
| -   | b) Fire service inlet                          | N/A           | N/A            | N/A   |
|     | c) Access to tank                              | N/A           | N/A            | N/A   |
| 1.  | d) Over head tank capacity                     | 5000 ltr.     | 5000 ltr.      | MR    |
| 15. | Exit Signage.                                  | Required      | Provided       | MR    |
| 16. | Provision of Lifts.                            |               |                | IVIIC |
|     | a) Pressurization of lift shaft                | N/A           | N/A            | N/A   |
|     | b) Pressurization of lift lobby                | N/A           | N/A            | N/A   |
|     | c) Communication in lift car                   | N/A           | N/A            | N/A   |
|     | d) Fireman's switch                            | N/A           | N/A            | N/A   |
| -   | e) Lift signage                                | N/A           | N/A            | N/A   |
| 17. | Stand by Power Supply                          | Required      | Provided       | MR    |
| 18. | Refuge Area                                    | N/A           | N/A            | N/A   |
|     | Total area location                            | N/A           | N/A            | N/A   |
| 19. | Fire Control Room                              | N/A           | N/A            | N/A   |
|     | <ul><li>a) Detector system<br/>panel</li></ul> | N/A           | N/A            | N/A   |
|     | b) Flow switch panel                           | N/A           | N/A            | N/A   |
|     | c) PA system panel                             | N/A           | N/A            | N/A   |
|     | d) Battery backup                              | N/A           | N/A            | N/A   |
|     | e) Building floor plan                         | N/A           | N/A            | N/A   |
| 20. | Special Fire Protection System Risk, if any:   | m for Protect | ion of special | NA    |

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2016/NDZ/361 dated 04/03/2016 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

verification is also Designation: - ADO (CC)
put up on file. please.