GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2019/ 807

Dated :- 12/4/15

FIRE SAFETY CERTIFICATE

Certified that the Hare Krishna Guest House located at 1572-73, Main Bazar, Pahar Ganj, New Delhi comprised of Ground + 04 Upper floors, Ground floor (Reception + lobby + 01 guest rooms), 1st floor to 3rd floor (06 guest rooms at each floor) & 4th floor (05 guest rooms), total 24 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2016/NDZ/520 dated 04/04/16. The premises was re-inspected by the officer concerned of this department on 20/03/19 in the presence of Sh. Ankur Goel and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 24 guest rooms only with effect from ---12-1-1-1-1------- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued - at New Delhi by.

(Sunil Chowdhary)
Dy. Chief Fire Officer
Delhi Fire Service

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi ref. letter no. 665/Jt. C.P./Lic. (H) dated 14.02.2019.
- 2. The Manager,

Hare Krishna Guest House at 1572-73, Main Bazar, Pahar Ganj, New Delhi.

- 3. The Commissioner North MCD.....with a request to get the height of the building measured and intimate to this department for taking further action at our end, if any. Condition for the validity of fire safety certificate
 - 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
 - 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
 - 3. The trained fire fighting staff should be available round the clock.
 - 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
 - 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
 - 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
 - 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
 - 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

	INIC	DECTION DED	ODT	***		
1	Name & address of the building Hare Krishna Guest House at 1572-73.					
1.	reame & address of the building	_				
2	Type of occupancy:-		Main Bazar, Pahar Ganj, New Delhi			
2.	The state of the s					
	Gr. + 04 Upper floors (total 24 Guest rooms) Ground floor (Reception + lobby + 01 guest rooms)					
	1 st floor to 3 rd floor (06 guest rooms at each floor) &					
2	4 th floor (05 guest rooms)					
	Type of case:- Renewal					
4.	4. Details of previous FSC:- No. F6/DFS/MS/GH/2015/NDZ/520 23/12/15.					
5.	5. Fire safety directives No N/A					
	Date of inspection:- 20/03/19					
	7. Name of the inspecting officer:- Sh. Manoj Kumar Sharma (ADO/CC)					
8.	British of office	r				
	From the building side:-	Sh. Ankur	Goel			
	Year of construction:-	1991				
10.	Applicant's letter No:-	665/Jt. C.P	² ./Lic. (H) dated 14.	02.2019.		
CAL				Old Case		
S.No.	Minimum Standards on fire	Requirement	Provided at site	Remarks		
	Prevention and fire safety	Existing fire		MR/NMR		
	U/R 33	safety		*		
1.	Aggas to Duilding	arrangements				
1.	Access to Building 1) Road width	N/A	12) (D)		
			12 mtr. (MR		
	2) Gate width	N/A	N/A	MR		
	3) Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Ari	angement of E	xits	-		
	A. Number of staircases		1			
	1. Upper floors	01 Nos.	02 Nos.	MR		
	2. Basements	N/A	N/A	N/A		
	B. Width of staircase		/.			
	1. Upper floors	0.80 mtr.	1.10 Mtr. 7 0.90	MR		
			mtr.			
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits					
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	N/A	N/A	N/A		
	staircase to terrace	27/4	27/1			
	E. Width of corridor	N/A	N/A	N/A		
3.	F. Door size	01 mtr.	01 mtr.	MR		
· .	Compartmentation	77/4	27/4			
	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
4.	Smoke Management System	00.1				
	1) Basements	30 ACPH		N/A		
	2) Upper floors	12 a/c per	Natural	MR		
		hour		20		

5.	Fire Extinguishers			
	1) Total numbers	10 Nos.	10 Nos.) (D)
	2) Types	ABC & CO2		MR.
	3) ISI marking			MR
6.	First-Aid Hose Reel	Required	Provided /.	MR
0.	1) Total number of eachfloor	01	0.1	
	2) Length of hose reel hose	30 mtr.	01	MR
	3) Nozzle diameter	05 mm	30 mtr.	MR
7.	Automatic Fire Detection &	03 mm	05 mm	MR
/ •	1) Type of detectors			The state of the s
	2) Location of main panel	N/A	N/A	N/A
		N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
`	5) Hooter's Location	N/A	N/A	N/A
3.	MOEFA	Required	Provided	MR
).	Public Address System	Required	Provided	MR
0.	Automatic Sprinkler System			The state of the s
	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling			
1.	Internal Hydrants			
	1) Size of riser/down-comer	100 mm	100 mm	MR
	2) Number of hydrants per	01	01	MR
	floor			
	3) Hose box	01	01	MR
2.	Yard Hydrants			
	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement			11/21
	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A
	pump	1777	14/71	IVA
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pum		N/A	N/A
	d) Jockey pump out put		N/A	N/A N/A
	e) Jockey pump head	N/A	N/A	N/A N/A
	f) Stand by pump outpu		N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A N/A
	h) Auto starting/Manual		N/A	N/A N/A
	stopping	14/11	IVA	IN/A
	2) Terrace level		/	
	a) Discharge of pump	225 LPM	225 I DM) (D
	b) Head of pump	30 mtr.	225 LPM	MR
	c) Power supply		30 mtr.	MR
		Required	Provided	MR
	d) Auto starting of pump	Required	Provided	MR

14.	Captive Water Storage for Fire Fighting				
	Under ground tank capacity	N/A	N/A	N/A	
	a) Draw-off connection	N/A	N/A	N/A	
	b) Fire service inlet	N/A	N/A	N/A	
	c) Access to tank	N/A	N/A	N/A	
	d) Over head tank capacity	5,000 ltr.	5,000 ltr.	MR	
15.	Exit Signage.	Required	Provided	MR	
16.	Provision of Lifts.			1111	
	 a) Pressurization of lift shaft 	N/A	N/A	N/A	
	b) Pressurization of lift lobby	N/A	N/A	N/A	
	c) Communication in lift car	N/A	N/A	N/A	
	d) Fireman's switch	N/A	N/A	N/A	
4 ==	e) Lift signage	N/A	N/A	N/A	
17.	Stand by Power Supply	Required	Provided	MR	
18.	Refuge Area	N/A	N/A	N/A	
	Total area location	N/A	N/A	N/A	
19.	Fire Control Room	N/A	N/A	N/A	
	a) Detector system panel	N/A	N/A	N/A	
	b) Flow switch panel	N/A	N/A	N/A	
	c) PA system panel	N/A	N/A	N/A	
	d) Battery backup	N/A	N/A	N/A	
	e) Building floor plan	N/A	N/A	N/A	
20.	Special Fire Protection Syster Risk, if any:	m for Protect	ion of special	NA	

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2016/NDZ/520 dated 04/04/2016 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

. 1

vor)

F. F. F.