FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[See sub-rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No.F.6/DFS/MS/2019/ 1122

Dated: 24/ 5/2019

FIRE SAFETY CERTIFICATE

Certified that the Symphony Celebrators Pvt. Ltd. located at D-11, Udyog Nagar, Delhi-110041, comprised of Basement, Ground + Two Upper Floors only owned / occupied by Symphony Celebrators Pvt. Ltd. with store in Basement, Banquet halls on Ground & 1st Floor & restaurant on 2nd Floor, have already been issued Fire Safety certificate by this department vide letter No. F6/DFS/MS/2016/Banquet/WZ/881 dated 30/05/2016. The premises was re-inspected by the officer concerned of Fire Service on 10/05/2019 in presence of Mr. Jagdish Nagpal (Manager) and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deemed complied with the Fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building / premises is fit for occupancy class Assembly (Banquet Wall) with effect from 24 / 5 /2019 for a period of three years in accordance with rule 30 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 24 5 119 at New Delhi by.

CHIEF FIRE OFFICER.

Copy to :-

Mr. Sanjay Gupta (Director). Symphony Celebrations Pvt. Ltd., D-11, Udyog Nagar, Delhi-110041.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided their in shall be maintained in good working conditions at all times.
- 2. Lors of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned build no sanctioning agency.
- 5. This partificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. "The owner / Occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, six ment is prior to its expiry".
- 7. Basement shall be used as per the NBC (Part-IV) read with BBL 1983.
- 8. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The from is available on

INSPECTION REPORT

1. Name & address of the building: Symphony Celebrations Pvt. Ltd., D-11, Udyog

Nagar, Delhi-110041.

2. Type of Occupancy : Assembly (Banquet Hall)

: Renewal (B+G+ 2 Upper Floors only)

3. Type of Case 4. Details of previous NOC : F6/DFS/MS/2016/Banquet/WZ/881 dated 30/05/2016

5. Fire Safety directives Letter No. : F6/DFS/MS/2000/1728 dated 25/09/2000

F6/DFS/MS/2008/363 dated 13/02/2008

6. Date of inspection

: 10/05/2019

7. Name of the Inspecting Officer: A.D.O. (JWP)

8. Name and designation of Officer

from the building side

: Mr. Jagdish Nagpal (Manager)

9. Year of Construction

: 2002

10. Applicant's letter No.

: - Nil

S No				Provided at site	Remarks MR/NMR	
	U/R 33			Site	IVIR/INIVIE	
1.	Access of building					
	 Road width 	06 mtr		06 mtr	MR	
	 Gate width 	05 mtr	05 mtr		MR	
	 Width of internal ro 	ad NR		NR	NR	
2.	Number, width, Type & Arrangements of exits					
	a. Number of staircase					
	 Upper floors 	3	3		MR	
	 Basements 	4	4		MR	
	b. Width of staircases			4		
	Upper floors	Old Case		1.82 m, 1.81 m & 1.50 m	MR	
	• Basements	Old Case			1	
	c. Protection of exits			de sa Cara a		
	Fire check door	Required	Required		MR	
	 Pressurization 	N/A			N/A	
	d. No of continuous staircase to terrace	1	1		MR	
	e. Width Of Corridor	1.5 mtr	1.5 mtr		NR	
	f. Door Size	Old Case (GF)	Old Case (GF) Old Case (FF) Old Case (2 nd floor)		MR	
					Ñ.	
3.	Compartmentation			1X2.0 mtrs		
	• Fire check door	Required	Required		MR	
	• Sealing of electrical shafts	Required	Required		MR	
	Fire Rating of shaft door	· NR	NR		NR	
	Water Curtain	NR	NR		NR	
	Fire Dampers	NR	NR		NR	
4.	Smoke managements System	n				
-	• Basements	Required	Required		MR	
	Upper floors	Required	Required		MR	
5.	Fire Extinguishers			Provided		
	Total numbers	28	28		MR	
	• Types	ISI marked	ISI marked ABC/CO ₂		MR	

• Total numbers on each floor • Length of hose reel hose • Nozzle diameter 7. Automatic fire detection and alarming system • Type of detector • Location of Main Panel • Location of Repeater • Alternate source of power • Hooters' Location 8. MOEFA 9. Public Address System 10. Automatic Sprinkler System • Basements • Upper Floor • Sprinkler above false ceiling 11. Internal Hydrants • Size of riser/down-comer • Number of hydrants per floor • Hose Box 12. Yard Hydrants • Ground Level • Ground Level • Croad and alarming system 2		
Length of hose reel hose Nozzle diameter Nozzle diameter Nozzle diameter Smm. Smm. Smm. Smm. Automatic fire detection and alarming system Smoke & Heat Nozale diameter Nozale diameter Nozale diameter Smoke & Heat Nozale diameter Nozale diameter Nozale diameter Smoke & Heat Nozale diameter		
Length of hose reel hose Somm. Somm. MR	MR	
Nozzle diameter		
Nozzle diameter		
• Type of detector • Location of Main Panel • Location of Repeater • Alternate source of power • Hooters' Location On each floor Provided MR 8. MOEFA Provided MR 8. MOEFA Provided MR 8. MOEFA Provided MR 8. MOEFA Provided MR Required Provided MR MR MR MR Provided MR MR MR MR MR MR MR MR MR M		
• Type of detector • Location of Main Panel • Location of Repeater • Alternate source of power • Hooters' Location On each floor Provided MR 8. MOEFA Provided MR 8. MOEFA Provided MR 8. MOEFA Provided MR 8. MOEFA Provided MR Required Provided MR MR MR MR Provided MR MR MR MR MR MR MR MR MR M		
Location of Main Panel Location of Repeater Location of Repeater Alternate source of power Hooters' Location Required Provided MR MOEFA Required Provided MR Moefa Required Provided MR Moefa Required Provided MR Moefa Required Provided MR MR Ne Required Provided MR Ne		
Panel Location of Repeater Alternate source of power Hooters' Location Required Provided MR MOEFA Required Provided MR MOEFA Required Provided MR MOEFA Required Provided MR MR MOEFA Required Provided MR MR NE Required Provided MR NE	MR	
Location of Repeater Alternate source of power Hooters' Location Required Hooters' Location Required Provided MR MOEFA Required Provided MR MOEFA Required Provided MR MR MOEFA Required Provided MR MR Provided MR		
 Alternate source of power Hooters' Location Required Provided MR MR MR MR Provided MR Upper Floor Sprinkler above false ceiling NR N		
MR MOEFA Public Address System NR Required Provided MR Provided MR Provided MR Provided MR MR MR Provided MR MR Provided MR MR MR Provided MR MR MR MR Provided MR MR MR NR NR NR NR NR NR MR M		
 Hooters' Location Required Provided MR NR NR<td colspan="2"></td>		
8. MOEFA 9. Public Address System 10. Automatic Sprinkler System • Basements • Upper Floor • Sprinkler above false ceiling 11. Internal Hydrants • Number of hydrants per floor • Hose Box 12. Yard Hydrants • Total number of hydrants • Hose Box 13. Pumping Arrangements • Ground Level		
8. MOEFA 9. Public Address System 10. Automatic Sprinkler System • Basements • Upper Floor • Sprinkler above false ceiling 11. Internal Hydrants • Size of riser/down-comer • Number of hydrants per floor • Hose Box 12. Yard Hydrants • Total number of hydrants • Hose Box 13. Pumping Arrangements • Ground Level		
9. Public Address System 10. Automatic Sprinkler System		
10. Automatic Sprinkler System Basements Upper Floor Sprinkler above false ceiling 11. Internal Hydrants Size of riser/down-comer Number of hydrants per floor Hose Box 12. Yard Hydrants Total number of hydrants Hose Box NR		
Basements Upper Floor Sprinkler above false ceiling 11. Internal Hydrants Size of riser/down-comer Number of hydrants per floor Hose Box 12. Yard Hydrants Total number of hydrants Hose Box NR	,	
● Upper Floor Required Howard NR ● Sprinkler above false ceiling NR NR NR 11. Internal Hydrants 100mm 100mm MR ● Size of riser/down-comer 02 02 MR ● Number of hydrants per floor 02 02 MR 12. Yard Hydrants NR NR NR ● Total number of hydrants NR NR NR ● Hose Box NR NR NR 13. Pumping Arrangements Oround Level Arrangements Arrangements Arrangements		
Sprinkler above false ceiling 11. Internal Hydrants Size of riser/down-comer Number of hydrants per floor Hose Box 12. Yard Hydrants Total number of hydrants Hose Box NR NR NR NR NR NR NR NR NR N		
11. Internal Hydrants		
11. Internal Hydrants 100mm 100mm MR • Size of riser/down-comer 02 02 MR • Number of hydrants per floor 02 02 MR • Hose Box 02 02 MR 12. Yard Hydrants NR NR NR • Total number of hydrants NR NR NR • Hose Box NR NR NR 13. Pumping Arrangements Ground Level A380 IPM MR		
• Size of riser/down-comer 100mm 100mm MR • Number of hydrants per floor 02 02 MR • Hose Box 02 02 MR 12. Yard Hydrants NR NR NR • Hose Box NR NR NR 13. Pumping Arrangements Ground Level A3280 IPM MR		
Comer		
 Number of hydrants per floor Hose Box Yard Hydrants Total number of hydrants Hose Box NR MR NR <l< td=""><td></td></l<>		
per floor O2 O2 MR 12. Yard Hydrants NR NR NR • Total number of hydrants NR NR NR • Hose Box NR NR NR 13. Pumping Arrangements Ground Level A380 IPM MR		
 Hose Box 12. Yard Hydrants Total number of hydrants NR NR		
12. Yard Hydrants Total number of hydrants NR NR NR NR Hose Box NR NR NR NR NR NR MR NR NR NR		
Total number of hydrants Hose Box R NR		
hydrants Hose Box NR NR NR NR NR MR MR MR MR		
Hose Box NR		
13. Pumping Arrangements Ground Level 2380 IPM MR		
• Ground Level 2380 IPM MR		
Discharge of main nump 2280 LPM 2280 LPM MR		
Discharge of main pamp AOMH MR		
Flead of main pump		
Number of many pumps 1901 PM MR		
Jockey pump out put		
Jockey pump nead 2280 LPM MR		
Standoy 1 dinp out put		
Standby 1 diffp fredd MR		
Auto Staring Wandar		
stopping Pump House Access Required Provided MR		
Tampa lavel		
COCLEMA GOOTPIN		
Discharge of pump		
Head of the pump 40 Will Provided MR		
> Power supply Required MR		
> Auto starting of pump Required Provided		
14. Captive water Storage for fire fighting)	
• Underground tank 50,000 lts. 1,50,000 ltrs. M/F	`	
capacity)	
Draw of connection Required Provided W/V		
Fire service inlet Required Provided NA/		
Access to tank Required Provided My		
• Overhead Tank 10,000 lts. 10,000 lts	IV.	
capacity		

	W/12					
15	Exit Signage	Required	Provided	M/R		
16.	Provision of Lifts					
	Pressurization of Lift Shaft	NR	NR	NR		
	Pressurization of lift lobby	NR	NR	NR		
	Car Communication in lift	NR	NR	NR		
	Fireman's Grounding Switch	NR	NR	NR		
	➤ Lift Signage	NR	NR	NR		
17.	Standby power supply	Required	Provided	MR		
18.	Refuge Area	NR	NR			
	> Total area	NR	NR	NR		
	Location	NR	NR	NR		
19.	Fire control room					
	Detector system panel	NR	NR	NR		
	Flow Switch Panel	NR	NR	NR		
	PA System Panel	NR	NR	NR		
	Battery backup	NR	NR	NR		
	Building Floor Plans	NR	NR	NR		
20.	Special Fire Protection Systems for Protection of special Risks, if any;	NR	NR	NR		

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection. MCB and Conduit Metal Wiring has also been provided.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter No. F6/DFS/MS/2016/Banquet/WZ/881 dated 30/05/2016 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of the Inspecting Officer

Name

: Ashok Kumar Jaiswal

Designation: A.D.O. (Jwala Puri)