FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6/DFS/MS/SCHOOL/2019/ 2012

Dated: 21/10/2019

FIRE SAFETY CERTIFICATE

Certified that the Govt. Sarvodaya Kanya Vidyalaya Located at Rampura Delhi-110035 comprised of 04 Blocks Ground+ 1Upper floor only was issued FSC vide Letter No. F6/DFS/MS/SCHOOL/2016/WZ/1657,Dated-11/11/2016, The premises was re inspected by the officer concerned of this department on 03/10/2019 in the presence of Mr. Kamal Kishor (State Manager) and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deem complied with the fire prevention and fire safety requirements in accordance Circular DOE 3298-3398 dated 01-03-2011 and that the premises is fit for occupancy class "Educational" Group B with effect from 21/10/19 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ... 2.1. 1.9... at New Delhi by.

(Dharampal Bhardwaj) DY. Chief Fire Officer Delhi Fire Service

Copy to:1. The Principal, Govt. Sarvodaya Kanya Vidyalaya Rampura. Delhi-190035

2. Directorate of Education Old Secretariat Delhi – 110054.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. All the exit route shall be kept free from any obstruction.
- 7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.dhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: Govt. Sarvodaya Kanya Vidyalaya Located at Rampura. Delhi-110035.

2. Type of Occupancy

: Educational Block 04(Ground + 1 Upper Floor)

3. Type of Case

: Renewal

4. Details of previous NOC 11/11/2016

: F6/DFS/MS/SCHOOL/2016/WZ/1657,Dated-

11/11/2010

5. Fire Safety directives Letter No.: DOE 3298-3398 dated 01-03-2011

6. Date of inspection

:03/10/2019

No. of Students=1888 No. of class rooms=32

7. Name of the Inspecting Officer: Udai vir singh, ADO (WP)

Plot area=12293sqm Covered area=6030 sqm

8. Name and designation of Officer

from the building side

:Mr. Kamal Kishor (State Manager)

9. Year of Construction

: 1958

10. Applicant's letter No.

:Form J dated -07/09/2019

| S No | Minimum standards on fire prevention and fire safety U/R 33 | Cr.No.3298- 3398 dated 1-3- | Provided at site | Remarks MR/NMR | |
|---------|--|--------------------------------|---------------------------------|-------------------|------|
| 1. | Access of building | 11 * | | | |
| | Road widthGate width | Accessible Accessible | 05 mtr 03 mtr | MR | |
| | Width of internal road | NA | NA | MR NA | - 10 |
| 2. | Number, width, Type & Arrang | rements of exits | | | |
| | a. Number of staircases | , services of exits | | | |
| | • Upper floors | Bl=2 Bl=1 each | BI=3 BI=1 each | MR | |
| | Basementsb. Width of staircases | NA | NA | NA | |
| | Upper floorsBasementsProtection of exits | BL=2x1.5cm BL=1.5 | Bl=2x150cm &1x Bl=150cm each | 123cm cm | MR |
| | Fire check door | NA | NA | | NA |
| | Pressurizationd. No of continuous | NA NA | NA NA | NA | |
| | staircase to terrace e. Width Of Corridor | NA | NA | NA NA | - |
| | f. Door Size | Required | 210cm | MR | |
| | | 1 mtr | 1 mtr Provided | MR | |

| 3. | Compartmentation | | | |
|-----|---|-----------------------|-----------------------|---------|
| J. | Fire check door | NA | NA | NA |
| | | NA | NA | NA |
| | Fire Rating of shaft | NA | NA | NA |
| | doorWater Curtain | NA | NA | NA |
| | | NA | NA | NA |
| | • Fire Dampers | NA | 187. | |
| 4. | Smoke managements System | NA | NA | NA |
| | Basements | INA | | |
| | Upper floors | NA | NA | NA |
| 5. | Fire Extinguishers | | | * * * · |
| ٥. | Total numbers | 21 nos. | Provided | MR |
| | Types | ABC & CO ₂ | Provided | MR |
| | IS marking | ISI marked | Provided | MR |
| 6. | First – Aid Hose Reels | | | |
| 0. | Total numbers on each | NA | Provided in Old BL | NA |
| | floor | NA | 30m Provided | NA |
| | Length of hose reel hose | NA | 5mm provided | NA |
| * | Nozzle diameter | 1112 | | |
| 7 | Automatic fire detection and ala | rming system | | |
| 7. | | NA NA | NA | NA |
| | Type of detectorsLocation of Main Panel | NA | NA | NA |
| | Location of Nam Fanct Location of Repeater | NA | NA | NA |
| | Panel | | | N. 1. |
| | Alternate source of | NA | NA | NA |
| | power | NA | NA | NA |
| | Hooters' Location | NA | NA | NA |
| 8. | MOEFA | NA NA | NA | NA |
| 9. | Public Address System | INA | 1471 | |
| 10. | | NA | NA | NA |
| | Basements | NA | NA | NA |
| | • Upper Floor | NA | NA | NA |
| | Sprinkler above false ceiling | INA | 1111 | × |
| 11. | | | (| 3 |
| 11. | Size of riser/down- | NA | NA | NA . |
| a | comerNumber of hydrants per | r NA | NA | NA |
| | floor • Hose Box | NA | NA | NA |
| 12 | | | | |
| 12 | Total number of | NA | NA | NA |
| | hydrants • Hose Box | NA | NA | NA |
| | | | | |

| | 13. Pumping Arrangements: | | 1 | |
|-------|---------------------------------------|---------|------------|--|
| | Ground Level | | | |
| | Discharge of main | - | | |
| | pump | NA |) AT A | |
| | Head of main pump | NIA | NA NA | NA |
| | Number of main pu | mne NA | NA | NA |
| | Jockey pump out pu | it NA | NA | NA |
| | Jockey pump head | NIA | NA | NA |
| | Standby Pump out r | uit NIA | NA | NA |
| | Standby Pump Head | 1 274 | NA | NA |
| | Auto Staring/Manua | 1 NA | NA | NA |
| | Stopping | * 12 1 | NA | NA |
| | Pump House Access | NA | 22 | |
| | • Terrace level | 11/1 | NA | NA |
| | Discharge of pump | NA | | |
| | Head of the pump | NA | 450lpm | NA |
| | Power supply | | 40m | NA |
| | Auto starting of pump | NA NA | provided | NA |
| 14. | Captive water Storage for fire | NA NA | NA | NA |
| | Under ground tank | | | 1111 |
| | capacity | NA | NA | NA |
| | > Draw off connection | | 2 | |
| | Fire service inlet | NA | NA | NA |
| | Access to tank | NA | NA | NA |
| | Overhead Tank | NA | NA | NA |
| | capacity | NA | 50001 ptov | ided NA |
| 15 | Exit Signage | | ptov | Idea NA |
| 16. | Provision of Lifts | NA | Provided | NA |
| | Prescurization Chic | | | NA NA |
| | Pressurization of Lift Shaft | NA | / NA | NIA |
| | | | | NA |
| | Pressurization of lift lobby | NA | NA | The state of the s |
| | Communication | 8 | 1111 | NA |
| | Communication in lift | NA | NA | NIA |
| | | NA | NA | NA |
| | Fireman's Grounding Switch | | INT | NA |
| | ► Lift Signage | NA | NA | |
| 7. | Standby power | | 11/1 | NA |
| 8. 1 | Standby power supply Refuge Area | NA | NA | NA |
| | | | ~ 11 A | NA |
| | Total area | NA | NA | 27.4 |
|). F | Location Location | NA | NA | NA |
| . [| ire control room | | IVA | NA |
| | Detector system panel | NA | NA | 28 |
| | Flow Switch Panel | NA | | NA |
| | PA System Panel | NA | NA | NA |
| | Battery backup | NA | NA | NA |
| | Building Floor DI | NA | NA | NA |
| | | INT | NA | NA |

| 20. | Special Fire Protection Systems for Protection of special Risks, if any; | NA | NA | NA |
|-----|--|----------------------------|-------------------|-----------------------|
| | The fire protection sy found functional at the time of | stems provide | d in the building | were test checked and |
| | In view of the deemed fire safety as required un F6/DFS/MS/SCHOOL/2016/W | compliance of nder the rul | es the NOC i | ssued vide letter no |

Signature of the Inspecting Officer Signature of the Inspecting Officer Vola Vir Digs Name ADOLUP Designation Designation De to W21

AND My FT

Sir FP letter is but up tring ple.

Proto

1919