GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F.6/DFS/MS/EH/SZ/2019/ 2 × 2 9

Dated: /3/11//9

FIRE SAFETY CERTIFICATE

Certified that M/s Kiko Ba & Dadel (A unit of Soul Sunshine Foods LLP), at LGF & GF, 62, Basant Lok, Vasant Vihar, New Delhi-110057, comprised of Ground floor (two level) & three upper floors but restaurant running at ground floor (two level) was issued FSC in the name of M/s Manchester United Restaurant (A unit of Twinkle Hospitality Pvt. Ltd) by this department vide letter No. F.6/DFS/MS/EH/2011/1020 dated 30/05/2011. The premise was re-inspected by the officer concerned of this department on 05/11/2019 in the presence of Sh. Uday Pandey (Manager) and found that the said premise have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Assembly, Group-D" (Restaurant) with effect from .1.3.4.6.2019 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 13/11 /2019 at New Delhi by

(Atul Garg)
Director
Delhi Fire Service
Tel, 011-23414000

Copy to: -

- 1. Sh. Arjun Jain (Partner), Kiko Ba & Dadel (A unit of Soul Sunshine Foods LLP), LGF & GF, 62, Basant Lok, Vasant Vihar, New Delhi-110057
- 2. The Dy. Health Officer, South Zone, SDMC, Public Health Department, Green Park, Aurobindo Marg, New Delhi-110003

Conditions for the validity of Fire Safety Certificate: -

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire fighting system.
- 4. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry."

		INCDECTIO	NDEDODT				
1	N	INSPECTIOn ame & Address of the Building		DEL (A	1		
1	INC	une & Address of the Building		DEL (A unit of Soul Su			
			Foods LLP), Commercial Area, LGF & GF, 62, Basant Lok, Vasant Vihar, New Delhi–110057				
2	Ty	pe of Occupancy	Assembly, "Group-D" (Eating House)				
3		illding Comprised of	Lower Ground, Ground floor & three upper floors.				
4		pe of Case	Renewal & Change of Name				
5	Details of Previous NOC		F.6/DFS/MS/EH/2011/1020 dated 30/05/2011 in r/o				
	Details of Frey lous 140C		M/s Manchester United Restaurant				
6	Fi	re Safety Directives Letter No	F6/DFS/MS/EH/2005/718 dated 04-04-2005 (N/3)				
7		ate of Inspection	05-11-2019				
8	Name of the Inspecting Officers		Mehmood, ADO (SJ)				
9	Name & Designation of Officers		Mr. Uday Pandey (Manager)				
	from the building side		in oddy i andoy (wianagor)				
10	Ye	ear of construction	Restt. at LGF & GF only				
11		pplicant letter No.	Outdoor Diary No. 23616 dated 29-10-2019				
S. No.		inimum standards on Fire Prevention	As Per Old	Provided at Site	Remarks		
		d Fire Safety U/R 33	NOC	1 Tovided at Site	MR/NMR		
1		cess to Building.			112241111224		
		Road width	Accessible	6 mtr	MR		
		• Gate width	-NA-	-NA-	-NA-		
		 Width of internal road 	-NA-	-NA-	-NA-		
2		mber, width, type & arrangement of ex	its.				
	a)	Number of Staircase					
		Upper floors.	-NA-	-NA-	-NA-		
		Lower ground floor.	Required	2 Nos	MR		
	b)	Width of Staircase					
		Upper floors	-NA-	-NA-	-NA-		
		Basement floor	Required	1.25m (each)	MR (old case		
	c)	Protection of exits		8			
		Fire check door	-NA-	-NA-	-NA-		
		Pressurization	-NA-	-NA-	-NA-		
	d)	No. of continuous staircase to terrace	One	Provided	MR		
	e)	Width of corridor	-NA-	-NA-	-NA-		
	f)	Door size	2 Exits	2m & 1.5m	MR		
3	Co	mpartmentation.	2				
			3.7.4	374			
		• Fire check door.	-NA-	-NA-	-NA-		
		 Sealing of electrical shafts. 	-NA-	-NA-	-NA-		
		Sealing of electrical shafts.Fire rating of shaft door.	-NA-				
		Sealing of electrical shafts.Fire rating of shaft door.Water curtain	-NA- -NA- -NA-	-NA- -NA- -NA-	-NA- -NA-		
	~	 Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. 	-NA-	-NA- -NA-	-NA-		
4	Sn	 Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. 10ke Management system.	-NA- -NA- -NA-	-NA- -NA- -NA- -NA-	-NA- -NA- -NA-		
4	Sm	 Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. hoke Management system. Lower Ground Floor 	-NA- -NA- -NA- -NA-	-NA- -NA- -NA- -NA-	-NA- -NA- -NA- -NA-		
		 Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Lower Ground Floor Ground Floor 	-NA- -NA- -NA-	-NA- -NA- -NA- -NA-	-NA- -NA- -NA-		
5		 Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Moke Management system. Lower Ground Floor Ground Floor Extinguishers. 	-NA- -NA- -NA- -NA- 30 ACPH 12 ACPH	-NANANA- Provided Provided	-NANANANA- MR		
		 Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Hoke Management system. Lower Ground Floor Ground Floor Extinguishers. Total numbers 	-NA- -NA- -NA- -NA- 30 ACPH 12 ACPH	-NANANANA- Provided Provided	-NANANANA- MR MR		
		 Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Hoke Management system. Lower Ground Floor Ground Floor Te Extinguishers. Total numbers Types 	-NANANANA- 30 ACPH 12 ACPH 8 Nos ABC/W.CO ₂ / CO ₂	-NANANANA- Provided Provided 10 Nos ABC & CO ₂	-NANANANANA- MR MR MR		
5	Fir	 Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Hoke Management system. Lower Ground Floor Ground Floor Extinguishers. Total numbers Types ISI Marking 	-NA- -NA- -NA- -NA- 30 ACPH 12 ACPH	-NANANANA- Provided Provided	-NANANANA- MR MR		
	Fir	 Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Noke Management system. Lower Ground Floor Ground Floor Extinguishers. Total numbers Types ISI Marking Tst Aid Hose Reels. 	-NANANANA- 30 ACPH 12 ACPH 8 Nos ABC/W.CO ₂ /CO ₂ ISI marked	-NANANANA- Provided Provided 10 Nos ABC & CO ₂ Provided	-NANANANANA- MR MR MR MR		
5	Fir	 Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Loke Management system. Lower Ground Floor Ground Floor Extinguishers. Total numbers Types ISI Marking st Aid Hose Reels. Total numbers on each floor. 	-NANANANA- 30 ACPH 12 ACPH 8 Nos ABC/W.CO ₂ / CO ₂ ISI marked One	-NANANANANA- Provided Provided 10 Nos ABC & CO ₂ Provided Provided	-NANANANANA- MR MR MR MR MR		
5	Fir	 Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Lower Ground Floor Ground Floor Extinguishers. Total numbers Types ISI Marking Total numbers on each floor. Length of hose-reel hose. 	-NANANANANA- 30 ACPH 12 ACPH 8 Nos ABC/W.CO ₂ / CO ₂ ISI marked One 30m	-NANANANANA- Provided Provided 10 Nos ABC & CO ₂ Provided Provided Provided	-NANANANANA- MR MR MR MR		
6	Fin	 Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Lower Ground Floor Ground Floor Extinguishers. Total numbers Types ISI Marking Aid Hose Reels. Total numbers on each floor. Length of hose-reel hose. Nozzle Diameter 	-NANANANANA- 30 ACPH 12 ACPH 8 Nos ABC/W.CO ₂ / CO ₂ ISI marked One 30m 5mm	-NANANANANA- Provided Provided 10 Nos ABC & CO ₂ Provided Provided	-NANANANANA- MR MR MR MR MR		
5	Fin	 Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Lower Ground Floor Ground Floor Ground Floor Total numbers Types ISI Marking rst Aid Hose Reels. Total numbers on each floor. Length of hose-reel hose. Nozzle Diameter tomatic fire detection & alarming system 	-NANANANANANA- 30 ACPH 12 ACPH 8 Nos ABC/W.CO ₂ / CO ₂ ISI marked One 30m 5mm	-NANANANANA- Provided Provided 10 Nos ABC & CO ₂ Provided Provided Provided	-NANANANANANANANA-		
6	Fin	 Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Lower Ground Floor Ground Floor Extinguishers. Total numbers Types ISI Marking Ist Aid Hose Reels. Total numbers on each floor. Length of hose-reel hose. Nozzle Diameter Type of detectors 	-NANANANANANA- 30 ACPH 12 ACPH 8 Nos ABC/W.CO ₂ / CO ₂ ISI marked One 30m 5mm m. Required	-NANANANANA- Provided Provided 10 Nos ABC & CO ₂ Provided Provided Provided	-NANANANANANANANA-		
5	Fin	 Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Toke Management system. Lower Ground Floor Ground Floor Extinguishers. Total numbers Types ISI Marking Tst Aid Hose Reels. Total numbers on each floor. Length of hose-reel hose. Nozzle Diameter Type of detectors Location of Main Panel 	-NANANANANANA- 30 ACPH 12 ACPH 8 Nos ABC/W.CO ₂ / CO ₂ ISI marked One 30m 5mm M. Required Ground floor	-NANANANANANA- Provided Provided 10 Nos ABC & CO ₂ Provided Provided Provided Provided Provided Provided	-NANANANANANANANA-		
6	Fin	 Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Lower Ground Floor Ground Floor Extinguishers. Total numbers Types ISI Marking Ist Aid Hose Reels. Total numbers on each floor. Length of hose-reel hose. Nozzle Diameter Type of detectors 	-NANANANANANA- 30 ACPH 12 ACPH 8 Nos ABC/W.CO ₂ / CO ₂ ISI marked One 30m 5mm m. Required	-NANANANANANANANA-	-NANANANANANANANA-		
5	Fin	 Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Toke Management system. Lower Ground Floor Ground Floor Extinguishers. Total numbers Types ISI Marking Tst Aid Hose Reels. Total numbers on each floor. Length of hose-reel hose. Nozzle Diameter Type of detectors Location of Main Panel 	-NANANANANANA- 30 ACPH 12 ACPH 8 Nos ABC/W.CO ₂ / CO ₂ ISI marked One 30m 5mm M. Required Ground floor	-NANANANANANANANA-	-NANANANANANANANA-		

KIKO BA & DADEL at LGF, LG, 62, Basant Lok, Vasant Vihar, New Delhi-110057

8	MOEFA	Dogwing 1	Provided	MD
9	Public Address System	Required -NA-	-NA-	MR -NA-
10	Automatic Sprinkler System	-INA-	-1N/A-	-INA-
10	Lower ground floor	Required	Provided	MR
	Ground floors	Required	Provided	MR
	 Sprinkler above false ceiling 	-NA-	-NA-	-NA-
11	Internal Hydrants.	-1471-	-11/1-	-14/1-
	Size of Riser/Down-comer	100mm	Provided	MR
	Number of Hydrant per floor	One	Provided	MR
	Hose box.	One	Provided	MR
12	Yard Hydrants.	One	11011404	17111
Action	Total number of hydrants.	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-NA-
13	Pumping arrangements.	-1471-	-1471-	-1471-
13	Ground Level			
	> Discharge of main pump.	1200 LPM	1200 LPM /	MR
	Head of main pump.	60m	60m	MR
	Number of main pumps.	One	One	MR
	➤ Jockey Pump output.	180 LPM	180 LPM	MR
	➤ Jockey Pump head.	60m	60m	MR
	Standby Pump output.	1200 LPM	1200 LPM	MR
	Standby Pump head.	60m	60m	MR
	Auto Starting/Manual Stopping.	Required	Provided	MR
	Pump house access.	Required	Provided	MR
	Terrace Level			
	Discharge of pump.	-NA-	-NA-	-NA-
	➤ Head of pump.	-NA-	-NA-	-NA-
	Power supply.	-NA-	-NA-	-NA-
	Auto starting of pump.	-NA-	-NA-	-NA-
14	Captive water storage for fire fighting.			
	 Underground tank capacity. 	-NA-	15,000 Ltr	-NA-
	Draw-off connection.	-NA-	-NA-	-NA-
	Fire Service Inlet.	Required	Provided	MR
	Access to tank.	-NA-	-NA-	-NA-
	Overhead tank capacity.	10,000 Ltr	10,000 Ltr	MR
15	Exit Signage.	Required	Provided /	MR
16	Provision of Lifts.			
	• Pressurization of lift shaft.	-NA-	-NA-	-NA-
	 Pressurization of lift lobby. 	-NA-	-NA-	-NA-
	 Communication in lift car. 	-NA-	-NA-	-NA-
	• Fireman's switch.	-NA-	-NA-	-NA-
	• Lift signage.	-NA-	-NA-	-NA-
17	Standby Power Supply	Required	Provided	MR
18	Refuge Area	required	TTOVIGG	TATIX
	Total area	-NA-	-NA-	-NA-
	• Location	-NA-	-NA-	-NA-
19	Fire Control Room.	1111	1177	-14/7-
	Detector system panel.	-NA-	-NA-	-NA-
	Tion switch paner.	-NA-	-NA-	-NA-
	PA system panel.	-NA-	-NA-	-NA-
	Battery backup.	-NA-	-NA-	-NA-
	Building floor plan.	-NA-	-NA-	-NA-
20	Special Fire Protection System for the	2 Nos ABC tvr	e fire extinguisher	MR

KIKO BA & DADEL at LGF, LG, 62, Basant Lok, Vasant Vihar, New Delhi-1 0057

M/s KIKO BA & DADEL (A Unit of Soul Sunshine Foods LLP) at LGF, LG, 62, Basant Lok, Vasant Vihar, New Delhi–110057

The fire protection system provided in the restaurant premises were test checked at random and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, the fire safety certificate issued vide letter No. F.6/DFS/MS/EH/2011/1020 dated 30/05/2011 in favour of M/s Manchester United Restaurant, renewal under Rule 37 of the Delhi Fire Service Rules, 2010 is recommended in favour of M/s Kiko Ba & Dadel (A unit of Sunshine Foods LLP)

Accordingly, DFA is put up for approval and signature please.

Signature of Inspecting Officer

Name: Mehmood Design: ADO (SJ)

DO (SD)

69/1

my h

Almin IIII

Anol ()

FT letter is publish for som

DIRECTOR MY

18/11/19 ADO (FM)