GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2019/ 2\22

Dated : 81 11119

FIRE SAFETY CERTIFICATE

Certified that the Raj Deluxe Guest House located at 8467, Arya Nagar, Pahar Ganj, New Delhi comprised of Ground floor + 03 Upper Floors Ground floor (reception + office + 01 guest rooms), 1st floor to 3rd floor (03 guest rooms at each floor), total 10 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2016/NDZ/104 dated 14/01/16. The premises was re-inspected by the officer concerned of this department on 30/10/19 in the presence of Mr. Karan has also submitted an affidavit not to use above third floor for any purpose and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued - 8 / 11 - 119 - at New Delhi by.

(Sunil Chowdhary) Dy. Chief Fire Officer Delhi Fire Service

Copy to:-

- 1. The Joint Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.
- 2. The Manager, Raj Deluxe Guest House located at 8467, Arya Nagar, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all
- Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the
- The trained fire fighting staff should be available round the clock.
- Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- This fire safety certificate may not be treated in any case for regularization of unauthorized construction,
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- Any flammable material for interior decoration is prohibited.
- 10. Owner/Occupier shall also ensure compliance of notification dated 27.05.19 and there of in r/o guest houses.

		1 1 2 4					
	INCD	ECTION REPO	NDT				
1.	Name & address of the building			ed at 8467			
1. A same of dadies of the banding		Raj Deluxe Guest House located at 8467, Arya Nagar, Pahar Ganj, New Delhi					
2.	Type of occupancy:-		, Sub Division-A-1				
		Ground floor	(Reception + office + 0	01 guest rooms),			
		1 st floor to 3 st total 10 gues	floor (03 guest rooms	at each floor),			
3.	Type of case:-	Renewal	t fooms.				
	Details of previous FSC:-		S/MS/GH/2016/ND	7/104 dated			
	1 County record and any remain	14/01/16.		-			
5.	Fire safety directives No	N/A					
	Date of inspection:-	30/10/19					
7.	Name of the inspecting officer:- Sh. Rajinder Atwal (DO/CD) &						
		Sh. Manoj	Kumar Sharma (AI	OO/CC)			
8.	Name & designation of officer						
0	From the building side:-	Mr. Karan					
	Year of construction:-	2002	W. H.				
10.	Applicant's letter No:-	Nil dated 27/09	/19.	Old Case			
S.No.	Minimum Standards on fire	Requirement/	Provided at site	Remarks			
	Prevention and fire safety	Existing fire	1 10 vided at Site	MR/NMR			
	U/R 33	safety					
1.	Access to Building	arrangements					
	1) Road width	N/A	04 mtr.	MR			
	2) Gate width	N/A	N/A	N/A			
	3)Width of internal road	N/A	N/A	N/A			
2.	Number, Width Type & Arra	12.45.35.35.35.30.		IVA			
	A. Number of staircases						
	1. Upper floors	01 Nos.	01 Nos.	MR			
	2. Basements	N/A	N/A	N/A			
	B. Width of staircase						
	1. Upper floors	80 cms.	95 cms.	MR			
	2. Basements	N/A	N/A	N/A			
	C. Protection of exits						
	1. Fire check door	N/A	N/A	N/A			
	2. Pressurization	N/A	N/A	N/A			
	D. No. of continuous	N/A	N/A	N/A			

N/A

N/A

N/A

N/A

N/A

N/A

12 ACPH

12 ACPH

01 mtr.

N/A

N/A

N/A

N/A

N/A

N/A

N/A

Natural

01 mtr.

N/A

MR

N/A

N/A

N/A

N/A

N/A

N/A

MR

staircase to terrace

2) Sealing of electrical shafts

Smoke Management System

3) Fire rating of shaft door

E. Width of corridor

Compartmentation

1) Fire check door

4) Water curtain

5) Fire Dampers

1) Basements

2) Upper floors

F. Door size

3.

4.

5.	Fire Extinguishers						*	
/ *	1) Total numbers		Nos.		Nos.	- 9	IR	
	2) Types		3C & CO2	-	BC & CO2	-	IR	
	3) ISI marking	Required		Pr	rovided	M	IR	
6.	First-Aid Hose Reel	3 N N						
	1) Total number of eachfloor	01		100	01		<u>IR</u>	
	2) Length of hose reel hose	30 mtr.			30 mtr.		MR	
×	3) Nozzle diameter	05 mm		05 mm		N	IR	
7.	Automatic Fire Detection & Alarming Syst							
	1) Type of detectors	N/A		N/A			N/A	
	2) Location of main panel	N/A		N/A		-	N/A	
	3) Location of repeater panel	N/		N/A		-	N/A	
	4) Alternate source of power	N/			N/A		N/A	
	5) Hooter's Location	N/A		N/A			N/A	
8.	MOEFA	N/A		N/A		1	J/A	
9.	Public Address System		Required		Provided		/IR	
10.	Automatic Sprinkler System					-		
	1) Basement		A	N/A		N/A		
	2) Upper floors	N/		_	[/A	-	N/A	
	3) Sprinkler above false	N/A		N/A		I	N/A	
	ceiling							
11.	Internal Hydrants						7/4	
	1) Size of riser/down-comer	N/A		N/A		- 1	N/A	
	2) Number of hydrants per	N/	'A	N/A		1	N/A	
	floor		3)		127/1			
	3) Hose box N/A		/A	N/A		1	N/A	
12.	Yard Hydrants	7			1-	T / A		
	1) Total number of hydrants	N/		_	I/A	_	V/A	
	2) Hose box	N	/A	I	J/A	1	V/A	
13.	Pumping Arrangement					-	27/4	
	1) Ground level		N/A		N/A		N/A	
	a) Discharge of main		N/A		N/A		N/A	
	pump			-	3.7.	-	3.T/A	
	b) Head of main pump		N/A		N/A	-	N/A	
	c) Number of main pu		N/A		N/A		N/A	
	d) Jockey pump out pu	ıt	N/A		N/A		N/A	
	e) Jockey pump head		N/A		N/A		N/A	
	f) Stand by pump outp		N/A		N/A	_	N/A	
	g) Stand by pump head		N/A		N/A	-	N/A	
	h) Auto starting/Manu	al	N/A		N/A	China Principal	N/A	
· · ·	stopping							
	2) Terrace level				107777		1 00	
	a) Discharge of pump		425 LPM		425 LPM	The same of the sa	MR	
	b) Head of pump		30 mtr.		30 mtr.		MR	
	c) Power supply		Required	-	Provided		MR	
	d) Auto starting of pur	np	Required		Provided	MACHINE STATE	MR	
			II.					



. .



14.	Captive Water Storage for	Fire Fighting		
	Under ground tank capacity	N/A	N/A	DI/A
	a) Draw-off connection	N/A	N/A	N/A N/A
	b) Fire service inlet	N/A	N/A	N/A N/A
	c) Access to tank	Required	Provided	MR
	d) Over head tank capacity	2,500 ltr.	2,500 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.		Tiovided	IVIK
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
-	d) Fireman's switch	N/A	N/A	N/A
4.00	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
×	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System Risk, if any:	m for Protecti	ion of special	N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection. Also owner has submitted an affidavit not to use above third floor.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2016/NDZ/104 dated 14/01/2016 renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name :- Rajinder Atwal Designation :- DO (CD)

Name: - M.K. Sharma

Designation :- ADO (CC)