GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2019/2175

Dated: 19/11/2019

FIRE SAFETY CERTIFICATE

Certified that the Diamond Guest house located at 3056/57, Gali No.1, Chuna Mandi, Pahar Ganj, New Delhi-110055 comprised of Ground + 04 Upper floors, Ground floor (reception) and 1st floor to and 3rd floor (05 guest rooms at each floor), 4th floor (02 staff rooms) total 15 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2016/1470 dated 04/10/16. The premises was re-inspected by the officer concerned of this department on 16/11/19 in the presence of Mr. Ajit Kumar (Manager) and has also submitted an affidavit not to use above third floor for any purpose and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 15 guest rooms only (upto 3rd floor only) with effect from 19-11-2019—for period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 19/11/2019 at New Delhi by.

(Sunil Chowdhary)
Dy. Chief Fire Officer
Delhi Fire Service

Copy to:-

- 1. The Joint Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.
- 2. The Manager,
 Diamond Guest House at 3056/57, Gali No.1, Chuna Mandi, Pahar Gani, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry'.
- 9. Any flammable material for interior decoration is prohibited.
- 10. Owner/Occupier shall also ensure compliance of notification dated 27.05.19 and there of in r/o guest houses.

| INSPECT | INSPECTION REPORT | | | |
|--------------------------------|--------------------------------|---|--|--|
| Name & address of the building | Diamond Guest house located at | 1 | | |

Gali No.1, Chuna Mandi, Pahar Ganj,

New Delhi-110055

2. Type of Occupancy:-Residential, Sub Division-A-1

Gr. + 04 Upper floors (total 15 Guest rooms)

Ground floor (reception),

1st floor to 3rd floor (05 guest rooms at each floor), & 4th floor (02 staff rooms)

3. Type of case:-Renewal

4. Details of previous FSC:-No. F6/DFS/MS/GH/2016/1470 dated

04/10/16.

5. Fire safety directives No.-N/A

6. Date of inspection:-16/11/19

7. Name of the inspecting officer:-Sh. Rajinder Atwal (DO/CD) &

Sh. Manoj Kumar Sharma (ADO/CC)

8. Name & designation of officer from the building side:-

Mr. Ajit Kumar (Manager)

9. Year of construction:-2010

Nil dated 14/09/2019. 10. Applicant's letter No:-

| | ** | | | Old Case |
|-------|---|---|------------------|-------------------|
| S.No. | Minimum Standards on fire Prevention and fire safety U/R 33 | Requirement/ Existing fire safety arrangements | Provided at site | Remarks MR/NMR |
| 1. | Access to Building | | | |
| | 1) Road width | N/A | 06 mtr. | N/A |
| | 2) Gate width | N/A | N/A | N/A |
| | 3)Width of internal road | N/A | N/A | N/A |
| 2. | Number, Width Type & Arr | angement of Ex | kits | |
| | A. Number of staircases | | | |
| | 1. Upper floors | 01 No. | 01 No. | MR |
| | 2. Basements | N/A | N/A | N/A |
| | B. Width of staircase | <u>/</u> | | |
| | 1. Upper floors | 80 cms. | 1.25 mtr. | MR |
| | 2. Basements | N/A | N/A | N/A |
| | C. Protection of exits | | 1.1.1 | - |
| | 1. Fire check door | N/A | N/A | N/A |
| | 2. Pressurization | N/A | N/A | N/A |
| | D. No. of continuous staircase to terrace | N/A | N/A | N/A |
| | E. Width of corridor | N/A | N/A | N/A |
| | F. Door size | 01 mtr. | 01 mtr. | MR |
| 3. | Compartmentation | | | |
| | 1) Fire check door | N/A | N/A | N/A |
| | 2) Sealing of electrical shafts | N/A | N/A | N/A |
| | 3) Fire rating of shaft door | N/A | N/A | N/A |
| | 4) Water curtain | N/A | N/A | N/A |
| | 5) Fire Dampers | N/A | N/A | N/A |
| 4. | Smoke Management System | | | 1 |
| | 1) Basements | 30 ACPH | N/A | N/A |
| | 2) Upper floors | 12 a/c per hour | Natural | MR |

| 5. | Fire Extinguishers | 4 | | |
|-----|-------------------------------|-----------------------|-----------|-------|
| | 1) Total numbers | 12 | 12 | MR |
| | 2) Types | ABC & CO2 | ABC & CO2 | MR |
| | 3) ISI marking | Required | Provided | MR |
| 6. | First-Aid Hose Reel | | | |
| | 1) Total number of eachfloor | 01 | 01 | MR |
| | 2) Length of hose reel hose | 30 mtr. | 30 mtr. | MR |
| (A) | 3) Nozzle diameter | 05 mm | 05 mm | MR |
| 7. | Automatic Fire Detection & | Alarming Syste | em | |
| | 1) Type of detectors | N/A | N/A | N/A |
| | 2) Location of main panel | N/A | N/A | N/A |
| | 3) Location of repeater panel | N/A | N/A | N/A |
| | 4) Alternate source of power | N/A | N/A | N/A |
| | 5) Hooter's Location | N/A | N/A | N/A |
| 8. | MOEFA | N/A | N/A | N/A |
| 9. | Public Address System | N/A | N/A | N/A |
| 10. | Automatic Sprinkler System | | AWAR | 11/11 |
| | 1) Basement | N/A | N/A | N/A |
| 3 | 2) Upper floors | N/A | N/A | N/A |
| | 3) Sprinkler above false | N/A | N/A | N/A |
| | ceiling | IVA | IN/A | IN/A |
| 11. | Internal Hydrants | | | |
| 11. | 1) Size of riser/down-comer | N/A | N/A | N/A |
| | 2) Number of hydrants per | N/A | N/A | N/A |
| - | floor | IV/A | IN/A | IN/A |
| | 3) Hose box | N/A | N/A | NT/A |
| 12. | Yard Hydrants | IV/A | IN/A | N/A |
| 12. | 1) Total number of hydrants | N/A | NI/A | DT/A |
| | 2) Hose box | | N/A | N/A |
| 13. | | N/A | N/A | N/A |
| 13. | Pumping Arrangement | 127/4 | 27/4 | |
| | 1) Ground level | N/A | N/A | N/A |
| | a) Discharge of main | N/A | N/A | N/A |
| | pump | 77/1 | | |
| | b) Head of main pump | N/A | N/A | N/A |
| | c) Number of main pump | N/A | N/A | N/A |
| | d) Jockey pump out put | N/A | N/A | N/A |
| | e) Jockey pump head | N/A | N/A | N/A |
| | f) Stand by pump output | N/A | N/A | N/A |
| | g) Stand by pump head | N/A | N/A | N/A |
| | h) Auto starting/Manual | N/A | N/A | N/A |
| | stopping | | | |
| | 2) Terrace level | _ | | |
| | a) Discharge of pump | 450 LPM | 450 LPM | MR |
| | b) Head of pump | 30 mtr. | 30 mtr. | MR |
| | c) Power supply | Required | Provided | MR |
| | d) Auto starting of pump | Required | Provided | MR |
| 14. | Captive Water Storage for F | | | |
| | 1) Under ground tank | N/A | N/A | N/A |
| | capacity | | | - |
| | a) Draw-off connection | N/A | N/A | N/A |
| | | | 1 | 1 |

| | b) Fire service inlet | N/A | N/A | N/A |
|-----|--|----------------|------------------|-----|
| | c) Access to tank | N/A | N/A | N/A |
| | d) Over head tank capacity | 2,500 ltr. | 2,500 ltr. | MR |
| 5. | Exit Signage. | Required | Provided | MR |
| 6. | Provision of Lifts. | | | |
| | a) Pressurization of lift shaft | N/A | N/A | N/A |
| | b) Pressurization of lift lobby | N/A | N/A | N/A |
| | c) Communication in lift car | N/A | N/A | N/A |
| | d) Fireman's switch | N/A | N/A | N/A |
| | e) Lift signage | N/A | N/A | N/A |
| 17. | Stand by Power Supply | Required | Provided | MR |
| 18. | Refuge Area | N/A | N/A | N/A |
| | Total area location | N/A | N/A | N/A |
| 19. | Fire Control Room | N/A | N/A | N/A |
| | a) Detector system panel | N/A | N/A | N/A |
| | b) Flow switch panel | N/A | N/A | N/A |
| | c) PA system panel | N/A | N/A | N/A |
| | d) Battery backup | N/A | N/A | N/A |
| | e) Building floor plan | N/A | N/A | N/A |
| 20. | Special Fire Protection Sys Risk, if any: | stem for Prote | ction of special | MR |

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection. Also owner has submitted an affidavit not to use above third floor.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2016/1470 dated 04/10/16 renewal under Rule 35 of the Delhi Fire Service Rules 2010, is recommended.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name :- Sh. Rajinder Atwal

Designation :- DO (CD)

F.t. please

Name:- M.K. Sharma

Designation: - ADO (CC)

F.T lester is DUCK (N/DZ)