GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No F 6 / DFS / MS / 2019 / 2155

Dated: 57/1/2019

FIRE SAFETY CERTIFICATE

> (Dharampal Bhardwaj) Dy.Chief Fire Officer Ph.-011-25104544

Copy to:-

- 1. The Director, Education, Government of N.C.T of Delhi. Old Sectt. Delhi 54.
- 2. The Principal, M.C Primary Girls School, Shakti Nagar, Delhi-110007

Conditions for the validity of Fire Safety Certificate:

- 1 All the means of escape/entry/exit shall be kept free from any obstruction.
- 3. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 4. All the staff members must know the correct method of operation of firefighting system.
- 4 The owner / occupier shall submit a declaration **every year** in **Form "K"** provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on http://delhi.gov.in./wps/wcm/connect/doit fire/FIRE/Home/Forms.
- 5 This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6 "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in **Form 'J'** [sub rule (1) of rule 37] along with a copy of this Certificate, **six months** prior to its expiry".

INSPECTION REPORT

1. Name & address of the building : M.C Primary Girls School, Shakti Nagar, Delhi-110007.

2. Type of Occupancy :Educational

3. Type of Case : Renewal (Ground +01 upper floor)

4. Details of previous NOC : F6/DFS/MS/School/2016/WZ/1337 dated: 01.09.2016

5. Fire Safety directives letter No : Director of Education Circular dated 01.03.2011

6. Date of inspection : 21.10.20197. Name of the Inspecting Officers : ADO (RN)

8. Name and designation of officers

from the building side : Mrs. Gurmeet Kaur (Principal)

9. Year of Construction : 1993

10. Applicant's letter No. : Nil Diary No.-20359 Dated: 13.09.2019

	Minim	um Standards on fire prevention and fire safety U/R 33	Circular of Director of Education	Provided at site	Remarks MR/NMR	
1	Access to building					
	•	Road width	Accessible	Accessible	MR	
	•	Gate width	Accessible	Accessible	MR	
	•	Width of internal road	NA	NA	NA	
2	Number, Width, Type & Arrangement of Exits					
	a. Numb	per of staircases				
	•	Upper Floors	02	02	MR	
		Basements	NA	NA	NA	
	b. Widt	h of staircases	_		MD	
	•	Upper Floors	1.5m	1.50m & 1.52m	MR	
		Basements	NA	NA	NA	
	c Prote	ection of exits				
	•	Fire check door	NA	NA	NA	
	•	Pressurization	NA	NA	NA	
	d. No.	of continuous staircases to terrace	. 01	01	MR 9	
	e. Widt	h of Corridor	2m NA	3.21m	MR NA	
	f. Door	Size	1.00 m	1.22m	MR	
3	Compartmentation.					
	•	Fire check door	NA	NA	NA	
	•	Sealing of electrical shafts	NA	NA	NA	
	•	Fire Rating of shaft door	NA	NA	NA	

	Water Curtain					
	• Fire Dampers	NA	NA	NA NA		
	- ne Bampers	NA	NA	NA		
1	Smoke Management System.					
	Buschients	30 a/c per hour	NA	NA		
	Upper floors	12 a/c per hour	Natural Ventilated	MR		
	Fire Extinguishers			1111		
	Total numbers	0.4				
	• Types	04 nos	05nos	MR		
	ISI marking	ABC/Co2	ABC-05	MR		
	First-Aid Hose Reels.	ISI Marked	Yes	MR		
	First-Aiu riose Reels.					
	 Total numbers on each floor 	NA	NA	NA		
	 Length of hose reel hose 	NA	NA			
	 Nozzle diameter 	NIA		NA		
	Automatic fire detection and alarming syste	NA em.	NA	NA		
-	Type of detectors					
		NA	NA	NA		
	Boothon of Main Panel	NA	NA	NA		
	200ation of Repeater Panel	NA	NA.	NA		
	Alternate source of powerHooters' Location	NA	NA	NA		
		NA	NA	NA		
ľ	MOEFA	NA	NA	NA		
F	Public Address System.	NA				
A	Iltomotic S II. a	NA	NA	NA		
1	Automatic Sprinkler System.					
	• Basement	NA	NA	NA		
	 Upper Floor 	NA	NA			
	 Sprinkler above false ceiling 	NA		NA		
In	ternal Hydrants	INA	NA	NA		
-	Size of riser/down as a second s					
	Size of riser/down-comerNumber of hydrants per floor	NA	NA	NA		
	Hose Box	NA	NA	NA		
Ya	rd Hydrants.	NA	NA	NA		
	7.55	-				
	Total number of hydrants	NA	NA	NA		
	Hose Box	NA	NA	=======================================		
			11/1	NA		

	Ground Level			N/A	
	Discharge of main Pump	N/A	N/A	/	
	➤ Head of Main pump	N/A	N/A	N/A	
	> Number of main pumps	N/A	N/A	N/A	
	Jockey Pump out put		N/A	N/A	
	Jockey pump head	N/A	N/A	N/A	
	> Standby Pump out put	N/A		N/A	
	> Standby Pump Head	N/A	N/A	*	
	Auto Starting/ Manual stoppingPump House Access	N/A	N/A	N/A N/A	
	Terrace level	N/A	N/A	IN/A	
	Discharge of pump	1			
	> Head of the pump	NA	N/A	NA	
	> Power Supply	NA	N/A	NA	
	> Auto Starting of pump	N/A	N/A	N/A	
		N/A	N/A	N/A	
	Captive Water Storage for fire fighting.				
		NA	NA	NA	
	Underground tank capacity	NA	NA	NA	
	> Draw-off connection	NA NA	NA	NA	
	> Fire service inlet	NA NA	NA	NA	
	> Access to tank			NA	
	Overhead Tank capacity	NA	N/A		
	Exit Signage.	NA	NA	NA	
5	Provision of Lifts.	- 2			
,		N/A	N/A	N/A	
	Pressurization of Lift Shaft	N/A	N/A	N/A	
	Pressurization of Lift lobby	N/A	N/A	N/A	
	Communication In lift Car			N/A	
	Fireman's Grounding Switch	N/A	N/A		
	Lift Signage	N/A	N/A	N/A	
7	Standby power supply	N/A	N/A	N/A	
18	Refuge Area.	I			
10		N/A	N/A	N/A	
	> Total Area	N/A	N/A	N/A	
	> Location				

	and the second s			
×	Detector System Panel	N/A	N/A	N/A
	Flow Switch Panel	N/A	N/A	N/A
	PA System Panel Patter backure	N/A	N/A	N/A
	Batter backupBuilding Floor Plans	N/A	N/A	N/A
		N/A	N/A	N/A
20	Special Fire Protection Systems for Protection of special Risks, if any:	N/A	N/A.	N/A

The fire protection systems provided in the building were tested/ checked randomly and found in working condition at the time of inspection.

Keeping in view the satisfactory compliance of the minimum standards on fire prevention and fire safety required as stipulated in director of education Circular dated 01.03.2011, it is recommended to renewal of fire safety certificate issued vide this department letter of even no.1337 dated 01.09.2016.

Signature of the Inspecting Officer

Name: - Rajesh Kumar Designation: - ADO/RN

rettel