GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. **F6/DFS/MS/Indl./2019/NDZ/** 2/37

Dated: 19/11/19

FIRE SAFETY CERTIFICATE

Certified that the Plot no. 346, FIE Patpargang, Industrial area Delhi-92, comprised of basement, ground plus one upper floor owned/occupied by Sage Metals Limited have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules 2010. The premises was re-inspected by the concerned of this department on dated 09/09/19 in the presence of Sh. Satish Kumar Rustgi (GM) and found that the premises is fit for occupancy Group G-1 (Industrial Building), with effect from....for a period of three years, in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010, printed overleaf.

Chief Fire Officer
Delhi Fire Service

5h

To,

The Excutive Engineer (Bldg.)HQ,
East Delhi Municipal Corporation,
Udyog Sadan, Patpargang, Industrial Area Delhi-92.
Copy to-

The Manager,
Plot no. 346, FIE,
Patpargang Ind. Area, Delhi-110092.

CONDITIONS:

- 1. All the means of escape shall be kept free of all the type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc. may be got verified from the authorities concerned.
- 5. This Fire Safety Certificate can not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. All comments/ directions of the Licensing Department shall always be permitted and followed.
- 7. The owner /occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form'J'[sub rule(1) of rule 37] along with a copy of this certificate,six months prior to its expiry"
- 8. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

ADOLAY

INSPECTION REPORT

1. Name & address of the building

: Plot no. 346, FIE Patpargang, Industrial area Delhi-92.

2. Building is comprised of

: Basement, Ground+1 Upper floor

3. Type of Occupancy

: Industrial(Low Hazard) G-I (##)

4. Type of Case

: Renewal

5. Details of Previous NOC

: F6/MS/DFS/BP/98/1419 Dated 29/07/98

6. Fire Safety direcțion letter No

7. Date of Inspection

: 09/09/19 *

8. Name of the Inspecting Officers: : R.K.Yadav (ADO)

9. Name of the designation of Officer

: Sh. Satish Kumar Rustgi (GM)

from the building side 10. Year of Construction

: 1997-98

: dated 24/07/19

11. Applicant's letter No	: dated	24/07/19					
	on fire	BBL/NBC	Provided at	Remarks			
N prevention and fire safety U/	R33	Part-IV	Site	MR/NMR			
1 Access to building	Access to building						
Road width		12 m	12 m	MR			
Gate width		4.5 m	4.5 m	MR			
Width of internal road	£.	N.A.	N.A.	N.A.			
Number, Width, Type and Arrangement of Exits							
a. Number of Staircases		2 nos.	2	MR			
Upper Floor	Upper Floor		2 nos.	MR			
Basement		2 no.	2 no.	IVIN			
b. Width of Staircases	b. Width of Staircases		10.0.00	MR			
Upper Floor	Jpper Floor		1.40 & .90 m				
Basement		1.40 & 1.25 m	1.40 & 1.30 n	n MR			
c. Protection of exits		3		8.4D			
Fire check door	A	Required	Provided	MR			
Pressurization		N.A.	N.A.	N.A.			
e. No. of continuous sta	ircases to	1 no.	1 no.	MR			
terrace	·	1.5 m	1.5 m	MR			
g. Width of Corridor h. Door Size		N.A.	N.A.	N.A.			
		1					
3 Compartmentation.		Required	Provided	MR			
Fire check door		N.A.	N.A.	N.A.			
Sealing of electrical shafts		N.A.	N.A.	N.A.			
Fire rating of shaft door Water curtain		N.A.	N.A.	N.A.			
Fire Dampers		N.A.	N.A.	N.A.			
System System	-m.	7					
	4	Required	Ventilated				
Basement / Upper floor		N.A.	N.A.	N.A.			
5 Fire Extinguisher				NAD			
Total numbers	· ·		Provided	MR			
types		CO ₂ & ABO					
ISI marking		ISI marked Provided		I MR			

Ny

6	First-aid-Hose Reels.		,					
	Total numbers of each floor	1 no.	Provided	MR				
	Length of hose reel hose	30 m	Provided	MR				
	Nozzle diameter	5 mm	Provided	MR				
Type of detectors Location of main panel	Automatic fire detection and alarming system.							
	Type of detectors	N.A.	N.A.	N.A.				
		N.A.	N.A.	N.A.				
	Location of repeater panel .	N.A.	N.A.	N.A.				
	Alternate source of power	N.A.	N.A.	N.A.				
		N.A.	N.A.	N.A.				
	Hooters's location	ST 81 1995 SERVI	(5)					
8	MOEFA	N.A.	N.A:	N.A.				
9 .	Public address System.	N.A.	N.A.	N.A.				
10	Automatic Sprinkler System.							
	Basement	Required	Provided	MR				
	upper floor	, N.A. s	N.A.	N.A.				
	sprinkler above false ceiling	N.A.	N.A.	N.A.				
11	Internal Hydrants		•					
	size of riser/down-comer	100 MM	Provided	MF				
	Total no. of hydrants each floor	01 No.	Provided	MF				
	Hose Box per floor	01 No.	Provided	MR				
12	Yard Hydrants.	2	*					
-	Total number of hydrants	N.A.	N.A.	N.A.				
100	Hose Box	N.A.	N.A.	N.A.				
13	Pumping Arrangements.							
	Ground Level							
	Discharge of main Pump	N.A.	N.A.	N.A				
	➤ Head of Main Pump	N.A.	N.A.	N.A				
	Number of main pumps	N.A.	N.A.	N.A				
	➢ Jockey pump out put	N.A.	N.A.	N.A				
	Jockey pump head	N.A.	, N.A.	N.A				
	Standby pump out put	N.A.	N.A.	N.A				
	> Standby pump Head	N.A.	N.A.	N.A				
C	Auto Starting /Manual stopping	N.A.	N.A.	N.A				
	> Pump House Access	N.A.	N.A.	. N.A				
	Terrace Level							
	Discharge of pump	900 LPM	Provided	M				
-	Head of the Pump	40 m	Provided	M				
	> Power supply	Required	Provided .	MI				
98	Auto Starting of pump	Required	Provided	MI				
14	Captive Water Storage for Fire Fighting.	1	2					
	Underground tank capacity	N.A.	N.A.	N.A				
	Draw-off connection			N.A				
	Fire service inlet	N.A. *	N.A.	N.A				
	Access to tank	N.A.	N.A.	N.A				
		15,000 Liters	15,000 liters	M				
15	Overhead Tank capacity Exit Signage.	Required	provided	M				
	L LUIZ LIGIDOGO	L COULTROO						

Provision of Lifts.	k.		24		
Pressurization of Lift Shaft	N.A.	N.A.	N.A.		
Pressurization of Lift lobby	N.A.	N.A.	N.A.		
Communication in lift car	N.A.	N.A.	N.A.		
Firemen's grounding switch .	N.A.	N.A.	N.A.		
Lift Signage	N.A.	N.A.	N.A.		
Standby power supply	N.Á.	' N.A.	N.A.		
Refuge Area.					
Total area	N.A.	N.A.	N.A.		
Location	N.A.	N.A.	N.A.		
Fire Control Room			8		
Detector system panel	N.A.	N.A.	N.A.		
Flow switch panel	N.A.	N.A.	N.A.		
PA system panel	N.A.	N.A.	N.A.		
Batter backup	N.A.	N.A.	N.A.		
Building Floor Plans	N.A.	N.A.	N.A.		
Special Fire Protection systems for protection of special Risks, if any:	N.A.	N.A.	N.A.		
	Pressurization of Lift Shaft Pressurization of Lift lobby Communication in lift car Firemen's grounding switch Lift Signage Standby power supply Refuge Area. Total area Location Fire Control Room Detector system panel Flow switch panel PA system panel Batter backup Building Floor Plans Special Fire Protection systems for	Pressurization of Lift Shaft Pressurization of Lift lobby N.A. Communication in lift car Firemen's grounding switch Lift Signage N.A. Standby power supply Refuge Area. Total area Location N.A. Fire Control Room Detector system panel Flow switch panel PA system panel Batter backup Building Floor Plans Special Fire Protection systems for N.A. N.A. N.A. Special Fire Protection systems for N.A. N.A. N.A. N.A. N.A. N.A. N.A. N.A	Pressurization of Lift Shaft Pressurization of Lift lobby Communication in lift car Firemen's grounding switch Lift Signage N.A. Standby power supply N.A. Refuge Area. Total area Location Detector system panel Flow switch panel PA system panel Batter backup Building Floor Plans N.A. N.A.		

The fire protection system provided in the building were tested/checked and found functional at the time of inspection.

Keeping in view the compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010.

Signature of the Inspecting Officer

Name: R.K.Yadav

Designation: ADO (LN)

. DY. CHO/ADZ

Ab)X

FEMILY

Any/LN

waystue heave