## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI- 110001

No.F.6/DFS/MS/School/2019/NDZ/ 2184

Dated: 2 ( ) 11/19

## FIRE SAFETY CERTIFICATE

Certified that the East End Public School running at ground & first floor building comprised of basement (vacant) ground & first floor at B-1/12,New Ashok Nagar, Delhi-110096, owned/occupied by East End Public School have complied with the fire prevention and fire safety requirements in accordance with the Circular No. 262-362 dated 17/01/2005 issued by the Director of Education and verified by the officer concerned of this department on 10/10/19 & 11/11/19 in the presence of Mr. Rahul (coordinator) of the school and found that the school building ground & first floor is fit for occupancy class B 'Educational Building' for with effect from Delhi fire prevention and found that the school building ground are period of three years in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010, printed overleaf.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

To,

The Principal,
 East End Public School,
 B-1/12, New Ashok Nagar, Delhi-110096.

## - Conditions -

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in good working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc. may be got verified from the authorities concerned.
- 5. This Fire Safety certificate can not be treated in any case for regularizations of unauthorized construction if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7."The owner /occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form'J'[sub rule(1) of rule 37] along with a copy of this certificate, six months prior to its expiry"

Sporm

				L R 1/12 New /	Ashol	<	
1. Name & address of the building	:East [	end Public S	CHOO	I, B-1/12,New			
1. Name & address or	Naga	ır, Delhi-110	096.	O fire	floo	r only)	
2. Building is comprised of	: Base	ement,G+1	scho	ool at gr. & first	. 1100		
		: Educational					
3. Type of Occupancy							
4. Type of Case	: Nil				1000		
5. Details of Previous FSC	· Ci	rcular No. 26	62-36	62 dated 17/01	/200	5	
6. Fire Safety direction letter No	. 10	0/10/19 & 1	1/11	/19			
7. Date of Inspection		K. Yadav (Al					
8. Name of the Inspecting Officers						•	
9. Name of the designation of Offi	· N	1r. Rahul (Co	ordi	nator)			
from the building side	. 10	11.11.01.01		*			
10. Year of Construction		Nil dated 16	/09/	19			
11. Applicant's letter No		Requirement P		Provided at Site		Remarks	
S.No Minimum Standards on fire	e Rec	ullement			MR	/NMR	
prevention & fire safety							
U/R33	-						
1 Access to building		,	20 -	2	MF	3	
Road width	6 m		20 n		N.	A	
Gate width	N.A		N.A		N.	A	
control road	N.A		N.A				
2 Number, Width, Type and	d Arrang	gement of E	XITS				
a. Number of Staircases			_		N	IR .	
Upper Floor	2 r	10.	·2 n			.A	
Basement	N.	Α	N.A	4			
B. Width of Staircases			<u> </u>	1	N	ЛR	
Upper Floor	1.	5 m	-	22 m each		I.A	
Basement	N	.A	N.	Α		V.A	
c. Protection of exits	N	.A	N.	Α			
Fire check door	N	.A	N.A			V.A	
Pressurization	N	I.A	N	Α.		N.A	
c continu		1 no.	0	1 no.		MR	
d. No. of continu							
e. Width of Corridor		1.5 m	1	5 m		MR	
1	-	1.5 III 1 m		0 m		MR	
f. Door Size		T 111					
3 Compartmentation.		NI A	1	V.A		N.A	
Fire check door	-	N.A		N.A		N.A	
Sealing of electrical sh	-	N.A		N.A		N.A	
Fire rating of shaft do	or	N.A		N.A		N.A	
Water curtain		N.A				N.A	
Fire Dampers		N.A		N.A			
4 Smoke Management	System			A1 A		N.A	
Basement		N.A		N.A		N.A	
Upper floor		N.A		N.A		IVIA	
- in index						NAD	
5. Fire Extinguisher  Total numbers	06 no		06 nos.			MR	
		CO <sub>2</sub> & AB	С	CO <sub>2</sub> & ABC	- N	MR	
types		ICI marke	d	ISI marked		MR	

6	First-aid-Hose Reels.									
	Total numbers of each floor	01 nos.	01 nos.	MR						
	Length of hose reel hose	30 mm	30 mm	MR						
	Nozzle diameter	5mm	5mm	MR						
7	Automatic fire detection and alarming system.									
	Type of detectors	N.A	N.A	N.A						
	Location of main panel	N.A	N.A	N.A						
	Location of repeater panel	N.A	N.A	N.A						
	Alternate source of power	N.A	N.A	N.A						
	Hooters	N.A	N.A.	N.A.						
8	MOEFA	Required	Provided	MR						
9	Public address System.	N.A	Provided	MR						
10	Automatic Sprinkler System.									
	Basement	Required	Provided	MR						
	upper floor	N.A	N.A	N.A						
	sprinkler above false ceiling	N.A	N.A	N.A						
11	Internal Hydrants	,								
	size of riser/down-comer	N.A	N.A	N.A · ·						
	Number of hydrants per floor	N.A	N.A	N.A						
	Hose Box	N.A	N.A	N.A						
12	Yard Hydrants.									
	Total number of hydrants	N.A	N.A	N.A						
	Hose Box	N.A	N.A	N.A						
13	Pumping Arrangements.									
	Ground Level	N.A	N.A	N.A						
	Discharge of main Pump	N.A	900 LPM	MR						
	Head of Main Pump	N.A	40 M	MR						
	Number of main pumps	N.A	N.A	N.A						
	Jockey pump out put	N.A	N.A	N.A						
	Jockey pump head	N.A	N.A	N.A						
	Standby pump out put	N.A	N.A	N.A						
	Standby pump Head	N.A	N.A	N.A						
	Auto Starting /Manual stopping	N.A	N.A	N.A						
	Pump House Access	N.A	N.A	N.A						
	Terrace Level									
	Discharge of pump	450 LPM	450 LPM	MR						
	Head of the Pump	40 M	40 M	MR						
9	Power supply	Required	Provided	MR						
	Auto Starting of pump	Required	Provided	MR						
14	Captive Water Storage for Fire Fighting.									
	Underground tank capacity	N.A	5000 liters	MR						
	Draw-off connection	N.A	N.A	N.A · ·						
	Fire service inlet	N.A	N.A	N.A						
	Access to tank	N.A	N.A	N.A						
	Overhead Tank capacity	5000 liters	5000 liters	MR						
1			Provided	MR						

16	Provision of Lifts.			
	Pressurization of Lift Shaft	N.A	N.A	N.A
Communic Firemen's	Pressurization of Lift lobby	N.A	N.A	N.A
	Communication in lift car Firemen's grounding switch Lift Signage	N.A	N.A	N.A
		N.A	N.A	N.A
17		N.A	N.A	N.A
.8	Standby power supply	N.A	N.A	N.A
.0	Refuge Area.			IV.A
ž	Total area	N.A	N.A	N.A
.9	Location	N.A	N.A	N.A
	Fire Control Room			
F B	Detector system panel Flow switch panel PA system panel Batter backup Building Floor Plans	N.A	N.A	N.A
		N.A	N.A	N.A
		N.A	N.A	N.A
		N.A	Ń.A	· N.A
		N.A	N.A	N.A
	Special Fire Protection systems	N.A	N.A	N.A
	for protection of special Risks, if any:	·		

The fire protection systems provided in the building were tested/checked at the time of Keeping in view the

Keeping in view the compliance of the minimum standards on fire prevention and fire safety required under the Circular No. 262-362 dated 17/01/20051 Director of Education, it is recommended to grant Fire Safety Certificate.

Signature of the Inspecting officer

Name-

R.K.Yadav

Designation-

ADO(LN)

DO(East)

M. Wol Many

Speak on 2 (A).

Remdon 31/2

31/X