GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2019 / 2201

Dated :- 2211119

FIRE SAFETY CERTIFICATE

Certified that the R.G. Guest House located at 3334, Gali Hari Mandir, Pahar Ganj, New Delhi comprises of Basement + Ground + 03 Upper floor, Basement (Sealed), Ground floor (02 guest rooms + reception + office), 1st floor to 3rd floor (04 guest rooms at each floor), total 14 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2016/NDZ/1772 dated 08/12/2016. The premises was re-inspected by the officer concerned of this department on 16/11/2019 in the presence of Sh. Rohit (Owner). Owner/Occupier has submitted an affidavit not to use above third floor and found that the said guest house building and have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential Group A-1 as above 14 guest rooms only with effect from ---2-1++1---2019 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on at New Delhi by.

(Sunil Chowdhary) Dy. Chief Fire Officer Delhi Fire Service

AC.

Copy to:-

- 1. The Addl. C.P./Lic(H), First Floor, P.S. Defence Colony New Delhi Ref. letter No. 15858/Addl. C.P./Lic.(H) dated 28/10/2019.
- 2. The Manager LA Budha Guest House located at 3334, Gali Hari Mandir, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 9. Any flammable material for interior decoration is prohibited.
- 10. Owner/Occupier shall also ensure compliance of notification dated 27.05.19 and there of in r/o guest houses.

		N/16 -		
	INSP	ECTION REPO	RT	
1.1	Name & address of the building		House located at 33	334.
			andir, Pahar Ganj,	
2.	Type of occupancy:-		Sub Division-A-1	
			per floors (14 Guest roo	oms)
		Basement (Sea	led), Ground floor (0	2 guest rooms +
			ice), 1st floor to 3rd fl	oor (04 guest
2	Type of case.	rooms at each	floor)	
	Type of case:-	Renewal		
4.	Details of previous FSC:-		GH/2014/NDZ/17	72 dated
_	F' C 1' 3'	08/12/2016.		
	Fire safety directives No	N/A		
6.	Date of inspection:-	16/11/19		
7.	Name of the inspecting officer:	- Sh. Rajinder	r Atwal (DO/CD)	&
		Sh. Manoj K	Lumar Sharma (AD	OO/CC)
8.	Name & designation of officer			
	From the building side:-	Sh. Rohit (Owner)	
9.	Year of construction:-	2010	~	
10.	Applicant's letter No:-	No. 15858/Addl	. CP/Lic.(H) dated 28/	10/19
S.No.	Minimum Standards on fire	Requirement/	Provided at site	Remarks
	Prevention and fire safety U/R	Existing fire		MR/NMR
	33	safety		,
		arrangements		
1.	Access to Building			

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR
1.	Access to Building			v
	1) Road width	N/A	N/A	N/A
	2) Gate width	N/A	N/A	N/A
	3)Width of internal road	N/A	N/A	N/A
2.	Number, Width Type & Arrangement of Exits			
	A. Number of staircases			
	1. Upper floors	01 No.	01 No.	MR
	2. Basements	01 No.	01 No.	MR
	B. Width of staircase	je.	200	
	1. Upper floors	0.80 mtr. Existing old case	1.22 mtr.	MR
	2. Basements	N/A	N/A	N/A
	C. Protection of exits		2.5	
	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A	N/A	N/A
	D. No. of continuous staircase to terrace	01	01	MR
	E. Width of corridor	1 mtr.	1 mtr.	MR
	F. Door size	1 mtr.	1 mtr.	MR
3.	Compartmentation			15
	1) Fire check door	N/A	N/A	N/A
	2) Sealing of electrical shafts	N/A	N/A	N/A
	3) Fire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	N/A	N/A
4.	Smoke Management System			
	1) Basements	NA	N/A	N/A
	2) Upper floors	12 a/c per	Natural Ventilation	MR

_1)/17 -

				1
5.	Fire Extinguishers			
	1) Total numbers	08 Nos.	10 Nos.	MR
	2) Types	ABC & CO2	ABC & CO2	MR
	3) ISI marking	Required	Provided	MR
6.	First-Aid Hose Reel			
	1) Total number of eachfloor	01	01	MR
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
	3) Nozzle diameter	05 mm	05 mm	MR
7.	Automatic Fire Detection &			
	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	N/A
8.	MOEFA	N/A	Provided	N/A
9.	Public Address System	N/A	N/A	N/A
10.	Automatic Sprinkler System		,	
×	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling		40°C 4331 Goodfeedo	12
11.	Internal Hydrants			
2	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	N/A	N/A
	floor		4	
	3) Hose box	N/A	N/A	N/A
12.	Yard Hydrants			
	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement			
10.	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A
	pump	14/21	1071	14/21
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump		N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output		N/A	N/A
		N/A	N/A	N/A
		N/A	N/A	N/A
	,	IN/A	IN/A	IN/A
	stopping 2) Terrace level			
		450 I DM	450 LPM	MR
	a) Discharge of pump	450 LPM		-
	b) Head of pump	30 mtr.	30 mtr.	MR
	c) Power supply	Required	Provided	MR
4.4	d) Auto starting of pump		Provided	MR
14.	Captive Water Storage for 1		27/4	DT/A
	1) Under ground tank	N/A	N/A	N/A



	capacity			
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	3000 ltr.	3000 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
3	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Sys Risk, if any:	tem for Protec	tion of special	NA

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2016/NDZ/1772 dated 08/12/2016 renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name :- Rajinder Atwal Designation:- DO (CC)

Name:- M.K. Sharma Designation:- ADO (CC)