GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No.F6/DFS/MS/School/2019/NDZ/ 2) 87

Dated: 21/11/19

FIRE SAFETY CERTIFICATE

Issued on..........at New Delhi by

(Sunil Chawdhary) Dy. Chief Fire Officer

To,

The Manager,

M/s Raman Modern Public School at 338, Gali No-5, Shagat Vihar, Delhi-110094

Copy:-

The Dy. Director of Education B–Block, Yamuna Vihar, North-East, Delhi-110053

Conditions for the validity of Fire Safety Certificate

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipment shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.

5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

7. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form 'J' [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry.

1. Name & address of the building

: Raman Modern Public School,

338, Gali No-5, Bhagat Vihar, Delhi-110094

2. Building is comprised of

:Ground plus two upper floors

(School is running on ground plus first floor only)

3. Type of Occupancy

:Educational

4. Type of Case

:Renewal

5. Details of Previous NOC letter

:F6/MS/DFS/MS/2009/3501 dated-20/11/09 (for G+1)

6. Fire Safety direction letter No

:Circular 262-362 dated 17/01/2005 issued by DoE

7. Date of Inspection

:23/10/2019

8. Name of the Inspecting officers

:DO F. Brown

9. Name and designation of Officer from the building side

: Mr. Rajpal Sharma (Manager)

10. Year of Construction

:2006

11. Applicant's letter No

:Nil, Dated- 29/07/19

Sr. No.	Minimum Standards on Fire	Circular Requirement	Provided at Site	Remarks MR/NMR			
01	Prevention and Fire Safety U/R33 Requirement MR/NMR Access to Building.						
<u> </u>	Road width Gate width	06 mtr.	4.50 mtr.	M (Old accepted)			
	Width of internal road	N/A	N/A	N/A			
	Width of internal road	N/A	N/A	N/A			
02	Number, Width, Type and Arrangement of Exits.						
	a. Number of Staircases			MD			
	 Upper floor 	01 nos	02 nos	MR			
	Basement	N/A	N/A.	N/A			
	b. Width of Staircases • Upper floor	1.50 mtr.	1.30 mtr. & 0.78 mtr	MR			
	Basement	· N/A	N/A	N/A			
	c. Protection of exits						
	Fire check door	N/A	N/A	N/A			
	Pressurization	N/A	N/A	N/A			
	d. No. of Continuous Staircases to Terrace	01 No.	01 No.	MR			
	e. Width of Corridor	1.50 mtr.	1.50 mtr.	MR			
	f. Door Size	01 mtr.	01 mtr.	MR			
03	Compartmentation.						
	Fire check door	N/A	N/A	N/A			
	Sealing of electrical shafts	N/A	N/A	N/A			
10	Fire rating of shaft door	N/A	N/A	N/A			
	Water curtain	N/A	N/A	N/A			
	Fire dampers	N/A	N/A	N/A			
04	Smoke Management System.						
	Basement	N/A	N/A	N/A			
	Upper floor	N/A	N/A	N/A			
05.	Fire Extinguishers.						
	Total numbers	04 nos.	08 nos.	MR			
	Types	ABC /CO ₂	ABC /CO ₂	MR			
1	IS marking	ISI marked	ISI marked	MR			

06	First-Aid-Hose Reels.	/					
	Total numbers on each floor	01 No.	01 No.	MR			
	 Length of hose reel hose 	30 mtr.	30 mtr.	MR			
	Nozzle diameter	05 mm	05 mm	MR			
07	Automatic Fire Detection and Alarming System.						
	 Type of detectors 	N/A	N/A	N/A			
	 Location of main panel 	N/A	N/A	N/A			
	 Location of repeater panel 	N/A	N/A	N/A			
	Alternate source of power	N/A	N/A	N/A			
08	Hooter's location	N/A	N/A	N/A			
	MOEFA	N/A	N/A	N/A			
09	Public Address System.	N/A	N/A	N/A			
10	Automatic Sprinkler System.						
	Basement	N/A	N/A	N/A			
	 upper floor 	N/A	N/A	N/A			
4.4	sprinkler above false ceiling	N/A	N/A	N/A			
11	Internal Hydrants						
	 size of riser/down-comer 	N/A	N/A	N/A			
	 Number of hydrants per floor 	N/A	N/A	N/A			
1.0	Hose box	N/A	N/A	N/A			
12	Yard Hydrants.						
	 Total number of hydrants 	N/A	N/A	N/A			
12	Hose Box	N/A	N/A	N/A			
13	Pumping Arrangements.						
	➢ Ground Level						
	Discharge of main pump	N/A	N/A	N/A			
	 Head of Main pump 	N/A	N/A	N/A			
	 Number of main pumps 	N/A	N/A	N/A			
	 Jockey pump out put 	N/A	N/A	N/A			
	Jockey pump head	N/A	N/A	N/A			
	Standby pump out put	N/A	N/A	N/A			
	Standby pump head Auto Starting /Manual stopping	N/A	N/A	N/A			
	rate starting rivialidal stopping	N/A N/A	N/A	N/A			
	Pump house accessTerrace Level	IN/A	N/A	N/A			
	Discharge of pump	220 Lpm.	220 1	NAD.			
	Head of the pump	40 M	220 Lpm. 40 M	MR MR			
	Power supply	Required	Provided	MR			
	Auto Starting of pump	Required	Provided	MR			
14	Captive Water Storage for Fire Fighting.	-					
	Underground tank capacity	N/A	N/A	N/A			
	Draw-off connection	N/A	N/A	N/A			
	Fire service inlet	N/A	N/A	N/A			
	Access to tank	N/A	N/A	N/A			
15	Overhead tank capacity Figure 2.2 F	2500 Ltr.	2500 Ltr	MR			
15	Exit Signage.	Required	Provided	MR			
16	Provision of Lifts.		şăs.				
	Pressurization of lift shaft	N/A	N/A	N/A			
	 Pressurization of lift lobby 	N/A	N/A	N/A			
	 Communication in lift car 	N/A	N/A	N/A			
	 Firemen's grounding switch 	N/A	N/A	N/A			
	 Lift signage 	N/A	N/A	N/A			

17	Standby Power Supply	N/A	N/A	N/A		
18	Refuge Area.	3.				
	Total area	N/A	N/A	N/A		
	Location	N/A	N/A	N/A		
19	Fire Control Room					
	Detector system panel	N/A	N/A	N/A		
	Flow switch panel	N/A	N/A	N/A		
	PA system panel Battery backup	N/A	N/A	N/A		
		N/A	N/A	N/A		
	Building floor plans	N/A	N/A	N/A		
20	Special Fire Protection Systems for Protection of Special Risks, if any:	N/A	N/A	N/A		

The fire protection systems provided in the building were tested/checked and found functional at the time of inspection.

Keeping in view the deemed compliance of the minimum standards on fire prevention and fire safety required under the circular No. 262-362 dated 17/01/2005, it is recommended to renew Fire Safety Certificate.

Signature of the Inspecting Officer

Name

- F. Brown

Designation - D.O (ED)

Dy. CFO(NOZ)

F. t. pleast

DO(E)

Fit lell is Prepar and put up for synats ph-

DY. CFO/MS-Z

19)11

M.S. Ol