FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6/DFS/MS/SCHOOL/2019/

2322

Dated: 13/11/2019

FIRE SAFETY CERTIFICATE

Certified that the Nigam Utkrisht Vidyalaya (ID: 1354136) Located at Nimri Colony,

Delhi-52 comprised of Ground+ 1Upper floor only was issued FSC vide Letter No.

F6/DFS/MS/SCHOOL/2016/WZ/1626,Dated-03/11/2016, The premises was re inspected by the officer concerned of this department on 25/11/2019 in the presence of Mr. Mukesh Rana (Principal) and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deem complied with the fire prevention and fire safety requirements in accordance Circular DOE 3298-3398 dated 01-03-2011 and that the premises is fit for occupancy class "Educational" Group B with effect from

13 12 19 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

(Dharmpal Bhardwaj) Dy. Chief Fire Officer

Delhi Fire Service

Copy to:

1. The Principal, Nigam Utkrisht Vidyalaya (ID: 1354136) Located at Nimri Colony, Delhi-52

2. Director of Education, Old Secretariat, Delhi-110054

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

3. The trained staff should be available round the clock.

- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

6. All the exit route shall be kept free from any obstruction.

7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.dhigovt.nic.in.

INSPECTION REPORT

1. Name & address of the building: Nigam Utkrisht Vidyalaya (ID: 1354136)

Located at Nimri Colony, Delhi-52

: Educational (Ground + 1 Upper Floor) 2. Type of Occupancy

: Renewal 3. Type of Case

: F6/DFS/MS/SCHOOL/2016/WZ/1626,Dated-4. Details of previous NOC

No. of Students=682

No. of class rooms=30

03/11/2016

5. Fire Safety directives Letter No.: DOE 3298-3398 dated 01-03-2011

:25/11/2019 6. Date of inspection

7. Name of the Inspecting Officer: Udai vir singh, ADO (WP)

Plot area=4556 m² Covered area=1344 m²

8. Name and designation of Officer

:Mr. Mukesh Rana (Principal) from the building side

: 2010 9. Year of Construction

:Nil dated 31/10/2019 10. Applicant's letter No.

| S No | Minimum standards on fire prevention and fire safety U/R 33 | Cr.No.3298- 3398 dated 1-3- 11 | Provided at site | Remarks MR/NMR | |
|--|---|--------------------------------------|--|--------------------|--|
| 1. | Access of building | | | | |
| | Road widthGate widthWidth of internal road | Accessible Accessible NA | 20 mtr Provided 300cmProvided NA | MR MR NA | |
| 2. | Number, width, Type & Arrange | ements of exits | | | |
| | a. Number of staircasesUpper floorsBasements | 2 NA | 2,Provided NA | MR NA | |
| | b. Width of staircasesUpper floorsBasements | 1.5cm NA | 2x192 NA | MR NA | |
| Fire cl Pressu d. No of to terr e. Width | c. Protection of exits Fire check door Pressurization d. No of continuous stairca to terrace e. Width Of Corridor f. Door Size | NA NA NA Required 1 mtr | NA NA NA 210Provided 2x110cm Provi | NA NA NA MR ded MR | |
| | | | | | |

| 3. | Compartmentation | | | | | | | |
|-----|--|----------------|-----------------------|-----|------------------|----|----------|-----|
| | Fire check door | | NA | | NA | | NA | |
| | Sealing of electrical sha | fts | NA | 1 | NA | | NA | 1 |
| | Fire Rating of shaft door | r | NA | 1 | NA | 1 | NA | |
| | Water CurtainFire Dampers | | NA | | NA NA | | NA NA | |
| | | | NA |] | | | | |
| 4. | Smoke managements System | | | | | | | 11 |
| | Basements | | NA | | NA | | NA | |
| | Upper floors | | NA |] | NA | | NA | |
| 5. | Fire Extinguishers | | | | | | < | |
| | Total numbersTypes | | 05 nos. | | 10 Provide | d | MR | |
| | | | ABC & CO ₂ | | Provided | я | MR | |
| | IS marking | | ISI marked | | Provided | | MR | |
| 6. | First – Aid Hose Reels | | | | | | | |
| | The state of the s | | NA | NA | | NA | | |
| | Total namous on court is a | | NA | | | NA | | |
| | Nozzle diameter | | NA | | NA | | NA | |
| 7. | Automatic fire detection and al | arming s | system | | 2 | | | |
| | Type of detectors | N _A | | NA | | NA | | |
| | Location of Main Panel | N | A | NA | | NA | 11 | |
| - | Location of Repeater Pa | | A | NA | y ⁽³⁾ | NA | 3 | |
| | Alternate source of pow | - T | A | NA | | NA | | |
| | Hooters' Location | N. | A n | NA | 9 | NA | | |
| 8. | MOEFA | N. | A | NA | NA | | NA | |
| 9. | Public Address System | N. | | | Provided | | NA | |
| 10. | Automatic Sprinkler System | 111 | | 110 | | | | |
| 10. | Basements | | NA | | NA | | NA | 48 |
| _ | Upper Floor | | NA | | NA | | NA | |
| | Sprinkler above false co | eiling | NA | | NA | | NA | |
| 11. | Internal Hydrants: | | | | | | | |
| 11. | Size of riser/down- con | | | | NA | | NA | |
| | Number of hydrants per | | NA | v | ∠NA | | NA | 4. |
| | Hose Box | | NA | | NA | 2 | NA | 6.6 |
| 12. | 11000 Box | Ya | rd Hydrant | ts | | | | |
| 12. | Total number of hydrar | | NA | | NA | | NA | 1 |
| | Hose Box | | NA | | NA | | NA | |
| 13. | Pumping Arrangements: | | | | | | | |
| 13. | Ground Level | | | | | | | |
| | Discharge of main pum | | | | NA | | NA | |
| | Head of main pump | | | - | NA | | NA | |
| | Number of main pump | S | NA NA | | NA | | NA | |
| | Jockey pump out put | | NA | | NA | | NA | |
| | Jockey pump head | | NA | | NA | | NA | |
| | > Standby Pump out put | | NA | | NA | | NA | |
| | > Standby Pump Head | | NA | | NA | | NA | |
| | > Auto Staring/Manual stopping | | NA | | NA | | NA | |
| | Pump House Access | | NA | | NA | | NA | |
| | Terrace level | | | | | | | |
| | Discharge of pump | | NA | NA | | NA | A | |
| | ➤ Head of the pump | | NA | NA | | NA | 1 | |
| | Power supply | | NA | NA | | N/ | 1 | |
| | > Auto starting of pump | | NA | NA | H 2 | N/ | 1 | |

| 14. | Captive water Storage for firefighting: | | | | | | |
|-----|---|---|----|----------|----|--|--|
| | Underground tank capa | city | NA | NA | NA | | |
| | Draw off connection Fire service inlet Access to tank | | NA | NA | NA | | |
| | | | NA | NA | NA | | |
| | | | NA | NA | NA | | |
| | Overhead Tank capacit | NA | NA | NA | | | |
| 15 | Exit Signage | | NA | Provided | NA | | |
| 16. | Provision of Lifts | | | | | | |
| | Pressurization of Lift Sl | NA | NA | - NA | | | |
| | Pressurization of lift lob | Communication in lift Car Fireman's Grounding Switch | | NA | NA | | |
| | | | | NA | NA | | |
| | | | | NA | NA | | |
| | ➤ Lift Signage | | NA | NA | NA | | |
| 17. | Standby power supply | | NA | NA | NA | | |
| 18. | Refuge Area | | | | | | |
| | Total area | | NA | NA | NA | | |
| | Location | Location | | NA | NA | | |
| 19. | Fire control room NA NA NA NA | | | | | | |
| | Detector system panel | NA | | NA | NA | | |
| | Flow Switch Panel | NA | | NA | NA | | |
| | PA System Panel | NA | | NA | NA | | |
| | ► Battery backup | | | NA | NA | | |
| | Building Floor Plans | NA | | NA | NA | | |
| 20. | Special Fire Protection NA | | | NA | NA | | |
| | Systems for Protection of special Risks, if any; | | | | 4 | | |

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F6/DFS/MS/SCHOOL/2016/WZ/1626, Dated-03/11/2016 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer Name Udat Vir

Designation

Signature of the Inspecting Officer

Name

Designation

lettering but up ?