GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No. F.6/DFS/MS/Indl./2019/SZ/ 2270

Dated: 06/12/19

FIRE SAFETY CERTIFICATE

Certified that M/s Supreme Metal Craft Medical Products (P) Ltd. Plot No. G-9, Block B-1, MCIE, Mathura Road New Delhi-110044, comprised of basement, ground plus two upper floors owned/occupied by M/s Supreme Metal Craft Medical Products(P) Ltd. was granted NOC by this department vide letter No. F6/DFS/MS/Indl./2015/SZ/1341 Dated 23/07/2015. The premises was re-inspected by officer concerned of this department on 21/11/2019 in the presence of Sh. Sagar Gupta and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of Delhi Fire Service Rules Act-2007 & Rules- 2010 and that premises/building is fit for occupancy class "Industrial" effect from 2.6. 12/9 for a period of Three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued of 12/19 at New Delhi by

(Atul Garg)
Director
Delhi Fire Service

Copy to: -

- 1. The Authorized Signatory, M/s Supreme Metal Craft Medical Products (P) Ltd.Plot No. G-9, Block B-1, MCIE, Mathura Road New Delhi-110044
- 2. The executive Engineer (Bldg.)-I, SDMC, 8th floor, Civic Centre, Minto Road, New Delhi-110002.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- 7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

		INSP'	ECTION REPORT				
1	Name & Add	Craft Medical Products	(P) Ltd. Plot				
			No. G-9, Block B-1, MCIE, Mathura Road New Delhi-				
			110044				
2	Type of Occupancy		Group-G (Industrial)				
3	Building Comprised of		Basement + Ground + 02 upper floors				
4	Type of Case		Renewal				
5	Details of Pro		F6/DFS/MS/Ind./2015/SZ/1341 dated 23/07/2015				
6	Fire Safety D	irectives Letter No	F.6/DFS/MS/BP/2008/574 DATED 28/02/2008 21/11/2019				
7	Date of Inspe	1					
8	Name of the	Inspecting Officers	AVTAR SINGH, ADO (MR)				
9	Name & Des	ignation of Officers	Mr. Sagar Gupta				
	from the buil	ding side	2006.07				
10	Year of cons		2006-07				
11	Applicant les		Outdoor diary no. 22000 dated 04/10/2019 BBL/NBC Provided at Site Remarks				
S. No		tandards on Fire and Fire Safety U/R 33	BBL/NBC Requirement	Provided at Site	MR/NMR		
1	Access to Building.						
		width	9 m	Provided	MR		
	Gate	width	4.5 m	4.5m	MR		
	> Widt	h of internal road	06m	Provided	MR		
2	Number, w	idth, type & arrangement	of exits.				
	a) Number of Staircase						
			Two	Provided	MR		
	Upper floors. Basement floor.		Two	Provided	MR		
				- 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1			
	Upper floors Basement floor		1.5m each	Provided	MR		
			1.5m each	Provided	MR		
			1.5m cach				
	c) Protection of exits		Required	Provided	MR		
	Fire check doorPressurizationd)No. of continuous staircase to		-NA-	-NA-	-NA-		
			-NA-				
			01	01	MR		
	terrace e)Width of corridor		-NA-	-NA-	-NA-		
	f) Door size		-NA-	-NA-	-NA-		
3	Compartn				95		
3		Fire check door.	Required	Provided	MR		
		Sealing of electrical shafts.		-NA-	-NA-		
		Fire rating of shaft door.	-NA-	-NA-	-NA-		
	•	Water curtain	-NA-	-NA-	-NA-		
	•	Fire dampers.	-NA-	-NA-	-NA-		
			-NA-	1177			
4.			20 A CDII	Provided	MR		
		sement	30 ACPH	Provided	MR		
	Upper floors		12 ACPH	Flovided	14117		
5.	. Fire Extin	nguishers.		D 111	MR		
		tal numbers	16 Nos	Provided	MR		
		pes	ABC /Co2	ABC /Co2			
	• IS	I Marking	ISI marked	Provided	MR		
6	. First Aid	Hose Reels.			MD		

	Nozzle Diameter	5mm	provided	MR
7	Automatic fire detection & alarming			
	Type of detectors	Smoke	provided	MR
	 Location of Main Panel 	ground floor	provided	MR
	• Location of Repeater Panel	-NA-	-NA-	-NA-
	Alternate source of powerHooter's location	Required	provided	MR
	Thooter's location	Required	Provided at each floor	MR
8.	MOEFA	Required	Provided	MR
9.	Public Address System	-NA-	-NA-	-NA-
10.	Automatic Sprinkler System			
	• Basement.	Required	Provided	MR
	• Ground & Above floors	Required	Provided	MR
	Sprinkler above false ceiling	-NA-	-NA-	-NA-
11.	Internal Hydrants.			d
	• Size of Riser / Down-comer	150mm	Provided	MR
	Number of Hydrant per floorHose box.	One	Provided	MR
	The second secon	One	Provided	MR
12.	Yard Hydrants	~		
	Total number of hydrantsHose box	One	Provided	MR
12	000000 (00000000 N) (000000000 N) (0000000000	One	Provided	MR
13.	Pumping arrangements.		T	
	Ground Level	2200 1 DM	D 111	MD
	Discharge of main pump.	2280 LPM	Provided	MR
	Head of main pump.	48m	Provided	MR
	Number of main pumps.Jockey Pump output.	One	Two	MR
	Jockey Pump head.	180LPM 48m	Provided Provided	MR
	Standby Pump output.	2280LPM	Provided	MR
	Standby Pump head.Auto Starting/Manual	48m	Provided	MR
	Auto Starting/Manual Stopping.	Required	Provided	MR
	Pump house access	Required	Provided	MR
	Terrace Level	Required	Tiovided	IVIIC
	> Discharge of pump.	900LPM	Provided	MR
	Head of pump.	35m	Provided	MR
	Power supply.	Required	Provided (DG Set)	MR
	Auto starting of pump.	Required	Provided	MR
14.	Captive water storage for firefighting			
	• Underground tank capacity.	1,00,000 Ltrs	Provided	MR
	Draw-off connection.Fire Service Inlet.	Required	Provided	MR
	> Access to tank.	Required	Provided	MR
		Required	Provided	MR
4 50	Overhead tank capacity.	20,000 ltrs	Provided	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.		271	NT.4
	Pressurization of lift shaft.Pressurization of lift lobby.	-NA-	-NA-	-NA-
-	 Pressurization of fit lobby. Communication in lift car. 	-NA-	-NA- Provided	-NA-
	• Fireman's switch.	Required	and the right of Displacements and	MR
		Required	Provided	MR

	Lift signage.	Required	Provided	MR				
17	Standby Power Supply	Required	Provided	MR				
18.	Refuge Area							
	Total area	-NA-	-NA-	-NA-				
	Location	-NA-	-NA-	-NA-				
19.	Fire Control Room.	e Control Room.						
	Detector System Panel.	Required	Provided	MR				
	• Flow Switch Panel.	-NA-	-NA-	-NA-				
	PA system Panel.Battery backup	-NA-	-NA-	-NA-				
	Building floor plan	-NA-	-NA-	-NA-				
	S	-NA-	-NA-	-NA-				
20.	Special Fire Protection System for the Protection of special Risk, if any.	Required	02 ABC type fire extinguisher found provided near electric panel	MR				

The fire protection system provided in the building were test checked and found functional at the time of inspection.

In view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules, it is recommended to grant Fire Safety Certificate under the Delhi Fire Service Act-2007 & Rule- 2010.

DFA is put up for approval & signature please.

Signature of the Inspecting Officer

: Avtar Singh

Designation: ADO (M.RD)

DO (SD)