## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2019/2285

Dated: 10/12/19

## FIRE SAFETY CERTIFICATE

Certified that the YWCA of India International Guest House located at 10, Sansad Marg, New Delhi comprised of Ground + 04 Upper floors, Ground floor (Reception + Lobby, Dinner Hall & YWCA Kitchen (Restaurant), 1<sup>st</sup> floor to 4<sup>th</sup> floor (06 guest rooms at each floor), total 24 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2017/NDZ/1061 dated 19/07/2017. The premises was re-inspected by the officer concerned of this department on 03/12/19 in the presence of Mr. Peter Pereira (Manager) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential building with effect from {a/2}} for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service/Rules 2010 printed below

2010, printed below.

Issued - 12 12 12 - at New Delhi by.

(Sunil Chowdhary)
Dy. Chief Fire Officer
Delhi Fire Service

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.
- 2. The Medical Officer of Health, Room No. 1002, 10<sup>th</sup> floor, Palika Kendra, New Delhi.
- 3. Mr. Peter Pereira,

Manager,

YWCA of India International Guest House, 10, Sansad Marg, New Delhi.

## Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 9. Any flammable material for interior decoration is prohibited.
- 10. Owner/Occupier shall also ensure compliance of notification dated 27.05.19 and clarification dated 25.09.19 and there of in r/o guest houses.

N/34

## **INSPECTION REPORT**

1. Name & address of the building: YWCA of India International Guest House at 10,

Sansad Marg, New Delhi

2. Type of occupancy : Residential building

Ground floor (Reception + Lobby, Dinner Hall & YWCA Kitchen (Restaurant), 1<sup>st</sup> floor to 4<sup>th</sup> floor (06 guest rooms at each floor), total 24 guest rooms

3. Type of case:- : Renewal

4. Details of previous FSC : F6/MS/DFS/2017/GH/NDZ/1061 dated

19/07/2017

5. Fire safety directives No. : N/A6. Date of inspection: 03/12/19

7. Name of the inspecting officer Sh. Rajinder Atwal (DO/CD) &

Sh. M. K. Sharma ADO/CC

8. Name & designation of officer

9. From the building side : Mr. Peter Pereira (Manager)

10. Year of construction :- 1982

11. Applicant's letter No. :- Nil dated 06/11/19.

	rippireant 5 letter 140.	- Wil dated 00/1	1/19.	Old Case				
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing fire safety arrangements	Provided at site	Remarks MR/NMR				
1.	Access to Building							
	1) Road width	12 mtr.	12 mtr.	MR				
	2) Gate width	4.5 mtr.	06 mtr.	MR				
	3) Width of internal road	N/A	N/A	N/A				
2.	Number, Width Type & Arrar	ngement of Exits						
	A. Number of staircases							
	1. Upper floors	01 No.	02 No.	MR				
	2. Basements	N/A	N/A	N/A				
	B. Width of staircase		2.101					
	1. Upper floors	1.25 mtr.	2 Nos. 1.41 mtr.	MR				
	2. Basements	N/A	N/A	N/A				
	C. Protection of exits							
	1. Fire check door	N/A	N/A	N/A				
	2. Pressurization	NA	NA	NA				
	D. No. of continuous	01	01	MR				
	staircase to terrace	4						
	E. Width of corridor	1.25 mtr.	1.31 mtr.	MR				
-	F. Door size	1.25 Mtr.	1.25 Mtr.	MR				
3.	Compartmentation							
	1) Fire check door	N/A	N/A	N/A				
\$	2) Sealing of electrical shafts	N/A	N/A	N/A				
	3) Fire rating of shaft door	N/A	N/A	N/A				
	4) Water curtain	N/A	N/A	N/A				
	5) Fire Dampers	N/A	N/A	N/A				
4.	Smoke Management System							
	1) Basements	30 ACPH	N/A	N/A				
-	2) Upper floors	12 ACPH	Provided	MR				
5.	Fire Extinguishers							
	1) Total numbers	10 Nos. 12 Nos.		MR				
	2) Types	ABC & CO2 ABC, CO2 & W.CO2		MR				
	3) ISI marking	Required	Provided	MR				

	First-Aid Hose Reel			01 1		MR	-0-	
	1)Total number of each	01 N	lo.	01 No	•	TATE		
	floor			20		MR		
	2) Length of hose reel hose	30 n		30 m		MR		
a) NI la diameter		5 mm		5 mm		IVIIC		
	Automatic Fire Detection & A	larmi	ng System	21/4		N/A		
	1) Type of detectors	N/A	1	N/A		N/A		
	2) Location of main panel	N/A	1	N/A		N/A		
	3) Location of repeater panel	N/A	A	N/A		N/A		
	4) Alternate source of power	N/A		N/A		N/A		
	5) Hooter's Location	N/A		N/A	• 1 1	MR		
`	MOEFA	Required		Provided Provided		MR		
3	Public Address System	Re	quired	Prov	ided	IVII		
9.	Automatic Sprinkler System				1	MI	2	
10.	1) Basement	Required		Provided		MR NA		
	1) Basement	NA		NA		NA NA		
	<ul><li>2) Upper floors</li><li>3) Sprinkler above false</li></ul>	2.1	A	NA		INF	7	
	3) Sprinklet above taise	N	A			-		
	ceiling Internal Hydrants				. 0.1	M	D	
11.	1) Size of riser/down-comer	10	00 MM		MM			
	2) Number of hydrants per	01		01		M	1/	
						M	TD.	
	floor  3) Hose box each floor	0	1	01		IV	IK	
	3) Hose box each floor					3.1	/ A	
12.	Yard Hydrants  1) Total number of hydrants	N	J/A	N/		1000	/A	
	1) Total number of flydrants		J/A	N/.	A	1	I/A	
	2) Hose box							
13.	Pumping Arrangement					-	T/A	
	1) Ground level		N/A	N	/A	1	N/A	
	a) Discharge of main						N T / A	
	pump		N/A	N	/A		N/A	
	b) Head of main pump	ımn	N/A	N	/A		N/A	
	c) Number of main pu	mp	N/A	N	[/A		N/A	
	d) Jockey pump out p	uı	N/A	N	I/A		N/A	
	e) Jockey pump head		N/A N/A		J/A		N/A	
	f) Stand by pump out	put_	N/A N/A		J/A		N/A	
	g) Stand by pump hea	10	N/A N/A		V/A		N/A	
	h) Auto starting/Man	ual	IN/A		- CA 1			
	stopping		2					
	2) Terrace level		450 LPM		900 LPM		MR	
	a) Discharge of pum	p	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		30 mtr.		MR	
	b) Head of pump		30 mtr.		Provided		MR	
	c) Power supply		Required		Provided		MR	
	1) Auto starting of p	ump	Required					
14	Captive Water Storage for Fire		e Fighting	ghting 50,000 ltr.			MR	
1-1	1) Under ground tan	k	50,000 ltr.		20,000 141.			
	capacity		D1		Provided		MR	
	a) Draw-off connection b) Fire service inlet		Required		Provided		MR	
			Required		Provided		MR	
	c) Access to tank		Required		20,000 Ltrs		MR	
	d) Over head tank		20,000 Ltrs.	ĝ	20,000 Lus			
	capacity				Provided		MR	
					PEDVICEU			
1	5. Exit Signage.		Required		1101100			

130

m

16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	Required	Provided	MR
	d) Fireman's switch	Required	Provided	MR
	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	Required	Provided	MR
	Total area location	N/A	N/A	N/A
19.	Fire Control Room			
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	Required	Provided	MR
	d) Battery backup	Required	Provided	MR
	e) Building floor plan	Required	Provided	MR
20.	Special Fire Protection System any: ABC, Co <sub>2</sub> WCo <sub>2</sub>	MR		

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/NDZ/2017/1061 dated 19/07/2017 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name: - Rajinder Atwal

Designation :- DO (CD)

Name:- M.K. Sharma

Designation :- ADO (CC)