GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F6/DFS/MS/Banquet/2019/WZ/

Dated: 01/01/2090

FIRE SAFETY CERTIFICATE

Certified that the Apsara Grand Banquet Halls at A-1 /20-B, Paschim Vihar, Rohtak Road, New Delhi-110063 comprised of Basement, Ground & Two Upper Floor only owned/ occupied by Apsara Grand Banquet Halls, has already been issued NOC / FSC by this department vide letter No. F6/DFS/MS/Banquet/2016/WZ/1792 dated 16/12/16. The premises was re-inspected by the officer concerned of this department on 23.12.2019 in the presence of Sh. Sandeep Walia (Owner) and observed that Fire prevention and fire safety arrangements provided in the premises, found in good working condition. The premises have therefore, deemed complied with the Fire Prevention and Fire Safety Requirements in accordance with rule 33 of the Delhi Fire Service Rule 2010 and that the Building /Premises is fit for occupancy class Assembly with effect from .e.j../..o.j.../2019 for a period of three years in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the DFS rules, 2010.

Issued on 01/01/2020 at New Delhi by.

(DHARAMPAL BHARDWAJ)
DY. CHIEF FIRE OFFICE

Copy to:-

1. Sh. Sandeep Walia, Apsara Grand Banquet Halls, A-1/20-B, Paschim Vihar, Rohtak Road, New Delhi-63.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided their in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. Use of Basement shall be strictly as per Building By-Laws 1983.
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The from is available on <u>WWW.dfs.Delhigovt.nic.in</u>
- 8. "The owner / Occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, six months prior to its expiry".

1 120

Basement + Ground +
Two Upper Floors

Plot Area = $326 \,\mathrm{M}^2$

Covered Area=326 M²

INSPECTION REPORT

1. Name & address of the building: Apsara Grand Banquet Halls

A-1/20-B, Paschim Vihar, Rohtak Road,

New Delhi-63.

2. Type of Occupancy : Assembly

3. Type of Case : Renewal

4. Details of previous NOC No. : F6/DFS/MS/Banquet/2016/WZ/1792 dated 16/12/16

5. Fire Safety directives Letter No.: F.6/DFS/MS/2013/2004 dated 13.08.2013

6. Date of inspection : <u>23.12.2019</u>

7. Name of the Inspecting Officer: A.K. Jaiswal

8. Name and designation of Officer

from the building side : Sh. Sandeep Walia

9. Year of Construction : 2004

10. Applicant's letter No. : Nil outdoor diary no.-26196 dated 27.11.2019

| S | Minimum standards on fire | | BBL/ | Provi | ded at | Remarks MR/N | MR |
|-----|---|-------------------------------|--------------------|----------|---------|---------------------|---------------------------------------|
| No | prevention and fire safety U/R 33 | | Requirements | site | | | |
| 1. | Access of building | | <u> </u> | , , , | | 7 | |
| | Road widthGate width | | 6 mtr | 6 mtr | | MR | 5 |
| | | | 5 mtr | 5 mtr | | MR | |
| | Width of inter | nal road | NA | NA | | NA | |
|) . | Number, width, Type | & Arrangeme | nts of exits | | | - | |
| | a. Number of staircases | | | | | n n | |
| | • Upper floors | | 2 | 2 | | MR | |
| | • Basements | | 2 | 2 | | MR | |
| | b. Width of stair | rcases | | | | | |
| | • Upper floors | | 1.50 mtr | 1.50 | mtr | MR | |
| | Basements | | 1.50 mtr | 1.50 | mtr | MR | · · · · · · · · · · · · · · · · · · · |
| | c. Protection of e | exits | | | | | |
| | • Fire check doo | or | Required | | Provide | d | MR |
| | • Pressurization | | Required Pro | | Provide | d | MR |
| | d. No of continu | d. No of continuous staircase | | | 1 | | MR |
| | to terrace e. Width Of Corridor | | NA | | NA | | NA |
| | f. Door Size | 00 | 2.00 mtr x 2 on ea | ch floor | 2.00 mt | r x 2 on each floor | MR |



| 1/1 | 1// |
|-----|-----|
| F 4 | 1 |
| | |

| 3. | Compartmentation | | | | 0 | |
|-----|--|-----------------------------|--------------|----------------|-------|--|
| | Fire check door | Required | Provided | MR | | |
| | | Required | Provided | MR | | |
| | Sealing of electrical shafts | Required | Provided | IVIK | | |
| | Fire Rating of shaft door | Required | Provided | MR | | |
| | Water Curtain | NA | NA | NA | | |
| | Fire Dampers | NA | NA | NA | | |
| 4. | Smoke managements System | | | | | |
| | • Basements | 30 a/c per hour | Exhaust fan | MR | | |
| | Upper floors | 12 a/c per hour | Open to sky | MR | | |
| 5. | Fire Extinguishers | | | | 1 | |
| | Total numbers | 10 | 15 | MR | 5 | |
| | • Types | ABC/Co2/Foam | Provided | MR | 6 | |
| | IS marking | ISI marked | Provided | MR | | |
| 6. | First – Aid Hose Reels | | | | | |
| | Total numbers on each floor | 1 | 1 | MR | | |
| | • Length of hose reel hose | 30 Mtr. | 30 Mtr. | MR | | |
| | Nozzle diameter | 5 mm | 5 mm | MR | 9 | |
| 7. | Automatic fire detection and alarming system | | | | | |
| | Type of detector | Smoke | Provided | MR | | |
| | Location of Main Panel | GF | Provided | MR | See 2 | |
| | Location of Repeater Panel | GF | Provided | MR | | |
| | Alternate source of power | Required | Provided | MR | | |
| | Hooters' Location | GF | Provided | MR | | |
| 8. | MOEFA | Required | Provided | MR | | |
| 9. | Public Address System | NR | NR | NR. | | |
| 10. | Automatic Sprinkler System | | | 1000 | | |
| | • Basements | Required | Provided | MR | | |
| | • Upper Floor | Not Required | Not Provided | Not Applicable | | |
| | Sprinkler above false ceiling | Required (Only Basement) | Provided | MR | a a | |

. . .



| 1 Internal Hydrants | | | |
|---|-------------|--------------|---|
| Size of riser/down- comer | 100 mm | 100 mm | MR |
| Size of fisci, down come. | (A) | | |
| Number of hydrants per | 1 | 1 | MR |
| floor | | | |
| | 1 | 1 | MR |
| Hose Box | | | |
| 12. Yard Hydrants | 1 | * | · |
| Total number of hydrants | NA | NA | NA |
| 1 9 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | | | |
| Hose Box | NA | NA | NA |
| 13. Pumping Arrangements | J., | | |
| Ground Level / Over Head | | О.Н. Т | ank |
| | | | - |
| Discharge of main pump | 2280 Lpm. | 2280 Lpm. | MR |
| 7 | | | * |
| ➤ Head of main pump | 60 MH | 60 MH | MR |
| | | | |
| Number of main pumps | 2 | 2 | MR |
| | | | |
| Jockey pump out put | 180 Lpm. | 180 Lpm. | MR |
| | 60.0411 | CONNIL | AAD. |
| Jockey pump head | 60 MH | 60 MH | MR |
| | 2280 LPM | 2280 LPM | NR |
| Standby Pump out put | 2200 LPIVI | 2200 LF W | I I I |
| S G 11 D 11 1 | 60 MH | 60 MH | NR |
| Standby Pump Head | 00 17111 | | |
| Auto Storing/Manual stonning | Required | Provided | MR |
| ➤ Auto Staring/Manual stopping | 1 | | |
| > Pump House Access | Required | Provided | MR |
| 1 ump flouse Access | | | |
| Terrace level | | | |
| Terrace lever | | | |
| > Discharge of pump | 450 LPM | 450 LPM | MR |
| Discharge of pamp | | | |
| ➤ Head of the pump | 40 MH | 40 MH | MR |
| T and T | | | 1.45 |
| > Power supply | Required | Provided | MR |
| | Danis d | Provided | MR |
| Auto starting of pump | Required | Provided | IVIK |
| | ting | | |
| 14. Captive water Storage for fire fight | ung | | |
| I Indon Cround Tonk Con | | | |
| Under Ground Tank Cap.Draw of connection | Required | Provided | MR |
| Draw of connection Fire service inlet | Required | Provided | MR |
| Access to tank | Required | Provided | MR |
| Overhead Tank capacity | 10,000 Ltr. | 60,000 Ltr.* | MR |
| Overmead Talik capacity | | | , |
| | | | |
| | | | |



| 15 | Exit Signage | Required | Provided | MR | | | |
|-----|--|----------|----------|---------------------------------------|---------------------------------------|--|--|
| 16. | Provision of Lifts | | | | | | |
| 10. | > Pressurization of Lift Shaft | Required | Provided | MR | | | |
| | > Pressurization of lift lobby | Required | Provided | MR | · · · · · · · · · · · · · · · · · · · | | |
| | Communication in lift Car | Required | Provided | MR | | | |
| 39 | Fireman's Grounding Switch | Required | Provided | MR | | | |
| | ➤ Lift Signage | Required | Provided | MR | | | |
| 17. | Standby power supply | Required | Provided | MR | 8 21 | | |
| 18. | Refuge Area | • | | · · · · · · · · · · · · · · · · · · · | | | |
| 10. | > Total area | NA | NA | NA | | | |
| | > Location | NA | NA | NA | | | |
| 19. | Fire control room | | | | | | |
| | Detector system panel | NA | NA | NA | 2.2 | | |
| | > Flow Switch Panel | NA | NA | NA | | | |
| | > PA System Panel | NÁ | NA | NA | | | |
| | Battery backup | NA | NA | NA | 2 1 6 | | |
| | Building Floor Plans | NA | NA | NA | | | |
| 20. | Special Fire Protection Systems for Protection of special Risks, if any; | NÁ | NA | NA | | | |

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter No. <u>F6/DFS/MS/Banquet/2016/WZ/1792 dated 16/12/16</u> renewal under rule 35 of the Service rules 2010 is recommended.

*Note:- Management has provided 60,000 lts capacity Over Head Tank in place of 50,000 lts Under Ground Tank and 10,000 lts Over Head Tank. All the Pumps are mounted on Terrace / Roof Top.

so (wes) on leave

Signature of the Inspecting Officer

Name : A. K. Jaiswal Designation : A.D.O. (JWP)

F.T. is put up per se