GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2020/ MD2/30

Dated : 10-6-1-20 20

FIRE SAFETY CERTIFICATE

Certified that the Stay Inn Guest House located at 3649, Gali Ram Nath Patwa, Pahar Ganj, New Delhi comprised of Ground floor + 04 Upper floors, Ground floor (01 guest rooms + reception + 01 office), 1st floor to 4th floor (04 guest rooms at each floor), rooms was granted FSC by this department guest No.F6/DFS/MS/GH/2017/472 dated 30/03/17. The premises was re-inspected by the officer concerned of this department on 14/01/2020 in the presence of Sh. Sumit Gupta. Owner/Occupier has also submitted an affidavit not to use above third floor for any purpose, Now the floor wise occupancy is Ground floor + 03 Upper floors, Ground floor (01 guest rooms + reception + 01 office), 1st floor to 3rd floor (04 guest rooms at each floor), total 13 guest rooms and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 13 guest rooms only(Upto 3rd floor only) with effect from - 101/2010 for period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued - La- - Off pats-at New Delhi by.

(Sunil Choudhary)
Dy. Chief Fire Officer
Delhi Fire Service

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.
- 2. The Manager, Stay Inn Guest House located at 3649, Gali Ram Nath Patwa, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 9. Any flammable material for interior decoration is prohibited.
- 10. Owner/Occupier shall also ensure compliance of notification dated 27.05.19 and clarification dated 25.09.19 and there of in r/o guest houses.

	× 2	- 1 // -				
	INSP	ECTION REPO	RT			
1.	Name & address of the building Stay Inn Guest House located at 3649			3649, Gali		
		Ram Nath Patwa, Pahar Ganj, New Delhi				
2.	Type of occupancy:-	Residential	Residential, Sub Division-A-1			
		Gr. + 03 Uppe	r floors (total 13 Guest	rooms)		
		Ground floor (01 guest rooms + reception + 01 office), 1 st floor to 3 rd floor (04 guest rooms at each floor). Renewal				
2	Type of case:-					
	Details of previous FSC:-	No. F6/DFS/MS/GH/2017/472 dated				
4,	30/03/17.					
5	Fire safety directives No	N/A				
	Date of inspection:-	14/01/2020				
7.	Name of the inspecting officer:	- Sh. Rajinder Atwal (DO/CD) &				
, ,	Sh. Manoj Kumar Sharma (ADO/CC)					
8.	Name & designation of officer					
	From the building side:-	Sh. Sumit				
9.	Year of construction:-	Prior to 2004				
10	. Applicant's letter No:-	nil dated 3	1/12/2019.	011.0		
				Old Case		
S.No.	Minimum Standards on fire	Requirement/	Provided at site	Remarks		
	Prevention and fire safety	Existing fire safety		MR/NMR		
	U/R 33	arrangements				
1.	Access to Building					
	1) Road width	Less then 6	02 mtr.	As per MPD - 2021 15.7.2 MF		
		mtr.				
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arrangement of Exits					
	A. Number of staircases					
	1. Upper floors	01 Nos.	01 Nos.	MR		
	2. Basements	N/A	N/A	N/A		
	B. Width of staircase					
	1. Upper floors	1.50 mtr.	1.50 mtr.	MR		
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits					
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	N/A	N/A	N/A		
	staircase to terrace					
	E. Width of corridor	N/A	N/A	N/A		
		1 O mater	1 0 mtr	MR		

1.0 mtr.

N/A

N/A

N/A

N/A

N/A

30 ACPH

12 ACPH

F. Door size

3.

4.

Compartmentation

2) Sealing of electrical shafts

Smoke Management System

3) Fire rating of shaft door

1) Fire check door

4) Water curtain

5) Fire Dampers

1) Basements

2) Upper floors

MR

N/A

N/A

N/A

N/A

N/A

N/A

MR

1.0 mtr.

N/A

N/A

N/A

N/A

N/A

N/A

Natural

5.	Fire Extinguishers			
	1) Total numbers	10 Nos.	10 Nos.	MR
	2) Types	ABC & CO2	ABC & CO2	MR
	3) ISI marking	Required	Provided	MR
6.	First-Aid Hose Reel	1		
	1) Total number of eachfloor	01	01	MR
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
	3) Nozzle diameter	05 mm	05 mm	MR
7.	Automatic Fire Detection &			
	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	N/A
8.	MOEFA	N/A	N/A	N/A
9.	Public Address System	N/A	N/A	N/A
10.	Automatic Sprinkler System			
	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling			
11.	Internal Hydrants			
	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	N/A	N/A
	floor	×	×	
	3) Hose box	N/A	N/A	N/A
12.	Yard Hydrants			
	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement	vi .	7	
	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A
	pump			
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump	N/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e). Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	N/A	N/A	N/A
	stopping	п		
	2) Terrace level	1.50.5		*
	a) Discharge of pump	450 LPM	450 LPM	MR
	b) Head of pump	30 mtr.	30 mtr.	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of pump	Required	Provided	MR
			ii ii	

14.	Captive Water Storage for I	Fire Fighting		
	Under ground tank capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	5,000 ltr.	5,000 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			2
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syst Risk, if any:	ction of special	N/A	

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the Rules the FSC issued vide letter no. F6/DFS/MS/GH/2017/472 dated 30/03/17 renewal under Rule 35 of the Delhi Fire Service Rules 2010, is recommended.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name :- Rajinder Atwal

Designation :- DO (CD)

Name :- M.K. Sharma Designation :- ADO (CC)

F. t. pl.

r. pati