FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD OUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

7

No. F6/DFS/MS/2020/53

Dated: 20/01/2020

FIRE SAFETY CERTIFICATE

Certified that the M2K Entertainment Pvt. Ltd, Plot no 4. Road no. 44, Community Center, Pitampura, New Delhi comprised B1+B2 +Ground + 03 Upper Floors was issued FSC vide Letter No. F6/DFS/MS/Cinema/2016/WZ/139dated 20/01/2016. The premises was re inspected by the officers concerned of this department on 16-01-2020 in the presence of Mr. Sanjay Koul (President) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Mercantile & Assembly Building" Group F & Group D with effect from Prevention and Supper Foundation of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ... 20 01 2020. at New Delhi by.

Atul Garg)

Copy to:

Sh. Sanjay Koul (President), M2K Entertainment Pvt Ltd, Plot no 4. Road no. 44, Community Center, Pitampura, New Delhi.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 9. All the doors, Exits and internal roads must be kept free from any obstruction.
- 10. The owner/occupier has submitted undertaking that lift will not be used in the basement and shall run from ground to upper floor only. The earth filling portion shown in the plan of second basement found excavated that portion shall be kept closed by brick work and shall not be used for any purpose.

MA.

INSPECTION REPORT

1. Name & address of the building: M2K Entertainment Pvt Ltd, Plot no 4.Road no. 44, community center, Pitampura, New Delhi

2. Type of Occupancy

: Class- F (Mercantile)

3. Type of Case

: Renewal

4. Details of previous NOC : F6/DFS/MS/Cinema/2016/WZ/139dated 20/01/2016

5. Fire Safety directives Letter No.: Letter No. F6/DFS/MS/BP/1611 Date 21-07-2003 & F6/DFS/MS/2004/468 dated 27/02/2004

6. Date of inspection

: 16-01-2020

7. Name of the Inspecting Officer: ADO (WP)

8. Name and designation of Officer

from the building side

: Mr. Sanjay Koul

9. Year of Construction

: 2004-05

10. Applicant's letter No.

: Nil Dated 13/01/2020

S No	Minimum standards on fire prevention and fire safety U/R 33		BBL Requirements		Provided at site		Remarks MR/NMR		
1.		s of building	-	4					
	Road widthGate width		09mtrs 5 mtr		24mtr.		MR		
					Provided	MR			
			6 m		Provided as per DDA control		MR (old case)		
2	N	: 1.1 TC 0 A		C	drawing				
2.	Number, width, Type & Arrang			its of exits					
	a.	Number of staircases		2	1 - 1 - 1	MD			
	٥	Upper floors		2 2+1 P	4 provided		MR MR		
		Basements		2+1 Ramp	Provided MI		<		
	b.	Width of staircases			0 150	N (T) 1			
	•	Upper floors	2x1.5mtrs		2x 170cm 2X145cm	2x 170cm MR being old case			
	 Basements 			2x1.5mtrs	Provided MR be case		eing old		
	C.	Protection of exits							
	• Fire check door			Required	Provided NA		MR		
	•	 Pressurization 		NA			NA		
		No of continuous stairc	ontinuous staircase		Provided		MR		
	e.	to terrace Width Of Corridor		1.5m	Provided (Old case)		MR Being old case		
	f. Door Size			1m	Provided(Old case)		MR Being old case		

 Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers A. Smoke managements System Basements Upper floors Fire Extinguishers Total numbers AB 	equired	Provided	MR				
 Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Red Basements System Upper floors Fire Extinguishers Total numbers Types IS marking First – Aid Hose Reels 	quired quired quired quired equired equired acquired acquired acquired acquired	Provided	MR				
 Fire Rating of shaft door Water Curtain Fire Dampers Rec Rec Rec Rec Rec Rec Smoke managements System Basements Upper floors Fire Extinguishers Total numbers Types IS marking First – Aid Hose Reels 	quired quired quired equired equired 3C,CO2 ty I marked	Provided	MR MR MR MR MR MR MR MR				
 Water Curtain Fire Dampers Red Red Red Red Red Smoke managements System Basements Upper floors Fire Extinguishers Total numbers Types IS marking First – Aid Hose Reels 	quired quired equired equired 3C,CO2 ty I marked	Provided Provided Provided Provided Provided Provided Provided Provided Provided	MR MR MR MR MR				
 Fire Dampers Rec Smoke managements System Basements Upper floors Fire Extinguishers Total numbers Types IS marking First – Aid Hose Reels 	quired equired equired SC,CO2 ty I marked	Provided Provided Provided Provided Provided Provided Provided	MR MR MR MR MR				
4. Smoke managements System Basements Upper floors Fire Extinguishers Total numbers Types IS marking First – Aid Hose Reels	equired equired sequired sequi	Provided Provided Provided Provided Provided Provided	MR MR MR MR				
 Basements Upper floors Fire Extinguishers Total numbers Types IS marking First – Aid Hose Reels 	equired BC,CO2 ty I marked	Provided Provided Provided Provided Provided	MR MR MR				
 Upper floors Fire Extinguishers Total numbers Types IS marking First – Aid Hose Reels 	equired BC,CO2 ty I marked	Provided Provided Provided Provided Provided	MR MR MR				
5. Fire Extinguishers • Total numbers • Types • IS marking 6. First – Aid Hose Reels	3C,CO2 ty I marked	Provided Provided Provided	MR MR				
 Total numbers Types IS marking First – Aid Hose Reels 	3C,CO2 ty I marked	Provided Provided	MR				
• Types • IS marking 6. First – Aid Hose Reels	3C,CO2 ty I marked	Provided Provided	MR				
• IS marking ISI 6. First – Aid Hose Reels	I marked	Provided					
6. First – Aid Hose Reels			IVIIX				
	m	D 111					
1 Otal numbers on each moor to	m		MR				
	111	Provided Provided					
		Provided	MR MR				
			17117				
7. Automatic fire detection and alarming sys	Provided	MR					
	equired ound floo		MR				
	ich floor	Provided	MR				
	equired	Provided	MR				
	equired	Provided	MR				
	Required Provided		MR				
Public Address System Required Provided MR							
10. Automatic Sprinkler System) o avriga d	MD					
	Required Required	Provided Provided	MR				
11	Required	Provided	MR				
8	cequired	Provided	MR				
	150 mm Provided		MD				
	J 111111	Provided Provided	MR MR				
2		Provided	MR				
• Hose Box 3	Flovided		IVIK				
The state of the s	• Total no. of hydrants Required Provided MR						
Hose Box Required		Provided	MR				
13. Pumping Arrangements	CI	Trovided	IVIIX				
Ground Level							
	2850LPM	1 Provided	MR				
	60 mtr	Provided	MR				
Number of main pumps 1	1	Provided	MR				
1 1	180 lpm	Provided	MR				
	60 m	Provided	MR				
	2850lpm	Provided	MR				
	60 mtr	Provided	MR				
	Required	Provided	MR				
TO TI	Required	Provided	MR				
Terrace level	1						
Discharge of pump	900lpm	MR					
	NA	Provided Provided	MR				

	have made in the to								
Power s		supply		NA Pr		vided	MR		
	Auto starting of pump		NA		Provided		MR		
	Captive water Sto	e water Storage for fire fighting							
a fam	Under gro	und tank capacit	Required Required		Provided Provided		MR		
1	Draw of c	onnection					MR		
	> Fire servi	ce inlet					MR		
	Access to	tank				Provided	MR		
	 Overhead 	Tank capacity				Provided	MR		
15	Exit Signage			Required		Provided	d MR		
16.	Provision of Lifts: Lift shall run from ground to upper floor only								
	Pressurization of Lift Sh		t	Required Provided		vided	MR		
	Pressurization of lift lobby		7	NA	NA		As lift lobby is		
							not shown in		
							DDA sanction		
							plan.		
	Communi	Communication in lift Car		Required	Provided		MR		
		Fireman's Grounding		Required	Provided		MR		
	Switch								
	Lift Signa			Required	Provided		MR		
17.	Standby power su	power supply		Required	Provided		MR		
18.	Refuge Area								
	Total area			NA	NA		NA		
	Location			NA	NA		NA		
19.	Fire control room								
	> Detector s	v 1	Required		Provided		MR		
		Flow Switch Panel Rec PA System Panel Rec		quired Pro		vided	MR		
						vided	MR		
	Battery ba		Required		Provided		MR		
	Building	Building Floor Plans F		Required		vided	MR		
20.	Special Fire Protection		NA		NA		NA		
	Systems for Protection of								
	special Risks, if any;						6		

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F6/DFS/MS/Cinema/2016/WZ/139dated 20/01/2016 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Note: - The owner/occupier has submitted undertaking that lift will not be used in the basement and shall run from ground to upper floor only. The earth filling portion show in the plant second basement found excavated that portion shall be kept closed by brick work and shall not be used for any purpose.

Signature of the Inspecting Officer

Name Udai Vir Singh

Designation ADO (WP)

musur us/iporo