GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2020/ 39

Dated: 27/1/2020

FIRE SAFETY CERTIFICATE

Issued on 27 [1] 20 at New Delhi by.

(Rajesh Panwar)
Dy. Chief Fire Officer (SZ)
Delhi Fire Service
Ph.- 011-26189168

Copy to:-

- 1. The Additional C.P. (Lic.), Police Station Defence Colony, 1st floor, New Delhi.
- 2. Municipal Health officer, NDMC, Karol Bagh Zone, Anand Parbat, New Delhi.
- 3. The Owner /Occupier, M/s Hotel City International, 8/21, WEA, Karol Bagh, New Delhi- 110005.

Conditions for the validity of Fire Safety Certificate: -

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. All comments / directions of licensing department shall always be permitted and followed.
- 7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.
- 9. Basement shall be used as per BBL.
- 10. No temporary shed is allowed on terrace.
- 11. The Fire Safety Certificate is only for Guest Rooms.
- 12. The Gazette Notification of UBBL-2016 amendment inserted as clause No. 7.31 of Chapter- 7 by the Directorate of Local Bodies vide letter No. F.5(1897/AD/LB/2016/4053-67 dated 27.05.2019, letter No. F.5(189)/AD/LB/2016/11940-55 dated 25.09.2019 and letter No. F.5(189)/AD/LB/2016/171-186 dated 27.12.2019, in respect of existing building shall be implemented by 31.03.2020 under intimation to Delhi Fire Service and if the provisions are not made within the stipulated time then the FSC shall stand null & void.

sporks

2. Type of Occupancy : Residential (Guest House)3. Type of Case : Renewal

4. Details of previous NOC : F.6/DFS/MS/GH/2016/SZ/1214 dated 29.07.2016

5. Fire Safety directives letter No : Nil

6. Date of inspection : 13.01.20207. Name of the Inspecting Officers : Rajbir Kharab, ADO (SRD)

8. Name and designation of officers from the building side : Mr. Praveen Anand, proprietor

9. Year of Construction : Before 2010 : Nil dated nil

The said guest house is comprised of basement (Hall/Storage), ground floor (reception, hall & 01 store room), first floor (06 guest rooms), second floor (06 guest rooms) and third floor (06 rooms).

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	BBL Requirement	Provided at site	Remarks MR/NMR			
1	Access to building						
	Road width	06 mts	9 mtrs	M/R			
	• Gate width		Directly accessible from	M/R			
	Width of internal road	N/A	road N/A	N/A			
2	Number, Width, Type & Arrangeme						
	a. Number of staircases	-	-				
	• Upper Floors	01	01	M/R			
	Basements	01	01	M/R			
	b. Width of staircases	-	-	_			
	 Upper Floors 	125 cms.	Provided	M/R			
	Basements	125 cms.	Provided	M/R			
	c. Protection of exits	123 01115.	-	-			
	Fire check door	N/A	N/A	N/A			
	Pressurization	N/A	N/A	N/A			
	d. No. of continuous staircases to		01	M/R			
	terrace	125 cms	160 & 250 cms	M/R			
	e. Width of Corridor f. Door Size	100 cms	80 cms	M/R being old cas			
3	Compartmentation.			. ,			
	Fire check door	N/A	N/A	N/A			
	Sealing of electrical shafts	N/A	N/A	N/A			
	Fire Rating of shaft door	N/A	N/A	N/A			
	Water Curtain	N/A	N/A	N/A			
	Fire Dampers	N/A	N/A	N/A			
4	Smoke Management System.						
	Basements	30 a/c per hour	Exhaust fan provided	M/R			
	Upper floors	12 a/c per hour	Natural Ventilation	M/R			
5	Fire Extinguishers						
	Total numbers	2 no's at each floor	Provided	M/R			
	Types	WCO ₂ /CO ₂ /ABC type	Provided	M/R			
	IS marking	ISI marked	Provided	M/R			
6	First-Aid Hose Reels.						
		01	Provided	M/R			
	Total numbers on each floor	30 m	Provided	M/R			
	Length of hose reel hose	5 mm	Provided	M/R			
	Nozzle diameter	J 111111	1 10 rided	1			

19	Fire Control Room	Control Room				
	Detector System Panel	N/A	N/A	N/A		
	 Flow Switch Panel 	N/A	N/A	N/A		
	 PA System Panel 	N/A	N/A	N/A		
	 Batter backup 	N/A	N/A	N/A		
	 Building Floor Plans 	N/A	N/A	N/A		
20	Special Fire Protection Systems for Protection of special Risks, if any:	N/A	N/A	N/A		

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/GH/2013/SZ/164 dated 09.04.2013, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

DO(KW)

17/1/2000

Signature of the Inspecting Officer

Name Rajbir Kharab

Assitt. Div. Officer (SRD)

Diary No. 13 Dated 1711 2018

Land 2011



dochi) Sir, DAA 15 not Signer. approved, Sign please.

20/1/06

Defo(\$2)

Ling

	 Location of Main Panel 	N/A	N/A	N/A	
	Location of Repeater Panel	N/A	N/A	N/A	
	Alternate source of power	N/A	N/A	N/A	
	Hooters' Location	N/A	N/A	N/A	
8 M	IOEFA	Required	Provided	M/R	
9 P t	ublic Address System.	Required	Provided	M/R	
10 Aı	utomatic Sprinkler System.				
	Basement	Required	Provided	M/R	
	Upper Floor	N/A	N/A	N/A	
	Sprinkler above false ceiling	N/A	N/A	N/A	
11 In	Internal Hydrants				
	Size of riser/down-comer	N/A	N/A	N/A	
	Number of hydrants per floor	N/A	N/A	N/A	
	Hose Box	N/A	N/A	N/A	
12 Y a	Yard Hydrants.				
	Total number of hydrants	N/A	N/A	N/A	
	Hose Box	N/A	N/A	N/A	
13 Pu	imping Arrangements.				
- 0	Ground Level				
	Discharge of main Pump	N/A	N/A	N/A	
	Head of Main pump	N/A	N/A	N/A	
	Number of main pumps	N/A	N/A	N/A	
	Jockey Pump out put	N/A	N/A	N/A	
	Jockey pump head	N/A	N/A	N/A	
	Standby Pump out put	N/A	N/A	N/A	
	Standby Pump Head	N/A	N/A	N/A	
_	Auto Starting/ Manual stopping	N/A	N/A	N/A	
	Pump House Access	N/A	N/A	N/A	
•	Terrace level				
	Discharge of pump	450 LPM	Provided	M/R being old case	
- 1	Head of the pump	30 mtrs	Service of the servic		
	Power Supply	Required	Provided	M/R Being old case	
	Auto Starting of pump		Provided	M/R M/R	
14 Ca	Auto Starting of pump Required Provided Captive Water Storage for fire fighting.				
	Underground tank capacity Draw off connection	N/A	N/A	N/A	
TO A CONTROL OF THE A C	> Draw-off connection	N/A	N/A	N/A	
	Fire service inletAccess to tank	N/A	N/A	N/A	
	Overhead Tank capacity	N/A	N/A	N/A	
		5,000 lts	a.	MR being old case	
	kit Signage.	Required	Provided	M/R	
16 Pr	ovision of Lifts.				
•	Tressarization of Bitt Shart	N/A	N/A	N/A	
•	Tresserization of Entrices	N/A	N/A	N/A	
•	Communication in the Car	N/A	N/A	N/A	
•	I if the first is discussed in the first ind	N/A	N/A	N/A	
•	Lift Signage	N/A	N/A	N/A	
	andby power supply	Required	Provided (125 KVA)	MR	
18 Re	fuge Area.				
	> Total Area	N/A	N/A	N/A	