GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F.6/DFS/MS/Hospital/2020/SZ/69

Dated: 28/01/2020

FIRE SAFETY CERTIFICATE

Certified that M/s **Medeor Hospital** (Formerly Rockland Hospital) located at B–33 & 34, Qutub Institutional Area, Tara Crescent Road, New Delhi–110016 comprised of basement, ground & 06 upper floors was issued Fire Safety Certificate by this department vide letter No. F6/MS/DFS/Hospital/2015/SZ/288 dated 27/02/2015. The premises was re-inspected by the officers concerned of this department on 14/01/2020 in the presence of Mr. Sehgal (Chief Engineer) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of Delhi Fire Service Rules, 2010 and that building is fit for occupancy class "Institutional Group—C" as above with effect from 20/01/2020 for period of Three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the condition under Rule 38 of the Delhi Fire Service Rules, 2010

Issued on 2/ /2020 at New Delhi by

(Atyl Garg) Director Tel: 011-23414000

Copy to: -

1. The Manager, M/s Medeor Hospital located at B-33 & 34, Qutub Institutional Area, Tara Crescent Road, New Delhi-110016

Conditions for the validity of Fire Safety Certificate:

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire fighting system.
- 4. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 5. The basement shall be used as per building bye laws 1983.
- 6. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL- 2016), if any.
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

NI	N	l	V		
----	---	---	---	--	--

	INSPI	ECTION REPORT	* * *			
1	Name & Address of the Building	Name & Address of the Building Medeor Hospital, B-33,34, Qutub Institutional Area, Tara Crescen				
•		Road, New Delhi-110010				
2	Type of Occupancy	Institutional "Group—C"				
3	Building Comprised of	Basement, Ground + 06 upper floors.				
4	Type of Case	Renewal				
5	Details of Previous NOC	F6/MS/DFS/Hospital/2015/SZ/288 Dt. 27/02/2015				
6	Fire Safety Directives Letter No	F6/DFS/MS/Hospital/98/266 dated 04/02/1988 & F6/DFS/MS/BP/Hospital/2009/3001 date 12/10/2009				
7	Date of Inspection	14/01/2020				
8	Name of the Inspecting Officers	D.B. Mukherjee DO (SD), Mehmood, ADO (SJ)				
9	Name & Designation of Officers from the building side	Mr. Sehgal (Chief Engineer)				
10	Year of construction	2003 & 2016				
11	Applicant letter No.	Outdoor diary No. 1646	dated 02/08/2019			
S.	Minimum standards on Fire Prevention	Old NOC	Provided at Site	Remarks		
No.	and Fire Safety U/R 33	Requirement	e e	MR/NMF		
1.	Access to Building.					
	Road width	9m	Provided	MR		
	Gate width	5m	Provided	MR		
	COSTONE (ALLE) AN ARTHUR COSTON					
	Width of internal road	As Per Approved Plan	Provided	MR		
2.	Number, width, type & arrangement of exi	ts.				
	a) Number of Staircase			0		
	Upper floors.	04 Nos	Provided	MR		
	Basement floor.	04 Nos	Provided	MR		
	b) Width of Staircase					
	> Upper floors	3 Nos of 2m				
	, oppu	& 1.20m	Provided	MR		
	> Basement floor	2m	4 Nos of 2m	MR		
	c) Protection of exits	2111	11(03 01 2111	TTTT		
	Fire check door	Required	Provided	MR		
	Pressurization	Required	Natural Ventilation	MR		
	at the state of th		Provided	MR		
	d) No. of continuous staircase to terrace e) Width of corridor	03 Nos	As per approved plan on 6th floor.	MR		
	e) Width of corridor	2m & 2.4m	Not Applicable on 5 th floor.	MR		
			As per approved plan below 4th floor	MR		
	f) Door size	2m for 5 th & 6 th Floor	1.25m in single/double patients' room & two No of 1.5m in ward	MR		
3.	Compartmentation.			ig "		
	Fire check door.	Required	Provided	MR		
	 Sealing of electrical shafts. 	Required	Provided	MR		
	Fire rating of shaft door.	-NA-	-NA-	-NA-		
	Water curtain	-NA-	-NA-	-NA-		
		-NA-	-NA-	-NA-		
	• Fire dampers.	-NA-	-INA-	-INA-		
4.	Smoke Management system.					
	Basement	30 ACPH	M.V. Provided	MR		
	Upper floors	12 ACPH	M.V. Provided	MR		
5.	Fire Extinguishers.					
	Total numbers	100 Nos	100 Nos	MR		
	• Types	ABC/CO2	ABC/W. CO2/ CO2 40/40/20 Nos	MR		
	ICI Madalara	ISI marked	Yes	MR		
	ISI Marking	151 marked	res	IVIK		
6.	First Aid Hose Reels.					
6.		2 No	Provided	MR		
6.	Total numbers on each floor.					
6.	Total numbers on each floor.Length of hose-reel hose.	30m 5mm	Provided Provided	MR MR		

7.	Automatic fire detection & alarming			7
	• Type of detectors	Smoke & Heat	Provided	MR
	 Location of Main Panel 	FCR	Provided	MR
	 Location of Repeater Panel 	-NA-	-NA-	-NA-
	Alternate source of power	Required	Provided	MR
	Hooter's location	Required	All Areas	MR
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System	Required	Trovided	IVIIC
10.	Basement	Required	Provided	MR
	Upper floors	Required	Provided	MR
	Sprinkler above false ceiling	Required	Provided	MR
11.	Internal Hydrants.	Troquired	1101100	
11.	Size of Riser/Down-comer	150mm	Provided	MR
	27 1 277 1 27	02 Nos	Provided	MR
		02 Nos	Provided	MR
1.0	Hose box.	UZ INUS	Flovided	IVIIX
12.	Yard Hydrants.	08 Nos	Provided	MR
	Total number of hydrants.			
1.7	Hose box.	08 Nos	Provided	MR
13.	Pumping arrangements.			
	• Ground Level	22001 DM	2400 % 1000 1 014	MD
	Discharge of main pump.Head of main pump.	2280LPM	2400 & 1800 LPM Provided	MR MR
	Number of main pumps.	60m Two	Provided	MR
	> Jockey Pump output.	2 x180 LPM	2 x180 LPM	MR
	Jockey Pump head.	60m	Provided	MR
	Standby Pump output.	2280 LPM	Provided	MR
	Standby Pump head.	60m	Provided	MR
	Auto Starting/Manual Stopping.	Required	Provided	MR
	Pump house access.	Required	Provided	MR
	Terrace Level			
	Discharge of pump.	450 LPM	450 LPM	MR
	Head of pump.Power supply.	40m	40m	MR
	Auto starting of pump.	Required	Provided Provided	MR
1.4	<u> </u>	Required	Provided	MR
14.	Captive water storage for firefighting.	2.00.000 I tr	Provided	MR
	 Underground tank capacity. Draw-off connection. 	2,00,000 Ltr Required	Provided	MR
	Fire Service Inlet.	Required	Provided	MR
	Access to tank.	Required	Provided	MR
	Overhead tank capacity.	20,000 Ltr	Provided	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	1		
	Pressurization of lift shaft.	Required	Provided	MR
	Pressurization of lift lobby.	Required	Provided	MR
	Communication in lift car.	Required	Provided	MR
	• Fireman's switch.	Required	Provided	MR
17.	Lift signage.	Required	Provided	MR
	Standby Power Supply	Required	Provided (DG Set)	MR
18.	Refuge Area	Required	11011404 (20 501)	1,111
. 0.	Total area	-NA-	-NA-	-NA-
	• Location	-NA-	-NA-	-NA-
19.	Fire Control Room.			\$ H
17.	Detector system panel.	Required	Provided	MR
	Detector system panel.Flow switch panel.	Required	Provided	MR
	PA system panel.	Required	Provided	MR
	Battery backup.	Required	Provided	MR
	Building floor plan.	Required	Provided	MR
20.	Special Fire Protection System for the	Required	Co2 flooding system	MR
	Protection of special Risk, if any.		provided.	

Note:

1. The basement is being used as business occupancy. Therefore, the required width of staircase shall be 1.5m. it is provided and meeting the requirement.

2. The required width of doors as required in UBBL-2016 (Amendment) is within the norms.

3. The shortcoming issued by this department vide letter No. F6/DFS/MS/Hospital/SZ/2019/1939 dated 09/04/2019 have been compiled.

The Fire protection systems provided in the building / premises were test checked at random and found functional at the time of inspection.

Keeping in view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No. F6/MS/DFS/Hospital/2004/1159 Dt. 31/05/2004, renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name: D.B. Mukherjee

Design: DO (SD)

Signature of the Inspecting Officer

Name: Mehmood Design: ADO (SJ)

What was the earlier use of basement approved

Desosz

lecated 2 1/1/2020

Lecated 2 1/1/2020

Lecated 2 1/1/2020

Lecated 2 2 1/1/2020