GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2020/62

Dated: 18/02/9020

FIRE SAFETY CERTIFICATE

Certified that the K. K. Guest House located at 3438, Dariba Pan, Panar Ganj, New Delhi comprised of Ground + 03 Upper floors, Ground floor (04 guest rooms + reception + 01 store room), 1st floor (05 guest rooms + 01 store room), 2nd floor (06 guest rooms + 01 store room) and 3rd floor (02 staff rooms) total 15 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2016/NDZ/1821 dated 23/12/16. The premises was re-inspected by the officer concerned of this department on 10/02/2020 in the presence of Sh. Phool Chand (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 15 guest rooms only(Upto 3rd floor only) with effect from -18/03/2030 for period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued <u>18/02/2020</u> at New Delhi by.

(Sunil Chawdhary)
Dy. Chief Fire Officer

Pelhi Fire Service

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.
- 2. The Manager, K. K. Guest House located at 3438, Dariba Pan, Panar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 9. Any flammable material for interior decoration is prohibited.
- 10. Owner/Occupier shall also ensure compliance of notification dated 27.05.19 and there of in r/o guest houses latest by 31.03.2020.

INSP	ECTION	REP	ORT
TIANT.	LUIUN	ILLI	UIVI

1. Name & address of the building K. K. Guest House located at 3438, Dariba

Pan, Pahar Ganj, New Delhi

Gr. + 03 Upper floors (total 15 Guest rooms) Ground floor (04 guest rooms + reception + 01 store room), 1st floor (05 guest rooms + 01 store room), 2nd floor (06 guest rooms + 01 store room) and 3rd floor (02 staff rooms)

2. Type of occupancy:-Residential, Sub Division-A-1

3. Type of case:-Renewal

4. Details of previous FSC:-No. F6/DFS/MS/GH/2016/NDZ/1821 dated

23/12/16.

5. Fire safety directives No.-N/A

6. Date of inspection:-10/02/2020

7. Name of the inspecting officer:-Sh. Rajinder Atwal (DO/CD) &

Sh. Manoj Kumar Sharma (ADO/CC)

8. Name & designation of officer From the building side:-

9. Year of construction:-

10 Applicant's letter No:-

Sh. Phool Chand (Manager)

2001

Nil dated 13/01/2020

10.	Applicant's letter No:-	Nil dated 1.	3/01/2020.		
		181	¥	Old Case	
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR	
1.	Access to Building				
	1) Road width	N/A	06 mtr.	N/A	
	2) Gate width	N/A	N/A	N/A	
	3)Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arrangement of Exits				
	A. Number of staircases				
	1. Upper floors	01 Nos.	01 Nos.	MR	
	2. Basements	N/A	N/A	N/A	
	B. Width of staircase				
	1. Upper floors	0.80 mtr.	0.80 Mtr.	MR	
	2. Basements	N/A	N/A	N/A	
	C. Protection of exits				
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous	01	01	MR	
	staircase to terrace				
	E. Width of corridor	1.25 mtr.	1.50 mtr.	MR	
	F. Door size	01 mtr.	01 mtr.	MR	
3.	Compartmentation				
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
	1) Basements	30 ACPH	N/A	N/A	
	2) Upper floors	12 ACPH	Natural	MR	
5.	Fire Extinguishers				
	1) Total numbers	10	10	MR	

	2) Types	ABC & CO2	ABC & CO2	MR
	3) ISI marking	Required	Provided	MR
6	First-Aid Hose Reel	Required	11011444	1
6.	1) Total number of eachfloor	01	01	MR
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
	3) Nozzle diameter	05 mm	05 mm	MR
7.	Automatic Fire Detection & A	A 57		
7.	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	N/A
8.	MOEFA	NR	Provided	MR
9.	Public Address System	NR	Provided	MR
	Automatic Sprinkler System	TVIC	TTOVIGCG	1711
10.	1) Basement	N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling	14/71	14/14	
11.	Internal Hydrants	2		
11.	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	N/A	N/A
	floor			
	3) Hose box	N/A	N/A	N/A
12.	Yard Hydrants			
14.	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A
13.	Pumping Arrangement	T		
	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A
	pump	1		6
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump		N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	N/A	N/A	N/A
	stopping			
	2) Terrace level	1 22		
	a) Discharge of pump	220 LPM	220 LPM	MR
	b) Head of pump	30 mtr.	30 mtr.	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of pump	Required	Provided	MR
14.	Captive Water Storage for Fire Fighting			
	1) Under ground tank	N/A	N/A	N/A
	capacity			
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A

hu

	d) Over head tank capacity	2500 ltr.	5000 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
72	a) Pressurization of lift shaft	N/A	N/A	N/A
-	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risk, if any: ABC, Co ₂			MR

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2016/NDZ/1821 dated 23/12/16 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name:- Rajinder Atwal Designation:- DO (CD)

Name :- M.K. Sharma Designation :- ADO (CC)

M.S. W