## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/NDZ/2020/5/

Dated :-25.02.2020

## FIRE SAFETY CERTIFICATE

Certified that the M/s Allure Resto and Bar located at P. No. 65, GF, D.B.G. Road, Pahar Ganj New Delhi comprises of Basement + Ground + 04 upper floor, Restaurant running ground floor only, Basement for (L-store) owned /occupied by M/s Allure Resto and Bar, has complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of Delhi Fire Service on 13/02/2020 in the presence of Mr. Manish Aggarwal (Owner) and that the building / premises, is fit for occupancy class Assembly Building Group D, Restaurant at ground floor only with effect from 25/2-22222 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010 printed below.

Issued 25/02/2020—at New Delhi by.

Atul Garg)
Director

Delhi Fire Service

Copy to:-

1. The Addl. Commissioner (Licensing)

1<sup>st</sup> Floor, Police Station Defence Colony, New Delhi.

1. The Medical Officer of Health,

Health Department,

North DMC, Civic Centre, Minto Road, New Delhi – 110002.

2. Mr. Manish Aggarwal (Owner),

M/s Allure Resto and Bar, P. No. 65, GF, D.B.G. Road, Pahar Ganj New Delhi.

## Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 9. Any flammable material for interior decoration is prohibited.

	D	ICDE CETON D					
	INSPECTION REPORT  1. Name & address of the building M/s Allure Resto and Bar situated at						
2	2. Type of occupancy:-  65, GF, D.B.G.Road, Pahar ganj New Delhi.  Assembly Building Group-D						
	1	B + G + 4	4 upper floor, Restaur	) <del>-</del> D			
	2	Ground f	loor only	ant running at			
	3. Type of case:-	New Ca	ise				
	4. Details of previous FSC:-  5. Fire safety directives No  6. Date of inspection:-  13/02/20						
1	7. Name of the inspecting officer:- Sh. Sunil Chawdhary Dy. CFO,						
		Sh. Rajir	ider Atwal (DO/C	D) &			
	Nome 0 1	Sh Mano	oj Kumar Sharma	(ADO/CC)			
0	B. Name & designation of office	er		(=====)			
0	From the building side: Year of construction:-	Sh. Man	nish Aggarwal (Ov	vner)			
10	Applicant's latter N	2010					
S.No.	O. Applicant's letter No:-	Nil dated 2:	3/12/2019				
5.110.	Minimum Standards on fire Prevention and fire safety U/R	Requirement/	Provided at sit	te Remarks			
	33	Existing fire safety		MR/NMR			
4	2 40	arrangements	9				
1.	Access to Building	3					
	1) Road width	6 mtr.	12 mtr.	MD			
	2) Gate width	N/A	N/A	MR			
	3) Width of internal road	N/A		N/A			
2.	Number, Width Type & Ar	rangament of l	N/A	N/A			
	A. Number of staircases	rangement of j	LXITS				
	1. Upper floors	N/A	27/4				
	2. Basements	N/A	N/A	N/A			
	B. Width of staircase	IN/A	N/A	N/A			
	1. Upper floors	N/A	27/4				
	2. Basements	N/A	N/A	N/A			
	C. Protection of exits	IN/A	N/A	N/A			
	1. Fire check door	NI/A					
	2. Pressurization	N/A	N/A	N/A			
	D. No. of continuous	N/A	N/A	N/A			
	staircase to terrace	N/A	N/A	N/A			
	E. Width of corridor	DT/A		- T			
	F. Door size	N/A	N/A	N/A			
3.	Compartmentation	02 mtr.& 1.5mtr	Provided	MR			
	1) Fire check door	1					
-	2) Seeling of alartic 1 1 2	N/A	N/A	N/A			
	2) Sealing of electrical shafts	N/A	N/A	N/A			
-	3) Fire rating of shaft door	N/A	N/A	N/A			
+	4) Water curtain	N/A	N/A	N/A			
	5) Fire Dampers	N/A	N/A	N/A			
	Smoke Management System	_		1			
_	1) Basements	12 ACPH	N/A	N/A			
	2) Upper floors	12 ACPH	Exhaust fan	MR			
	Fire Extinguishers						
	1) Total numbers	08 Nos.	08 Nos.	MR			
	0) m						
	2) Types 3) ISI marking	ABC & CO2	ABC & CO2	MR			

	)			
6.	First-Aid Hose Reel			
	1) Total number of eachfloor	01	01	MR
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
	3) Nozzle diameter	05 mm	05 mm	MR
7.	Automatic Fire Detection &	Alarming Sy	stem	1.11
	1) Type of detectors	N/A	N/A	N/A
	2) Location of main panel	N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A	N/A	N/A
	5) Hooter's Location	N/A	N/A	N/A
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	Provided	
10.	Automatic Sprinkler System	MR		
	1) Basement (Less than 200 SQM)	N/A	N/A	27/4
	2) Upper floors/ Gr. floor	Required	Provided	N/A
	3) Sprinkler above false	N/A		MR
	ceiling	11/14	N/A	N/A
11.	Internal Hydrants			
	1) Size of riser/down-comer	Required	Duori 1 1	1.00
	2) Number of hydrants per		Provided	MR
	floor	Required	Provided	MR
	3) Hose box	Daguina 1	D., 11 1	
12.	Yard Hydrants	Required	Provided	MR
14.	1) Total number of hydrants	NI/A	DT/A	
	2) Hose box	N/A	N/A	N/A
13.		N/A	N/A	N/A
10.	Pumping Arrangement	37/4		
	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A
	pump	27/		H.
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump		N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
				The second secon
	h) Auto starting/Manual	N/A	N/A	N/A
	stopping	N/A	N/A	N/A
	stopping 2) Terrace level	N/A	N/A	N/A
	stopping 2) Terrace level a) Discharge of pump	N/A 450 LPM	N/A 450 LPM	
	stopping 2) Terrace level a) Discharge of pump b) Head of pump		450 LPM	MR
	stopping 2) Terrace level a) Discharge of pump	450 LPM 40 mtr.	450 LPM 40 mtr.	MR MR
D	stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump	450 LPM 40 mtr. Required Required	450 LPM 40 mtr. Provided	MR MR MR
4.	stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump	450 LPM 40 mtr. Required Required	450 LPM 40 mtr. Provided Provided	MR MR
4.	stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply	450 LPM 40 mtr. Required Required re Fighting	450 LPM 40 mtr. Provided Provided (Common)	MR MR MR MR
4.	stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for Fi	450 LPM 40 mtr. Required Required	450 LPM 40 mtr. Provided Provided	MR MR MR
4.	stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump  Captive Water Storage for Fi 1) Under ground tank capacity	450 LPM 40 mtr. Required Required re Fighting N/A	450 LPM 40 mtr. Provided Provided (Common) N/A	MR MR MR MR
4.	stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump  Captive Water Storage for Fi 1) Under ground tank capacity a) Draw-off connection	450 LPM 40 mtr. Required Required re Fighting N/A N/A	450 LPM 40 mtr. Provided Provided (Common) N/A	MR MR MR MR N/A
4.	stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump  Captive Water Storage for Fi 1) Under ground tank capacity a) Draw-off connection b) Fire service inlet	450 LPM 40 mtr. Required Required re Fighting N/A N/A	450 LPM 40 mtr. Provided Provided (Common) N/A N/A N/A	MR MR MR MR N/A
4.	stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump  Captive Water Storage for Fi 1) Under ground tank capacity a) Draw-off connection b) Fire service inlet c) Access to tank	450 LPM 40 mtr. Required Required re Fighting N/A N/A	450 LPM 40 mtr. Provided Provided (Common) N/A	MR MR MR MR N/A

15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	N/A	N/A	N/A
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syste Risk, if any:	ion of special	N/A	

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Shortcomings communicated vide letter No. F6/DFS/MS/EH/NDZ/2019/7112 dated 28/11/2019 have been rectified. The restaurant is running since Jan, 2010 for 48 seats under license from MCD (Copy placed on file).

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules, grant of fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010 / is recommended please.

Signature of the Inspecting Officer Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name :- Sh. Sunil Chawdhary

Name: - Rajinder Atwal Designation: DCFO (NDZ) Designation: - DO (CD)

Name: - M.K. Sharma

Designation: - ADO (CC)