[FORM 'H'] FORM FOR ISSUING FIRE SAFETY CERTIFICATE [SEE SUB RULE (1) OF RULE 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No. F6/DFS/MS/Banquet/2020/) 50

Dated 2/03/2020

FIRE SAFETY CERTIFICATE

Certified that the Celebration Banquet Hall Located at Basement + Ground Floor+1ST Floor only, A-16/3, Wazirpur Industrial Area, New Delhi – 110052 in a building comprised of Basement + Ground+2 upper Floor only was issued FSC vide Letter No. F-6/DFS/MS/Banquet/2017/100 Dated 21/01/2017. The premises was re inspected by the officers concerned of this department on 28-02-2020 in the presence of Sh. Sanjeev Verma (Owner) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Assembly" Group D (Ground Floor+1ST Floor only) with effect from for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ... 200 3 2000 at New Delhi by.

(Dharampal Bhardwaj)
Dy. Chief Fire Officer
Delhi Fire Service

Copy to: Sh.Sanjeev Verma, Celebration Banquet Hall, A-16/3, Wazirpur Industrial Area, New Delhi – 110052.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in
- 8. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 9. 2nd floor shall be used for kitchen purpose only.

INSPECTION REPORT

1. Name & address of the building: Celebration Banquet Hall Located at, Basement Ground and 1st floor at A-16/3, Wazirpur Industrial Area, New Delhi - 110052.

2. Type of Occupancy : Assembly (Basement+ Ground+1nd floor only in a building comprised of Basement+ Ground+2 Upper floors)

:Renewal 3. Type of Case

4. Details of previous NOC : F6/DFS/MS/Banquet/2017/100 Dated 21/01/2017

5. Fire Safety directives Letter No.: F-6/DFS/MS/BP/2011/43 Dated 06/01/2012

: 28-2-2020 6. Date of inspection

7. Name of the Inspecting Officer: ADO (WP)

8. Name and designation of Officer

: Sh. Sanjeev Verma (Owner) from the building side

9. Year of Construction : 1975

: Nil Dated 06/02/2020 10. Applicant's letter No.

	10. Applicant s letter 140.						1		
S	Minimum standards on fire		ARABARA EL PARA		ovided at site	Rem			
No	prevention and fire safety U	/R 33	Directiv	ve	22	MR/	MR/NMR		
1.	Access of building								
	Road width	6m		9m		MR			
	 Gate width 		5m		5m		MR		
	 Width of internal roa 	ıd	NA		NA		NA		
2.	Number, width, Type & Arrangements of exits								
	a. Number of staircases					V	>		
	 Upper floors 		3		Provided		MR MR		
	Basements		2		Provided				
	b. Width of staircases								
	 Upper floors 			1x175cm,1x100cm			R(Old Case)		
			1x100cm		1x150 cm provided				
	Basements		1x1.65 m		1x165cm &1x90cm				
		,1x	100cm	n Provided					
	c. Protection of exits						MR		
	 Fire check door 	Rec	Required (In Basem NA 02						
	 Pressurization 				NA Provided				
	d. No of continuous								
	staircase to terrace		-						
	e. Width Of Corridor		NA	¥.	• NA		NA		
	f. Door Size				GF=2m,1x100cm		MR		
					F=185cm,90cm &100cm				
3.	Compartmentation								
	Fire check door			Require	d Provid	ded	MR		
	Sealing of electrical sha			NA	NA		NA		
	 Fire Rating of shaft door 			NA	NA		NA		
	Water Curtain			NA	NA		NA		
	Fire Dampers			NA NA			NA		

4.	Smok	e managements System							
	•	Basements	R		Required	Pro		vided	MR
	•	Upper floors			Required		Provided		MR
5.	Fire E	xtinguishers							1-
	•	Total numbers	10 nos.				Provided		MR
	•	Types	ABC	& C(02		Provided		MR
	•	IS marking	ISI ma	arked	d	Pro		vided	MR
6.	First –	Aid Hose Reels	-						
	•	m 1 1 1 1 1 1			2		Provided		MR
	•	Length of hose reel hos	se	30 m			30 mtr Provided		MR
	•	Nozzle diameter		4	5 mm				MR
7.	Automatic fire detection and alarming system								
	•	Type of detectors		Smoke	& Hea	at	Provided	MR	
	•	T			Ground flo		loor Provided		MR
	•	Location of Repeater P	Panel		Ground floor Required		•	Provided	MR
	•	Alternate source of pov						Provided	MR
	•	Hooters' Location	.,		The second secon				MR
8.	MOEF	These Artist age are parameteral and particular productions and		Re			-5 AC 58 N -10 -255 N -55	MR	
9.		Address System			equired		30, 30, 30	vided	MR
10.		natic Sprinkler System		100	quired		110	viaca	IVIIC
10.	7141011	Basements		Т	Require	equired Provided		MR	
				-	NA		NA		NA
		 Upper Floor Sprinkler above false ceiling			NA	_	NA NA		NA
11.	Interne	*	eming		1471			1421	1411
11.	• Interna	Internal Hydrants • Size of riser/down- comer			4 inc	h	n Provided		MR
	•				2	11		vided	MR
	•	Number of hydrants per floor			2	Provided			MR
12.	Hose Box Vand Hydronta						110	viaca	IVIIC
12.		Yard Hydrants			A NA			NA	
	•	Total number of Hyd Hose Box		NA NA			NA		NA
12	Dyyman	THE WAS DESCRIPTION OF THE PARTY OF THE PART		INA			147	1	IVA
13.	Pumpi	ng Arrangements							
	•	Ground Level		-	NA	NA		NA	
		Discharge of main pump			NA NA		NA		NA
		Head of main pump Number of main pump	a	_	NA NA	NA NA			NA
		Jockey pump out put	S		NA NA	A			NA
		Jockey pump head			NA NA	NA NA			NA
	>				NA NA	NA NA			NA
					NA NA	NA NA			NA NA
		Auto Staring/Manual		_	NA NA	NA NA		NA NA	
		stopping			INA		INA		NA
	· >	Pump House Access		-	NA	NA		NA	
	•	_ ^			INA		INZ	1	INA
	>	Discharge of pump		900 lpm		1)rox	ided	MR
	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Head of the pump			0 ipiii 0 m	Prov			MR
		Power supply		_	-			ided	MR
	>	Auto starting of pump			quired				MR
1.4	1 Tequired 1 Tovided 141								
14.	Captive water Storage for fire fighting				NT A			NΙΛ	NA
	•		round tank capacity		NA		NA NA		
	A	Draw of connection			NA			NA NA	NA
	1800	Fire service inlet		-	NA				NA
		Access to tank			NA	14	NA D : 1 1		NA
	•	Overhead Tank capacit	.y		20,000	itrs	P	rovided	MR

Provision of Lifts(Lift run from G	round to	-rd							
TIOVISION OF ENERGY CT : C C1 C		Exit Signage Required Provided MR Provision of Lifts (Lift run from Ground to 2 rd Floor)							
Pressurization of Lift Shaft		NA NA		NA	NA				
> Pressurization of lift lobby				NA	NA				
Communication in lift Car		Required		Provided	MR				
				Provided	MR				
					MR				
				Provided	MR				
Ø 1		NA		NA					
		NA		NA	NA				
		NA		NA	NA				
30 - 30 - 30 - 40 - 40 - 40 - 40 - 40 -									
	NA	JA :			NA				
	NA		NA		NA				
	NA	NA		*	NA				
	NA	NA			NA				
> Building Floor Plans	NA		NA		NA				
Special Fire Protection Systems for Protection of special Risks, if	NA		NA		NA				
	Standby power supply Refuge Area > Total area > Location Fire control room > Detector system panel > Flow Switch Panel > PA System Panel > Battery backup > Building Floor Plans Special Fire Protection Systems	 ➢ Fireman's Grounding Switch ➢ Lift Signage Standby power supply Refuge Area ➢ Total area ➢ Location Fire control room ➢ Detector system panel ➢ Flow Switch Panel ➢ PA System Panel ➢ Battery backup ➢ Building Floor Plans NA Special Fire Protection Systems for Protection of special Risks, if 	 ➢ Fireman's Grounding Switch ➢ Lift Signage R Standby power supply Refuge Area ➢ Total area ➢ Location Fire control room ➢ Detector system panel ➢ Flow Switch Panel ➢ PA System Panel ➢ Battery backup ➢ Building Floor Plans NA Special Fire Protection Systems for Protection of special Risks, if 	 ➢ Fireman's Grounding Switch ➢ Lift Signage Required Required Required Required Required Required NA NA ➤ Total area ➢ Location Fire control room ➢ Detector system panel ➢ Flow Switch Panel ➢ PA System Panel ➢ PA System Panel ➢ Battery backup ➢ Building Floor Plans NA NA<	 Fireman's Grounding Switch Lift Signage Required Required Provided Required Provided Refuge Area NA Total area Location NA NA				

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the FSC issued vide letter no. F6/DFS/MS/Banquet/2017/100 Dated 21/01/2017renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Name

Designation

Signature of the Inspecting Officer

Name

Designation

Six ff letter is but up der cit ble