FORM 'H'
FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No. F6/DFS/MS/WZ/2020/ / 3 7

Dated: 30 /03/2020

FIRE SAFETY CERTIFICATE

Certified that the M.C. Primary School, Located at Ramesh Nagar-2, Namdhari Colony, Kirti Nagar, New Delhi-110015 comprised of Ground + 02 Upper Floor owned/ occupied by M.C. Primary School have complied with the fire prevention and fire safety requirements in accordance with the Director of Education Circular No-F.16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01.03.2011 and verified by the officer concerned of Fire Service on 26-02-2020 in the presence of Ms. Sunita Guliani (Incharge) and that the building / premises is fit for the occupancy class "Educational" Group B Sub Division B – 1 with effect from . 20./3. for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 30./2./2..... at New Delhi by.

Director

Delhi Fire Service

Copy to:

- 1. The Principal, M.C. Primary School, Located at Ramesh Nagar-2, Namdhari Colony, Kirti Nagar, New Delhi-110015
- 2. Directorate of Education Old Secretariat Delhi 110054.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

1. Name & address of the building: M.C. Primary School, Located at Ramesh Nagar-2, Namdhari Colony, Kirti Nagar, New Delhi-110015.

2. Type of Occupancy

: Educational (Ground +02 Upper Floor)

3. Type of Case

: New

4. Details of previous NOC

: NII

5. Fire Safety directives Letter No.: DOE 3298-3398 dated 1-3-11

6. Date of inspection

: 26/02/2020

No. of Students=288

7. Name of the Inspecting Officer: ADO (WP)

(WP) No. of class rooms=16 Plot area=1155sqm

Covered area=795Sqm

8. Name and designation of Officer

from the building side

: Ms. Sunita Guliani (Incharge)

9. Year of Construction

: 1997

10. Applicant's letter No.

: Nil Dated- 03/02/2020

| S | Minimum standards on fire | | E 3298- | Prov | ided at site | Remarks | | |
|--|--|-------|---------|------|------------------|--|--|--|
| No | prevention and fire safety | | 8 dated | | | MR/NMR | | |
| | U/R 33 | 1-3- | -11 | | | | | |
| 1. | Access of building | | | | | | | |
| | Road width | | 6 mtr | | 6m Provided | MR | | |
| | Gate width | | Accessi | ible | On Road | MR | | |
| | Width of internal road | | NA | | NA | NA | | |
| 2. Number, width, Type & Arrangements of exits | | | | | | | | |
| | a. Number of staircases | | | | | 9 | | |
| | Upper floors | | 1 | | Provided | MR | | |
| | Basements | | NA | | NA | NA | | |
| | b. Width of staircases | | | | | 20 29 20 20 20 20 20 20 20 20 20 20 20 20 20 | | |
| | Upper floors | | 1.5 | m | 1x117cm &1x150cm | MR | | |
| | Basements | | NA | | NA | NA | | |
| | c. Protection of exits | | | | | | | |
| | Fire check door | | N | ΙA | NA | NA | | |
| | Pressurization | | N | ΙA | NA | NA | | |
| - 1 | d. No of continuous stair | rcase | N | ΙA | NA | NA | | |
| | to terrace | | | | | | | |
| | e. Width Of Corridor | | 1.: | 5m | 230cmProvided | MR | | |
| | f. Door Size | | 1 | m | 110cm Provided | MR | | |
| 3. | Compartmentation | | | | | | | |
| | Fire check door | N | A | NA | NA | | | |
| | Sealing of electrical shafts | | N | A | NA | NA | | |
| | • Fire Rating of shaft do | oor | N | A | NA | NA | | |
| | Water Curtain | | N | A | NA | NA | | |
| | Fire Dampers | N | A | NA | NA | | | |
| 4. | Smoke managements System | | | | 9 | | | |
| | • Basements | | N | A | NA | NA | | |
| | Upper floors | | N | A | NA | NA. | | |

M9

| 5. | Fire Extinguishers | | | | | | |
|-----|---|---------|--------------|--------|----------|-------|--|
| | Total numbers | | nos. | | rovided | MR | |
| | • Types | | $3C \& CO_2$ | | ovided | MR | |
| | IS marking | IS | marked | Pı | ovided | MR | |
| 6. | First – Aid Hose Reels | | | | | | |
| | Total numbers on each floor | | 1 | | Provided | MR | |
| 1 | Length of hose reel hose | | 30m1 | tr. | Provided | MR | |
| | Nozzle diameter | | 5mm | | Provided | MR | |
| 7. | Automatic fire detection and alarmi | ng sy | ystem | | | | |
| | Type of detectors | | NA | - | NA | NA | |
| | Location of Main Panel | | NA | | NA | NA | |
| | Location of Repeater Panel | | NA | | NA | NA | |
| | Alternate source of power | | NA | | NA | NA | |
| | Hooters' Location | | NA | | NA | NA | |
| 3. | | VA | | | NA | NA | |
| 9. | 11102211 | VA | | | NA | NA | |
| 10. | Automatic Sprinkler System | Sund on | | | | | |
| | Basements | | NA | A NA | | NA | |
| | Upper Floor | | NA | | NA | NA | |
| | Sprinkler above false ceiling | y | NA | | NA | NA | |
| 11. | Internal Hydrants: | | | | | | |
| 1. | Size of riser/down- comer | | NA | | NA | NA | |
| | Number of hydrants per floor | | NA | | NA | NA | |
| | Hose Box | | NA | | NA | NA | |
| 12. | Yard Hydrants | | | | | | |
| 12. | Total number of hydrants | | NA | | NA | NA | |
| 1 | Hose Box | | NA | | NA | NA | |
| 13. | Pumping Arrangements: | | | | | | |
| 15. | Ground Level | | | | | | |
| | Discharge of main pump | | NA | | NA | NA | |
| | > Head of main pump | | NA | | NA | NA | |
| | Number of main pumps | | NA | | NA | NA | |
| | > Jockey pump out put | | NA | | NA | NA | |
| | > Jockey pump head | | | | NA | NA | |
| | Standby Pump out put | | NA | | NA | NA | |
| | Standby Pump Head | | NA | | NA | NA | |
| | Auto Staring/Manual stopping | ng | NA | | NA | NA | |
| | Pump House Access | | NA | | NA | NA | |
| | Terrace level | | | | | | |
| | Discharge of pump | | 450lpm | 1 | Provided | MR | |
| | > Head of the pump | | 40m | | Provided | MR | |
| | > Power supply | | Required | | Provided | MR | |
| | > Auto starting of pump | A | Require | ed | Provided | MR | |
| 14. | Captive water Storage for firefighti | ng: | | | ж | 3.7.4 | |
| | Under ground tank capacity | 7 | NA | | NA | NA | |
| | Draw off connection | | NA | | NA | . NA | |
| | > Fire service inlet | | | A | NA | NA | |
| | > Access to tank | | | A | NA | NA | |
| | Overhead Tank capacity | | | Oltrs. | Provided | MR | |
| 15 | Exit Signage NA | | NA | | | NA | |

nello

| | | | -1- | | | | | | |
|------------------------|------------------------------|-------|-----|----|----|----|--|--|--|
| 16. Provision of Lifts | | | | | | | | | |
| | Pressurization of Lift | Shaft | N. | A | NA | NA | | | |
| | Pressurization of lift lobby | | NA | | NA | NA | | | |
| | > Communication in life | | NA | | NA | NA | | | |
| | > Fireman's Grounding | | NA | | NA | NA | | | |
| | > Lift Signage | | | A | NA | NA | | | |
| 17. | Standby power supply | | N. | A | NA | NA | | | |
| 18. | Refuge Area | | | | | | | | |
| | > Total area | | | A | NA | NA | | | |
| | > Location | | N. | A | NA | NA | | | |
| 19. | . Fire control room | | | | | | | | |
| | Detector system panel | NA | | NA | | NA | | | |
| | > Flow Switch Panel | NA | | NA | | NA | | | |
| | > PA System Panel | NA | | NA | | NA | | | |
| | Battery backup | NA | | NA | | NA | | | |
| | Building Floor | NA | | NA | | NA | | | |
| | Plans | | | ä | | | | | |
| 20. | Special Fire Protection | NA | | NA | | NA | | | |
| | Systems for Protection of | | | | | | | | |
| | special Risks, if any; | | | | | | | | |

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/issue shortcomings as noted at serial numbers

Signature of the Inspecting Officer Name Voluvia

Designation Apolut

Signature of the Inspecting Officer

Name

Designation

CE .

Stanks Jam

FIPLS