GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F.6/DFS/MS/Audi/2020/SZ/ 262

Dated: 17/07/2020

FIRE SAFETY CERTIFICATE

Certified that the Auditorium Building at Chinmaya Mission, 89, Lodhi Road, New Delhi–110003, comprised of basement, ground plus two upper floors but Auditorium at first floor only, owned/occupied by Sri Chinmaya Mission was issued FSC by this department vide letter No. F6/DFS/MS/2017/SZ/626 dated 03/05/2017. The premise was re-inspected by the officer concerned of this department on 06/07/2020 in presence of Mr. Vinod Kumar Rawat and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises fit for occupancy class Group "D" Assembly (Auditorium) as above with effect from 17/57/2020 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010 as below.

Issued on 17/07/2020 at New Delhi by

(Sunil Choudhary) Dy. Chief Fire Officer (SZ) Delhi Fire Service

Copy to: -

- 1. Sh. Jitender Mohan Dhir (General Manager), M/s Chinmaya Mission located at 89, Lodhi Estate, New Delhi–110003
- 2. The Addl. Commissioner of Police (Lic.), 1st Floor, PS Defence Colony, New Delhi-49

Conditions for the validity of Fire Safety Certificate: -

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire fighting system.
- 4. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of DFS Rules, 2010. The form is available on www.dfs.delhigovt.nic.in
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of
- 6. UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.

	INSPECTIO	M/s Auditorium l	Building at Chinmaya Missi	ion,	
1	Name & Address of the Building	M/s Auditorium Building at Chinmaya Mission, 89, Lodhi Road, New Delhi–110003			
		Assembly, Group-D			
2	Type of Occupancy	Basement, (storage & service) Ground plus Two Upper			
3	Building Comprised of	Floor (Auditorium at first floor only having 430 seats)			
		Ground Floor-Ope	en Hall & Second Floor- O	ffices and	
		Residence of Swamiji.			
	m	Renewal			
4	Type of Case	F6/DFS/MS/2017/SZ/626 Dt. 03-05-1017			
5	Details of Previous NOC	F6/DFS/MS/BP/94/902 Dated 16/06/1994			
6	Fire Safety Directives Letter No	06-07-2020			
7	Date of Inspection				
8	Name of the Inspecting Officers	Mehmood, ADO (SJ)			
9	Name & Designation of Officers	Mr. Vinod Kumar Rawat			
	from the building side				
10	Year of construction	1996	1 (002 1 + 124 06 2020		
11	Applicant letter No.	Outdoor Diary No. 6083 dated 24-06-2020 Old NOC Provided at Site Remarks			
S. No.	Minimum standards on Fire Prevention	Old NOC	I Tovided at Site	MR/NMR	
5. 140.	and Fire Safety U/R 33	Requirement	I	VIR/INIVIR	
1.	Access to Building.			1.40	
1.	Road width	9m	15 m	MR	
	Gate width	5m	5m	MR	
	Width of internal road	-NA-	-NA-	-NA-	
	Width of internal road				
2.	Number, width, type & arrangement of ex	its.			
	a) Number of Staircase	GF to FF= 03nos	GF to FF=03nos	MR	
	> Upper floors.	FF to SF=02nos			
		02nos	02nos	MR	
	> Basement floor.	021105	021100		
	b) Width of Staircase	7 1	02nos=2.40m each up	MR	
	> Upper floors	Required	to SF & 1no=1.5m upto FF	(old case	
				MR	
	> Basement floor	Required	1.70m & 2.40m	(old case	
	c) Protection of exits	Required	Provided at basement	MR	
	Fire check door	Required	floor only	(old case	
		-NA-	-NA-	-NA-	
	Pressurization		Provided	MR	
	d) No. of continuous staircase to terrace	One	-NA-	-NA-	
	e) Width of corridor	-NA-		MR	
	f) Door size	1.2 mtr (each) 03 exit gates at 1 st floor	(old case	
	1) 1		(1.6m, 1.6m & 1.50m	(Old Case	
2	Compartmentation.		,	MD	
3.	Compartmentation.	Required	Provided in basement	MR	
3.	Fire check door.	Required Required	Provided	MR	
3.	Fire check door. Sealing of electrical shafts.		Provided -NA-	MR -NA-	
3.	Fire check door.Sealing of electrical shafts.Fire rating of shaft door.	Required	Provided	MR -NA- -NA-	
3.	Fire check door.Sealing of electrical shafts.Fire rating of shaft door.Water curtain	Required -NA- -NA-	Provided -NA-	MR -NA- -NA-	
3.	 Fire check door. Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. 	Required -NA-	Provided -NA- -NA-	MR -NA- -NA-	
3.	Fire check door.Sealing of electrical shafts.Fire rating of shaft door.Water curtain	Required -NANANA-	Provided -NANANA-		
	 Fire check door. Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. 	Required -NANANA- 30 ACPH	Provided -NANANA- Provided	MR -NANANA-	
	Fire check door. Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement	Required -NANANA-	Provided -NANANA-	MR -NANANA-	
4.	Fire check door. Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors.	Required -NANANA- 30 ACPH 12 ACPH	Provided -NANANA- Provided Exhaust fan provided	MR -NANANA- MR MR	
	Fire check door. Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors. Fire Extinguishers.	Required -NANANA- 30 ACPH 12 ACPH	Provided -NANANA- Provided Exhaust fan provided	MR -NANANA- MR MR	
4.	Fire check door. Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors. Fire Extinguishers. Total numbers	Required -NANANA- 30 ACPH 12 ACPH	Provided -NANANANA- Provided Exhaust fan provided 14 Nos ABC, CO ₂ & W.CO ₂	MR -NANANA- MR MR MR	
4.	Fire check door. Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors. Fire Extinguishers. Total numbers Types	Required -NANANA- 30 ACPH 12 ACPH	Provided -NANANANA- Provided Exhaust fan provided 14 Nos ABC, CO ₂ & W.CO ₂	MR -NANANA- MR MR MR	
4.	Fire check door. Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors. Fire Extinguishers. Total numbers Types ISI Marking	Required -NANANANA- 30 ACPH 12 ACPH 12 Nos ISI marked	Provided -NANANANA- Provided Exhaust fan provided 14 Nos ABC, CO ₂ & W.CO ₂	MR -NANANANA- MR MR MR	
4.	Fire check door. Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors. Fire Extinguishers. Total numbers Types ISI Marking First Aid Hose Reels.	Required -NANANANA- 30 ACPH 12 ACPH 12 Nos ISI marked	Provided -NANANANA- Provided Exhaust fan provided 14 Nos ABC, CO ₂ & W.CO ₂	MR -NANANANA- MR MR MR	
4.	Fire check door. Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors. Fire Extinguishers. Total numbers Types ISI Marking	Required -NANANANA- 30 ACPH 12 ACPH 12 Nos ISI marked	Provided -NANANANA- Provided Exhaust fan provided 14 Nos ABC, CO ₂ & W.CO ₂ Provided	MR -NANANANA- MR MR MR MR	
4.	Fire check door. Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors. Fire Extinguishers. Total numbers Types ISI Marking First Aid Hose Reels.	Required -NANANANA- 30 ACPH 12 ACPH 12 Nos ISI marked	Provided -NANANANA- Provided Exhaust fan provided 14 Nos ABC, CO ₂ & W.CO ₂ Provided 01no & 02nos additional in Audi	MR -NANANA- MR MR MR	

7.	7. Automatic fire detection & alarming system.				
	Type of detectors	Smoke & Heat	Smoke & Heat	MR	
	 Location of Main Panel 	Ground Floor	Ground Floor	MR	
	 Location of Repeater Panel 	-NA-	-NA-	-NA-	
	Alternate source of power	Required	Battery Backup	MR	
	Hooter's location	All Areas	All Areas	MR	
8.	MOEFA	Required	Provided	MR	
9.	Public Address System	Required	Provided	MR	
10.	Automatic Sprinkler System	1 100,1000		1,11	
	Basement	Required	Provided	MR	
	 Upper floors 	-NA-	Provided at stage only	-NA-	
	 Sprinkler above false ceiling 	-NA-	-NA-	-NA-	
11.	Internal Hydrants.			1471	
	Size of Riser/Down-comer	150 mm	Provided	MR	
	 Number of Hydrant per floor 	01no	Provided	MR	
	Hose box.	01no	Provided	MR	
12.	Yard Hydrants.		11011000	IVIIC	
	Total number of hydrants.	-NA-	-NA-	-NA-	
	Hose box.	-NA-	-NA-	-NA-	
13.	Pumping arrangements.		11/1	-IVA-	
	Ground Level	s .			
	Discharge of main pump.	-NA-	-NA-	-NA-	
	Head of main pump.	-NA-	-NA-	-NA-	
	Number of main pumps.	-NA-	-NA-	-NA-	
	Jockey Pump output.Jockey Pump head.	-NA-	-NA-	-NA-	
	Standby Pump output.	-NA-	-NA-	-NA-	
	Standby Pump head.	-NA-	-NA-	-NA-	
	Auto Starting/Manual Stopping.	-NA-	-NA-	-NA-	
	Pump house access.	-NA-	-NA-	-NA-	
	Terrace Level			1471	
	Discharge of pump.	900 + 180 LPM	900 + 180 LPM	MR	
	Head of pump.	40m	40m	-NA-	
	Power supply.	Required	Provided	MR	
	Auto starting of pump.	Required	Provided	MR	
14.	Captive water storage for fire fighting.				
	 Underground tank capacity. 	100,000 Ltr	100,000 Ltr provided	MR	
	> Draw-off connection.	-NA-	-NA-	-NA-	
	Fire Service Inlet.	-NA-	-NA-	-NA-	
	Access to tank.	Required	Provided	MR	
	Overhead tank capacity.	20, 000 Ltr	20, 000 Ltr provided	MR	
15.		Exit Signage. Required Provided		MR	
16.	Provision of Lifts.)	27.		
	Pressurization of lift shaft.	-NA-	-NA-	-NA-	
	Pressurization of lift lobby.	-NA-	-NA-	-NA-	
	• Communication in lift car.	Required	Provided	MR	
	• Fireman's switch.	Required	Provided	MR	
15	Lift signage.	Required	Provided	MR	
17.	Standby Power Supply	Required	Provided	MR	
18.	Refuge Area • Total area	-NA-	NT A	» T.A	
	Location	-NA-	-NA-	-NA-	
	Location	-INA-	-NA-	-NA-	

Nf 44

		And the second s			
19.	Fire	Control Room.			
		D 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Required	Provided	MR
	 Flow switch panel. PA system panel. Battery backup. 	-NA-	-NA-	-NA-	
			Required	Provided	MR
		Required	Provided	MR	
		Building floor plan.	-NA-	-NA-	-NA-
20		al Fire Protection System for the	ABC & CO ₂ Fire Extinguishers provided for		MR
	Prote	ection of special Risk, if any.	electric panel		

The fire protection system provided in the building/ premises were checked, tested at random and found functional at the time of inspection. Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No. F.6/DFS/MS/Auditorium/2016/SZ/197 dated 03.02.2016, renewal under Rule 37 of the Delhi Fire Service Rules, 2010, is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: Mehmood Design: ADO (SJ)

M/s Auditorium Building at Chinmaya Mission, 89, Lodhi Estate, New Delhi-110003

DO (SD)

(10/07) (Sept.)

F, t. p

p lease

A DOS. J.

pu)-ug

16/22 rec

apous

M. S. Of