## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI **HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001**

No.F6/DFS/MS/NDZ/2020/RLGS/317

## FIRE SAFETY CERTIFICATE

Certified that St. Peters Jacobite Syrian Cathedral located at Plot no. 1 & 2, Bhai Veer Singh Marg, New Delhi comprised of Basement + Mezzanine + Ground + 02 upper floors owned /occupied by St. Peters Jacobite Syrian Cathedral was granted NOC by this department vide letter No.F6/DFS/MS/2000/399 dated 02/03/2000. The premises was reinspected by the officer concerned of this department on 05/08/2020 in the presence of Mr. Vergia and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Assembly Building with effect from ------19/08/2020 for period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010, printed below.

(Sunil Chawdhary) Dy. Chief Fire Officer Delhi Fire Service

Copy to:-

Mr. A.I. Varghese,

Secretary,

St. Peters Jacobite Syrian Cathedral,

Plot no. 1 & 2, Bhai Veer Singh Marg, New Delhi

Condition for the validity of fire safety certificate

1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.

2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of

an emergency.

8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

	INSPECTION	IREPORT
--	------------	---------

1. Name & address of the building : St. Peters Jacobite Syrian Cathedral located at Plot no. 1 & 2, Bhai Veer Singh Marg,

New Delhi

2. Type of occupancy : Assembly Building

Basement + Mezzanine + Ground + 02 Upper floor

3. Type of case:-

4. Details of previous NOC

:F6/DFS/MS/2000/399 dated 02/03/2000

5. Fire safety directives No.

: F6/DFS/MS/BP/98/265 dated 04/02/1998

6. Date of inspection:-

05/08/20

: Renewal

7. Name of the inspecting officer

: Sh. Rajinder Atwal (DO/CD) & Sh. M.K. Sharma ADO/CC

8. Name & designation of officer From the building side

: Mr. Vergia

9. Year of construction

: 1998

	year of construction	11.1.	1 24 07 20			
10.	Applicant's letter No	: email dated		Remarks		
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement as per BBL/NBC part IV	Provided at site	MR/NMR		
1.	Access to Building					
	1) Road width	09 mtr.	09 mtr.	MR		
	2) Gate width	05 mtr.	05 mtr.	MR		
	3)Width of internal road	NA	NA	NA		
2.	Number, Width Type & Arrangement of Exits					
2.	A. Number of staircases					
	1. Upper floors	02 No.	02 No.	MR		
	2. Basements	02 No.	02 No.	MR		
	B. Width of staircase					
	1. Upper floors	0.80 & 1.25 mtr.	0.80 & 1.25 mtr.	MR		
	2. Basements	0.80 & 1.25 mtr.	0.80 & 1.25 mtr.	MR		
	C. Protection of exits					
	1. Fire check door	NA	NA	NA		
	2. Pressurization	NA	NA	NA		
	D. No. of continuous	NA	NA	NA		
	staircase to terrace					
	E. Width of corridor	1.5 Mtr.	1.5 Mtr.	MR		
	F. Door size	1.5 Mtr.	2 Mtr.	MR		
3.	Compartmentation					
	1) Fire check door	NA NA		NA		
	2) Sealing of electrical shafts	NA	NA	NA		
	3) Fire rating of shaft door	NA	NA	NA		
	4) Water curtain	NA	NA	NΛ		
	5) Fire Dampers	NA	NA	NA		
4.	Smoke Management System					
	1) Basements	12 ACPH	Exhaust fan	MR		
	2) Upper floors	12 ACPH	Natural	MR		
5.	Fire Extinguishers					
	1) Total numbers	15	16	MR		
	2) Types	ABC & CO2 ABC &				
	3) ISI marking	Required	Provided	MR		
6.	First-Aid Hose Reel					
	1)Total number of each floor		NA	NA		
	2) Length of hose reel hose	NA	NA	NA		
	3) Nozzle diameter	NA	NA	NA .		

7.	Automatic Fire Detection &	Alarming Sy	stem	
	1) Type of detectors	NA	NA	NA
	2) Location of main panel	NA	NA	NA
	3) Location of repeater pane	l NA	NA	NA
	4) Alternate source of power	· NA	NA	NA
	5) Hooter's Location	NA	NA	NA
8.	MOEFA	NA	NA	
9.	Public Address System	NA	NA NA	NA
10.	Automatic Sprinkler System	1111	INA	NA
	1) Basement	NA	NA	1
	2) Upper floors	NA		NA
	3) Sprinkler above false	INA	NA	NA
	ceiling	NA	NA	NA
11.	Internal Hydrants			
	1) Size of riser/down-comer	1314		
	2) Number of hydrod	NA	NA	NA
	2) Number of hydrants per floor	NA	NA	NA
12.	3) Hose box each floor	NA	NA	NA
12.	Yard Hydrants			
	1) Total number of hydrants	NA	NA	NA
10	2) Hose box	NA	NA	NA
13.	Pumping Arrangement			
	1) Ground level			
	a) Discharge of main	27.4	NA	NA
	pump	NA	117	INA
	b) Head of main pump	NA	NA	NIA
	c) Number of main		NA	NA
	pump	NA	INA	NA
	d) Jockey pump out put		NIA	
	(2 Nos.)	NA	NA	NA
	e) Jockey pump head	NA		
			NA	NA
	J paring output	NA	NA	NA
	g) Stand by pump head h) Auto starting/Manual	NA	NA	NA
	, and a second	NA	NA	NA
	stopping			
	2) Terrace level			*
	a) Discharge of pump	NA	NA	NA
	b) Head of pump	NA	NA	NA
	c) Power supply	NA	NA	NA
	d) Auto starting of pump	NA	NA	NA
14.	Captive Water Storage for Fire	Fighting		1111
	1) Under ground tank		NA	NA
	capacity	NA		INA
	a) Draw-off connection	NA	NA	NA
	b) Fire service inlet	NA	NA	
	c) Access to tank	NA	NA NA	NA
	d) Over head tank	9		NA
	capacity	NA	NA	NA
15.	D . C.	Dogwing d	D '1 '	
16.	Provision of Lifts.	Required	Provided	MR
	a) Pressurization of lift	NA	NA	NA
	Shall	11/1		
	b) Pressurization of lift	NIA	NA	NA
	lobby	NA		1.7/1
	c) Communication in	NA		

m

N	2:	
1	11	

	lift car	27.4	NA	NA
	d) Fireman's switch	NA	NA	NA
17	e) Lift signage	NA	NA	NA
17.	Stand by Power Supply	NA		NA
18.	Refuge Area	NA	NA	
10.		NA	NA .	NA
	Total area location	1471		
19.	Fire Control Room		NA	NA
	a) Detector system	NA	INA	
	panel	214	NA	NA
	b) Flow switch panel	NA		NA
	c) PA system panel	NA	NA .	NA
	d) Battery backup	NA	NA	
		NA	NA	NA
	e) Building floor plan	INA	ion of special Risk if any:	NA
20.	Special Fire Protection Syste	em for Protect	Tion of special Risk, if any	

The fire protection systems provided in the building were randomly tested, checked and

found functional at the time of inspection. In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F6/DFS/MS/2000/399 dated 02/03/2000 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name :- Rajinder Atwal Designation :- DO (CD) Signature of the Inspecting Officer

Name: - M.K. Sharma 7 7 7 20 Designation :- ADO (CC)