FORM 'H': FORM FOR ISSUING FIRE SAFETY CERTIFICATE [See sub-rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F6/DFS/MS/2020/WZ/

Dated: 01 / 10 /2020

FIRE SAFETY CERTIFICATE

Certified that the Bindra Brothers located at Ground Floor, C-38-39, Rajdhani Market, Raghubir Nagar, New Delhi-110027 in a building comprising of Ground & 1st Floor only owned / occupied by Bindra Brothers, has already been issued FSC by this department vide letter No. No. F5/(5)/DFS/2009/227 dated 13.07.2009. The premises was re-inspected by the officer concerned of Fire Service on 23.09.2020 in the presence of Mr. Roshan (Manager) and found that building / premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building / premises is fit for occupancy class Storage of rectified spirit and Absolute Alcohol with effect from 1/2 0/2020 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010.

Issued on 01 10 2020 at New Delhi by.

(DHARAMPAL BHARDWAJ)
DY.CHIEF FIRE OFFICER.

Copy to :-

- 1. Authorized Signatory, Bindra Brothers, Ground Floor, C-38-39, Rajdhani Market, Raghubir Nagar, New Delhi-110027.
- 2. Assistant Commissioner, (M & TP) Govt. of NCT of Delhi, O/o Commissioner of Excise, L & N Block, Vikas Bhawan, New Delhi-110002.

Conditions for the validity of Fire Safety Certificate:

- 1. Fire Safety Certificate is valid for Ground Floor only.
- 2. All the fire safety arrangement provided their in shall be maintained in good working conditions at all times.
- 3. Loss of life or property due to non-functional fire safety measure shall be at the responsibility of the management.
- 4. The trained fire fighting staff should be available round the clock.
- 5. The Correct labeling of rectified Spirit & Absolute Alcohol be followed.
- 6. Any deviation with regard to the construction etc. shall be verified by the concerned building sanctioning agency.
- 7. This certificate cannot be treated in any case for regularizations of unauthorized construction.
 - 8. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The from is available on www.dfs.delhigovt.nic.in
- 9. "The owner / Occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, six months prior to its expiry".

INSPECTION REPORT

- 1. Name & address of the building: Bindra Brothers, C-38-39, Rajdhani Market, Raghubir Nagar, New Delhi-110027.
- 2. Type of Occupancy : Godown (Storage of rectified spirit and Absolute Alcohol)
- 3. Type of Case: Renewal (Bldg. is Ground & 1st Floor but storage is only on Ground Floor only)

4. Details of previous NOC : No.F5/(5)/DFS/2009/227 dated 13.07.2009

5. Fire Safety directives Letter No.: Nil

6. Date of inspection : 23/09/2020

7. Name of the Inspecting Officer: A.D.O. (Jwala Puri)

8. Name and designation of Officer

from the building side : Mr. Roshan (Manager)

| S | pplicant's letter received throu Minimum standards on fire | BBL | Provided at | Remarks |
|----|---|--|-------------|---------|
| No | prevention and fire safety U/R 33 | Requirements | site | MR/NMR |
| 1. | Access of building | | I | |
| | Road width | Accessible | Accessible | MR |
| | Gate width | Accessible | Accessible | MR |
| | Width of internal road | 1 NA | NA | NA |
| 2. | Number, width, Type & Arra | ngements of exits | | |
| | a. Number of staircases | | | |
| | Upper floors | N/A | N/A | N/A |
| | Basements | N/A | N/A | N/A |
| | b. Width of staircases | N/A | 8 | , to a |
| | Upper floors | N/A | N/A | N/A |
| | Basements | N/A | N/A | N/A |
| | c. Protection of exits | N/A | | |
| | Fire check door | N/A | N/A | N/A |
| | Pressurization | N/A | N/A | N/A |
| | d. No of continuous | N/A | N/A | N/A |
| | staircase to terrace | | | 2 |
| | e. Width Of Corridor | N/A | N/A | N/A |
| | f. Door Size | 1.00 mtr | 1.50 mtr | MR |
| 3. | Compartmentation | | | |
| | Fire check door | N/A | N/A | N/A |
| | Sealing of electrical shafts | N/A | N/A | N/A |
| | Fire Rating of shaft door | N/A | N/A | N/A |
| | Water Curtain | N/A | N/A | N/A |
| | Fire Dampers | N/A | N/A | N/A |
| 4. | Smoke managements System | | 3 | |
| | Basements | N/A | N/A | N/A |
| | Upper floors | N/A | N/A | N/A |
| 5. | Fire Extinguishers | * | | |
| | Total numbers | 3 | 6 | MR |
| | • Types | ISI marked ABC/CO ₂ /Mecha nical Foam | Provided | MR |
| | IS marking | Required | Provided | MR |

| | | | 11. | V | | | |
|-----|--|------------|-------|--|-----|------------|--|
| 6. | First – Aid Hose Reels | | 141 | | | | |
| | Total numbers on | N/A | | N/A | ı | N/A | |
| | each floor | | | | | | |
| | • Length of hose reel | N/A | | N/A | 1 | N/A | |
| | hose | 21/2 | | | | | |
| 7. | Nozzle diameter Automatic fire data di | N/A | | N/A | 1 | V/A | |
| /. | and distributed the state of th | | | | | | |
| | Type of detectorLocation of Main | N/A | | N/A | | N/A | |
| | Panel | N/A | | N/A | ı | N/A | |
| | Location of Repeater | N/A | | N/A | | 1/4 | |
| | Panel | N/A | | N/A | | N/A | |
| | Alternate source of | N/A | | N/A | | N/A N/A | |
| | power | , | , | | " | 1/14 | |
| | Hooters' Location | N/A | | N/A | | I/A | |
| 8. | MOEFA | N/A | | | | • | |
| 9. | Public Address System | N/A N/A | | N/A | | /IR | |
| 10. | Automatic Sprinkler System | IN/A | | N/A | IN. | I/A | |
| | Ground Floor | Required | | Provided | N | 1R | |
| | Upper Floor | N/A | | N/A | | I/A | |
| | Sprinkler above false | N/A | | N/A | | /A | |
| | ceiling | | | 1.77 | | // | |
| 11. | Internal Hydrants | | | | | | |
| | Size of riser/down- | N/A | | N/A | N | /A | |
| | comer | * | | , | | , | |
| | Number of hydrants | N/A | | N/A | N | /A | |
| | per floor | | | | | | |
| | Hose Box | N/A | | N/A | N | /A | |
| 12. | Yard Hydrants | | | | | | |
| | Total number of | N/A | | N/A | N | /A | |
| | hydrants | | | | | | |
| | Hose Box | N/A | | N/A | N, | /A | |
| 13. | Pumping Arrangements | | | | | | |
| • | Oloulia Bovel | | | | | n | |
| • | Bisenaige of main pump | N/A | | N/A | | /A | |
| | Head of main pump | N/A | | N/A | | /A | |
| | Number of main pumpsJockey pump out put | N/A | | N/A | | /A | |
| 7 | The part have | N/A | | N/A | N/ | | |
| > | J T T | N/A N/A | | N/A | N/ | | |
| > | J III P III | N/A | | N/A N/A | N/ | | |
| > | | N/A | | N/A | N/ | | |
| | stopping | 1,7,7 | | 11/7 | IN/ | ^ | |
| > | | N/A | | N/A | N/ | A | |
| • | Terrace level | | | | | | |
| > | Discharge of pump | 450 LPM | 450 l | -PM x 2 | - | MR | |
| > | | 40 MH | 40 M | The state of the s | | MR | |
| > | | Required | Provi | | | MR | |
| > | | Required | Provi | | | MR | |
| 14. | Captive water Storage for fire | | 1.001 | | | 17111 | |
| | Underground tank N/A N/A N/A | | | | A | | |
| | capacity | | | | | | |
| | Draw of connection | N/A | | N/A | N/A | | |
| | Fire service inlet | N/A | | N/A | N/ | 4 | |
| | Access to tank | N/A | | N/A | N/A | | |
| | Overhead Tank | 10,000 ltr | | 10,000 ltr | MF | | |

| | 15 | Exit Signage | N/A | N/A | N/A |
|---|-----------------|---|-----|-----|-------|
| | 16. | Provision of Lifts | | | |
| | | Pressurization of Lift Shaft | N/A | N/A | N/A |
| | | Pressurization of lift lobby | N/A | N/A | N/A |
| | | Communication in lift Car | N/A | N/A | N/A |
| | | Fireman's Grounding Switch | N/A | N/A | N/A |
| | | Lift Signage | N/A | N/A | N/A |
| | 17. | Standby power supply | N/A | N/A | N/A |
| | 18. Refuge Area | | N/A | N/A | |
| | | Total area | N/A | N/A | N/A |
| L | | Location | N/A | N/A | N/A |
| | 19. | Fire control room | | | |
| | | Detector system panel | N/A | N/A | N/A |
| | | Flow Switch Panel | N/A | N/A | N/A |
| | | PA System Panel | N/A | N/A | N/A |
| | | Battery backup | N/A | N/A | N/A |
| | | Building Floor Plans | N/A | N/A | N/A |
| | 20. | Special Fire Protection | N/A | N/A | N/A |
| | | Systems for Protection of | | e . | n - , |
| | | special Risks, if any; | | | |

Note:- Building comprised of Ground & 1st Floor only. Storage is done on Ground Floor only. 1st Floor is being used as rest room for the labours.

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection. MCB and Conduit Metal Wiring has also been provided.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter No. F5/(5)/DFS/2009/227 dated 13.07.2009 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Do (Ch D)

ADO (CHW) mention at C-4 Act

Signature of the Inspecting Officer

Name: Ashok Kumar Jaiswa

Designation: A.D.O. (Jwala Puri)

in this section. If greed, case may be considered.

Moreover the property of the Inspecting Officer

Name: Ashok Kumar Jaiswa

Designation: A.D.O. (Jwala Puri)

Moreover the Inspecting Officer

Name: Ashok Kumar Jaiswa

Designation: A.D.O. (Jwala Puri)

In this section. If greed, case may be considered.

Moreover the Inspecting Officer

Name: Ashok Kumar Jaiswa

Designation: A.D.O. (Jwala Puri)

: Ashok Kumar Jaiswal