## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No. F.6 DFS/MS/2020/SZ/ 395

Dated: 05 10 2020

## **FIRE SAFETY CERTIFICATE**

Certified that Prius Commercial Pvt. Ltd. Plot No.D-3 & P3B, Saket District Centre, Saket, New Delhi-110017 comprised of 3 tier basement, ground and five upper floors was granted FSC by this department vide letter No. F.6/DFS/MS/Mixed/SZ/2017 dated 20/09/2017. The said premises was re-inspected by officer concerned of this department on 25/09/2020 in presence of Mr. Makdoom Ahmed (Facility Manager) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of Delhi Fire Service Rule 2010 and that the building/premises is fit for Mixed Occupancy (Mercantile & Business) with effect from Service for a period of Three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire service Rules, 2010.

Issued on 05 10 2626 at New Delhi by

(Atul Garg) Director Delhi Fire Service

Copy to: -

- 1. The General Manager, Prius Commercial Pvt. Ltd. Plot No.D-3 & P3B,Saket District Centre, Saket, New Delhi-110017
- 2. The Jt. Director (Bldg.), DDA, Building Section, INA, Vikas Sadan, New Delhi.

## Conditions for the validity of Fire Safety Certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of firefighting system.
- 4. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

	INSF	PECTIO	N REPORT		
1	Name & Address of the Building  Prius Commercial Pvt. Ltd. Plot No.D-3 & P3B,S District Centre, Saket, New Delhi-110017				
2	Type of Occupancy	Class Mixed (E & F) (Mixed Occupancy (1)			Mercantile &
,	- Jr	Business)			
3	Building Comprised of	3 tier Basement, Ground and Five upper floors.			100
4	Type of Case	Renewal			
5	Details of Previous NOC	F.6/DF	S/MS/Mixed/SZ	Z/2017 dated 20/09/2017	
6	Fire Safety Directives Letter No	F6/MS/	DFS/BP/2006/198	363162 dated 07/08/2006	
7	Date of Inspection	25/09/2020			
8	Name of the Inspecting Officers	D.B. Mukherjee DO (SD)			
9	Name & Designation of Officers		Mr. Makdoom Ahmed (Facility Manager)		
	from the building side				
10	Year of construction	2007			
11	Applicant letter No.	Outdoo	or Diary No.7216	dated 11/09/2020	
S. No	Minimum standards on Fire		Old NOC Directives/Requirement  Provided at Site		Remarks
	Prevention and Fire Safety U/R 33	Directi			MR/NMR
1	Access to Building.			3	4
	Road width		9m	Provided	MR
	Gate width		N/A	Abuts on Road	-N/A-
	Gate width		14/11		-1V/A-
		N/A	3 sides road	MR	
	Width of internal road			(No Boundary)	
2	Number, width, type & arrangement of exits.				
	a) Number of Staircase				
	Upper floors		05Nos	Provided	MR -
		B-3 to	B-2	Provided	
		(05nos +	+1 ramp)		3
	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1				MR
	➢ Basement floor	B-2 to Ground (09 + 02 Ramp)			
		(09 + 02 Kamp)			
			T		4
81 4 1	Upper floors	1.5m	1.55m,1.50m,	1.50m,1.50m & 1.50m	MR
	6.9		B-3=1.55,1.77	,1.75,1.50 & 1.50m,1	
			ramp-7.13m		
		1.5m B-2 to Ground- 1.47,1.45,1.48,1.49,1.55,1.77,1.75 0 & 1.50m,02 ramp-7.13m & 0.80		-	MR -
	Basement floor				
	D. 4. (* C			1amp-7.13m & 0.00m	
	c) Protection of exits  Fire check door		D ! 1	D 111	MD
		Required		Provided	MR
	> Pressurization	Required		Provided	MR
	d) No. of continuous staircase to terrace	05nos		Provided	MR
	e) Width of corridor	1.5m		Provided	MR
	f) Door size	1 m		1m (Final Exit)	MR
3	Compartmentation.				
	• Fire check door.	Required		Provided	MR
	<ul> <li>Sealing of electrical shafts.</li> </ul>	Required		Provided	MR
	• Fire rating of shaft door.				211111111111111111111111111111111111111
	Water curtain	N/A		N/A	N/A
	• Fire dampers.	N/A		N/A	N/A
		Required Provided		Provided	MR

4.	Smoke Management system.			
	Basement	30 a/c per hour	Provided	MR /
	Upper floors	12 a/c per hour	Provided	MR /
5.	Fire Extinguishers.			
	Total numbers	109No 's	120Nos	MR ,
	• Types	ABC / Co2/W Co2	ABC/C02/WCo2	MR -
	ISI Marking	ISI Marked	Provided	MR -
6.	First Aid Hose Reels.	1		
0.	Total numbers on each floor.	B3-05nos,B2 & B1-	y 5	- 4
	Total named on each need.	09nos,Ground &	Provided	MR
		Upper Floors-03nos		
	Langth of hose real hose	30m	Provided	MR
	• Length of hose-reel hose.	5mm	Provided	MR
	Nozzle Diameter		riovided	IVIIX
7	Automatic fire detection & alarming syste	Smoke & Heat	Provided	MR
	Type of detectors  I agetion of Main Panel	Ground	1 <sup>st</sup> Basement	MR
	Location of Main Panel     Location of Reporter Panel	N/A	N/A	N/A
	Location of Repeater Panel     Alternate source of powers	Required	Provided	MR
	<ul><li>Alternate source of power</li><li>Hooter's location</li></ul>	Required	Provided	MR
8.	Hooter's location     MOEFA	Required	Provided	MR
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System	Required	Tiovided	IVIIX
IU.	Basement.	Required	Provided	MR
	• Upper floors	Required	Provided	MR
	<ul> <li>Sprinkler above false ceiling</li> </ul>	Required	Provided	MR
11.	Internal Hydrants.	xtoquilou	Tiovided	
11.	Size of Riser / Down-comer	100mm	Provided	MR
	Size of Risel / Down-come	B3 -05nos,B2 &	Tioriaca	1711
	Number of Hydrant per floor	B1-09nos,Ground	D 111	
	rumber of Hydrane per moor	& Upper Floors-	Provided	MR
	<ul> <li>Hose box.</li> </ul>	03nos		9
		B3 -05nos,B2 &		
		B1-09nos,Ground	Provided	MR
		& Upper Floors-	Tiovided	1111
-		03nos		
12.	Yard Hydrants.	06	D	MD
	Total number of hydrants.	06nos	Provided Provided	MR
4.0	Hose box.	06nos	Provided	MR
13.	Pumping arrangements.		·	, n
	Ground Level     Disabages of main nump	2280LPM	2280LPM	MR
	<ul><li>Discharge of main pump.</li><li>Head of main pump.</li></ul>	75m	75m	MR
	<ul><li>Head of main pump.</li><li>Number of main pumps.</li></ul>	Two	Two	MR
	<ul><li>Jockey Pump output.</li></ul>	180 LPM	180LPM	MR
	> Jockey Pump head.	75m	75m	MR
	<ul><li>Standby Pump output.</li></ul>	2280LPM	2280LPM	MR
	> Standby Pump head.	75m	75m	MR
	➤ Auto Starting/Manual stopping		Provided	MR /
	Pump house access.	Required	Provided	MR /
	Terrace Level	Acoquitou		
	<ul><li>Perrace Level</li><li>Discharge of pump.</li></ul>	-N/A-	N/A	-N/A-
	- LOUISING OF PHILIPS	4 11 4 5		

			DI/A	-N/A-	
	Power supply.	-N/A-	N/A		
	Auto starting of pump.	-N/A-	N/A	-N/A-	
14.	Captive water storage for firefighting.			) (D	-
	<ul> <li>Underground tank capacity.</li> </ul>	1,50,000liter	Provided	MR	_
	> Draw-off connection.	Required	Provided	MR	_
	Fire Service Inlet.	Required	Provided	MR	-
	Access to tank.	Required	Provided	MR	
	<ul> <li>Overhead tank capacity.</li> </ul>	20,000liter	Provided	MR	_
15.	Exit Signage.	Required	Provided	MR	-
16.	Provision of Lifts.				_
10.	Pressurization of lift shaft.	Required	Provided	MR	_
	Pressurization of lift lobby.	Required	Provided	MR	,
	• Communication in lift car.	Required	Provided	MR	
	• Fireman's switch.	Required	Provided	MR .	
	Lift signage.	Required	Provided	MR	•
17	Standby Power Supply	Required	Provided	MR	
18.	Refuge Area		and a conference of the second	5.	
10.	Total area	-N/A-	-N/A-	-N/A-	
	• Location	-N/A-	-N/A-	-N/A-	
9.	Fire Control Room.			MD	_
	Detector System Panel.	Required	Provided in basement	MR	-
	Flow Switch Panel.	Required	Provided in basement	MR	-
	<ul> <li>PA system Panel.</li> </ul>	Required	Provided in basement	MR	-
	Battery backup	Required	Provided in basement	MR	0
	Building floor plan	Required	Provided in basement	MR	_
20.	Special Fire Protection System for	Required	Co2 Flooding System	MR	
200	the Protection of special Risk, if any		Provided	я ,	_

The Fire protection systems provided in the premises were checked / operated at random and found functional at the time of inspection.

Keeping in view of the deemed substantial compliance of the minimum standards on fire prevention and fire safety required under the rules the FSC issued vide letter No. F.6/DFS/MS/Mixed/SZ/2017 dated 20/09/2017, renewal under rule37 of the Delhi Fire Service Rules, 2010 is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name

: D.B. Mukherjee

Designation: DO (SD)

DY.CFO (SZ)

29 P