GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/NDZ/2020/142

Dated:- 08 .10.2020

FIRE SAFETY CERTIFICATE

Connaught Place, New Delhi comprised of Ground + Mezzanine + 02 upper floor restaurant running at Ground floor only & Mezzanine floor store, owned /occupied by Punjab Grill, was granted FSC by this department vide letter No.F6/DFS/MS/EH/2017/NDZ/968 dated 07/07/17. The premises was re-inspected by the officer concerned of this department on 05/10/20 in the presence of Mr. Deepak Kumar (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Assembly Building Group D with effect from 100 100 for period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued on ... 08 10 20 20 at New Delhi by.

(Sunil Chawdhary)
Dy. Chief Fire Officer
Delhi Fire Officer

Copy to:-

- 1. The Deputy Commissioner (Licensing)

 1st Floor, Police Station Defence Colony, New Delhi......Online ID no. 2020071705754 dated 29/09/20.
- The Manager,
 Punjab Grill (A unit of Delhi Photo Company),
 78, Janpath, Connaught Place, New Delhi.

 Condition for the validity of fire safety certificate
 - 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
 - 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

9. Any flammable material for interior decoration is prohibited.

10. In column no. a.1 number of staircase have been marked 16 staircase occupier explain these are steps.

N/12

INSPECTION REPORT

1. Name & address of the building

2. Type of occupancy:-

3. Type of case:-

4. Details of previous FSC:-

5. Fire safety directives No.-

6. Date of inspection:-

7. Name of the inspecting officer:-

8. Name & designation of officer From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

Punjab Grill (A unit of Delhi Photo Company) at 78, Janpath, Connaught Place, New Delhi Assembly Building Group-D

Gr. + Mezzanine + 02 upper floor

Restaurant running at Ground floor only & Mezzanine floor store

Renewal

F6/DFS/MS/EH/2017/NDZ/968 dated 07/07/17

N/A

05/10/2020

Sh. Rajinder Atwal (DO/CD) &

Sh. Manoj Kumar Sharma (ADO/CC)

Sh. Deepak Kumar (Manager)

Old Heritage Bldg.

online application ID-2020090306633 dated 07/092020

| S.No. | Minimum Standards on fire Prevention and fire safety U/R 33 | Requirement/ existing fire safety arrangements | Provided at site | Remarks MR/NMR | | |
|-------|---|---|------------------|-------------------|--|--|
| 1. | Access to Building | | | | | |
| .,, | 1) Road width | 09 mtr. | 09 mtr. | MR | | |
| | 2) Gate width | N/A | N/A | N/A | | |
| | 3)Width of internal road | N/A | N/A | N/A | | |
| 2. | Number, Width Type & Arra | angement of Ex | its | | | |
| | A. Number of staircases | | | | | |
| | 1. Upper floors | Required | 02 | MR | | |
| | 2. Basements | N/A | N/A | N/A | | |
| | B. Width of staircase | | | | | |
| | 1. Upper floors | 1.3 mtr. | 1.3 mtr. | MR | | |
| | 2. Basements | N/A | N/A | N/A | | |
| | C. Protection of exits | | | - | | |
| | 1. Fire check door | N/A | N/A | N/A | | |
| | 2. Pressurization | N/A | N/A | N/A | | |
| | D. No. of continuous | Required | 01 | MR | | |
| | staircase to terrace | 1 | | | | |
| | E. Width of corridor | N/A | N/A | N/A | | |
| | F. Door size | 1.06 mtr. x 2 mtr. | 1.16 mtr. x 2 | MR | | |
| 3. | Compartmentation | | | | | |
| | 1) Fire check door | N/A | N/A | N/A | | |
| | 2) Sealing of electrical shafts | N/A | N/A | N/A | | |
| | 3) Fire rating of shaft door | N/A | N/A | N/A | | |
| | 4) Water curtain | N/A | N/A | N/A | | |
| | 5) Fire Dampers | N/A | N/A | N/A | | |
| 4. | Smoke Management System | | | | | |
| 7. | 1) Basements | 12 ACPH | N/A | N/A | | |
| | 2) Upper floors | 12 a/c per hour | Exhaust fan | MR | | |
| 5. | Fire Extinguishers | | | | | |
| | 1) Total numbers | 10 Nos. | 10 Nos. | MR | | |
| | 2) Types | ABC & CO2 | ABC & CO2 | MR | | |
| | 3) ISI marking | Required | Provided | MR | | |
| 6. | First-Aid Hose Reel | | | | | |
| | 1) Total number of eachfloor | 01 | 01 | MR | | |
| | 2) Length of hose reel hose | 30 mtr. | 30 mtr. | MR | | |

11/13

| | 3) Nozzle diameter | 05 mn | 1 (|)5 mm | MR |
|-----|-----------------------------------|---------------------------|----------------------|---------------|-------|
| | Automatic Fire Detection & A | Alarmi | ng System | 1 | |
| | 1) Type of detectors | N/A |] | N/A | . N/A |
| | 2) Location of main panel | N/A |] | N/A | N/A |
| | 3) Location of repeater panel | N/A | | N/A | N/A |
| | 4) Alternate governo of power | N/A | | N/A | N/A |
| | 4) Alternate source of power | N/A | | N/A | N/A |
| | 5) Hooter's Location | | | Provided | MR |
| 3. | MOEFA | Requi | 100 | N/A | N/A |
| 9. | Public Address System | N/A | | IN/A | 14/11 |
| 10. | Automatic Sprinkler System | /- | | DT/A | N/A |
| | 1) Basement | N/A | | N/A | MR |
| | 2) Upper floors | Requi | | Provided | N/A |
| | 3) Sprinkler above false | N/A | | N/A | IN/A |
| | ceiling | | | | |
| 11. | Internal Hydrants | | | 8 | 37/4 |
| 11. | 1) Size of riser/down-comer | N/A | | N/A | N/A |
| | 2) Number of hydrants per | N/A | | N/A | N/A |
| | floor | | | | |
| | 3) Hose box | N/A | | N/A | N/A |
| 12 | Yard Hydrants | | | | |
| 12. | 1) Total number of hydrants | N/A | | N/A | N/A |
| | | N/A | | N/A | N/A |
| | 2) Hose box | 14/11 | * * | | |
| 13. | Pumping Arrangement | DT/A | | N/A | N/A |
| | 1) Ground level | N/A | | N/A | N/A |
| | a) Discharge of main | N/A | | IN/A | 1072 |
| | pump | 27/4 | | DI/A | N/A |
| | b) Head of main pump | N/A | | N/A | N/A |
| | c) Number of main | N/A | | N/A | IN/A |
| | pump | | | | DI/A |
| | d) Jockey pump out put | N/A | | N/A | N/A |
| | e) Jockey pump head | N/A | 1 | N/A | N/A |
| | f) Stand by pump outpu | t N/A | 1 | N/A | N/A |
| | g) Stand by pump head | N/A | A | N/A | N/A |
| | h) Auto starting/Manual | N/A | A | N/A | N/A |
| | stopping | | | 8 | (4) |
| | 2) Terrace level | | | | |
| | | Rec | quired | 450 & 180 LPM | MR |
| | | | quired | 30 mtr. | MR |
| | b) Head of pump | | | Provided | MR |
| | c) Power supply | Required Required | | Provided | MR |
| | d) Auto starting of pum | | | | |
| 14. | Captive Water Storage for | Fire F | Ignung | N/A | N/A |
| | 1) Under ground tank | | N/A | 11/71 | 11/12 |
| | capacity | | 27/4 | DI/A | N/A |
| | a) Draw-off connection | L | N/A | N/A | MR |
| | b) Fire service inlet | | Required Required | | |
| | c) Access to tank | c) Access to tank | | Provided | MR |
| | d) Over head tank capacity | | 5,000 ltr | | MR |
| 15. | Exit Signage. | - | Required | l Provided | MR |
| | Provision of Lifts. | | | | |
| 16. | Clift alsoft | | N/A | N/A | N/A |
| | a) Pressurization of lift shaft | | | N/A | N/A |
| | b) Pressurization of lift lobby | | N/A N/A | N/A N/A | N/A |
| | | Communication in lift car | | | N/A |
| | d) Fireman's switch | | N/A | N/A | N/A |
| | e) Lift signage | | N/A | N/A | INA |

7114

| 17. | Stand by Power Supply | N/A | N/A | NI/A |
|-----|--|-----|-----|------|
| 18. | Refuge Area | N/A | N/A | N/A |
| | 3 | | | N/A |
| | Total area location | N/A | N/A | N/A |
| 19. | Fire Control Room | N/A | N/A | N/A |
| | a) Detector system panel | N/A | N/A | N/A |
| | b) Flow switch panel | N/A | N/A | N/A |
| | c) PA system panel | N/A | N/A | N/A |
| | d) Battery backup | N/A | N/A | N/A |
| | e) Building floor plan | N/A | N/A | N/A |
| 20. | Special Fire Protection System Risk, if any: | N/A | | |

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/EH/2017/NDZ/968 dated 07/07/17 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name :- Rajinder Atwal Designation :- DO (CD)

Signature of the Inspecting Officer

Name: - M.K. Sharma
Designation: - ADO (CC)

Sycho (moz)