GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE **NEW DELHI- 110001**

No.F.6/DFS/MS/School/2020/NDZ/434

Dated: 20/10/2020

FIRE SAFETY CERTIFICATE

Certified that the East Delhi Public School, Janta, Garden, F- Block Pandav Nagar, Delhi-91, comprised of ground plus three upper floor owned/occupied by East Delhi Public Schoolhave complied with the fire prevention and fire safety requirements in accordance with the NBC Part-IV and verified by the officer concerned of this department on 09/09/2020 in the presence of Sh.B.P.Singh (Manager) of the school and found that the school building is fit for occupancy class B 'Educational Building' for with effect from . 🔑 പ്രവിശ് 🎎 for a period of **three** years in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010, printed overleaf

Issued on 30 10 20 30 at New Delhi by

Delhi Fire Service

To

The Principal, East Delhi Public School. Janta, Garden, F- Block Pandav Nagar, Delhi-91.

Copy to:-

1 The Director of Education, EDMC Plot No. 419, UdyogSadan, Patparganj Industrial Area, Delhi-92.

- Conditions -

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in good working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc. may be got verified from the authorities concerned.
- 5. This Fire Safety certificate can not be treated in any case for regularizations of unauthorized construction if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 7."The owner /occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form'J'[sub rule(1) of rule 37] along with a copy of this certificate, six months prior to its expiry"

1. Name & address of the building : East Delhi Public School, Janta, Garden, F-

Block Pandav Nagar, Delhi-91.

2. Building is comprised of : Ground +3 upper floors

: Educational 3. Type of Occupancy

: Addition/alteration 4. Type of Case

: F6/MS/DFS/2005/1160 Dated 03/06/2005 Details of Previous NOC

6. Fire Safety direction letter No : NBC Part IV

: 09/09/2020 7. Date of Inspection

8. Name of the Inspecting Officers: : ADO R.K. Yadav

9. Name of the designation of Officer

: Sh. B.P. Singh (Manager) from the building side

: 2005 & 2015 10. Year of Construction

11.	Applicant's letter No. : I	Nil dated 02/09/2	020				
S.	Minimum Standards on fire safety	y NBC	Provided at	Remarks			
N.	requirements as per	Requirement	Site	MR/NMR			
1.	Access to building						
	Road width	06m	06 m	MR			
	Gate width	4.5 m	4.5 m	MR			
	Width of internal road	N.A	N.A	N.A			
2.	Number, Width, Type and Arrangement of Exits						
	a. Number of Staircases						
	 Upper Floor 	2 nos.	02 nos	MR			
	Basement	N.A	N.A	N.A			
	b. Width of Staircases		0.445	MD Old sees			
	Upper Floor	1.5 m &.75 M	1.5 m & 1.15 m	MR Old case			
	Basement C. Protection of exits	N.A	N.A	N.A			
	Fire check door	N.A	N.A	N.A			
	Pressurization	N.A	N.A	N.A			
	d. No. of continuous staircases to	1 No.	1 No.	MR			
	terrace	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1					
	e. Width of Corridor	1.5 m	1.5 m	MR MR			
	f. Door Size	1 m	n 1 m				
3.	Compartmentation.						
	Fire check door	N.A	N.A	N.A			
	Sealing of electrical shafts	N.A	N.A	N.A			
	Fire rating of shaft door	N.A	N.A	N.A			
	Water curtain	N.A	N.A	N.A			
	Fire Dampers	N.A	N.A	N.A			
4.	Smoke Management System.						
	Basement	N.A	N.A	N.A			
	Upper floor	N.A	N.A	N.A			
5.	Fire Extinguisher						
	Total numbers	08 nos.	08nos.	MR			
	Types	CO ₂ & ABC	CO ₂ & ABC	MR			
	ISI marking	ISI marked	ISI marked	MR			

	· f cook floor			Dro	/ided	MF	ζ	
	I numbers of each floor	01 n		30 r	71404	MR		
	gth of hose reel hose	30 m		5 m	11	MF		
	zle diameter	5 mr		5 111	111			
		ning sy	stem.	NI A		N	A	
		1000				N.A		
Location of main panel								
Loca	ation of repeater panel							
1		N.A		10 2000000				
Hoo	oters	N.A						
MO	FFA	N.A	0	N.A	\		N.A	
		N.A		N.A	\	N.A		
Aut	omatic Sprinkler System.							
					4	N.A		
		N.A	\	N.A	A			
spr	inkler above false ceiling	N.A	1	N.A	4	N	.Α	
		N.A	N.A N		.Α		N.A	
				N.	Ą	N	.Α	
		N.A	4	N.	A	N	I.A	
			4	N.A		N.A		
1		N.	A	N.	A	1	1.A	
		N.	N.A N.A				N.A	
				N.A		N.A		
1				N.A			N.A	
	Number of main pumps			N.A			N.A	
		1		N.A			N.A	
				N.A			N.A	
	Standby pump out put			N.A			N.A	
				N.A			N.A	
				N.A			N.A	
	stopping			NA			N.A	
>	- A	IN		1 1.7	•			
•	Terrace Level	1	50 I PM	450	LPM		MR	
>							MR	
>			The state of the s				MR	
>							MR	
>	Auto Starting of pump		•					
4	Captive Water Storage for Fi	re Figh	nting.		ΝΔ		N.A	
							N.A	
	130000000000000000000000000000000000000	3					N.A	
All Accounts							N.A	
	Access to tank							
		711	10,000 L	trs	10,000 ltrs		MR	
	block Exit Signage.		Require	ed.	Provided		MR	
	Type Loca Loca Alte Hoo MO Puk Aut bas upp spr Inte siz Nu Ho Ya To Ho Pu	Type of detectors Location of main panel Location of repeater panel Alternate source of power Hooters MOEFA Public address System. Automatic Sprinkler System. basement upper floor sprinkler above false ceiling Internal Hydrants size of riser/down-comer Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. Ground Level bischarge of main Pump head of Main Pump humber of main pumps Jockey pump out put Jockey pump out put Standby pump Head Standby pump Head Auto Starting /Manual stopping Pump House Access Terrace Level Discharge of pump Head of the Pump Power supply Auto Starting of pump Head of the Pump Captive Water Storage for Fi Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity each	Type of detectors Location of main panel Location of repeater panel Alternate source of power Hooters MOEFA Public address System. Automatic Sprinkler System. basement upper floor sprinkler above false ceiling Internal Hydrants size of riser/down-comer Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. Ground Level Discharge of main Pump Head of Main Pump Number of main pumps Jockey pump out put Jockey pump out put Standby pump Head Number of main pumps Auto Starting /Manual stopping Pump House Access Terrace Level Discharge of pump Head of the Pump Power supply Auto Starting of pump 4 Captive Water Storage for Fire Fight Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity each	Location of main panel Location of repeater panel Alternate source of power Hooters MOEFA Public address System. Automatic Sprinkler System. basement upper floor sprinkler above false ceiling Internal Hydrants size of riser/down-comer Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. Ground Level Discharge of main Pump Head of Main Pump Head of Main Pump Number of main pumps Jockey pump out put Jockey pump out put Standby pump out put Standby pump Head Auto Starting /Manual stopping Pump House Access Terrace Level Discharge of pump Head of the Pump Power supply Auto Starting of pump 4 Captive Water Storage for Fire Fighting. Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity each	Type of detectors Location of main panel Location of repeater panel Alternate source of power Hooters MOEFA Public address System. Automatic Sprinkler System. basement upper floor sprinkler above false ceiling Internal Hydrants size of riser/down-comer Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. Ground Level Discharge of main Pump Head of Main Pump Head of Main Pump Number of main pumps Jockey pump out put Standby pump out put Standby pump Head Auto Starting /Manual stopping Pump House Access Terrace Level Discharge of pump Head of the Pump Power supply Auto Starting of pump 4 Captive Water Storage for Fire Fighting. N.A N.A N.A N.A N.A N.A N.A N.A N.A N	Type of detectors Location of main panel Location of repeater panel Alternate source of power Hooters MOEFA Public address System. Automatic Sprinkler System. basement upper floor sprinkler above false ceiling Internal Hydrants size of riser/down-comer Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. Ground Level Discharge of main Pump Head N.A	Type of detectors Location of main panel Location of repeater panel Alternate source of power Hooters M.A. N.A. N.A. N.A. N.A. N.A. N.A. N.A.	

16	Provision of Lifts.		1.1.0	NI A		
	Pressurization of Lift Shaft	N.A	N.A	N.A		
	Pressurization of Lift lobby	N.A	N.A	N.A		
	Communication in lift car	N.A	N.A	N.A		
	Firemen's grounding switch	N.A	N.A	N.A		
	Lift Signage	N.A	N.A	N.A		
17	Standby power supply	N.A	N.A	N.A		
18	Refuge Area.					
	Total area	N.A	N.A	N.A		
	Location	N.A	N.A	N.A		
19	Fire Control Room					
	Detector system panel	N.A	N.A	N.A		
	Flow switch panel	N.A	N.A	N.A		
	PA system panel	N.A	N.A	N.A		
	Batter backup	N.A	N.A	N.A		
	Building Floor Plans	N.A	N.A	N.A		
20	Special Fire Protection systems for protection of special Risks, if any:	N.A	N.A	N.A		

The fire protection systems provided in the building were tested/checked and found functional at the time of inspection.

Keeping in view the compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under the rule 35 of the Delhi Fire Service Rule 2010.

> Signature of the Inspecting Office 3 2000 Name:- R. K. Yadav

Designation:- ADO (LN)