Frequent hand sanitization-wearing of face mask-keep physical distance to prevent from Covid-19

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE **NEW DELHI-110 001.**

No.F.6/DFS/MS/School/2020/SZ / 47 3

Dated: 511 1020

FIRE SAFETY CERTIFICATE

Certified that the Oxford Sr. Secondary School, E-Block, Vikaspuri, New Delhi-110018, comprised of two basements, ground floor plus three upper floors having total 113 rooms (Including Class Rooms, Offices, Sci. Lab, Comp. Lab, Library & Sports Room etc.) owned/occupied by Oxford Sr. was issued Fire Safety Certificate by this department vide letter School F.6/DFS/MS/School/2017/SZ/1100 dated 26.07.2017. The School building was re-inspected by the officer concerned of this department on 29.10.2020 in the presence of Sh. Suraj Prabhakar (Manager) and found that the Oxford Sr. Secondary School have deemed complied the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class "Educational" for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed as below.

Issued on st New Delhi.

(SUNIL CHOWDHARY) Dy. CHIEF FIRE OFFICER SOUTH ZONE

Copy to:-

- The Manager, 1. Oxford Sr. Secondary School, E-Block, Vikaspuri, New Delhi-110018
- 2. Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi-110054.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at
- 2. The means of escape shall be kept unlocked and unobstructed for unhindered evacuation of occupants in case of emergency.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- Basement shall be used as per the building bye laws.
- The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

INSPECTION REPORT Oxford Sr. Secondary School, E-Block, Vikaspuri, New Delhi-18. Name & address of the building: 2. Type of Occupancy Educational Type of Case 3. Renewal Details of Previous NOC F.6/DFS/MS/School/2017/SZ/1100 dated 26.07.2017 Fire Safety directives letter No N/A Date of inspection 29.10.2020 Name of Inspecting Officer A.D.O. Sandeep Duggal Name and designation of officers From the building side Sh. Suraj Prabhakar (Manager) 9. Year of Construction 1994-95 email letter dated 08.10.2020 & Form "J" & "K" 10. Applicant's letter No. NBC/BBL S. No. Minimum Standards on fire prevention and Provided at Remarks Requirement MR/NMR site fire safety U/R 33 1. Access to building Accessible 6 mtrs Road width 12 mtrs MR MR, being old case 4.5 mtrs 04 & 04 mtrs Gate width N/A N/A N/A Width of internal road Number, Width, Type & Arrangement of Exits 2. a. Number of staircases Upper Floors MR 04 No's 04 No's **Basements** 04 No's 04 No's MR b. Width of staircases MR, being old 150 cms 180, 180, 180 Upper Floor & 133 cms case MR, being old 150 cms 160 & 157 cms, **Basements** 190 & 75 cms case c. Protection of exits Fire check door N/A N/A N/A Pressurization N/A N/A N/A d. No. of continuous staircases to terrace MR Three Required Width of Corridor MR 240 & 250 cms 150 cms MR Door Size 100 cms 112 cms f. 3. Compartmentation N/A N/A N/A Fire check door Sealing of electrical shafts N/A N/A N/A Fire Rating of shaft door N/A N/A N/A Water Curtain N/A N/A N/A Fire Dampers N/A N/A N/A **Smoke Management System** 4. MR Required Exhaust fans Basements are provided MR Natural Required Upper floors ventilation Fire Extinguishers 5. MR Provided 25 no.'s Total numbers ABC/CO₂ type Provided MR Types MR ISI marked ISI marked IS marking **First-Aid Hose Reels** 6. 03 no.'s Provided MR Total numbers on each floor Provided MR 30 mtrs Length of hose reel hose Nozzle diameter 5 mm Provided MR

rised of two separate Basements,

| 7. | Automatic fire detection and alarming system | Ty No. | | |
|-----|--|----------|-----------------------|--------------------|
| | Type of detectors | N/A | N/A | N/A |
| | Location of Main Panel | N/A | N/A | N/A |
| | Location of Repeater Panel | N/A | N/A | N/A |
| | Alternate source of power | N/A | N/A | N/A |
| | Hooters' Location | N/A | N/A | N/A |
| 8. | MOEFA | N/A | N/A | N/A |
| 9. | Public Address System | N/A | Provided | N/A |
| 10. | Automatic Sprinkler System | 1 | | |
| | • Basement | Required | Provided | MR |
| | Ground Floor | N/A | N/A | N/A |
| | Sprinkler above false ceiling | · N/A | N/A | N/A |
| 11. | Internal Hydrants | | | |
| | Size of riser/down-comer | N/A | 100 mm | N/A |
| | Number of hydrants per floor | N/A | Three | N/A |
| | Hose Box | N/A | Three | N/A |
| 12. | Yard Hydrants | | | |
| | Total number of hydrants | N/A | N/A | N/A |
| | Hose Box | N/A | N/A | N/A |
| 13. | Pumping Arrangements | | | |
| | Ground Level | | | |
| | Discharge of main Pump | N/A | N/A | N/A |
| | Head of Main pump | N/A | N/A | N/A |
| | Number of main pumps | N/A | N/A | N/A |
| | > Jockey Pump out put | N/A | N/A | N/A |
| | > Jockey pump head | | | |
| | Standby Pump out putStandby Pump Head | N/A | N/A | N/A |
| | > Auto Starting/Manual Stopping | N/A | N/A | N/A |
| | Auto Starting Manual Stopping | N/A | N/A | ·N/A |
| | | N/A | N/A | N/A |
| | | N/A | N/A | N/A |
| | > Pump House Access | | | |
| | • Terrace level | Old case | 450 LPM & 180 | MR, being old case |
| | Discharge of pump | | LPM provided | |
| | Head of the pumpPower Supply | 40 mtrs | Provided | MR |
| | > Auto Starting of pump | Required | Provided | MR |
| | , ratio starting or pump | N/A | N/A | N/A |
| 1.4 | Continue State Change Continue | | | |
| 14. | Captive Water Storage for fire fighting | 27/4 | 50,000 1 | NI/A |
| | Underground tank capacity | N/A | 50,000 ltrs | N/A |
| | Draw-off connectionFire service inlet | N/A | N/A | N/A |
| | Access to tank | N/A | Provided | N/A |
| | Overhead Tank capacity | N/A | Provided | N/A |
| | Overhead Talik capacity | Old case | 5000 ltrs Provided | MR, being old case |
| 15. | Exit Signage. | Required | Provided | MR |
| , | D 11 0 0 10 | * | | NT T OF |
| 16. | Provision of Lifts. | Th.T / A | NT/A | No Lift |
| | Pressurization of Lift Shaft Pressurientian of Lift Johnson | N/A | N/A | N/A |
| | Pressurization of Lift lobby Communication In lift Com | N/A | N/A | N/A |
| | Communication In lift Car Fireman's Grounding Switch | N/A | N/A | N/A |
| | • Fireman's Grounding Switch | N/A | N/A | N/A |
| | Lift Signage | N/A | N/A | N/A |
| 17. | Standby power supply | N/A | Provided | N/A |
| 18. | Refuge Area. | | | • |
| | > Total Area | N/A | N/A | N/A |
| | 1000111100 | 11/11 | 11/11 | 1411 |

2/13

| 19. | Fire Control Room | | | |
|-----|---|-----|-----|-------|
| | Detector System Panel | N/A | N/A | N/A |
| | Flow Switch Panel | N/A | N/A | N/A |
| | PA System Panel | N/A | N/A | N/A |
| | Battery backup | N/A | N/A | . N/A |
| | Building Floor Plans | N/A | N/A | N/A |
| 20. | Special Fire Protection System for Protection of special Risks, if any: | N/A | N/A | N/A |

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the Fire Safety Certificate issued vide letter number <u>F.6/DFS/MS/School/2017/SZ/1100</u> dated <u>26.07.2017</u> renewal under rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Signature of Inspecting Officer

Name: - Sandeep Duggal

Designation:- Asstt. Divisional Officer

D.O. (South West)

D.O. (South West)

F. J. Ir least

A DD Candel A)

F. J. Ir least

F. J. Ir least

A DD Candel A)

Dyero(82)

Dyero(82)

Dyero(82)