FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F.6/DFS/MS/SZ/2020 / 1 6 7

Dated 27/11/2020

FIRE SAFETY CERTIFICATE

Certified that M/s Haldiram Products Pvt. Ltd, Located at 4B/16,GF,FF&SF, Najafgarh Road, Tilak Nagar, New Delhi-110018 in a building comprised of B,G &2 UF was issued FSC vide Letter No. F6/DFS/MS/2018/EH/SZ/421 dated 15-03-2018. The premises was re inspected by the officers concerned of this department on 19-11-2020 in the presence of Mr. Sunil Kumar) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Assembly" Group D (At ground, 1st & 2nd Floors only) with effect from 27/11/2020 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on In at New Delhi by.

Sunil Choudhary
Dy Chief Fire Officer
Delhi Fire Service

Copy to:

- 1. The Addl. Commissioner of Police (Lic), 1st Floor, Licensing Unit, Police Station, Defence Colony, New Delhi.
- 2. M/s Haldiram Products Pvt. Ltd, Located at 4B/16, Najafgarh Road, Tilak Nagar, New Delhi-

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- **6.** The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

1. .Name & address of the building: M/s Haldiram Products Pvt. Ltd, Located at

2. 4B/16, Najafgarh Road, Tilak Nagar, New Delhi-110018

3. Type of Occupancy: Group D – Assembly (Building) The building comprised of Basement+G+2 Upper Floor & Restaurant Running at Ground & 2upper Floors only)

4. Type of Case

: Renewal

5. Details of previous NOC

: F6/DFS/MS/2018/EH/SZ/421 dated 15-03-

2018

6. Fire Safety directives Letter No.: Nil

7. Date of inspection

: 19-11-2020

8. Name of the Inspecting Officer: ADO (DWK)

9. Name and designation of Officer

a. from the building side

: Mr. Sunil Kumar (Shift Manager)

10. Year of Construction

: 2005

11. Applicant's letter No.

: 2020102708069 dated 28/102020

No	prever	num standards on fire ntion and fire safety U/R 33	I DELLE OF DEL	Provided at site	Rema	rks MR/NMR	
1.	Access	s of building	Noting N/12 -14.				
	•	Road width	Accessible(09mtrs)	10			
	•	Gate width	06mtr	12mtrs		MR	
			Odiffi	Directly accessible from road		MR	
	•	Width of internal road	NA	NA		NIA	
	Numbe	r, width, Type & Arrangem	ents of oxita		ă	NA	
	a.	Number of staircases	chts of exits				
		Upper floors	2	0.0			
		Basements	NA	02	MR		
			IVA	1	NA, re	staurant running at	
	b.	Width of staircases			GF, FF	&SF	
	•	Upper floors	1.5 & 1 mtrs	150.0			
	•]	Basements	NA NA	153 & 104 cms		IR (Old Case)	
	c. I	Protection of exits	1471	NA	NA		
	• I	ire check door	Required	*			
		Pressurization	NA	Provided	MR		
		No of continuous staircase	Required	NA	NA		
	to	o terrace	required	One	MR		
		Vidth Of Corridor	1.5mtr	0 : : :	0	, t	
	f. Door Size	00	Opening in hall		MR		
			· · · · · · · · · · · · · · · · · · ·	Provided	MR ((old case)	

3.	Compartmentation		1				
	Fire check door	NA	NA	NA			
		NA	NA	NA	-		
	 Sealing of electrical shafts 	NA	NA	NA			
	 Fire Rating of shaft door 						
	 Water Curtain 	NA	NA	NA			
	 Fire Dampers 	NA	NA	NA			
4.	Smoke managements System						
	Basements	Required	Provided	MR	4		
	 Upper floors 	Required	Natural	MR			
	**		ventilation	. «			
5.	Fire Extinguishers	• 1					
0	 Total numbers 	03no's/floor	Provided	MR			
	• Types	ABC & CO ₂	Provided	MR			
	 IS marking 						
	The state of the s	ISI marked	ISI marked	MR	8		
6.	First – Aid Hose Reels						
	 Total numbers on each 	1	Provided	MR			
	floor		D 11 1	7.00			
	 Length of hose reel hose 	30 m	Provided	MR			
	 Nozzle diameter 	5 mm	Provided	MR	-		
7.	Automatic fire detection and alarmi	, = -					
	 Type of detectors 	Smoke& Heat	Provided	MR			
	 Location of Main Panel 	Required	Basement	MR			
	 Location of Repeater Panel 	NA	NA	NA			
	 Alternate source of power 	Required	Provided	MR	X:		
	Hooters' Location	Required	Near exit	MR			
8.	MOEFA	Required	Provided	MR			
9.	Public Address System	Required	Provided	MR	2		
10.	Automatic Sprinkler System						
10.	Basements	Required	Provided	MR			
	Upper Floor	Required	Provided	MR	-		
	Sprinkler above false	NA	NA	NA	2 6		
	ceiling						
11.	Internal Hydrants:	1			ū.		
	Size of riser/down- comer	100mm	Provided	MR			
	Number of hydrants per	01No's	Provided	MR			
	floor	01110 5	110 (1000)				
	Hose Box	01No's	Provided	MR			
12.	Yard Hydrants		Sup 29 9 9 9 9 90				
12.	Total number of hydrants	NA	NA	NA			
	Hose Box						
	Tiose Box	NA	NA	NA			
			.				
			* •				
		e e					
	*			e e			
	,						

13.	Pump	ing Arrangements:			
	•	Ground Level			
	•	Discharge of main pump	NA	NIA	
	>	Head of main pump	NA	NA	NA
	>	Number of main pumps	NA	NA	NA
	>	Jockey pump out put	NA	NA	NA
	>	Jockey pump head	Table (State of State	NA	NA
	>	Standby Pump out put	NA	NA	NA
	>	Standby Pump Head	NA	NA	NA
	>	Auto Staring/Manual	NA	NA	NA
		stopping	NA	NA	NA
	>	Pump House Access	NIA	27.1	*
	•	Terrace level	NA	NA	NA
	>	Discharge of pump	0001		-
	~	Head of the pump	900lpm	Provided	MR
		Power supply	40 mtrs	Provided	MR
	>	Auto starting of pump	Required	Provided	MR
14.	Cantin		Required	Provided	MR
14.		e water Storage for fire fight			
	•	Under ground tank	NA	NA	NA
		capacity			* a*
	1	Draw off connection	NA	NA	NA
		Fire service inlet	NA	NA	NA
	>	Access to tank	NA	NA	MR
	•	Overhead Tank capacity	10000ltrs	Provided	MR
15	Exit Si		Required	Provided	MR
16.	Provisi	on of Lifts			
		Pressurization of Lift Shaft	NA	NA	NA
=	>	Pressurization of lift lobby	NA	NA	NA
		Communication in lift Car	NA	NA	NA
	~	Fireman's Grounding	NA	NA	NA
		Switch			1121
		Lift Signage	NA	NA	NA
17.	Standby	y power supply	Required	Provided	MR
18.	Refuge	Area	1	Trovided	IVIIC
	>	Total area	NA .	NA	NA
		Location	NA	NA	NA NA
19.	Fire cor	itrol room		1471	INA
	>	Detector system panel	NA	NA	NA
		Flow Switch Panel	NA	NA	
		PA System Panel	NA		NA
		Battery backup	NA	NA	NA
		Building Floor Plans	NA	NA	NA
		g rieer rams	NA ·	NA	NA
				¥ *	
				15.	
		10 miles			"

20. Special Fire Protection Systems	NA	NA	NA
for Protection of special Risks, if			
any;	*		
The fire protection systems provided found functional at the time of inspection. In view of the deemed compliance fire safety as required under the F6/DFS/MS/2018/EH/421 dated 15/03/2 Service Rules 2010 is recommended. Signature of the Inspecting Officer Name Was Vita Complete Designation ALO/Dwx	. e of minimum standard rules the NOC is	ds on fire prevent ssued vide lett le 35 of the De	tion and
Dycrole2 A DO			
Descrots 2	18 put op		t ble