FORM 'H' FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No.F6/DFS/MS/2020/ 506

8 37

Dated: 07/12/2020

FIRE SAFETY CERTIFICATE

Certified that the Residential Blocks No. 03, 07, 08 & 09 [(04 Nos) excluding basement] Type-IV Quarters, GPRA Complex, Kidwai Nagar (East), New Delhi-110023, comprised of 3 Tier Basement, Ground Floor + 14 Upper Floors (All 04 Blocks) owned / occupied by NBCC (India) Limited, have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and verified by the officers concerned of this department on 01/12/2020 in the presence of Mr. Mahabir Singh (DGM) and found that the building / premises is fit for the occupancy class "Residential" (Group-A) with effect from .0.7./12./2020. for a period of five years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 07/12/3030 at New Delhi by.

Copy to:-

Delhi Fire Service

- 1. Sh. A.K. Sharma, CGM (Engg.), Project Office: Redevelopment of Kidwai Nagar (East), Ground Floor, Office Block No.-4, Along Ring Road, East Kidwai Nagar, New Delhi-110023.
- 2. The Executive Engineer (Bldg.), New Delhi Municipal Council, Palika Kendra, New Delhi-110001.

Conditions for the validity of Fire Safety Certificate:

- All the means of escape/entry/exit shall be kept free from any obstruction.
- All the fire safety arrangement provided their in shall be maintained in good working conditions at all times. 2.
- 3. All the staff members must know the correct method of operation of fire fighting system.
- 4. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 5. The trained fire fighting staff should be available round the clock. 6.
- Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 7. This Fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 9. "The owner / Occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, six months prior to its expiry".
- 10. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The from is available on <u>WWW.dfs.Delhigovt.nic.in.</u> 11. Basement underneath of these Residential Blocks shall not be occupied or used till the receipt of its clearance / FSC from DFS as undertaken by NBCC vide its letter No. NBCC/EKN-Type IV/CGM/DFS/2020/1237 date 26/10/2020.

1. Name & address of the building: Residential Blocks No. 03, 07, 08 & 09 [(04 Nos)

excluding basement] Type-IV Quarters, GPRA

Complex, Kidwai Nagar (East), New Delhi-110023.

2. Type of Occupancy : Residential (Group-A)

3. Building Comprised of: 3 Tier Basement, Ground Floor + 14 Upper Floors (All 04 Blocks)

4. Type of Case : New 5. Details of previous NOC : Nil

6. Fire Safety directives Letter No.: F6/DFS/MS/BP/2013/01 dated 02/01/2014

7. Date of inspection : 01/12/2020

8. Name of the Inspecting Officer: A.D.O. (S.J.) & Dy.C.F.O. (S.Z.)

9. Name and designation of Officer

		: Sh. Mahabir Si	ingh	(DGM)			
	ear of Construction	: 2018		PG/2020/1420 1-4	-107/	11/2020	
S	pplicant's letter No. : - NBCC/E Minimum standards on fire		KN-TYPE IV/CGM/DFS/2020/1430 dated 27/11/2020 UBBL-2016 Provided at Remarks				
No			UBBL-2016		7.7	AR/NMR	
110	prevention and fire safety U/R 33	Requirements		site	IVIIO	IVIIC	
1.							
1.	Access of building	12 m		Provided	MR		
	Road width	4.5 m		Provided	MR		
	• Gate width			Provided	MR		
	Width of internal road		C	Flovided			
2.	2. Number, width, Type & Arrangements of exits						
	a. Number of staircases	2 No. /oach blo	2 No. (each block) Provided		MR	MR	
	Upper floors	NA	JCK)	NA	NA		
	Basements	INA		IVA	14/3		
	b. Width of staircases	1.35 Mtr.		Blk-3 (1.40m & 1.3	37m)	MR	
	Upper floors	1.55 Mitt.		Blk-7(1.42m & 1.4		14111	
		1		Blk-8(1.36m & 1.4			
			Blk-9(1.36m & 1.36		6m)		
	Basements	NA			NA		
	c. Protection of exits						
	Fire check door	Required	Required Provided Required in Provided in Lift well Lift well Natural Ventilation in Staircase			MR	
	Pressurization	Required in				MR	
		Lift well			ase		
	d. No of continuous	2 No. (each bll	k)	r) Provided		MR	
	staircase to terrace						
	e. Width Of Corridor	NA	NA			NA	
		5					
	f. Door Size	1.00mtr		1.00 mtr		MR	
3.	Compartmentation	In each resid	entia	l Block No. 03,0	07,08	& 09	
	Fire check door	Required	Pro	vided	MF	₹	
	Sealing of electrical	Required	Pro	Provided		MR	
	shafts	45					
	Fire Rating of shaft door.	Required	Pro	Provided N/A		R	
	Water Curtain	N/A	N/			N/A	
	Fire Dampers	N/A	N/	A	N/	Ά	
4.	Smoke managements System	In each resid	In each residential Block No. 03,07,08 & 09				
	Basements	N/A N/A				N/A	
	Upper floors	12 ACPH	<u> </u>	tural Ventilation	М	R	

5.	Fire Extinguishers	In each residenti	al Block No. 03,0°	7 08 & 09
J.				M/R
	• Total numbers	30 (Each Blk)	60 (Each Blk)	
	 Types 	ISI marked	Provided	M/R
		ABC/CO ₂		110
	IS marking	Required	Provided	M/R
6.	First – Aid Hose Reels		n each residential Block No. 03,0	
	 Total numbers on 	One at each floor	One at each	MR
	each floor		floor	NAD
	 Length of hose reel hose 	30 Mtr.	30 Mtr.	MR
	Nozzle diameter	5mm	5mm	MR
7.	Automatic fire detection and a	larming system		
	Type of detector	N/A	N/A	N/A
	Location of Main	N/A	N/A	N/A
	Panel • Location of Repeater	N/A	N/A .	N/A
	Panel	NI/A	N/A	N/A
	 Alternate source of power 	N/A	IN/A	
	Hooters' Location	N/A	N/A	N/A
8.	MOEFA (In each residential Block No. 03,07,08 & 09)	Required	Provided	M/R
9.	Public Address System	Required	Provided	M/R
10.	Automatic Sprinkler System (I	n each residential	Block No. 03,07,08	3 & 09)
	Basements	N/A	N/A	N/A
	Upper Floor	N/A	N/A	N/A
	 Sprinkler above false ceiling 	N/A	N/A	N/A
11.	Internal Hydrants (In each residue)	dential Block No. (03,07,08 & 09)	
	 Size of riser/down- 	100 mm	150 mm	MR
	comerNumber of hydrants	1	1	MR
	 Number of hydrants per floor 		_	
	Hose Box	1	1	MR
12.	Yard Hydrants (In each resider	ntial Block No. 03,	07,08 & 09)	
	Total number of	1	1	MR
	hydrants			
	Hose Box	1	1	MR
13.	Pumping Arrangements (In each			19)
	Ground Level	Common Pump Ro		5/ 100
•	Discharge of main pump	Hyd. & Sprinkler (H&S) 2850 LPM (Each)	Hyd. & Sprinkler (H&S	S) MR
		Water Curtain (WC): 2 of 2280 LPM	Water Curtain (WC): 2 of 2280 LPM	
-	Head of main pump	H&S: 90m (each)	Provided	MR
′	Trous or main pamp	WC: 45m (each)	1,001464	
7	> Number of main pumps	4	Providea	MR
> Jockey pump out put		2 of 280 LPM	Provided	MR
Jockey pump head		H&S 90m (Each)	Provided	MR
. > Standby Pump out put		2850 LPM	Provided	MR
> Standby Pump Head		90m	Provided	MR
7	Auto Staring/Manual	Required	Provided	MR
7	stopping > Pump House Access	Required	Provided	MR
		المري الم		
			H	

	T lovel		Grand Control of the				
•	Terrace level	N/A	N/A	N/A			
	Discharge of pump	N/A	N/A	N/A			
>		N/A	N/A	N/A			
>		N/A	N/A	N/A			
>	Auto starting of pump		'				
14.	Captive water Storage for fire	fighting (In each resid	lential Block No. 0.	3,07,08 & 09)			
17.	 Underground tank 	2,00,000 lts	Provided	MR			
	capacity	Required	Provided	MR			
	> Draw of connection	Required	Provided	MR			
	> Fire service inlet	Required	Provided	MR			
	> Access to tank	10000 Ltr	10,000 Ltrs.	MR			
	Overhead Tank	10000 Lti	10,000				
	capacity	Required	Provided	M/R			
15	Exit Signage	1-4-1 Block No. 0					
16.	Provision of Lifts (In each residual)	dential block 140. 0.	Provided	MR			
	Pressurization of Lift Shaft	Required					
	Pressurization of lift	Required	Provided	MR			
	lobby Communication in lift	Required	Provided	MR			
	Car > Fireman's Grounding	Required	Provided	MR			
	Switch	Required	Provided	MR			
	Lift Signage						
17.	Standby power supply	Required	Provided (DG)	MR			
18.	Refuge Area		-1/4	N/A			
	> Total area	N/A	N/A	N/A N/A			
	> Location	N/A	N/A	N/A			
19.	Fire control room (Provided at	entrance level of 10)wer No.0)	MR			
	> Detector system panel	Required	Provided	N/A			
	> Flow Switch Panel	N/A	N/A Dravidad	MR			
	PA System Panel	Required	Provided	MR			
	> Battery backup	Required	Provided Provided	MR			
	➤ Building Floor Plans	Required		N/A			
20.	Special Fire Protection	N/A	N/A				
	Systems for Protection of						
	special Risks, if any;		tt vido	letter No			
Note:-	Shortcomings issued b	y this depart					
<u>F</u>	6/DFS/MS/Resd./2020/SZ/2812	dated 10/11/2020	Have been run,	compile.			
_		1 1 1 4 - building	tested che	aled and found			
	The fire protection systems provide	ded in the building	Were lesieu, once	ikeu anu iour			
	al at the time of inspection.	6		~ 7.			
Keeping	in view of the substantial comp	liance of the minim	um standards of	fire prevention			
and fire safety required under the rules it is recommended to grant Fire Safety Certificat under rule 35 of the Delhi Fire Service Rules 2010 is recommended.							
under ru	le 35 of the Delhi Fire Service Ki	ules 2010 is recomm		1			
	\ \d			/			
(18/202		/4	2112/2020			
	11/12/2			3/14			

Signature of the Inspecting Officer
Name : Ashok Kumar Jaiswal Designation: A.D.O. (S.J.)

Signature of the Inspecting Officer Name: Sunil Chawdhary Designation: Dy.C.F.O. (S.Z.)