## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE **NEW DELHI-110001**

No. F.6/DFS/MS/Indl./2020/SZ/

Dated: 08/12/2020

## **FIRE SAFETY CERTIFICATE**

Certified that the Multani Pharmaceuticas Ltd, at C-100, Okhla Industrial Area, Phase-I, New Delhi comprised of Basement + Ground floor + Mezzanine floor + First floor was issued NOC by this department vide letter No. F.5/(J)/DFS/2009/206 dated 17/06/2009. The premise was re-inspected by officer concerned of this department on 24/11/2020 in the presence of Mr. Kamal Kumar (Production Manager) and found that the said Industrial building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of Delhi Fire Service Rules, 2010 and that the building/premises is fit for occupancy class G accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued \_\_\_\_\_ag/12/2020 at New Delhi by

(Sunil Chawdhary) Dy. Chief Fire Officer Delhi Fire Service

Copy to: -

The Authorised Signatory, Multani Pharmaceuticas Ltd, at C-100, Okhla Industrial Area, Phase-I, New Delhi

2. The Executive Engineer (Building), SDMC, Jal Vihar, Lajpat Nagar, New Delhi-110024.

## Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- 7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

1	INS	PECTION REPOR	T				
1	Name & Address of the Building	Multani Pharmace	uticas Ltd, at C-100, Ok	hla Industrial			
2			Area, Phase-I, New Delhi				
	Type of Occupancy	Group-G (Industr	Group-G (Industrial)				
3	Building Comprised of	Basement + Groun	Basement + Ground floor + Mezzanine floor + First floor				
<u>4</u> 5	Type of Case	Renewal					
	Details of Previous NOC	F.5/(J)/DFS/2009/	206 dated 17/06/2009				
<u>6</u> 7	Fire Safety Directives Letter No	Nil 27/11/2020 ADO Avtar Singh,					
8	Date of Inspection						
	Name of the Inspecting Officers						
9	Name & Designation of Officers from the building side	Mr. Kamal Kumar (Production Manager)					
10	Year of construction	1986					
11	Applicant letter No.	Email dated 10/11/2020					
S. No	Minimum standards on Fire Prevention and Fire Safety U/R 33	BBL/NBC Requirement	Provided at Site	Remarks MR/NMR			
1	Access to Building.						
	Road width	6 m	Provided	MR			
	Gate width	4.5 m	Directly accessible	MR			
	Width of internal road	-N/A-	-N/A-	-N/A-			
2	Number, width, type & arrangement	of exits.					
	a) Number of Staircase						
	Upper floors.	2 nos	2 nos	MR			
	Basement floor.	2 nos	2 nos	MR			
	b) Width of Staircase		1				
	> Upper floors	1.25 m& 1,20 m	1.25 m & 1.20 m	MR			
	Basement floor	1.25 m & 1.20 m	1.23 m &1.25 m (Iron)	MR			
		1.25 11 & 1.20 11	1.23 III (1.23 III (11011)				
	c) Protection of exits	-NA-	-NA-	-NA-			
	Fire check door			-NA-			
	> Pressurization	-NA-	-NA-	-NA-			
	d)No. of continuous staircase to	Required	One	MR			
	e)Width of corridor	-NA-	-NA-	-NA-			
	f) Door size	-NA-	-NA-	-NA-			
3	Compartmentation.						
•	• Fire check door.	-NA-	-NA-	-NA-			
	Sealing of electrical shafts.	-NA-	-NA-	-NA-			
	• Fire rating of shaft door.	-NA-	-NA-	-NA-			
	Water curtain	-NA-	-NA-	-NA-			
	Fire dampers	-NA-	-NA-	-NA-			
	Smoke Management system.						
	Basement	30 ACPH	Exhaust fan	MR			
	<ul> <li>Upper floors</li> </ul>	12 ACPH	Provided	MR			
	Fire Extinguishers.	1					
	Total numbers	20 nos	20 nos	MR			
	Types	ABC / CO <sub>2</sub>	ABC /CO <sub>2</sub> type	MR			
	ISI Marking	ISI marked	Provided	MR			
	First Aid Hose Reels.	151 markeu	Tiovided	IVIIX			
•		0	Provided	MR			
	Total numbers on each floor	One					
	<ul><li>Length of hose-reel hose.</li><li>Nozzle Diameter</li></ul>	30m	Provided	MR			
	Nozzie I hameter	5mm	Provided	MR			

		4111 -		2
		,		-N/A-
	<ul> <li>Type of detectors</li> </ul>	-N/A-	-N/A-	-N/A-
	<ul> <li>Location of Main Panel</li> </ul>	-N/A-	-N/A-	-N/A-
	<ul> <li>Location of Repeater Panel</li> </ul>	-N/A- -N/A-	-N/A-	-N/A-
	Alternate source of power	-N/A-	-N/A-	-N/A-
	Hooter's location		-N/A- Provided	MR
8.	MOEFA	Required	-N/A-	-N/A-
9.	Public Address System	-N/A-	-14/74	
10.	Automatic Sprinkler System		Provided	MR
	Basement.	Required	-N/A-	-N/A-
	Ground & Above floors  Class calling	-N/A-	-N/A-	-N/A-
	Sprinkler above false ceiling	-N/A-	-11///	
11.	Internal Hydrants.	100	Provided	MR
	Size of Riser / Down-comer	100 mm	Provided	MR
	Number of Hydrant per floor	01 no	Provided	MR
	Hose box.	01 no	110.120	
12.	Yard Hydrants	DT/A	-N/A-	-N/A-
	Total number of hydrants	-N/A-	-N/A-	-N/A-
	Hose box	-N/A-	-14/72-	
13.	Pumping arrangements.			
	Ground Level	27/4	-N/A-	-N/A-
	Discharge of main numn	-N/A-	-N/A-	-N/A-
	<ul><li>Discharge of main pump.</li><li>Head of main pump.</li></ul>	-N/A-	-N/A-	-N/A-
	Number of main pumps.	-N/A-		-N/A-
	Jockey Pump output.	-N/A-	-N/A-	-N/A-
	> Jockey Pump head.	-N/A-	-N/A-	-N/A-
	<ul><li>Standby Pump output.</li><li>Standby Pump head.</li></ul>	-N/A-	-N/A-	-N/A-
	> Auto Starting/Manual	-N/A-	-N/A-	
	Stopping.	-N/A-	-N/A-	-N/A-
	Pump house access	-N/A-	-N/A-	-N/A-
	Terrace Level		222 7 777	MR
	Discharge of pump.	900 LPM	900 LPM 39 m	MR
	> Head of pump.	39 m	Provided	MR
	> Power supply.	Required Required	Provided	MR
	> Auto starting of pump.	•	110 / 100 /	
14.	Captive water storage for firefighting.	50,000 ltrs	50,000 ltrs	MR
	<ul> <li>Underground tank capacity.</li> <li>Draw-off connection.</li> </ul>	-N/A-	-N/A-	-N/A-
	. To G the Inlot	Required	Provided	MR
		Required	Provided	MR
		•	15,000ltrs	MR
	Overhead tank capacity.	15,000 ltrs Required	Provided	MR
15.	Exit Signage.	Required	110.1444	
16.	Provision of Lifts.	-N/A-	-N/A-	-N/A-
	Pressurization of lift shaft.	-N/A-	-N/A-	-N/A-
	Pressurization of lift lobby.	-N/A-	-N/A-	-N/A-
	Communication in lift car.		-N/A-	-N/A-
	• Fireman's switch.	-N/A-	-N/A-	-N/A-
	<ul> <li>Lift signage.</li> </ul>	-N/A-		
17	Standby Power Supply	Required	Provided	MR
18.	Refuge Area		27/4	NI/A
10.	Total area	-N/A-	-N/A-	-N/A-
	• Location	-N/A-	-N/A-	-N/A-
	200			

10					
19.	Fire	Control Room.			
	•	Detector System Panel.	-N/A-	-N/A-	-N/A-
	•	Flow Switch Panel.	-N/A-	-N/A-	-N/A-
	•	PA system Panel.	-N/A-	-N/A-	-N/A-
	•	Battery backup	-N/A-	-N/A-	-N/A-
	•	Building floor plan	-N/A-	-N/A-	-N/A-
20.	Spe the l	Protection System for Protection of special Risk, if any.	Required for HT/LT panels	02 ABC fire extinguishers provided near LT Panel	MR

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view of the substantial compliance of the minimum standards of fire prevention and fire safety measures as required under the rules of NOC issued vide letter no.F.5/(J)/DFS/2009/206 dated 17/06/2009, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: Avtar Singh Designation: ADO (MR)

DO(SD)

Dy. C.F.O. Su

FT letter is put up fær sign plense.

DCP0(9/2)

M.S. Ull