FORM 'H' FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE. CONNAUGHT PLACE, NEW DELHI

No. F6/DFS/MS/2020/ pospitel/ 509

Dated: 07/12/2020

FIRE SAFETY CERTIFICATE

Certified that the Manipal Hospital (A unit of Human Care Medical Charitable Trust) Located at Sector-6, Dwarka, New Delhi in a building comprised of Three Basement, Ground + Nine Upper Floors) owned/occupied by M/s. Human Care Medical Charitable was issued FSC vide Letter No.F6/DFS/MS/SZ/Hospital/2017/1874 dated 28/12/2017, The premises was re inspected by the officers concerned of this department on 24/11/2020 in the presence of Sh. Varun Vats (Fire & Safety Officer) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class " Institutional" Group C with effect from 67/12/2020 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010. Issued on 6.7/12/20.20... at New Delhi by.

Copy to: -

1. The Joint Director (L&I)Bldg. DDA, Vikas Sadan, INA, New Delhi.

The Human Care Medical Charitable Trust Located at Sector-6, Dwarka, New Delhi

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

3. The trained staff should be available round the clock.

- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

6. Basement shall be used as per building bye laws.

- The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expired.

		1)	9		
-	Compartmentation		,		
	Fire check door	Danis			
		Required	Prov		MR
	 Sealing of electrical shafts 	Required	Prov	Provided MF	
	 Fire Rating of shaft door 	2 Hours	Prov	ided	MR
	 Water Curtain 	Required	Prov	ided	MR
	 Fire Dampers 	Required	Prov	ided	MR
1.	Smoke managements				
	System				
	 Basements 	30 AC Charge	Prov		MR
_	 Upper floors 	12 AC Charge	Prov	ided	MR
5.	Fire Extinguishers				1.48
	 Total numbers 	As per IS	165N		MR
	 Types 	2190/1992		ABC & CO2 MR Provided MR	
	IS marking	ABC & CO2 ISI marked	Prov	ıded	MR
6.	First – Aid Hose Reels	_		• 1 • •	MD
	 Total numbers on 	5	Prov		MR MR
	each floor	30 m	Prov Prov		MR
	 Length of hose reel 	5 mm	Prov	ided	IVIK
	hose				
	Nozzle diameter	larming system			
7.	Automatic fire detection and a	Heat/Smoke	Provi	Provided	
	Type of detectors	Ground Floor		Ground Floor	
	Location of Main	Ground Floor			
	Panel • Location of Repeater	Each Floor	Each	Floor	NR
,	Panel • Alternate source of	Required	Provi		MR
	power	Required	Provi	ded	MR
	Hooters' Location	Required	Provi	ded	MR
8.	MOEFA	Required	Provi	ded	MR
9.	Public Address System Automatic Sprinkler System	110	·	- 10-	N N/D
10.	Basements	Required	Provided except MRI & C.T Scan room		
	Upper Floor	Required	Provi		MR MR
	 Opper Floor Sprinkler above false ceiling 	Required	Provi	ded	IVIK
	1.I.I. Juantos		150		MR
11.	Size of riser/down-	150mm	150 r	11111	IVIIC
	comer Number of hydrants	5Nos	Provi	ided	MR
	per floor	Dogwinad	Provi	ided	MR
	Hose Box	Required			
12	Vard Hydrants	9 Nos.	9 No	S.	MR
	Total number of hydrants		9 No	S.	MR
	Hose Box	9 Nos.	7110	71100	

1/	D	Pumping A					
13		rumping Arrangements:					
	•	Ground Level					
	 Discharge of main 		2850 lpm&1800	Provided	MR		
		pump	lpm for W.				
		Hood -C.	Curtain Pump				
		Head of main pump	90 m	Provided	MR		
		Number of main	2Nos& 1Nos. W.	Provided	MR		
	>	pumps	Curtain Pump				
		pump out put	180 lpm(2)	Provided	MR		
			90 m	Provided	MR		
		put	2850 lpm	Provided	MR		
	. >	•	90 m	Dungidad	MR		
	>			Provided	MR		
.		stopping	Required Provided		IVIK		
	>		Required	equired Provided			
	•	Terrace level	Required	Required Provided			
	>		NR	NR	NR		
	>	•	NR				
	>		NR	NR	NR NR		
	>	Auto starting of	NR	NR	NR		
		pump		7.12			
14.	Captiv	ve water Storage for fire		,	10.00		
	•	Under ground tank	1,50000 litre	2,00,000 litres	NMR		
		capacity) (D		
	>	Draw off connection	NA	Provided	MR		
	>	Fire service inlet	Required	Provided	MR		
	>	Access to tank	Reqired	Provided	MR		
		Overhead Tank	20000 litres	30, 000 Litres	MR		
		capacity		Provided	MD		
15	Exit S	xit Signage Required Provided		Provided	MR		
16.	Provis	Provision of Lifts		D 11 1	MR		
	>	Pressurization of Lift	Required	Provided	MK		
		Shaft		D 11-1	MR		
	>	Pressurization of lift	Required	Provided	IVII		
		lobby		D	MR		
	>	Communication in	Required	Provided	IVIIX		
		lift Car		D i do d	MR		
	>	Fireman's	Required	Provided	IVIIX		
		Grounding Switch		D - 11-1	MR		
	>	Lift Signage	Required	Provided	IVIK		
		1.	Required	DG set 1250	MR		
17.	Standb	y power supply	Required	KVA(2)			
				, ,			
18.	Refuge	Area	232m2	Provided (Old case)	MR		
		Total area	7 th floor	7 th floor	MR		
		Location	/ UI HOOI				
19.	Fire co	ntrol room	Required Provided				
17.	>	Detector system	Required	Provided	MR MR		
		nanel	Required		MR		
		Flow Switch Panel	Required	Provided	MR		
	>	PA System Panel	Required	Provided			
	<i>D</i>	Rattery backup	Required	Provided	MR		
	>	Building Floor Plans					
		Danama					

Special Fire Protection	Required		
Systems for Protection c	Required	Co 2 Flooding	MR
special Risks, if any;		system provided	
		in HT/LT Panels and FM-200 in	
The		1	
The fire protection sy found functional at the time of	stems provided in t	he building were test of	hecked and
In view of the deemed and fire safety as required F6/DFS/MS/S7/Hospital/2015	compliance of min	imum standards on fire	prevention
- 5. 5. 1. 10. 52/1105pital/201/	71 8/4 dated 2 X/1 2/	ille NOC issued vide 2017 renewal under ru	le 35 of the
Delhi Fire Service Rules 2010	is recommended.	2017 Tellewal allaci Tu	ic 33 of the
. 5	٧.		
2214		7.	N C C
Signature of the Inspecting Of	ficer Signa	ature of the Inspecting C	officer
Signature of the Inspecting Of Name War Name Designation	mgh Namo	e /	
Designation ADOMS	Desig	gn a tion	
7,000			
Dycfo/\$2	•	10	<u>'</u>
Decre 17 2	_ 4	Windsoll	00
	2 W/'	W They were	;
. ,	1 10 8-	Vintert a.m.	
2 4 h1	vt 10.30	977	\prec
2///	VI !	201	= /+/
/			7 / //
00	In I MAY	175W.	/
() () ·	WYAR		
			&
Reinspected ADD (DWANN)	alongwith	1 nel	o marino
Reinsper	27/11/202	o me	,
Aso (Duaria) of		Cub mitted	of ,
an eneral of	TAGE !		
for me			
. /	\cap		2.3/111/20
0 6/2-7	//		
Dy cho			
	/ ~		
21/11			
/	٨		
6	1000	- / <u>)</u> ,	
		\ \ \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	
	, , , , , , , , , , , , , , , , , , , ,	V	
\ \ \	\sim	,	
\ '	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\		
. 4	//// /	(147/\	
Mixel/160	1 // 1//	MID	
Divertod	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	<i>/</i>	
		\	