GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No F 6/DFS/MS/2020/ 590

Dated: 14 / /2/2020

FIRE SAFETY CERTIFICATE

(Sunil Chawdhary) Dy. Chief Fire Officer

Copy to: -

The Dy. Director, Govt. of India, CWC, Library & information Bureau, Library building, R. K. Puram, New Delhi-110066.

Conditions for the validity of Fire Safety Certificate:

1 All the means of escape/entry/exit shall be kept free from any obstruction.

2 All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to nonfunctional fire safety measures shall be at the responsibility of the management.

3. All the staff members must know the correct method of operation of firefighting system.

The owner / occupier shall submit a declaration every year in Form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on http://delhi.gov.in./wps/wcm/connect/doit fire/FIRE/Home/Forms.

5 This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if

any.

6 "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".

INSPECTION REPORT

1. Name & address of the building

Type of Occupancy

Type of Case 3.

Details of previous NOC

Fire Safety directives letter No

Date of inspection

Name of the Inspecting Officers

Name and designation of officers from the building side

9. Year of Construction

10. Applicant's letter No.

: Auditorium at CWC library Building, West block, R.K. Puram, New Delhi.

: Assembly Building

:Renewal B+G+03 upper floors (Auditorium at 1^{st} floor)

: F6/DFS/MS/2013/SZ/658 Dated: 01.08.2013

: F6/DFS/MS/BP/2003/987 Dated: 08.05.2003

: 07.12.2020

: DO(SZ) / ADO (BCP)

: Sh. S. S. Nath, Asstt. Director

: No.14/ Fire Safety/Lib/2019/PCP/1433-35 dated: 28.10.2020

	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirements	Provided at site	Remarks MR/NMR		
	Access to building					
	Road width	12m	12m	MR		
	Gate width	4.5m	5m	MR		
	Width of internal road	6m	6m	MR		
	Number, Width, Type & Arrangement of Exits					
	a. Number of staircases		X.			
150 1	• Upper Floors	02 nos	02 nos +1 no GD to FF	MR		
0	Basements	03 nos.	03 nos	MR		
	b. Width of staircases					
	Upper Floors	1.5 m	1.50m, 1.30m & 1.36m	MR		
	Basements	1.5 m	1.50m, 1.25m & 2.00m 1 ramp	MR		
c. Protection of exits						
	Fire check door	Required	Provided	MR		
	Pressurization	NA	NA	NA		
	d. No. of continuous staircases to terrace	02	02	MR		
	e. Width of Corridor	1.5m	1.5m	MR		
	f. Door Size	1.5m	1.50m, 1.55m & 1.65m, 1.75m	MR		
	Compartmentation.					
	Fire check door	Required	Provided	MR		
	Sealing of electrical shafts	Required	Provided	MR		
	Fire Rating of shaft door	NA	NA	NA		

	Water Curtain				
	• Fire Dampers	NA	NA	NA	
4	Smoke Management System.	Required	Provided	MF	
	Basements		The same of the sa		
	Upper floors	30 a/c per hour	Exhaust Fan	MR	
5	Fire Extinguishers	12 a/c per hour	Natural Ventilated	MR	
t					
	Total numbers	31nos	31 nos	1	
	• Types	ABC/Co2	ABC-20/Co2-11	MR	
	 ISI marking 	ICINA		MR	
6	First-Aid Hose Reels.	ISI Marked	Provided	MR	
	Total numbers on each floor				
		02	02	MR	
	• Length of hose reel hose	30m	30m	2 2	
7	Nozzle diameter	5mm		MR	
	Automatic fire detection and alarming sys	tem.	5mm	MR	
	Type of detectors	Required	The state of the s		
	 Location of Main Panel 	Required	Provided	MR	
	 Location of Repeater Panel 		Provided GF	MR	
	Alternate source of power	Required	Provided	MR	
		Required	Provided	MD	
	 Hooters' Location 	Required	-	MR	
	MOEFA		Provided	MR	
	Public Address System.	Required	Provided	MR	
	Automatic Sprinkler System.				
-	Basement				
-		Required	Provided	MD	
	 Upper Floor 	NA	NA	MR	
	 Sprinkler above false ceiling 	NA	NA	NA	
	Internal Hydrants			IVA	
	• Size of riser/down-comer	150			
	 Number of hydrants per floor 	150m	150m	MR	
	• Hose Box	02	02	MR	
Y	ard Hydrants.	02	02	MR	
	Total number of hydrantsHose Box	06	06	MD	
		06		MR	
Pı	umping Arrangements.		06	MR	
	gentents,				
	Ground Level				
	Discharge of main Pump	1620 lpm	Provided		

	➤ Head of Main pump	60m	60m	MR		
	Number of main pumps	01 no	01 no	MR		
4	> Jockey Pump out put	180 lpm	180 lpm	MR		
	Jockey pump head	60m	60m	MR		
2	Standby Pump out put Standby Pump Head	1620 lpm	1620 lpm			
	Times y Tump Head		6	MR		
	Auto Starting/ Manual stopping	60m	60m	MR		
	Pump House Access	Required	Provided	MR		
	Terrace level			_		
	Discharge of pump	4501pm	450 lpm	MR		
	➤ Head of the pump	40m	40m	MR		
	➤ Power Supply	Required	Provided	MR		
	Auto Starting of pump	Required	Provided	MR		
14	Captive Water Storage for fire fighting.	_				
	Underground tank capacity	50,000 ltr.	50,000 ltr.	MR		
	Draw-off connection	Required	Provided	MR -		
	Fire service inlet	Required	Provided	MR		
	Access to tank	Required	Provided	MR		
	Overhead Tank capacity	20,000 ltrs	20,000 ltr.	MR		
15	Exit Signage.	Required	Provided	MR		
16	Provision of Lifts.					
	Pressurization of Lift Shaft	N/A	N/A	N/A		
	Pressurization of Lift lobby	N/A	N/A	N/A		
	Communication In lift Car	Required	Provided	MAD		
	Fireman's Grounding Switch			MR		
	Lift Signage	Required	Provided	MR		
		Required	Provided	MR		
17	Standby power supply	Required	Provided	MR		
18	Refuge Area.					
	> Total Area	N/A	N/A	N/A		
Dr.	Location	N/A	N/A	N/A		
19	Fire Control Room					
	Detector System Panel	Required	Provided	MR		
	Flow Switch Panel	Required	Provided	MR		
		and the second s				
	PA System PanelBatter backup	Required	Provided	MR		

Bullo	ding Floor Plans	N/A	NI/A	The second of th
O Special Fire Protection Systems for Protection of special Risks, if any:	taction C		IN/A	N/A
	N/A	N/A	N/A	
	, , , , , , , , , , , , , , , , , , , ,			

The fire protection systems provided in the building were test checked and found in working conditions at the time of inspection.

Keeping in view the satisfactory compliance of the minimum standards on fire prevention and fire safety required as stipulated in NBC art 4, the FSC issued vide letter of even no. 658 dated 01.08.2013 renewed under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of the Inspecting Officer

Name S.K. Qua Designation DolsD Signature of the Inspecting Officer
Name Rajesh Ceunal

Designation ADO BCR

Diro(p)

F.J. poleu

HDQ. Rayesh)

As opposed, F.T. tetter in putup for your

Synature Pl

10/12/200

Dy cfo/s2

m.s W