## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/School/SZ/2020/539

Dated: 07/12/2020

## FIRE SAFETY CERTIFICATE

Certified that J.D. Tytler School located at R-Block, New Rajendra Nagar, New Delhi- 110060 comprised of basement, ground plus three upper floors was granted Fire Safety Certificate by this department vide letter NO F.6/DFS/MS/School/2017/SZ/1363 dated 15.09.2017. The school buildig was re-inspected by the officer concerned of this department on 17.11.2020 in presence of Mr. J. G. Babbar, Manager of the school and found that the School management have complied with the fire prevention and fire safety requirements in accordance with the Directorate of Education circular No. F.6/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01.03.2011 and that the school building is fit for occupancy class "Educational" with effect from \_\_\_\_\_\_\_\_ for a period of 03 years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions printed overleaf under rule 38 of Delhi Fire Service Rules-2010.

Issued on 07/12/2020 at New Delhi by.

(SUNIL CHAUDHARY) Dy. CHIEF FIRE OFFICER DELHI FIRE SERVICE

Copy to: -

- 1. The Principal, J.D. Tytler School, R-Block, New Rajendra Nagar, New Delhi- 110060.
- 2. The Directorate of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi-110054.

## Conditions for the Validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. Basement used only for storage purpose as per BBL.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [ sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.
- 9. All the means of escapes /exits shall not be locked/blocked at any time for safe evacuation of the occupants in case of emergency.

THE RESERVE THE PROPERTY OF TH

1. Name & address of the building : J.D. Tytler School, R-Block, New Rajender Nagar, New

Delhi- 110060.

2. Type of Occupancy : Educational

3. Type of Case : Renewal

4. Details of previous NOC : F.6/DFS/MS/School/2017/SZ/1363 dated 15.09.2017

5. Fire Safety directives letter No : N/A

6. Date of inspection : 17.11.2020

7. Name of the Inspecting Officers: P.V.Rathee, Asst. Div. Officer (SRD)

8. Name and designation of officers

from the building side : Mrs. J.G.Babbar, Manager

9. Year of Construction : 1985-86

10. Applicant's letter No. : Nil dated 22.10.2020

J.D. Tytler school is comprised of basement, ground plus three upper floors.

S. No.		Ainimum Standards on fire vention and fire safety U/R 33	NBC/ BBL Requirement	Provided at site	Remarks MR/NMR		
1	Access	to building					
	8	Road width	06 mts	Provided	MR		
	6	Gate width	4.5 mts	Provided	MR		
	0	Width of internal road	Required	Provided from two sides	MR		
)	Number, Width, Type & Arrangement of Exits						
	a. Num	ber of staircases			and the day has been the sale and the sale and		
	9	Upper Floors	04 Nos.	Provided	MR		
	•	Basements	03 Nos.	03 Nos.	MR -		
	b. Wid	h of staircases					
	•	Upper Floors	1.5 mts or less & 0.75 mt	2.47, 1.50, 1.47 mts	MR		
	۵	Basements	1.5 mts or less & 0.75 mt	1.48, 1.47, 1.50 mts.	MR		
	c. Prote	ction of exits	AND AND AND AND AND AND AND AND		MR. See, 300 year 300, one, sun see, 304 apr.		
	•	Fire check door	N/A	N/A	N/A		
	8	Pressurization	N/A	N/A	N/A		
	e. No. o	of continuous staircases to terrace	01	01	MR		
	g. Widt	h of Corridor	1.5	Provided	MR		
	h. Door	Size	1.0 mt.	Provided	MR		
}	Compa	rtmentation.					
	•	Fire check door	N/A	N/A	N/A		
The first state of the first sta		Sealing of electrical shafts	N/A	N/A	N/A		
	•	Fire Rating of shaft door	N/A	N/A	N/A		
	•	Water Curtain	N/A	N/A	N/A		
	*	Fire Dampers	N/A	N/A	N/A		
1	Smoke	Management System.					
	•	Basements	30 a/c per hour	Exhaust fan provided	MR		
	•	Upper floors	12 a/c per hour	Natural ventilation provided	MR		

5	Fire Extinguishers					
	Total numbers	24 nos.	Provided	MR		
	• Types	ABC, CO <sub>2</sub> type	Provided	MR		
	IS marking	ISI marked	Provided	MR		
6	First-Aid Hose Reels.					
	Total numbers on each floor	03	Provided	MR		
	<ul> <li>Length of hose reel hose</li> </ul>	30 m	Provided	MR		
	Nozzle diameter	5 mm	Provided	MR		
7	Automatic fire detection and alarming	system Not	required			
'		N/A	N/A	N/A		
	Type of detectors		N/A	N/A		
	<ul> <li>Location of Main Panel</li> </ul>	N/A	N/A	IN/A		
THE REPORT OF THE PARTY AND TH	• Location of Repeater Panel	N/A	N/A	N/A		
CONTRACTOR OF CO	Alternate source of power	N/A	N/A	N/A		
And a second sec	<ul> <li>Hooters' Location</li> </ul>	N/A	N/A	N/A		
8	MOEFA	N/A	N/A	N/A		
9	Public Address System.	Required	Provided	MR		
10	Automatic Sprinkler System					
	Basement	Required	Provided	MR		
	Upper Floor	N/A	N/A	N/A		
	Sprinkler above false ceiling	N/A	N/A	N/A		
11	Internal Hydrants					
1.1	Size of riser/down-comer	N/A	N/A	N/A		
		N/A	N/A	N/A		
	<ul><li>Number of hydrants per floor</li><li>Hose Box</li></ul>	N/A	N/A	N/A		
10		IVA	IVI	1.4/ 1.1		
12	Yard Hydrants.	N/A	N/A	N/A		
	Total number of hydrants	N/A	N/A	N/A		
1.0	Hose Box	IN/A	IVA	11/71		
13	Pumping Arrangements					
	Ground Level	> T / A	NT/A	NI/A		
	Discharge of main Pump	N/A N/A	N/A N/A	N/A N/A		
	Head of Main pump	N/A	N/A	N/A		
	Number of main pumps					
	Jockey Pump out put	N/A	N/A	N/A		
	Jockey pump head	N/A N/A	N/A N/A	N/A N/A		
	Standby Pump out put	N/A N/A	N/A N/A	N/A		
To a series of control of the contro	> Standby Pump Head	(100 d) (35 d) (40)	8			
THE PERSON NAMED IN COLUMN TO VALUE	Auto Starting/ Manual stopping	N/A	N/A	N/A		
	Pump House Access	N/A	N/A	N/A		
	Terrace level	02 X 450 LPM each	OOOT DAY	MD		
	Discharge of pump		900LPM	MR		
	Head of the pump	30 mts	30 mts	MR		
	Power Supply	N/A	N/A	N/A		
	> Auto Starting of pump	N/A	N/A	N/A		
14	Captive Water Storage for fire fighting		DT/A	NT/A		
	• Underground tank capacity	N/A	N/A	N/A		
	> Draw-off connection	N/A	N/A	N/A		
	Fire service inlet Access to tank	N/A	N/A	N/A		
	Overhead Tank capacity	N/A	N/A Provided	N/A MR		
	Overmond rank capacity	15,000 lts	riovided	IVIN		

6	Provision of Lifts.	Not Applicable				
	Pressurization of Lift Shaft	N/A	N/A	N/A		
	• Pressurization of Lift lobby .	N/A	N/A	N/A		
	Communication In lift Car	N/A	N/A	N/A		
	Fireman's Grounding Switch	N/A	N/A	N/A		
	Lift Signage	N/A	N/A	N/A		
7		N/A	N/A	N/A		
7	Standby power supply  Refuge Area.					
18	Total Area	N/A	N/A	N/A		
	Location	N/A	N/A	N/A		
19	Fire Control Room					
	Detector System Panel	N/A	N/A	N/A		
	Flow Switch Panel	N/A	N/A	N/A		
	PA System Panel	N/A	N/A	N/A		
	Batter backup	N/A	N/A	N/A		
	Building Floor Plans	N/A	N/A	N/A		
0	Special Fire Protection Systems for Protection of special Risks, if any:	Required 02 ABC type fire extinguishers near elect. panel	Provided	MR		

In view the substantial compliance of minimum standards on fire prevention and fire required under the rules, it is recommended to grant certificate under Delhi Fire Service 2007& Rules 2010.

DFA is put up for approval & signature please

Signature of the Inspecting Officer (P.V.Rathee)

Asst. Div. Officer, (SRD)

tufo 11112020

Dy (60 (5/2)

F, t. pleuse

AngsRd.

Sis, f.T. Letter is peet ee for Sign please

84/12