GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No. F.6/DFS/MS/GH/2020/SZ/ 147

Dated: 11. 1.2. 1000

FIRE SAFETY CERTIFICATE

Issued Market at New Delhi by

(Sunil Chawdhary)
Dy. Chief Fire Officer
Delhi Fire Service

Copy to: -

- 1. The Additional Commissioner of Police,(LIC.), 1st floor P.S. Defence Colony, New Delhi 110049
- 2. The Proprietor M/s River View Guest House located at B-9, Bhaskar Compound Okhla Kalindi Kunj Road, Jamia Nagar, New Delhi-110025

Conditions for the validity of Fire Safety Certificate:

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the firefighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.
- 5. The fire safety certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. All comments / directions of licensing department shall always be permitted and followed.
- 7. The owner/occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rule of 2010. The form is available on www.dfs.delhigovt.nic.in.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

~	INS	SPECTION REPORT			
1	Name & Address of the Building	River View Guest House B-9, Bhaskar Compound Okhla Kalindi Kunj Road, Jamia Nagar, New Delhi-25			
2	Type of Occupancy	Residential & Lodging, Group-A (Guest house)			
3	Building Comprised of	Basement, Ground + 03 upper floors			
4	Type of Case	Renewal			
5	Details of Previous NOC	F6/DFS/MS/GH/2017/SZ/1171 dated 04/08/2017			
6	Fire Safety Directives Letter No	Nil			
7	Date of Inspection	04/12/2020			
8	Name of the Inspecting Officers	ADO Avtar Singh			
9	Name & Designation of Officers from the building side	Mr. Mohd. Mifzal (Manager)			
10	Year of construction	Basement (Storage), Gd floor (Rec. & 08 G/rooms), 1 st floor (09 G/rooms), 2 nd & 3 rd floor (owner's residence) total 17 G/rooms			
11	Applicant letter No.	Online Application no: 2020022703070 Dated 01/09/2020			
S. No	Minimum standards on Fire Prevention and Fire Safety U/R 33	Old FSC Requirements	Provided at Site	Remarks MR/NMR	
1	Access to Building.			1	
8	Road width	Required	6 m	MR	
	Gate width	-N/A-	Directly accessible	-N/A-	
	Width of internal road	-N/A-	-N/A-	-N/A-	
2	Number, width, type & arrangemen	nt of exits.		8 2	
	a) Number of Staircase			9 25 X	
	> Upper floors	Required	One	MR	
	> Basement floor	Required	Two	MR	
	b) Width of Staircase				
	> Upper floors	Required 1.25 m		MR	
	Basement floor	Required	1.55 & 1.12 m	MR(old case)	
	c) Protection of exits				
	Fire check door	Required	Provided	MR	
	> Pressurization	-N/A-	-N/A-	-N/A-	
	d)No. of continuous staircase to	Required	One	MR	
	terrace e) Width of corridor	-N/A-	-N/A-	-N/A-	
	f) Door size	Required	1.10 m (final exit)	MR	
3	Compartmentation.	required	,		
3	Fire check door.	Required	Provided	MR	
	Sealing of electrical shafts.	-N/A-	-N/A-	-N/A-	
	• Fire rating of shaft door.	-N/A-	-N/A-	-N/A-	
	Water curtain	-N/A-	-N/A-	-N/A-	
	• Fire dampers.	-N/A-	-N/A-	-N/A-	
	C Management system	-14/74	11/12		
4.		30 ACPH	-N/A-	-N/A-	
	Basement Linear floors	12 ACPH	-N/A-	-N/A-	
-	Upper floors Fig. Extinguishers	12 110111			
5.		Paguired 06 nos N			
	Total numbers	Required ABC /CO ₂	ABC / CO ₂	MR	
	• Types	ISI marked	Provided	MR	
	ISI Marking Resk	151 marked	11011404		
6	. First Aid Hose Reels.	One	One	MR	
	letel supplier on agen floor	VIIV	~ ~ ~ ~		

	• Length of hose-reel hose.	30 m	30 m	MR			
	Nozzle Diameter	5 mm 5 mm		MR			
7	Automatic fire detection & alarming system.						
	Type of detectorsLocation of Main Panel	Carbon monoxide (CO) type	Provided	MR			
	 Location of Repeater Panel 	-N/A-	Ground floor	-N/A-			
	Alternate source of power	-N/A-	-N/A-	-N/A-			
	 Hooter's location 	-N/A-	Provided	-N/A-			
		-N/A-	Each floor	-N/A-			
8.	MOEFA	-N/A-	Provided	-N/A-			
9.	Public Address System	-N/A-	-N/A-	-N/A-			
10.	Automatic Sprinkler System						
	Basement	Required	Provided	MR			
	• Upper floors	-N/A-	-N/A-	-N/A-			
	Sprinkler above false ceiling	-N/A-	-N/A-	-N/A-			
11.	Internal Hydrants.	<u></u>					
	Size of Riser / Down-comer	-N/A-	-N/A-	-N/A-			
	Number of Hydrant per floor	-N/A-	-N/A-	-N/A-			
	Hose box.	-N/A-	-N/A-	-N/A-			
12.	Yard Hydrants.						
	 Total number of hydrants. 	-N/A-	-N/A-	-N/A-			
	Hose box.	-N/A-	-N/A-	-N/A-			
13.	Pumping arrangements.						
	Ground Level		. »				
	Discharge of main pump.	-N/A-	-N/A-	-N/A-			
	Head of main pump.	-N/A-	-N/A-	-N/A-			
	Number of main pumps.	-N/A-	-N/A-	-N/A-			
	Jockey Pump output.Jockey Pump head	-N/A-	-N/A-	-N/A-			
	Jockey Pump head.Standby Pump output.	-N/A-	-N/A-	-N/A-			
	> Standby Pump head.	-N/A-	-N/A-	-N/A-			
	> Auto Starting/Manual	-N/A-	-N/A-	-N/A-			
	Stopping. > Pump house access.	-N/A-	-N/A-	-N/A-			
	r ump nouse access.	-N/A-	-N/A-	-N/A-			
	Terrace Level						
	Discharge of pump.	-N/A-	900 LPM	-N/A-			
	Head of pump.Power supply.	-N/A-	40 m	-N/A-			
	Auto starting of pump.	Required Required	Provided Provided	MR			
14.	Captive water storage for firefighting.	_	Provided	MR			
	Underground tank capacity.	-N/A-	-N/A-	-N/A-			
	Draw-off connection.	-N/A-	-N/A-				
	Fire Service Inlet.	-N/A-	-N/A-	-N/A-			
	Access to tank.	-N/A-	-N/A-	-N/A-			
	Overhead tank capacity.			-N/A-			
15.	Exit Signage.	Required	10,000 ltrs	MR			
16.	Provision of Lifts.	Required	Provided	MR			
	Pressurization of lift shaft.	NI/A	77/4	21/4			
	 Pressurization of lift lobby. 	-N/A-	-N/A-	-N/A-			
	• Communication in lift car.	-IN/A-	-N/A-	-N/A-			

M	11	1-
/	11	1

(• Lift signage.	Required	Provided	MR			
17	Standby Power Supply	Required	Provided	MR			
18.	Refuge Area						
	Total area	-N/A-	-N/A-	-N/A-			
	 Location 	-N/A-	-N/A-	-N/A-			
19.	Fire Control Room.						
	Detector System Panel.	-N/A-	-N/A-	-N/A-			
	Flow Switch Panel.PA system Panel.Battery backupBuilding floor plan	-N/A-	-N/A-	-N/A-			
		-N/A-	-N/A-	-N/A-			
		-N/A-	-N/A-	-N/A-			
		-N/A-	-N/A-	-N/A-			
20.	Special Fire Protection System for the Protection of special Risk, if any.	Required	ABC type fire extinguished provided near electric	er MR			
			panel				

The Fire protection systems provided in the premises were checked / operated at random and found at the time of inspection. The condition of the Gazette Notification no. F.5/(189)/AD/LB/2016/4053/67 dated 27/05/2019 found complied.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No. F6/DFS/MS/GH/2017/SZ/1171 dated 04/08/2017, renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name

: Avtar Singh

Designation: ADO (M.Rd)

DO (SD)

Deroist Pl. speak on compliand

Spoken, Condon monoxide detresties ence Fore cheek Dool provided. Resubmitted pl. Manny