GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No. F.6/DFS/MS/EH/SZ/2020/09

Dated.07./.01./2020

FIRE SAFETY CERTIFICATE

Certified that M/s ITP Laidback Café (A Unit of Jhakaas Restaurants Pvt. Ltd) running at ground, first, second and third floor of M-51, M Block Market, Greater Kailash -II, New Delhi 110048 comprised of basement (not part of restt.) ground and three upper floor this department issued Fire Safety Certificate by F 6/DFS/MS/EH/2017/SZ/1476 dated 10/10/2017. The restaurant premise was re-inspected by the officer concerned of this department on 29/12/2020 in the presence of Sh. Dhiraj Arora of the restaurant and found that the said premise have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy Class D "Assembly Building" Restaurant as above with effect under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 07 / 01 /2020 at New Delhi by

(Sunil Chawdhary)
Dy. Chief Fire Officer (SZ)
Delhi Fire Service

Copy to: -

1. The Dy. Health Officer, Public Health Department, South Zone, Green Park, Delhi.

2. ITP Laidback Café (A Unit of Jhakaas Restaurants Pvt. Ltd) running at ground, first, second and third floor of M-51, M Block Market, Greater Kailash -II, New Delhi 110048

Conditions for the validity of Fire Safety Certificate: -

1. All the means of escape/entry/exit shall be kept free from any obstruction.

2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.

3. All the staff members must know the correct method of operation of fire fighting system.

4. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if

any.

6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry."

2	II, New Delhi 110048 (A Olin of a			lakaas 10stt.		
2		Pvt. Ltd) Group–D Assembly Building.				
	Type of Occupancy	Basement, Ground + Three upper floors				
3	Building Comprised of	Renewal				
4	Type of Case		2017/SZ/1476 dated 10	/10/2017		
5	Details of Previous NOC		/MS/ 2005/718 dated 04/			
6	Fire Safety Directives Letter No	29/12/2020	71VIS/ 2003/710 dates 5 //			
7	Date of Inspection	Sh. Rajesh Kumar	· ADO (RCP)			
8	Name of the Inspecting Officers		ADO (BCI)			
9	Name & Designation of Officers	Mr. Dhiraj Arora				
	from the building side	1999 Restt. at ground, 1 st 2 nd & 3 rd floor of the				
10	Year of construction	bldg.				
11	Applicant letter No.		00707432 dated 01/12			
S. No.	Minimum standards on Fire Prevention	CII. 110 / 10 dt		Remarks		
D. 140.	and Fire Safety U/R 33	04/04/2005		MR/NMR		
1	Access to Building.					
	Road width	Required	9m	MR		
	Gate width	N/A	N/A	N/A		
	Width of internal road	N/A	N/A	N/A		
2	Number, width, type & arrangement of ex	cits.				
	a) Number of Staircase					
	> Upper floors.	02 Nos	02 Nos	MR		
	> Basement floor.	N/A	Not part of Restt.	N/A		
	b) Width of Staircase	4				
	> Upper floors	1 & 1.25 m	1 & 1.25 m	MR (old case		
	Basement floor	N/A	N/A	N/A		
	c) Protection of exits					
	> Fire check door	N/A	N/A	N/A		
	> Pressurization	N/A	N/A	N/A		
	d) No. of continuous staircase to terrace	Required	One	MR		
	e) Width of corridor	N/A	N/A	N/A		
	f) Door size	1 mtr	1 m (2 mtr)	MR (old cas		
3	Compartmentation.					
		N/A	N/A	N/A		
	Fire check door.	N/A	N/A	N/A		
	Sealing of electrical shafts.	N/A	N/A	N/A		
	Fire rating of shaft door.	N/A	N/A	N/A		
	Water curtain		N/A	N/A		
	Fire dampers.	N/A	IN/A	1472		
4	Smoke Management system.					
	Basement	30 ACPH	N/A	N/A		
	Upper floors	12 ACPH	Exhaust Fans Provide	ed MR		
5	Fire Extinguishers.					
	Total numbers	10 Nos	10 Nos	MR		
	• Types	ABC/CO ₂	ABC-07 & CO ₂ -	MR		
			03			
	ISI Marking	ISI marked	Provided	MR		
6		ISI marked	Provided	MR		
6	ISI Marking First Aid Hose Reels.			MR		
6	ISI Marking	One 30m	Provided Provided Provided			

,	The Carry of the C	**************************************	27/4	27/4
	Type of detectors	N/A	N/A	N/A
	Location of Main Panel Location of Reporter Panel	N/A	N/A	N/A
	Location of Repeater PanelAlternate source of power	N/A	N/A	N/A
	Hooter's location	N/A	N/A	N/A
		N/A	N/A	N/A
8	MOEFA	Required	Provided	MR
9	Public Address System	N/A	N/A	N/A
10	Automatic Sprinkler System			<u></u>
	Basement	N/A	N/A	N/A
	Ground floor.	Required	Provided	M/R
	Sprinkler above false ceiling	N/A	N/A	N/A
11	Internal Hydrants.			
	Size of Riser/Down-comer	Required	100 mm	MR
	Number of Hydrant per floor	Required	One	MR
	Hose box.	Required	One	MR
12	Yard Hydrants.			
	 Total number of hydrants. 	N/A	N/A	N/A
	Hose box.	N/A	N/A	N/A
13	Pumping arrangements.			
	Ground Level			
	Discharge of main pump.	N/A	N/A	N/A
	Head of main pump.	N/A	N/A	N/A
	Number of main pumps.	N/A	N/A	N/A
	Jockey Pump output.Jockey Pump head.	N/A	N/A	N/A
	> Standby Pump output.	N/A	N/A	N/A
	Standby Pump head.	N/A	N/A	N/A
	Auto Starting/Manual Stopping.	N/A	N/A	N/A
	Pump house access.	N/A	N/A	N/A
And the second s		N/A	N/A	N/A
	Terrace Level			
	Discharge of pump.	225 & 180 LPM	450 LPM x 2	MR
	Head of pump.	40 m	Provided	MR
	Power supply.	Required	Provided	MR
2	Auto starting of pump.	Required	Provided	MR
14	Captive water storage for fire fighting.			
	 Underground tank capacity. 	N/A	N/A	N/A
	Draw-off connection.	N/A	N/A	N/A
	Fire Service Inlet.	N/A	N/A	N/A
	Access to tank.	N/A	N/A	N/A
	Overhead tank capacity.	5,000 Ltrs	10,000 ltr	MR
15	Exit Signage.	Required	Provided	MR
16	Provision of Lifts.			
	Pressurization of lift shaft.	N/A	N/A	N/A
	 Pressurization of lift lobby. 	N/A	N/A	N/A
	Communication in lift car.	N/A	N/A	N/A
	Fireman's switch.	N/A	N/A	N/A
	Lift signage.	N/A	N/A	N/A
17	Standby Power Supply	Required	Provided	MR
18	Refuge Area			
-11-	Total area	N/A	N/A	N/A
SILA SILA	• Location	N/A	N/A	N/A

19	Fire Control Room.			
	Detector system panel.	N/A	N/A	N/A
	Flow switch panel.	N/A	N/A	N/A
	PA system panel.	N/A	N/A	N/A
	Battery backup.	N/A	N/A	N/A
	Building floor plan.	N/A	N/A	N/A
20	Special Fire Protection System for the	N/A	N/A	N/A
	Protection of special Risk, if any.	14/11	. 1/ / 1	

The Fire protection systems provided in the premises were test checked at random and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no F.6/DFS/MS/EH/2017/SZ/1476 dated 10/10/2017, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: Sh. Rajesh Kumar Designation: ADO (BCP)

Dolso- on Leav

ADABIT

As approved, F.T. Lettree el prutis Jone synatura B1