GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI – 110001

No. F6/DFS/MS/NDZ/2020/ //

Dated: 08/01/1021

FIRE SAFETY CERTIFICATE

(Dr. S.K. Tomar)

Dy. Chief Fire Officer

Tel: 011-23412025

Copy to:-

- 1 .The Joint Commissioner (Licensing), P S Defense Colony, New Delhi. Online I.D No. 2020022603059 dated 18.12.2020.
- 2. The Licensee, M/s Hotel India, 691, Queen Garden Bagh Deewar, Fateh Puri, Delhi-06

Condition for the validity of fire safety certificate

- 1. This clearance/FSC shall stand cancelled if guest house owner/occupier fails to comply all other conditions mentioned in the gazette notification dated 27.05.2019 and any violation of clarification issued on 25.09.2019 & 17.12.2020 latest by 31.03.2021
- 2. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 3. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 4. The trained fire fighting staff should be available round the clock.
- 5. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

 Any change in the occupancy shall be intimated to this Deptt. and approval shall be obtained there to before occupancy of the same.

1			ECTION REPORT			
+	Non	ne & address of the building	M/s Hotel India, 691, Que	en Garden Bagh Dee	ewar, Fateh	
	INall		Puri, Delhi-06		-	
4	D:	lding is comprised of	Ground + 03 upper floor			
	Bui	iding is comprised of	Ground floor –05 guest roc	oms + reception + off	ice	
			1 st floor – 07 guest rooms	- 01 staff room		
			2 nd floor -08 guest rooms			
			3 rd floor -02 guest rooms -	- 01 store room + 01	staff room	
0			Residential Group A-1		2 70 2	
	Typ	ie (ii Occupanc)		0 8		
		be of Casc	Renewal 23 03 2018			
T	Det	tails of Previous FSC	F6/DFS/MS/GH/2018/495 dated 23.03.2018 Nil			
	Fire	e Safety direction letter No				
+	Date of Inspection Name of the Inspecting Officers		05.01.2021 Rajesh Kumar Shukla ADO (SPM)			
_	NIC	me of the designation of Officer				
) :	Name of the designation of Officer					
	iro	m the building side	Old			
0			Online I.D No. 2020022603059 dated 18.12.2020			
1		oplicant's letter No	Requirement/ Existing	Provided at Site	Remarks	
S.N	lo	Minimum Standards on fire	fire safety		MR/NMR	
		Prevention and fire safety				
١	*	requirements U/R 33	arrangements			
					# X **	
1		Access to building		07 m	NA	
		Road width	NA		NA	
	22	Gate width	NA .	NA NA	NA	
		Width of internal road	NA CE :	INA	1111	
2	•	Number, Width, Type and Arrai	ngement of Exits			
	-	A. Number of Staircases	* · · · · · · · · · · · · · · · · · · ·		MR	
		Upper Floor	01 no.	01 no.	NA	
		Basement	NA	NA	INA	
		B. Width of Staircases			MR	
		Upper Floor	80 cms	97 cms	NA	
1		Basement	NA	NA	INA	
1		C. Protection of exits	per	Not Provided	Last date of	
		Fire check door	(required as GN dated	Not Provided	complianc	
			27.05.2019		extended	
			S y e		till	
					31.03.202 vide order	
			N N N N N N N N N N N N N N N N N N N		dated	
				а 2 а и	17.12.202	
			NA	NA	NA	
		Pressurization	The state of the s	NA	NA	
		D. No. of continuous staircases to	NA NA		*	
		terrace	NA	NA	NA	
		E. Width of Corridor	82 cms	82 cms	MR	
	1	G. Door size	02 CIIIS		a se	
3		Compartmentation	DIA	NA	NA	
T		Fire check door	NA NA	NA	NA	
		Sealing of electrical shafts	NA	NA	NA	
		Fire rating of shaft door	NA	NA NA	NA	
		Water.curtain	NA	NA NA	NA	
		Fire Dampers	NA	INA	,	
1	1	Smoke Management System.	V 2	NIA	NA	
H		Basement	30a/cper hour	NA Natural	MR	
			12a/cper hour	Notural	VIII	



~/30

-	Fire Extinguisher Total numbers	07 no.	07 no.	MR				
3		CO ₂ & ABC	CO ₂ & ABC	MR				
	types	ISI marked	ISI marked	MR				
n 2	IS marking							
	First-aid-Hose Reels.	Required	01 no. at Ground	MR				
	Total numbers of each floor	Roquis	& 2 nd floor					
	Length of hose reel hose	30 m	30 m	MR				
		5 mm	5 mm	MR				
	Nozzle diameter							
7	Automatic fire detection and alarming sy	CO detectors	Not Provided	Last date of				
	Type of detectors	(required as GN dated 27.05.2019		compliance extended till 31.03.2021 vide order dated 17.12.2020				
		NA	NA	NA				
	Location of main panel	NA	NA	NA				
	Location of repeater panel Alternate source of power	NA	NA	NA				
	Hooters	NA	NA	NA				
8	MOEFA	NA	NA	NA				
9	Public address System.	Required	Provided	MR				
10	Automatic Sprinkler System.							
10	basement	NA	NA	NA				
		NA	NA	NA				
	upper floor	NA	NA	NA				
	Sprinkler above false ceiling	1122	-	4 2 4				
11	Internal Hydrants	NA '	NA	NA				
	size of riser/down-comer	NA NA	NA NA	NA				
	Number of hydrants per floor		NA NA	NA				
	Hose Box	NA	IVA					
12	Yard Hydrants.	Tour services	LATA	NA				
	Total number of hydrants	NA	NA	1 2				
	Hose Box	NA	NA	NA				
13	Pumping Arrangements.	e e e e e e e e e e e e e e e e e e e		- Control				
	Ground Level							
	Discharge of main Pump	NA	NA	NA				
*	> Head of Main Pump	NA	NA	NA				
	Number of main pumps	NA	NA	NA				
	> Jockey pump out put	NA	NA	NA ·				
	> Jockey pump head	NA	NA	NA				
= .	> Standby pump out put	NA	NA	NA				
	> Standby pump Head	NA ·	NA	NA				
0	> Auto Starting /Manual stopping		NA	NA				
	> Pump House Access	NA	NA NA	NA				
	Terrace Level		005 105					
	Discharge of pump	225 LPM	225 LPM	MR				
	> Head of the Pump	30 m	30 m	MR				
	Power supply.	Required	Provided	MR				
-22	> Auto Starting of pump	Required	Provided	MR				



	Captive Water Storage for Fire Fig	hting.	NA	NA	
1	Underground tank capacity	NA		NA	
		NA	NA	· NA	
	Draw-off connection	NA	NA	NA NA	
	Fire service inlet	NA	NA	No. Mark Co.	
	Access to tank	2,500 ltrs	2,500 ltrs	MR	
	Overhead Tank capacity	Required	Provided	MR	
15	Exit Signage.	Required			
16	Provision of Lifts.	DIA	NA	NA	
	Pressurization of Lift Shaft	NA	NA .	ŅA	
	Pressurization of Lift lobby	NA NA	NA	NA	
	Communication in lift car	. NA	NA	NA	
	Firemen's grounding switch	NA		NA	
	Lift Signage	NA	NA	MR	
		Required	Provided	IVAL	
17	7 Standby power suppry				
18	Refuge Area.	N.A	N.A	N.A	
	Total area		N.A	N.A	
	Location	N.A	11112	E a	
19	Fire Control Room	1214	NA	NA	
17	Detector system panel	NA	NA NA	NA	
	Flow switch panel	NA	NA NA	NA NA	
	PA system panel	NA	NA	NA NA	
	Batter backup	NA	NA .	NA	
	Dlane	NA siel	NA ·	NA	
20	Special Fire Protection systems for protection of special NA				
20	Risks, if any:				

The fire protection systems provided in the building were tested, checked at randomly and found functional at the time of inspection.

Keeping in view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the Rules, the FSC issued vide letter No F6/DFS/MS/GH/2018/495 dated 23.03.2018 it is recommended to be renewed under Rule 35 of the Delhi Fire Service Rules 2010.

05.01.21

Signature of the Inspecting Officer

Name

Rajesh Kumar Shukla

Designation

ADO (SPM)

DO (CD)

Dycho (ms2)

04) om (7) 1121

M.S.Cell