GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/GH/SZ/2020/ 06

Dated: 06/01/2021

FIRE SAFETY CERTIFICATE

Certified that M/s. Sagar Palace Guest House located at 47/16, Old Rajinder Nagar, Bara Bazaar Marg, New Delhi- 110060 comprised of basement (storage/hall), ground floor (reception + 02 guest rooms), first floor (04 guest rooms), second floor (04 guest rooms) and half portion of third floor (02 guest rooms) (total 12 guest rooms), remaining half portion of third floor i.e. 02 guest rooms has been sealed by pucca brick wall by the owner. The guest house was granted FSC by this department vide letter No. F6/DFS/MS/GH//SZ/20017/847 dated 13.06.2017. The premises was re-inspected by the officer concerned of this department on 23.12.2020 in presence of Mr. Vinod Sagar, Owner of the guest house and found that the guest house is deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from component cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued of for to 21 at New Delhi by.

(Sunil Chaudhary)
Dy. Chief Fire Officer (SZ)
Delhi Fire Service

Copy to:-

- 1. The Manager, M/s. Sagar Palace Guest House, 47/16, Old Rajinder Nagar, Bara Bazaar Marg, New Delhi- 110060.
- 2. The Joint C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi.
- 3. The Municipal Health officer, NDMC, Civic centre, New Delhi- 110002.

Conditions for the Validity of Fire Safety Certificate 1. The Gazette Notification of UBBL-2016 amendment inserted as clause No. 7.31 of Chapter- 7 by the Directorate of Local Bodies vide letter No. F.5(1897/AD/LB/2016/4053-65 dated 27.05.2019 and letter No. F.5(189)/AD/LB/2016/710-725 dated 17.12.2020 in respect of existing building (copy enclosed) shall be implemented by 31.03.2021 under intimation to Delhi Fire Service and if the provisions are not made within the stipulated time then the FSC shall stand null & void. 2. All the means of escape shall be kept free of all type of obstruction all the time. 3. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency. 4. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible. 5. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities. 6. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any. 7. All comments / directions of licensing department shall always be permitted and followed. 8. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in 9. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry. 10. Basement shall be used as per BBL. 11. No temporary shed is allowed on terrace. 12. The Fire Safety Certificate is only for Guest Rooms. Dipo 52

INSPECTION REPORT

1. Name & address of the building : M/s Sagar Palace guest house, 47/16, Old Rajinder Nagar,

Bara bazaar Marg, New Delhi-60.

2. Type of Occupancy : Lodging House

3. Type of Case : Renewal

4. Details of previous NOC : F.6/DFS/MS/GH/SZ/2017/847 dated 13.06.2017

5. Fire Safety directives letter No : N/A.

6. Date of inspection : 23.12.2020

7. Name of the Inspecting Officers: P.V Rathee, Asstt. Divisional Officer (SRD)

8. Name and designation of officers

from the building side : Mr. Vinod Sagar, Owner

9. Year of Construction : before 2008

10. Applicant's letter No. : nil dated 11.12.2020

The said guest house is comprised of basement, ground and three upper floors. FSC was granted for basement (Storage), ground (reception & 02 guest room), first floor (04 guest rooms), second floor (04 guest rooms) and half portion of third floor (02 guest rooms). Half portion of third floor (02 rooms) sealed by owner.

No.		mum Standards on fire tion and fire safety U/R 33	Requirement as per letter dated- 28.11.2013	Provided at site	Remarks MR/NMR			
1	Access t	ecess to building						
	Road width		06 mts	06 mts	MR			
	• (ate width	Required	Directly accessible	MR			
	• 7	Width of internal road	N/A	N/A	N/A			
2	Number							
	a. Numb	er of staircases		-				
	• [Jpper Floors	01	01	MR being old case			
		Basements	02	02	MR			
	b. Width	of staircases		- 7.				
	• [Jpper Floors	0.80 mts	0.80 mt.	MR being old casse			
	• I	Basements	0.80 mts	115 cms & 73 cms	MR			
	c. Protec	etion of exits		-	= -			
	• 1	Fire check door	N/A	N/A	N/A			
	• 1	Pressurization	N/A	N/A	N/A			
	e. No. of	continuous staircases to terrace	01	01	MR			
	g. Width	of Corridor	1.0 mt.	1.40 mts.	MR			
	h. Door	Size	1.0 mt.	0.80 mt.	MR being old cas			
3	Compa	rtmentation.						
	-	Fire check door	N/A	N/A	N/A			
		Sealing of electrical shafts	N/A	N/A	N/A			
		Fire Rating of shaft door	N/A	N/A	N/A			
		Water Curtain	N/A	N/A	N/A			
	•	Fire Dampers	N/A	N/A	N/A			
4	Smoke Management System.							
		Basements	30 a/c per hour	Exhaust fan provide	ed MR			
	• [Jpper floors	12 a/c per hour					
				Natural ventilation	MR			

5	Fire Extinguishers		CONTROL OF THE STATE OF THE STA	1.00				
7	Total numbers	12	Provided	MR				
	• Types	CO ₂ , ABC type	Provided	MR				
	IS marking	ISI marked	Provided	MR				
6	First-Aid Hose Reels.							
	Total numbers on each floor	Required	Provided	MA				
	 Length of hose reel hose 	30 m	Provided	MAR				
	Nozzle diameter	5 mm	Provided	MIR				
7	Automatic fire detection and alarming system.							
	Type of detectors	N/A	N/A	N/A				
	Location of Main Panel	N/A	N/A	N/A				
	Location of Repeater Panel	N/A	N/A	N/A				
	Alternate source of power	N/A	N/A	N/A				
	Hooters' Location	N/A	N/A	N/A				
8	MOEFA	Required	Provided	MR				
9	Public Address System.	Required	Provided					
10	Automatic Sprinkler System.							
10	Basement	N/A	Area less than 200 m ²	N/A				
	Upper Floor	N/A	N/A	N/A				
	Sprinkler above false ceiling	27/4	N/A	DT/A				
		N/A	IN/A	N/A				
11	Internal Hydrants							
11	Size of riser/down-comer	N/A	N/A	N/A				
	Number of hydrants per floor	N/A	N/A	N/A				
	TT D	N/A	N/A	N/A				
12								
12	Total number of hydrants	N/A	N/A	N/A				
	Hose Box	N/A	N/A	N/A				
13	Pumping Arrangements.							
13	Ground Level							
	Discharge of main Pump	N/A	N/A	N/A				
	> Head of Main pump	N/A	N/A	N/A				
	Number of main pumps	N/A	N/A	N/A				
	> Jockey Pump out put	N/A	N/A	N/A				
	Jockey pump head	N/A	N/A	N/A				
	> Standby Pump out put	N/A	N/A	N/A				
	> Standby Pump Head	N/A	N/A	N/A				
	> Auto Starting/ Manual	N/A	N/A	N/A				
	stopping	N/A	N/A	N/A				
	> Pump House Access	1V/A	*					
	• Terrace level	225 LPM	Provided	MR				
	Discharge of pump	30 mts	Provided	MR				
	Head of the pump	N/A	N/A	N/A				
	Power Supply Acta Starting of nump	N/A	N/A	N/A				
	Auto Starting of pump							
14		N/A	N/A	N/A				
	Underground tank capacity	N/A	N/A	N/A				
	> Draw-off connection	N/A	N/A	N/A				
	Fire service inletAccess to tank	N/A	N/A	N/A				
	Access to tank Overhead Tank capacity	2500 lts	3000 lts	MR				
	Overnead Talik Capacity							

15	Exit Signage.	Required	Provided	MR			
16	Provision of Lifts.						
	Pressurization of Lift Shaft	N/A	N/A	N/A			
	 Pressurization of Lift lobby 	N/A	N/A	N/A			
	Communication In lift Car	N/A	N/A	N/A			
	• Fireman's Grounding Switch	N/A	N/A	N/A			
	• Lift Signage	N/A	N/A	N/A			
17	Standby power supply	Required	Provided	MR			
18	Refuge Area.						
	> Total Area	N/A	N/A	N/A			
	> Location	N/A	N/A	N/A			
19	Fire Control Room						
	Detector System Panel	N/A	N/A	N/A			
4	 Flow Switch Panel 	N/A	N/A	N/A			
	PA System Panel	N/A	N/A	N/A			
	Batter backup	N/A	N/A	N/A			
	Building Floor Plans	N/A	N/A	N/A			
20	Special Fire Protection Systems for	Required	Two ABC type fire	MR			
	Protection of special Risks, if any:		extinguisher found				
			provided near elect.				
			panel				

The fire protection systems provided in the building were checked and found functional at the time of inspection.

The Gazette Notification of UBBL-2016 amendment inserted as clause No. 7.31 of Chapter- 7 by the Directorate of Local Bodies vide letter No. F.5(1897/AD/LB/2016/4053-65 dated 27.05.2019 and letter No. F.5(189)/AD/LB/2016/710-725 dated 17.12.2020 in respect of existing building (copy enclosed) shall be implemented by 31.03.2021 under intimation to Delhi Fire Service and if the provisions are not made within the stipulated time then the FSC shall stand null & void.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/GH/SZ/2017/847 dated 13.06.2017, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

P.V Rathee

Asstt. Divisional Officer (SRD)

29/12/2020

Dy CF0 (52)

d F.t. pleus

and S. An