GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/2021/ 14

Dated: 18/01/2021

FIRE SAFETY CERTIFICATE

Certified that the Banana Leaf Restaurant located at N-12, Connaught Place, New Delhi comprises of Ground + 02 Upper floor, Restaurant running at Ground floor only was granted FSC by this department vide letter No.F6/DFS/MS/EH/2017/NDZ/1016dated 13/07/17. The premises was re-inspected by the officer concerned of this department on 05/07/17 in the presence of Mr. Santosh and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Assembly Building Group D for Restaurant running at Ground floor only with effect from Parad-for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -18-101/2-1---at New Delhi by.

(Dr. S.K. Tomar) Dy. Chief Fire Officer Delhi Fire Service

04 0mm

Copy to:-

- 1. The Joint Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi Id No. 2020121609036 dated 22/12/2020
- 2. The Manager,

Banana Leaf Restaurant located at N-12, Connaught Place, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 9. Inflammable material, if any for interior decoration, shall strictly be prohibited.

| | | ECTION REPO | | | | |
|-------|---|-------------------------------|--|--------------|--|--|
| 1. | Name & address of the building | | eaf Restaurant at N | -12, | | |
| | T | Connaught Place, New Delhi | | | | |
| 2. | Type of occupancy:- | | Building Group-D | | | |
| | | | er floor, Restaurant r | unning at | | |
| 3 | Type of case:- | Ground floo Renewal | ronly | | | |
| | Details of previous FSC:- | | C/MS/EH/2017/ND | 7/1016 datad | | |
| | Details of previous 1 be | 13/07/17. | No.F6/DFS/MS/EH/2017/NDZ/1016 dated | | | |
| 5. | Fire safety directives No | | | | | |
| | Date of inspection:- 04/01/2021 | | | | | |
| | Name of the inspecting officer:- Sh. Ravinder Singh (ADO/CC) | | | | | |
| | Sh. Rajinder Atwal, DO (CD) | | | | | |
| 8. | Name & designation of officer | | | | | |
| | from the building side:- Mr. Santosh | | | | | |
| | Year of construction:- | Old Heritag | | | | |
| 10. | Applicant's letter No:- | 2020121609 | 9036 dated 22/12/2 | | | |
| | | | T= | Old renewal | | |
| S.No. | Minimum Standards on fire | Requirement/ Existing fire | Provided at site | Remarks | | |
| | Prevention and fire safety | safety | | MR/NMR | | |
| | U/R 33 | arrangements | | | | |
| 1. | Access to Building | 3 | | | | |
| | 1) Road width | 09 mtr | 12 mtr. | MR | | |
| | 2) Gate width | N/A | N/A | N/A | | |
| | 3)Width of internal road | N/A | N/A | N/A | | |
| 2. | Number, Width Type & Arra | angement of E | xits | | | |
| | A. Number of staircases | | | | | |
| | 1. Upper floors | 01 No. | 01 No. | MR | | |
| | 2. Basements | N/A | N/A | N/A | | |
| | B. Width of staircase | | | 1 2 2 | | |
| | 1. Upper floors | 80 cms. | 120 cms | MR | | |
| | 2. Basements | N/A | N/A | N/A | | |
| | C. Protection of exits | N/A | N/A | N/A | | |
| | 1. Fire check door | N/A | N/A | N/A | | |
| | 2. Pressurization | N/A | N/A | N/A N/A | | |
| 4 | D. No. of continuous | N/A | N/A | IN/A | | |
| 2 | staircase to terrace | N/A | N/A | N/A | | |
| | E. Width of corridor | 1.70 mtr. | 1.70 mtr. | MR | | |
| 2 | F. Door size | 1.70 mm. | 1.70 mu. | IVIIC | | |
| 3. | Compartmentation | N/A | N/A | N/A | | |
| | 1) Fire check door | N/A N/A | N/A | N/A | | |
| | 2) Sealing of electrical shafts | N/A N/A | N/A | N/A | | |
| | 3) Fire rating of shaft door4) Water curtain | N/A | N/A | N/A | | |
| | | N/A | N/A | N/A | | |
| 4. | Smoke Management System | 5) The Dampers | | | | |
| 4 | | 30 ACPH | N/A | N/A | | |
| | | | The state of the s | | | |
| | 1) Basements 2) Upper floors | | Natural | MR | | |
| 5. | 2) Upper floors Fire Extinguishers | 12 ACPH | Natural | MR | | |

| N | 115 |
|---|-----|
|---|-----|

| | 10.5 | | | | | |
|-----|--|--------------|-----------------|------|------|--|
| | 2) Types | ABC & CO2 | ABC & CO2 | MR | • | |
| | 3) ISI marking | Required | Provided | MR | | |
| | | | | | | |
| 6. | First-Aid Hose Reel | | | | | |
| | 1) Total number of eachfloor | 01 | 01 | MR | - | |
| | 2) Length of hose reel hose | 30 mtr. | 30 mtr. | MR | - | |
| | 3) Nozzle diameter | 05 mm | 05 mm | MR | | |
| 7. | Automatic Fire Detection & Alarming System | | | | | |
| | 1) Type of detectors | N/A | N/A | N/A | | |
| | 2) Location of main panel | N/A | N/A | N/A | | |
| | 3) Location of repeater panel | | N/A | N/A | | |
| | 4) Alternate source of power | N/A | N/A | N/A | | |
| | 5) Hooter's Location | N/A | N/A | N/A | | |
| 8. | MOEFA | COLUMN TOTAL | | | | |
| 9. | Public Address System | Required N/A | Provided | MR | | |
| 10. | Automatic Sprinkler System | | N/A | N/A | | |
| | 1) Basement | N/A | NT/A | 77/1 | | |
| | 2) Upper floors | Required | N/A Provided | N/A | 41 | |
| | 3) Sprinkler above false | N/A | | MR | | |
| | ceiling | IN/A | N/A | N/A | | |
| 11. | Internal Hydrants | | | | | |
| | 1) Size of riser/down-comer | N/A | N/A | DT/A | - | |
| | 2) Number of hydrants per | N/A | | N/A | | |
| | floor | IN/A | N/A | N/A | | |
| | 3) Hose box | N/A | NT/A | 27/ | | |
| 12. | Yard Hydrants | IN/A | N/A | N/A | | |
| 4. | 1) Total number of hydrants | N/A | N/A | 27/4 | | |
| | 2) Hose box | N/A | N/A | N/A | | |
| 3. | Pumping Arrangement | IN/A | IN/A | N/A | | |
| | 1) Ground level | N/A | NI/A | DT/A | | |
| | a) Discharge of main | N/A | N/A N/A | N/A | | |
| | | IN/A | N/A | N/A | | |
| | b) Head of main pump | N/A | N/A | NT/A | 1 22 | |
| | c) Number of main | N/A | | N/A | | |
| | | IN/A | N/A | N/A | | |
| | d) Jockey pump out put | N/A | NI/A | DT/A | | |
| | | | N/A | N/A | | |
| | e) Jockey pump head | N/A | N/A | N/A | | |
| | f) Stand by pump output | N/A | N/A | N/A | | |
| | 1 | NT/A | NI/A | NT/A | | |
| | g) Stand by pump head | N/A N/A | N/A N/A | N/A | | |
| | h) Auto starting/Manual | IN/A | IN/A | N/A | | |
| | stopping 2) Terrace level | | | | | |
| | | 450 I DM | 450 I DM | MD | | |
| | a) Discharge of pump | 450 LPM | 450 LPM | MR | | |
| | b) Head of pump | 30 mtr. | 30 mtr. | MR | | |
| | c) Power supply | Required | Provided | MR | | |
| | d) Auto starting of | Required | Provided | MR | | |
| | pump Captive Water Storage for F | • 17. 14. | | | | |
| 4 | Lantive Water Storage for H | ire Highfing | | | | |
| 4. | 1) Under ground tank cap | | N/A | | N/A | |

| 4 1 1/50 | | | | |
|----------|--|--------------|---------------------|-----|
| | a) Draw-off connection | N/A | N/A | N/A |
| | b) Fire service inlet | N/A | N/A | N/A |
| | c) Access to tank | N/A | N/A | N/A |
| | d) Over head tank capacity | 2500 ltr. | 2500 ltr. | MR |
| 15. | Exit Signage. | Required | Provided | MR |
| 16. | Provision of Lifts. | | * * * | |
| | a) Pressurization of lift shaft | N/A | N/A | N/A |
| | b) Pressurization of lift lobby | N/A | N/A | N/A |
| | c) Communication in lift car | N/A | N/A | N/A |
| | d) Fireman's switch | N/A | N/A | N/A |
| | e) Lift signage | N/A | N/A | N/A |
| 17. | Stand by Power Supply | N/A | N/A | N/A |
| 18. | Refuge Area | N/A | N/A | N/A |
| | Total area location | N/A | N/A | N/A |
| 19. | Fire Control Room | N/A | N/A | N/A |
| | a) Detector system panel | N/A | N/A | N/A |
| | b) Flow switch panel | N/A | N/A | N/A |
| | c) PA system panel | N/A | N/A | N/A |
| | d) Battery backup | N/A | N/A | N/A |
| | e) Building floor plan | N/A | N/A | N/A |
| 20. | Special Fire Protection System fo any: | r Protection | of special Risk, if | NA |

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No.F6/DFS/MS/EH/2017/NDZ/1016 dated 13/07/17, renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended for approval.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name: - Rajinder Atwal Designation: - DO (CD) Name :- Ravinder Singh Designation :- ADO (CC)

Asoppoored Ar is port up for Kund Pured and System Pl