GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No F 6 / DFS / MS / 2021 / 38

Dated | 9 / 0 | /2021

FIRE SAFETY CERTIFICATE

Certified that the Missionaries of Charity (Mother Teresa's) on ground floor at Magazine Road, Near Majnu Ka Tilla (Petrol Pump), Civil Line, Delhi-10054 comprised of Basement, Ground and First floor owned/ occupied by Missionaries of Charity, Nirmal Hriday was granted NOC by this department vide letter no. F6/MS/DFS/MS/2014/805 dated 30.06.2014. The premises was re-inspected by the officers concerned of this department on 18.01.2021 in the presence of Sr. Nishaj MC and found that the building/premise have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules,2010 and the building/ premises is fit for occupancy of Institutional Building for ground floor only with effect from 19012021 for a period of 03 (Three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 19012021 at New Delhi by

(DharampalBhardwaj) Dy. Chief Fire Officer Ph-011-25156707

Copy to:-

1. Sr. Nishaj MC, Nirmal Hriday Home, Magazine Road, Near Majnu Ka Tlla (Petrol Pump), Civil Line, Delhi-110054.

Conditions for the validity of Fire Safety Certificate:

- 1 All the means of escape/entry/exit shall be kept free from any obstruction.
- 2 All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3 All the staff members must know the correct method of operation of firefighting system.
- 4 The owner / occupier shall submit a declaration **every year** in **Form "K"** provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on http://delhi.gov.in./wps/wcm/connect/doit fire/FIRE/Home/Forms.
- 5 This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6 "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in **Form 'J'** [sub rule (1) of rule 37] along with a copy of this Certificate, **six months** prior to its expiry".
- 7 This Fire Safety Certificate is valid only Ground floor for institutional occupancy only. In case of any violation, this FSC will be treated as null & void.

INSPECTION REPORT

1. Name & address of the building: Nirmal Hriday Home, Magazine Road, Near Majnu Ka Tilla

(Petrol Pump), Civil Line, Delhi-110054.

2. Type of Occupancy

: Institutional

3. Type of Case

: Renewal B+ G+01 upper floor (Running at ground floor only)

4. Details of previous NOC

: F6/DFS/MS/2014/805 Date: 30.06.2014

5. Fire Safety directives letter No : F6/DFS/MS/BP/2009/2127 dated 16.07.2009.

6. Date of inspection

: 18.01.2021

Basement-Vacant

7. Name of the Inspecting Officers: ADO (RN)

Ground-Destitute

8. Name and designation of officers

First floor- servant room

from the building side

: Sr. Nishaj MC

9. Year of Construction

: 2009

10. Applicant's letter No.

: Online E-Mail I.D dated: 25.09.2020

S. No	Minim	m Standards on fire ion and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR			
1	Access	Access to building						
	•	Road width	06m	18m	MR			
	•	Gate width	4.5m	4.5m	MR			
	•	Width of internal road	NA	NA	NA			
2	Numbe	r, Width, Type & Arrangemen	t of Exits					
	a.	a. Number of staircases						
	•	Upper Floors	NA	04 + 01 ramp	NA			
	•	Basements	NA	03	NA			
	b.	Width of staircases	•					
	•	Upper Floors						
	•	Basements	NA	NA	NA			
	c. Prote	ction of exits	NA	NA	NA			
	•	Fire check door						
		Dunanningting	Required	Provided	MR			
		Pressurization of continuous staircases to	NA	NA	NA			
	terra		NA	NA	NA			
	e. Widt	h of Corridor	NA	NA	NA			
	f. Door	Size	1.0m	1.0m	MR			
3	Compa	rtmentation.						
	•	Fire check door	Required	Provided	MR			
	•	Sealing of electrical shafts	NA	NA	NA			
	•	Fire Rating of shaft door	NA	NA	NA			
)	•	Water Curtain	NA	NA	NA			

	Fire Dampers	Required	Provided	MR			
4	Smoke Management System.						
	Basements	30ACPH	Provided	MR			
	Upper floors	12ACPH	NA	NA			
		*	1111	INA			
5	Fire Extinguishers						
	Total numbers	16nos	18 nos	MR			
	• Types	ABC/CO2	ABC-12 /CO2-06	MR			
	IS marking	Required	Provided	MR			
6	First-Aid Hose Reels.						
	Total numbers on each floor	02	02	MR			
	Length of hose reel hose	30m	30m	MR			
	Nozzle diameter	6mm	6mm	MR			
7	Automatic fire detection and alarmin	ng system.					
The second desired des	Type of detectors	NA	NA	NA			
	 Location of Main Panel 	NA	NA	NA			
	Location of Repeater Panel	NA	NA	NA			
	Alternate source of power	NA	NA	NA			
	Hooters' Location	NA	NA	NA			
8	MOEFA	Required	Provided	MR			
9	Public Address System.	Required	Provided	MR			
10	Automatic Sprinkler System.						
10	Basement	Required	Provided	MR			
	Upper Floor	NA	NA	NA			
	Sprinkler above false ceiling	NA	NA	NA			
1.1							
11	Internal Hydrants	0.422	D :111	N.CD			
×	Size of riser/down-comer	04''	Provided	MR			
	Number of hydrants per floor	02	Provided	MR			
	Hose Box	02	Provided	MR			
12	Yard Hydrants.						
۰	Total number of hydrants	NA	NA	NA			
	Hose Box	NA	NA	NA			
13	Pumping Arrangements.						
	Ground Level						
	Discharge of main Pump	NA	NA	NA			
	➤ Head of Main pump	NA	NA	NA			
	Number of main pumps	NA	NA	NA			
	Jockey Pump out put	180lpm	Provided	MR			
	> Jockey pump head	40m	Provided	MR			
	Standby Pump out putStandby Pump Head	NA	NA	NA			
	> Auto Starting/ Manual	NA	NA	NA			
		NIA	NIA	NIA			

-		stopping	NA	NA	NA		
		> Pump House Access	1111				
		Terrace level	9001pm	900lpm	MR		
			40m	Provided	MR		
		Discharge of pump	NA	NA	NA		
		Head of the pump	NA	NA	NA		
		Power Supply	INA	IVA	1471		
		Auto Starting of pump					
14	Captive Water Storage for fire fighting.						
	•	Underground tank capacity	NA	NA	NA		
	A	Draw-off connection	NA	NA	NA		
	>	Fire service inlet	NA	NA	NA		
	>	Access to tank	NA	NA	NA		
	•	Overhead Tank capacity			MR		
			20,000 ltrs	20,000 ltr.	IVIK		
15	Exit Si	gnage.	Required	Provided	MR		
6	Provision of Lifts.						
	• Pr	essurization of Lift Shaft	NA	NA	NA		
	• Pr	essurization of Lift lobby	NA	NA	NA		
	• Co	mmunication In lift Car	NA	NA	NA		
	Fireman's Grounding Switch		NA	NA	NA		
		ft Signage	NA	NA	NA		
17	Standb	y power supply	Required	Provided DG Set	MR		
18	Refuge Area.						
	>	Total Area	NA	NA	NA		
	>	Location	NA	NA	NA		
19	Fire Control Room						
		Detector System Panel	NA	NA	NA		
			NA	NA	NA		
			NA	NA	NA		
				NA	NA		
			NA				
	•	Building Floor Plans	NA	NA	NA		
20		Fire Protection Systems for ion of special Risks, if any:	NA	NA	NA		

The fire protection systems provided in the building were tested/ checked randomly and found in working condition at the time of inspection.

Keeping in view the satisfactory compliance of the minimum standards on fire prevention and fire safety required as stipulated in NBC Part-IV the FSC issued vide letter of even no 805 dated 30.06.2014 renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended.

DO (MM)

19/01/2021

Signature of the Inspecting Officer
Name: - C.L. Meena